








PRODUCT NUMBER SEE SHEET 2



spec ref *				dr	Vicking Liu	2016/01/14	projection	MM	size	A3	scale	3:2
tolerance std ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Vicking Liu	2016/01/29			ecn no	-		
				chr	Fancy Zhang	2016/01/29						
				appr	Pei-Ming Zheng	2016/01/29						product family
surface	linear	0.X	±0.5		title 3HP + 20S + 2HP RA PF RECEPTACLE			dwg no	10106127-5005001		rev A	
		0.XX	±0.25									
		0.XXX	±0.10									
ASME Y14.5	angular	0°	±2°	www.fci.com	cat. no.			Product - Customer Drw		sheet 1 of 3		

PRODUCT NO.	ROWS	HP			SIGNAL					HP			E2
		E1	P5	P4	5	4	3	2	1	P3	P2	P1	
10106127-5005001LF	DCBA		H7	H7	S	S	S	S	S	H5	H7	H7	
					R	R	R	R	R				
					P	P	P	P	P				
					N	N	N	N	N				

CODE	DESCRIPTION
H5	MFBL HIGH POWER CONTACT(3.02)
H7	STD HIGH POWER CONTACT(3.02)
N	STD SIGNAL CONTACT, ROW A
P	STD SIGNAL CONTACT, ROW B
R	STD SIGNAL CONTACT, ROW C
S	STD SIGNAL CONTACT, ROW D




dr	Vicking Liu	2016/01/14	projection	MM	size	A3	scale	3:2	
eng	Vicking Liu	2016/01/29			ecn no	-			
chr	Fancy Zhang	2016/01/29			rel level	Released			
appr	Pei-Ming Zheng	2016/01/29			product family	PwrBlade+			
			title		3HP + 20S + 2HP		dwg no		rev
			RA PF RECEPTACLE		10106127-5005001				A
www.fci.com			cat. no.		Product - Customer Drw			sheet 2 of 3	



Copyright FCI.

NOTES:

- 1) "FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 2) MATERIALS:
-HOUSING - GLASS FILLED WITH HIGH TEMP THERMOPLASTIC, UL94V-0.
-SIGNAL CONTACT - COPPER ALLOY.
-POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY.
- 3) PLATING SPECIFICATION: 10116351
- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS ARE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) 1.15 ±0.025MM DRILLED HOLE PLATED WITH 0.00762MM MIN Sn
OVER 0.0254-0.0762MM Cu PLATING TO ACHIEVE A 1.02 ±0.07MM HOLE.
- 8) PRODUCT SPECIFICATION: GS-12-658.
APPLICATION SPECIFICATION: GS-20-141.
PRODUCT PACKAGED IN TRAYS: GS-14-1502.
- 9) THE VOID CORING IN BETWEEN POWER MODULES, SIGNAL
MODULES AND END MODULES ARE OPTIONAL AND THE SHAPE
MAY BE DIFFERENT FOR OPTIMIZING THE MOLDING PROCESS. THE
VOID CORING WILL NOT EFFECT TO PRODUCT FUNCTION.

dr	Vicking Liu	2016/01/14	projection 	MM 	size	scale
eng	Vicking Liu	2016/01/29			A3	3:2
chr	Fancy Zhang	2016/01/29			ecn no	-
appr	Pei-Ming Zheng	2016/01/29			rel level	Released
			product family	PwrBlade+		
 3HP + 20S + 2HP RA PF RECEPTACLE			dwg no	10106127-5005001	rev	A
www.fci.com			cat. no.	Product - Customer Drw		
			sheet 3 of 3			

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9