



Main

|                           |                             |
|---------------------------|-----------------------------|
| Range of product          | Harmony 9001K               |
| Product or component type | Illuminated selector switch |
| Device short name         | 9001K                       |
| Type of operator          | Maintained                  |
| Operator profile          | Gloved hand knob green      |

Complementary

|                               |                          |
|-------------------------------|--------------------------|
| Bezel material                | Chromium plated metal    |
| Mounting diameter             | 1.18 in (30 mm)          |
| Product weight                | 0.54 lb(US) (0.245 kg)   |
| Shape of signaling unit head  | Round                    |
| Operator position information | 3 positions              |
| Contacts type and composition | Without contact block    |
| Mechanical durability         | 500000 cycles            |
| Light block supply            | Via integral transformer |
| Light source                  | Incandescent             |
| Bulb base                     | BA 9s                    |
| [Us] rated supply voltage     | 110...120 V AC 50/60 Hz  |
| Device presentation           | Basic element            |

Environment

|                                       |                                                                                                                |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|
| protective treatment                  | TC                                                                                                             |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                     |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                                     |
| electrical shock protection class     | Class II conforming to IEC 61140                                                                               |
| IP degree of protection               | IP66 conforming to IEC 60529                                                                                   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 6                                |
| standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>JIS C 4520<br>JIS C 852<br>UL 508<br>CSA C22.2 No 14 |
| product certifications                | NEMA<br>UL 508                                                                                                 |
| vibration resistance                  | 7 gn (f = 2...500 Hz) conforming to IEC 60068-2-6                                                              |
| shock resistance                      | 50 gn conforming to IEC 60068-2-27                                                                             |

Offer Sustainability

|                                                   |                                                              |
|---------------------------------------------------|--------------------------------------------------------------|
| WARNING: This product can expose you to chemicals | WARNING: This product can expose you to chemicals including: |
|---------------------------------------------------|--------------------------------------------------------------|

including:

|                                                                                                                                  |                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|

|                                                                                               |                                                                                               |
|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> |
|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|

Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9