



# LM193, LM293, LM393

## Low power dual voltage comparators

Datasheet –production data

### Features

- Wide single-supply voltage range or dual supplies: +2 V to +36 V or  $\pm 1$  V to  $\pm 18$  V
- Very low supply current (0.45 mA) independent of supply voltage (1 mW/comparator at +5 V)
- Low input bias current: 20 nA typ.
- Low input offset current:  $\pm 3$  nA typ.
- Low input offset voltage:  $\pm 1$  mV typ.
- Input common-mode voltage range includes ground
- Low output saturation voltage: 80 mV typ. ( $I_{\text{sink}} = 4$  mA)
- Differential input voltage range equal to the supply voltage
- TTL, DTL, ECL, MOS, CMOS compatible outputs
- Available in DIP8, SO-8, TSSOP8, MiniSO-8, and DFN8 2 x 2 mm packages


### Description

The LM193, LM293, and LM393 devices consist of two independent low voltage comparators designed specifically to operate from a single supply over a wide range of voltages. Operation from split power supplies is also possible.


These comparators also have a unique characteristic in that the input common-mode voltage range includes ground even though operated from a single power supply voltage.




**DIP8**  
(plastic package)



**SO-8**  
(plastic micropackage)



**TSSOP8**  
(thin shrink small outline package)



**MiniSO-8**  
(plastic micropackage)




**DFN8 2 x 2 mm**  
(plastic micropackage)

## Contents

|          |                                                                |           |
|----------|----------------------------------------------------------------|-----------|
| <b>1</b> | <b>Pin connections</b> .....                                   | <b>3</b>  |
| <b>2</b> | <b>Schematic diagram</b> .....                                 | <b>4</b>  |
| <b>3</b> | <b>Absolute maximum ratings and operating conditions</b> ..... | <b>5</b>  |
| <b>4</b> | <b>Electrical characteristics</b> .....                        | <b>6</b>  |
| <b>5</b> | <b>Typical applications</b> .....                              | <b>8</b>  |
| <b>6</b> | <b>Package information</b> .....                               | <b>11</b> |
| 6.1      | DIP8 package information .....                                 | 12        |
| 6.2      | SO-8 package information .....                                 | 13        |
| 6.3      | TSSOP8 package information .....                               | 14        |
| 6.4      | MiniSO-8 package information .....                             | 15        |
| 6.5      | DFN8 package information .....                                 | 16        |
| <b>7</b> | <b>Ordering information</b> .....                              | <b>18</b> |
| <b>8</b> | <b>Revision history</b> .....                                  | <b>19</b> |


# 1 Pin connections

Figure 1. Pin connections (top view)



## 2 Schematic diagram

Figure 2. Schematic diagram (1/2 LM193)



### 3 Absolute maximum ratings and operating conditions

**Table 1. Absolute maximum ratings**

| Symbol                   | Parameter                                                                                                    | Value                         | Unit                 |
|--------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------|
| $V_{CC}$                 | Supply voltage                                                                                               | $\pm 18$ or 36                | V                    |
| $V_{id}$                 | Differential input voltage                                                                                   | $\pm 36$                      | V                    |
| $V_{in}$                 | Input voltage                                                                                                | -0.3 to +36                   | V                    |
|                          | Output short-circuit to ground <sup>(1)</sup>                                                                | Infinite                      |                      |
| $R_{thja}$               | Thermal resistance junction to ambient <sup>(2)</sup><br>SO-8<br>TSSOP8<br>DIP8<br>MiniSO-8<br>DFN8 2 x 2 mm | 125<br>120<br>85<br>190<br>57 | $^{\circ}\text{C/W}$ |
| $R_{thjc}$               | Thermal resistance junction to case <sup>(2)</sup><br>SO-8<br>TSSOP8<br>DIP8<br>MiniSO-8<br>DFN8 2 x 2 mm    | 40<br>37<br>41<br>39          | $^{\circ}\text{C/W}$ |
| $T_j$                    | Maximum junction temperature                                                                                 | 150                           | $^{\circ}\text{C}$   |
| $T_{stg}$                | Storage temperature range                                                                                    | -65 to +150                   | $^{\circ}\text{C}$   |
| ESD Class <sup>(3)</sup> | HBM: human body model                                                                                        | H1B                           |                      |
|                          | MM: machine model                                                                                            | M2                            |                      |
|                          | CDM: charged device model                                                                                    | C5                            |                      |

- Short-circuits from the output to  $V_{CC+}$  can cause excessive heating and potential destruction. The maximum output current is approximately 20 mA independent of the magnitude of  $V_{CC+}$ .
- Short-circuits can cause excessive heating and destructive dissipation. Values are typical.
- ESD class definition from AEC-Q100:  
HBM class H1B: ESD voltage level from 500 V to 1000 V  
MM class M2: ESD voltage level from 100 V to 200 V  
CDM class C5: ESD voltage level greater than 1500 V.

**Table 2. Operating conditions**

| Symbol     | Parameter                                                                                                                                                    | Value                                      | Unit               |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|--------------------|
| $V_{CC}$   | Supply voltage ( $V_{CC+} - V_{CC-}$ )                                                                                                                       | 2 to 36                                    | V                  |
| $V_{icm}$  | Common mode input voltage range ( $V_{CC+} = 30\text{ V}$ ) <sup>(1)</sup><br>$T_{amb} = +25\text{ }^{\circ}\text{C}$<br>$T_{min} \leq T_{amb} \leq T_{max}$ | 0 to $V_{CC+} - 1.5$<br>0 to $V_{CC+} - 2$ | V                  |
| $T_{oper}$ | Operating free-air temperature range<br>LM193, LM193A<br>LM293, LM293A<br>LM393, LM393A                                                                      | -55 to +125<br>-40 to +105<br>0 to +70     | $^{\circ}\text{C}$ |

- The input common-mode voltage of either input signal voltage should not be allowed to go negative by more than 0.3 V. The high end of the common-mode voltage range is  $V_{CC+} - 1.5\text{ V}$ , but either or both inputs can go to +30 V without damage.

## 4 Electrical characteristics

**Table 3.**  $V_{CC}^+ = +5V$ ,  $V_{CC}^- = 0V$ ,  $T_{amb} = +25\text{ }^{\circ}C$  (unless otherwise specified)

| Symbol     | Parameter                                                                                                                            | LM193A - LM293A<br>LM393A |             |            | LM193- LM293<br>LM393 |             |            | Unit          |
|------------|--------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------------|------------|-----------------------|-------------|------------|---------------|
|            |                                                                                                                                      | Min.                      | Typ.        | Max.       | Min                   | Typ.        | Max.       |               |
| $V_{io}$   | Input offset voltage <sup>(1)</sup><br>$T_{min} \leq T_{amb} \leq T_{max}$                                                           |                           | 1           | 2<br>4     |                       | 1           | 5<br>9     | mV            |
| $I_{io}$   | Input offset current<br>$T_{min} \leq T_{amb} \leq T_{max}$                                                                          |                           | 3           | 25<br>100  |                       | 3           | 50<br>150  | nA            |
| $I_{ib}$   | Input bias current ( $I^+$ or $I^-$ ) <sup>(2)</sup><br>$T_{min} \leq T_{amb} \leq T_{max}$                                          |                           | 20          | 100<br>300 |                       | 20          | 250<br>400 | nA            |
| $A_{vd}$   | Large signal voltage gain<br>$V_{CC} = 15\text{ V}$ , $R_L = 15\text{ k}\Omega$ , $V_o = 1\text{ V}$ to $11\text{ V}$                | 50                        | 200         |            | 50                    | 200         |            | V/mV          |
| $I_{CC}$   | Supply current (all comparators)<br>$V_{CC} = +5\text{ V}$ , no load<br>$V_{CC} = +30\text{ V}$ , no load                            |                           | 0.45<br>0.6 | 1<br>2.5   |                       | 0.45<br>0.6 | 1<br>2.5   | mA            |
| $V_{id}$   | Differential input voltage <sup>(3)</sup>                                                                                            |                           |             | $V_{CC}^+$ |                       |             | $V_{CC}^+$ |               |
| $V_{OL}$   | Low level output voltage<br>$V_{id} = -1\text{ V}$ , $I_{sink} = 4\text{ mA}$<br>$T_{min} \leq T_{amb} \leq T_{max}$                 |                           | 80          | 400<br>700 |                       | 80          | 400<br>700 | mV            |
| $I_{OH}$   | High level output current<br>$V_{CC} = V_o = 30\text{ V}$ , $V_{id} = 1\text{ V}$<br>$T_{min} \leq T_{amb} \leq T_{max}$             |                           | 0.1         | 1          |                       | 0.1         | 1          | nA<br>$\mu A$ |
| $I_{sink}$ | Output sink current $V_{id} = 1\text{ V}$ , $V_o = 1.5\text{ V}$                                                                     | 6                         | 18          |            | 6                     | 18          |            | mA            |
| $t_{re}$   | Response time <sup>(4)</sup><br>$R_L = 5.1\text{ k}\Omega$ connected to $V_{CC}^+$                                                   |                           | 1.3         |            |                       | 1.3         |            | $\mu s$       |
| $t_{rel}$  | Large signal response time<br>$R_L = 5.1\text{ k}\Omega$ connected to $V_{CC}^+$<br>$e_l = \text{TTL}$ , $V_{(ref)} = +1.4\text{ V}$ |                           | 300         |            |                       | 300         |            | ns            |

1. At output switch point,  $V_o \approx 1.4\text{ V}$ ,  $R_s = 0$  with  $V_{CC}^+$  from  $5\text{ V}$  to  $30\text{ V}$ , and over the full common-mode range ( $0\text{ V}$  to  $V_{CC}^+ - 1.5\text{ V}$ ).
2. The direction of the input current is out of the IC due to the PNP input stage. This current is essentially constant, independent of the state of the output, so no loading charge exists on the reference of input lines.
3. Positive excursions of input voltage may exceed the power supply level. As long as the other voltage remains within the common-mode range, the comparator will provide a proper output state. The low input voltage state must not be less than  $-0.3\text{ V}$  (or  $0.3\text{ V}$  below the negative power supply, if used).
4. The response time specified is for a  $100\text{ mV}$  input step with  $5\text{ mV}$  overdrive. For larger overdrive signals  $300\text{ ns}$  can be obtained.

Figure 3. Supply current vs. supply voltage




Figure 4. Input current vs. supply voltage




Figure 5. Output saturation voltage vs. output current




Figure 6. Response time for various input overdrives - negative transition





Figure 7. Response time for various input overdrives - positive transition



## 5 Typical applications

Figure 8. Basic comparator




Figure 9. Driving TTL




Figure 10. Low frequency op amp




Figure 11. Driving CMOS




Figure 12. Low frequency op amp





Figure 13. Transducer amplifier










**Figure 14. Low frequency op amp with offset adjust****Figure 15. Zero crossing detector (single power supply)****Figure 16. Limit comparator****Figure 17. Crystal controlled oscillator****Figure 18. Split-supply applications - zero crossing detector****Figure 19. Comparator with a negative reference**

Figure 20. Two-decade high frequency VCO



## 6 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

## 6.1 DIP8 package information

Figure 21. DIP8 package outline




Table 4. DIP8 package mechanical data

| Symbol | Dimensions  |      |       |        |       |       |
|--------|-------------|------|-------|--------|-------|-------|
|        | Millimeters |      |       | Inches |       |       |
|        | Min.        | Typ. | Max.  | Min.   | Typ.  | Max.  |
| A      |             |      | 5.33  |        |       | 0.210 |
| A1     | 0.38        |      |       | 0.015  |       |       |
| A2     | 2.92        | 3.30 | 4.95  | 0.115  | 0.130 | 0.195 |
| b      | 0.36        | 0.46 | 0.56  | 0.014  | 0.018 | 0.022 |
| b2     | 1.14        | 1.52 | 1.78  | 0.045  | 0.060 | 0.070 |
| c      | 0.20        | 0.25 | 0.36  | 0.008  | 0.010 | 0.014 |
| D      | 9.02        | 9.27 | 10.16 | 0.355  | 0.365 | 0.400 |
| E      | 7.62        | 7.87 | 8.26  | 0.300  | 0.310 | 0.325 |
| E1     | 6.10        | 6.35 | 7.11  | 0.240  | 0.250 | 0.280 |
| e      |             | 2.54 |       |        | 0.100 |       |
| eA     |             | 7.62 |       |        | 0.300 |       |
| eB     |             |      | 10.92 |        |       | 0.430 |
| L      | 2.92        | 3.30 | 3.81  | 0.115  | 0.130 | 0.150 |

## 6.2 SO-8 package information

Figure 22. SO-8 package outline




Table 5. SO-8 package mechanical data

| Symbol | Dimensions  |      |      |        |       |       |
|--------|-------------|------|------|--------|-------|-------|
|        | Millimeters |      |      | Inches |       |       |
|        | Min.        | Typ. | Max. | Min.   | Typ.  | Max.  |
| A      |             |      | 1.75 |        |       | 0.069 |
| A1     | 0.10        |      | 0.25 | 0.004  |       | 0.010 |
| A2     | 1.25        |      |      | 0.049  |       |       |
| b      | 0.28        |      | 0.48 | 0.011  |       | 0.019 |
| c      | 0.17        |      | 0.23 | 0.007  |       | 0.010 |
| D      | 4.80        | 4.90 | 5.00 | 0.189  | 0.193 | 0.197 |
| E      | 5.80        | 6.00 | 6.20 | 0.228  | 0.236 | 0.244 |
| E1     | 3.80        | 3.90 | 4.00 | 0.150  | 0.154 | 0.157 |
| e      |             | 1.27 |      |        | 0.050 |       |
| h      | 0.25        |      | 0.50 | 0.010  |       | 0.020 |
| L      | 0.40        |      | 1.27 | 0.016  |       | 0.050 |
| L1     |             | 1.04 |      |        | 0.040 |       |
| k      | 0           |      | 8°   | 1°     |       | 8°    |
| ccc    |             |      | 0.10 |        |       | 0.004 |

## 6.3 TSSOP8 package information

Figure 23. TSSOP8 package outline




Table 6. TSSOP8 package mechanical data

| Symbol | Dimensions  |      |      |        |        |       |
|--------|-------------|------|------|--------|--------|-------|
|        | Millimeters |      |      | Inches |        |       |
|        | Min.        | Typ. | Max. | Min.   | Typ.   | Max.  |
| A      |             |      | 1.20 |        |        | 0.047 |
| A1     | 0.05        |      | 0.15 | 0.002  |        | 0.006 |
| A2     | 0.80        | 1.00 | 1.05 | 0.031  | 0.039  | 0.041 |
| b      | 0.19        |      | 0.30 | 0.007  |        | 0.012 |
| c      | 0.09        |      | 0.20 | 0.004  |        | 0.008 |
| D      | 2.90        | 3.00 | 3.10 | 0.114  | 0.118  | 0.122 |
| E      | 6.20        | 6.40 | 6.60 | 0.244  | 0.252  | 0.260 |
| E1     | 4.30        | 4.40 | 4.50 | 0.169  | 0.173  | 0.177 |
| e      |             | 0.65 |      |        | 0.0256 |       |
| k      | 0°          |      | 8°   | 0°     |        | 8°    |
| L      | 0.45        | 0.60 | 0.75 | 0.018  | 0.024  | 0.030 |
| L1     |             | 1    |      |        | 0.039  |       |
| aaa    |             |      | 0.10 |        |        | 0.004 |

## 6.4 MiniSO-8 package information

Figure 24. MiniSO-8 package outline




Table 7. MiniSO-8 package mechanical data

| Symbol | Dimensions  |      |      |        |       |       |
|--------|-------------|------|------|--------|-------|-------|
|        | Millimeters |      |      | Inches |       |       |
|        | Min.        | Typ. | Max. | Min.   | Typ.  | Max.  |
| A      |             |      | 1.1  |        |       | 0.043 |
| A1     | 0           |      | 0.15 | 0      |       | 0.006 |
| A2     | 0.75        | 0.85 | 0.95 | 0.030  | 0.033 | 0.037 |
| b      | 0.22        |      | 0.40 | 0.009  |       | 0.016 |
| c      | 0.08        |      | 0.23 | 0.003  |       | 0.009 |
| D      | 2.80        | 3.00 | 3.20 | 0.11   | 0.118 | 0.126 |
| E      | 4.65        | 4.90 | 5.15 | 0.183  | 0.193 | 0.203 |
| E1     | 2.80        | 3.00 | 3.10 | 0.11   | 0.118 | 0.122 |
| e      |             | 0.65 |      |        | 0.026 |       |
| L      | 0.40        | 0.60 | 0.80 | 0.016  | 0.024 | 0.031 |
| L1     |             | 0.95 |      |        | 0.037 |       |
| L2     |             | 0.25 |      |        | 0.010 |       |
| k      | 0°          |      | 8°   | 0°     |       | 8°    |
| ccc    |             |      | 0.10 |        |       | 0.004 |

## 6.5 DFN8 package information

Figure 25. DFN8 2 x 2 x 0.6 mm package outline (pitch 0.5 mm)





Table 8. DFN8 2 x 2 x 0.6 mm package mechanical data (pitch 0.5 mm)

| Symbol | Dimensions  |      |      |        |       |       |
|--------|-------------|------|------|--------|-------|-------|
|        | Millimeters |      |      | Inches |       |       |
|        | Min.        | Typ. | Max. | Min.   | Typ.  | Max.  |
| A      | 0.51        | 0.55 | 0.60 | 0.020  | 0.022 | 0.024 |
| A1     |             |      | 0.05 |        |       | 0.002 |
| A3     |             | 0.15 |      |        | 0.006 |       |
| b      | 0.18        | 0.25 | 0.30 | 0.007  | 0.010 | 0.012 |
| D      | 1.85        | 2.00 | 2.15 | 0.073  | 0.079 | 0.085 |
| D2     | 1.45        | 1.60 | 1.70 | 0.057  | 0.063 | 0.067 |
| E      | 1.85        | 2.00 | 2.15 | 0.073  | 0.079 | 0.085 |
| E2     | 0.75        | 0.90 | 1.00 | 0.030  | 0.035 | 0.039 |
| e      |             | 0.50 |      |        | 0.020 |       |
| L      |             |      | 0.50 |        |       | 0.020 |
| ddd    |             |      | 0.08 |        |       | 0.003 |

**Figure 26. DFN8 2 x 2 footprint recommendation**

## 7 Ordering information

**Table 9. Order codes**

| Order code          | Temperature range | Package    | Packing                  | Marking |
|---------------------|-------------------|------------|--------------------------|---------|
| LM193AD<br>LM193ADT | -55 °C, +125 °C   | SO-8       | Tube or<br>tape and reel | 193A    |
| LM193D<br>LM193DT   |                   |            |                          | 193     |
| LM193AN             |                   | DIP8       | Tube                     | LM193AN |
| LM193N              |                   |            |                          | LM193N  |
| LM293AD<br>LM293ADT | -40 °C, +105 °C   | SO-8       | Tube or<br>tape and reel | 293A    |
| LM293D<br>LM293DT   |                   |            |                          | 293     |
| LM293AN             |                   | DIP8       | Tube                     | LM293AN |
| LM293N              |                   |            |                          | LM293N  |
| LM293PT             |                   | TSSOP8     | Tape and reel            | 293     |
| LM293ST             |                   | MiniSO-8   | Tape and reel            | K512    |
| LM293QT             |                   | DFN8 2 x 2 | Tape and reel            | K59     |
| LM393AD<br>LM393ADT | 0 °C, +70 °C      | SO-8       | Tube or<br>tape and reel | 393A    |
| LM393D<br>LM393DT   |                   |            |                          | 393     |
| LM393AN             |                   | DIP8       | Tube                     | LM393AN |
| LM393N              |                   |            |                          | LM393N  |
| LM393PT             |                   | TSSOP8     | Tape and reel            | 393     |
| LM393ST             |                   | MiniSO-8   | Tape and reel            | M393    |
| LM393QT             |                   | DFN8 2 x 2 | Tape and reel            | K5C     |

## 8 Revision history

**Table 10. Document revision history**

| Date        | Revision | Changes                                                                                                                                                                                                                                                                                                                                                        |
|-------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 02-Jul-2002 | 1        | First release.                                                                                                                                                                                                                                                                                                                                                 |
| 02-Jan-2005 | 2        | Class A of the product included in the datasheet.                                                                                                                                                                                                                                                                                                              |
| 02-May-2005 | 3        | PPAP references inserted in the datasheet, see <a href="#">Table 7: Ordering information on page 18</a> .                                                                                                                                                                                                                                                      |
| 02-Jul-2005 | 4        | Modification on PPAP references - Errors on part numbers, see <a href="#">Table 7: Ordering information on page 18</a> .                                                                                                                                                                                                                                       |
| 22-Nov-2005 | 5        | Modification on <a href="#">Table 3 on page 6</a> . LM293,A must be -40/+105°C instead of -40/+125°C.                                                                                                                                                                                                                                                          |
| 16-Feb-2006 | 6        | Unit error for $V_{OI}$ parameter see <a href="#">Table 3 on page 6</a> .                                                                                                                                                                                                                                                                                      |
| 23-Aug-2007 | 7        | Corrected error in DIP8 package information related to lead thickness, see <a href="#">Figure 21 on page 12</a> .<br>Added values for $R_{thja}$ and $R_{thjc}$ , and ESD parameters in <a href="#">Table 1: Absolute maximum ratings</a> .                                                                                                                    |
| 08-Nov-2007 | 8        | Updated MiniSO-8 package information.<br>Reformatted package information.<br>Added automotive grade order codes.                                                                                                                                                                                                                                               |
| 19-Feb-2008 | 9        | Corrected error in SO-8 package mechanical data: E dimension in drawing was marked with an F in table.                                                                                                                                                                                                                                                         |
| 15-Dec-2008 | 10       | Corrected heading in <a href="#">Figure 5</a> .                                                                                                                                                                                                                                                                                                                |
| 22-Feb-2010 | 11       | Deleted automotive grade order codes for LM293 and LM393.                                                                                                                                                                                                                                                                                                      |
| 22-Jun-2011 | 12       | Updated typical performance curves.<br>Updated typical values on <a href="#">Table 3 on page 6</a> .<br>Updated ESD parameters with ESD classes in <a href="#">Table 1: Absolute maximum ratings</a> .<br>Added DFN8 2x2mm package mechanical drawing.<br>Added DFN8 2x2mm recommended footprint.<br>Added DFN8 2x2mm order codes in <a href="#">Table 9</a> . |
| 27-Jun-2012 | 13       | Updated <a href="#">Features</a> (added package information), <a href="#">Description</a> (added RPNs), <a href="#">Figure 1: Pin connections (top view)</a> moved to page 3, added <a href="#">Contents</a> , updated marking of the LM293QT device in <a href="#">Table 9</a> , minor text corrections throughout document.                                  |
| 18-Jan-2013 | 14       | Updated <a href="#">Table 8</a> (added dimensions in inches).                                                                                                                                                                                                                                                                                                  |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2013 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9