




SERIES: PBO-3 | **DESCRIPTION:** AC-DC POWER SUPPLY

FEATURES


- up to 3 W continuous power
- ultra-compact SIP package
- available in straight-pin and bent-pin configurations
- wide input voltage range
- over current and short circuit protections
- 3,000 Vac isolation
- UL 60950-1, CE safety approvals
- efficiency up to 77%



| MODEL | output voltage (Vdc) | output current | | output power max (W) | ripple and noise ¹ max (mVp-p) | efficiency ² typ (%) |
|------------|-------------------------|----------------|-------------|----------------------------|---|---------------------------------------|
| | | min (mA) | max (mA) | | | |
| PBO-3-S3.3 | 3.3 | 60 | 600 | 1.98 | 150 | 65 |
| PBO-3-S5 | 5 | 60 | 600 | 3 | 150 | 70 |
| PBO-3-S9 | 9 | 33.3 | 333 | 3 | 150 | 73 |
| PBO-3-S12 | 12 | 25 | 250 | 3 | 150 | 74 |
| PBO-3-S15 | 15 | 20 | 200 | 3 | 150 | 75 |
| PBO-3-S24 | 24 | 12.5 | 125 | 3 | 150 | 77 |

Notes: 1. At full load, nominal input, 20 MHz bandwidth oscilloscope, with a 1 µF ceramic and 10 µF electrolytic capacitor on the output.
 2. At 230 Vac input.
 3. All specifications are measured at Ta=25°C, humidity <75%, 115 or 230 Vac input voltage, and rated output load unless otherwise specified.

PART NUMBER KEY



INPUT

| parameter | conditions/description | min | typ | max | units |
|---------------------------|------------------------|-----|-----|------|-------|
| voltage | | 85 | | 305 | Vac |
| | | 70 | | 430 | Vdc |
| frequency | | 47 | | 63 | Hz |
| current | at 115 Vac | | | 0.12 | A |
| | at 277 Vac | | | 0.06 | A |
| inrush current | at 115 Vac | | 13 | | A |
| | at 277 Vac | | 23 | | A |
| no load power consumption | at 230 Vac | | | 0.25 | W |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|----------------------------|---|-----|--------------|-----|--------|
| capacitive load | 3.3 Vdc output models | | | 820 | μF |
| | 5 Vdc output models | | | 680 | μF |
| | 9/12 Vdc output models | | | 470 | μF |
| | 15 Vdc output models | | | 330 | μF |
| | 24 Vdc output models | | | 100 | μF |
| initial set point accuracy | 3.3 Vdc output models | | | ±6 | % |
| | all other models | | | ±5 | % |
| line regulation | at full load | | | | |
| | 3.3 Vdc output models all other models | | ±2.5 ±1.5 | | % % |
| load regulation | from 10~100% load | | ±2.5 | | % |
| switching frequency | | | | 65 | kHz |
| temperature coefficient | | | ±0.15 | | %/°C |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------|---------------------------|-----|-----|-----|-------|
| over current protection | auto recovery | 110 | | 500 | % |
| short circuit protection | continuous, auto recovery | | | | |

SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|---------------------|--|-------|-----|-----|-------|
| isolation voltage | input to output for 1 minute | 3,000 | | | Vac |
| safety approvals | UL 60950-1, EN 60950-1 | | | | |
| safety class | class II | | | | |
| conducted emissions | CISPR22/EN55022 Class A, (external circuit required, see figure 1) | | | | |
| | CISPR22/EN55022 Class B, (external circuit required, see figure 2) | | | | |
| radiated emissions | CISPR22/EN55022 Class A, (external circuit required, see figure 1) | | | | |
| | CISPR22/EN55022 Class B, (external circuit required, see figure 2) | | | | |
| ESD | IEC/EN61000-4-2 Class B, contact ±4 kV | | | | |
| radiated immunity | IEC/EN61000-4-3 Class A, 10V/m (external circuit required, see figure 2) | | | | |
| EFT/burst | IEC/EN61000-4-4 Class B, ±2 kV (external circuit required, see figure 1) | | | | |
| | IEC/EN61000-4-4 Class B, ±4 kV (external circuit required, see figure 2) | | | | |
| surge | IEC/EN61000-4-5 Class B, line to line ±1 kV (external circuit required, see figure 1) | | | | |
| | IEC/EN61000-4-5 Class B, line to line ±1 kV/line to ground ±2 kV (external circuit required, see figure 2) | | | | |
| conducted immunity | IEC/EN61000-4-6 Class A, 10 Vr.m.s (external circuit required, see figure 2) | | | | |

Notes: 1. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

SAFETY & COMPLIANCE (CONTINUED)

| parameter | conditions/description | min | typ | max | units |
|------------------------------|--|---------|-----|-----|-------|
| voltage dips & interruptions | IEC/EN61000-4-11 Class B, 0%-70% (external circuit required, see figure 2) | | | | |
| MTBF | as per MIL-HDBK-217F at 25 °C | 300,000 | | | hours |
| RoHS | 2011/65/EU | | | | |

Notes: 1. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | see derating curves | -40 | | 85 | °C |
| storage temperature | | -40 | | 105 | °C |
| storage humidity | non-condensing | | | 85 | % |

SOLDERABILITY

| parameter | conditions/description | min | typ | max | units |
|----------------|------------------------|-----|-----|-----|-------|
| hand soldering | for 3~5 seconds | 350 | 360 | 370 | °C |
| wave soldering | for 5~10 seconds | 255 | 260 | 265 | °C |




DERATING CURVES


load vs. ambient temperature
(at 85~110 Vac / 70~130 Vdc input voltage)



load vs. ambient temperature
(at 110~305 Vac / 130~430 Vdc input voltage)




load vs. input voltage
(at 25°C)




EFFICIENCY CURVES

Efficiency Curve
(Efficiency vs. Input Voltage)



Efficiency Curve
(Efficiency vs. Load Current)



MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|------------|---|-----|-----|-----|----------|
| dimensions | vertical models: 35.00 x 11.00 x 18.00 (1.38 x 0.43 x 0.71 inches) right-angle models: 35.00 x 18.00 x 11.00 (1.38 x 0.71 x 0.43 inches) | | | | mm mm |
| weight | | | 6 | | g |

MECHANICAL DRAWING

Vertical Orientation



units: mm[inch]

tolerance: $\pm 0.50[\pm 0.020]$


pin section tolerance: $\pm 0.10[\pm 0.004]$

| PIN CONNECTIONS | |
|-----------------|----------|
| PIN | Function |
| 1 | AC (N) |
| 3 | AC (L) |
| 5 | +V(CAP) |
| 7 | -V(CAP) |
| 10 | -Vo |
| 12 | +Vo |

Note: 1. It is required to add C1 between pins 5 & 7 (see application circuits).



Note: Grid 2.54*2.54mm



MECHANICAL DRAWING (CONTINUED)

Right-angle Orientation





units: mm[inch]

tolerance: ± 0.50 [± 0.020]

pin section tolerance: ± 0.10 [± 0.004]

| PIN CONNECTIONS | |
|-----------------|----------|
| PIN | Function |
| 1 | AC (N) |
| 3 | AC (L) |
| 5 | +V(CAP) |
| 7 | -V(CAP) |
| 10 | -Vo |
| 12 | +Vo |

Note: 1. It is required to add C1 between pins 5 & 7 (see application circuits).



APPLICATION CIRCUIT




Table 1

| Recommended External Circuit Components | | | | | | | | | | | |
|---|-------------------|---------|-------|-------|-----------------|------------|-------------------|-----------------|-----------------|----------|-----------|
| Vo (Vdc) | FUSE ¹ | MOV1 | NTC | L2 | C1 ¹ | CY0 | C2 ^{1,2} | L1 ¹ | C3 ¹ | TVS | C4 |
| 3.3 | 1A/300V | S14K350 | 13D-5 | 4.7mH | 10µF/450V | 1nF/400Vac | 270µF/16V | 4.7µH | 120µF/25V | SMBJ7.0A | 0.1µF/50V |
| 5 | 1A/300V | S14K350 | 13D-5 | 4.7mH | 10µF/450V | 1nF/400Vac | 270µF/16V | 4.7µH | 68µF/35V | SMBJ7.0A | 0.1µF/50V |
| 9 | 1A/300V | S14K350 | 13D-5 | 4.7mH | 10µF/450V | 1nF/400Vac | 270µF/16V | 4.7µH | 68µF/35V | SMBJ12A | 0.1µF/50V |
| 12 | 1A/300V | S14K350 | 13D-5 | 4.7mH | 10µF/450V | 1nF/400Vac | 270µF/16V | 4.7µH | 68µF/35V | SMBJ20A | 0.1µF/50V |
| 15 | 1A/300V | S14K350 | 13D-5 | 4.7mH | 10µF/450V | 1nF/400Vac | 470µF/35V | 4.7µH | 47µF/35V | SMBJ20A | 0.1µF/50V |
| 24 | 1A/300V | S14K350 | 13D-5 | 4.7mH | 10µF/450V | 1nF/400Vac | 220µF/35V | 4.7µH | 47µF/35V | SMBJ30A | 0.1µF/50V |

Note: 1. Required components.
2. For 3.3, 5, 9, & 12 Vdc outputs, C2 should be a solid-state capacitor.

EMC RECOMMENDED CIRCUIT




Table 2

| Recommended External Circuit Components | |
|---|----------------------|
| FUSE | 1A/300V, slow fusing |
| MOV2 | S14K350 |
| LCM | 3.50mH |
| CX | 0.1µF/310 Vac |
| LDM | 0.33mH |
| CY2/CY3 | 1nF/400 Vac |
| R2/R3 | 12Ω/2W |
| CY1 | 2.2nF/400 Vac |

Note: Also refer to Table 1.

Notes: 3. C1 is required for both AC and DC inputs.
4. It is required to add pi-type filter circuit (C2, C3, & L1) to the output. The capacitors are recommended to be high frequency and low impedance electrolytic capacitors. For capacitance and rated ripple current of capacitors, refer to the datasheets provided by the manufacturers. Voltage derating of capacitors should be 80% or above.
5. When operating in the -40~+20°C temperature range, it is recommended to use a 22 µF / 450 V capacitor for C1.
6. C4 is a ceramic capacitor used to filter high frequency noise.
7. For current of L1 & L2 refer to the datasheets provided by the manufacturers. Current derating should be 80% or above.
8. TVS is a recommended component to protect post-circuits (if converter fails).
9. It is required to have a distance ≥6.4 mm for safety between external components in primary and secondary circuit.
10. It is recommended to add an insulation sheet between the bottom of the right-angle versions and the PCB when mounting.

REVISION HISTORY

| rev. | description | date |
|------|---------------------------|------------|
| 1.0 | initial release | 10/18/2016 |
| 1.01 | internal IC changed | 05/11/2017 |
| 1.02 | updated efficiency curves | 02/05/2018 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9