

Product: [9914](#) 



50 Ohm Wireless Transmission Cable, RG8, 10 AWG, Solid BC, Foil + 95% TC Braid, PVC Jkt, CMG

Product Description

50 Ohm Wireless Transmission Cable, RG8, 10 AWG, Solid Bare Copper Conductor , PE Insulation, Foil + 95% Tinned Copper Braid Shield, PVC Jacket, CMG rated

Technical Specifications

Product Overview

Suitable Applications:	Wireless microphones, Two-Way Radios, Amateur (Ham) Radio, Low Power FM, GPS, RFID (Radio Frequency Identification)
------------------------	---

Construction Details

RG Type:	8
----------	---

Conductor

AWG	Stranding	Nom. Diameter	Material
10	Solid	0.103 in	BC - Bare Copper

Insulation

Material	Nom. Diameter
PE - Polyethylene (Foam)	0.285

Outer Shield Material

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
2	Braid	Tinned Copper (TC)		95%

Outer Jacket Material

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.403 in

Electrical Characteristics

VSWR

Frequency [MHz]	Max. VSWR
5-2250 MHz	1.43:1

Attenuation

Frequency	Nom. Attenuation [dB/100ft]
5 MHz	0.4 dB/100ft
10 MHz	0.5 dB/100ft
50 MHz	1.0 dB/100ft
100 MHz	1.4 dB/100ft
200 MHz	1.8 dB/100ft
400 MHz	2.6 dB/100ft
700 MHz	3.6 dB/100ft
900 MHz	4.1 dB/100ft
1000 MHz	4.4 dB/100ft

1500 MHz	5.5 dB/100ft
1800 MHz	6.1 dB/100ft
2000 MHz	6.5 dB/100ft
2500 MHz	7.5 dB/100ft
3000 MHz	8.3 dB/100ft
4000 MHz	9.9 dB/100ft

Power Rating

Frequency [MHz]	Max. Power Rating [W]
5 MHz	4,021 W
10 MHz	3,217 W
50 MHz	1,609 W
100 MHz	1,149 W
200 MHz	894 W
400 MHz	619 W
700 MHz	447 W
1,000 MHz	366 W
1,500 MHz	293 W
2,000 MHz	248 W
2,500 MHz	215 W
3,000 MHz	194 W
4,000 MHz	163 W

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Impedence	Nom. Velocity
1.0 Ohm/1000ft	1.3 Ohm/1000ft	24.8 pF/ft	50 Ohm	82%

Voltage

UL Voltage Rating	Non-UL Voltage Rating
30 V RMS (UL AWM Style 1354)	300 V RMS

Mechanical Characteristics

Temperature

UL Rating	Operating
60°C (UL AWM Style 1354)	-30°C to +75°C

Bend Radius

Installation Min.
4.0 in

Bulk Cable Weight:	101 lbs/1000ft
Max. Pull Tension:	194 lbs

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	UL1685 FT4 Loading, FT4
NEC / UL Compliance:	CMG
AWM Compliance:	1354
CEC / C(UL) Compliance:	CMG
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.310 Revision Date: 06-19-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product

Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9