



Featuring superior reliability for smartphones and tablet devices, the Nano-SIM card socket mates seamlessly with standard Nano-SIM as well as specially fitted micro-SIM cards

The continued miniaturization of Subscriber Identity Module (SIM) cards with the introduction of Nano-SIM – a 4th generation SIM card standard - to make PCB space for more electronic components, a larger battery and slimmer phone design, has left micro-SIM card users with existing cards that are too big and too thick to fit standard sized Nano-SIM card sockets. Some users have resorted to trimming their micro-SIM cards to fit the smaller socket but realize their micro-SIM cards are still too thick to fit sockets that accept only standard, 0.67mm height Nano-SIM cards.

Molex has designed a Nano-SIM card socket shell with a 1.30mm profile height to enable use of standard height (0.67mm) Nano-SIM cards as well as the thicker (0.76mm) specially fitted micro-SIM cards. The series is used with a 0.30mm block-style SIM connector (series 78545) to provide a high contact normal force (0.30N) that ensures card-to-socket contact integrity and electrical reliability.

The 3-piece socket design with its separate block-style SIM connector and the ejector tray lowers the risk of SMT warpage especially during high IR-processing temperatures.

This compact set of components comes complete with card polarization and detection, as well as tray-locking features. Removal of SIM card is easy. Simply insert a paper clip (with 0.80mm diameter) into the pin-hole located on the right of the tray cover and the tray ejects instantly.

All parts are halogen-free for environmental sustainability and are shipped in embossed tape-on-reel packaging.

For more information, visit our website at: www.molex.com/link/nanosim.html

Block-style SIM Connector with Nano-SIM Card Socket Shell

(For use with customer-supplied ejector tray)

78545 SIM Connector, Block-style, 0.30mm height

78790 Nano-SIM Card Socket Shell, 1.30mm height

Use with Ejector Tray (customer-supplied, customizable upon request)



Nano-SIM Card Socket Shell, 1.30mm height (Series 78790)



Block-Style SIM Connector, 0.30mm height (Series 78545)



Recommended assembly with SIM connector and Nano-SIM card socket shell fitted with customer-supplied ejector tray

Features and Benefits

Block-Style SIM Connector (Series 78545)

High Contact Normal Force (0.30N)	Improves card-to-socket (electrical) contact when used with card and socket shell
0.38micron Gold (Au) on contact and 0.05micron Gold-flash on soldertail	Ensures high connector reliability by providing a stable and low contact resistance over the operating life of applications
0.30mm connector height	For maximum vertical space savings in low-profile applications
Rounded geometry of contact terminals	Ensures smooth gliding action of the SIM card during insertion
Halogen-free, lead-free	For environmental sustainability

Specifications

Block-Style SIM Connector (Series 78545)

Reference Information

Packaging: Embossed Tape-on-Reel
Use With:
 Nano-SIM or modified micro-SIM cards
Terminal Used: Copper Alloy
Designed In: Millimeters
RoHS: Yes
Halogen Free: Yes
Glow Wire Compliant: No

Electrical

Voltage (max.): 15V DC
Current (max.): 0.5A per contact
Low Level Contact Resistance (max.):
 100 milliohm initial
Dielectric Withstanding Voltage:
 500V AC
Insulation Resistance (min.):
 1000 Megohm

Mechanical

Contact Normal Force: (min.) 0.30N
Tray Insertion Force with card (min.):
 0.30N
Tray Withdrawal Force with card (max.):
 20N
Solder Joint Peel Strength (min.): 20N
Durability:
 240-550 cycles per hour to 500 cycles

Physical

Housing:
 LCP, UL94V-0, Glass-filled, Black
Contact: Copper Alloy
Plating:
 Contact Area —
 0.38µm (15µ") Gold (Au)
 Solder Tail Area —
 0.05µm (2µ") Gold (Au) Flash
 Other Areas —
 Nickel (Ni) Plating
 Underplating —
 2.00µm (µ") Nickel (Ni)
Operating Temperature:
 -30 to +85°C

Features and Benefits

Socket Shell (Series 78790)

1.30mm socket shell profile height	Accepts both standard 0.67mm Nano-SIM as well as modified, 0.76mm height micro-SIM cards
Miniature socket footprint	Frees up expensive PCB real estate for maximum space and cost savings
Tray lock feature	Ensures secure locking of tray when inserted
Detect Switch with First-Mate-Last-Break capability	For reliable tray and SIM card detection
Integral shell tabs and stainless steel tab on shaft housing	Reinforces soldering hold-down of socket and housing components
Card polarization features	Ensure correct card orientation when used with socket

Specifications

Socket Shell (Series 78790)

Reference Information

Packaging: Embossed Tape-on-Reel
Use With:
 Nano-SIM or modified micro-SIM cards
Terminal Used: Copper Alloy
Designed In: Millimeters
RoHS: Yes
Halogen Free: Yes
Glow Wire Compliant: No

Electrical

Voltage (max.): 10V DC
Current (max.): 0.5A per contact
Low Level Contact Resistance (max.):
 100 milliohm initial
Dielectric Withstanding Voltage:
 500V AC
Insulation Resistance (min.):
 1000 Megohm

Mechanical

Contact Normal Force: (min.) 0.30N
Tray Insertion Force with card (min.):
 0.30N
Tray Withdrawal Force with card (max.):
 20N
Durability:
 1000 cycles at rate of 720 cycles per hour max.

Physical


Housing: Insert mold, LCP, UL94V-0
Contact: Copper Alloy
Plating
(Detect Spring of 78790 Socket):
 Contact Area —
 0.127µm (5µ") Gold (Au)
 Solder Tail Area —
 1.27µm (50µ") Tin (Sn)
 Underplating —
 1.27µm (50µ") Nickel (Ni)
Plating (Shell of 78790 Socket):
 Contact and Soldering Area —
 0.025µm (1µ") Gold (Au)
 Underplating —
 1.27µm (50µ") Nickel (Ni)
Plating (Shaft of 78790 Socket):
 Solder Tail Area —
 1.27µm (50µ") Tin (Sn)
Operating Temperature:
 -40 to +85°C

Applications

- Smartphones and mobile devices
- SIM cards
 - Other mobile devices



Tablet PCs



Smartphones

Block-style SIM Connector with Nano-SIM Card Socket Shell



Mobile Wi-Fi* devices

Ordering Information

Order No.	Component	Profile Height (mm)	Number of soldering points
78545-0010	Block-style SIM connector, 0.30mm height	0.30mm	6
78790-1001	Nano-SIM card socket shell with detect switch (tray supplied by customer)	1.30mm	7

*Wi-Fi is a registered trademark of the Wi-Fi Alliance

www.molex.com/link/nanosim.html

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9