



Power Partners

PPWAMD300 Series 300W Power Supply



- IEC 60601-1-2 4th Edition EMC Compliant
- Class I and Class II Versions
- Medical and ITE Approvals
- Meets Efficiency Level VI Requirements
- BF (Body Floating) Rated Output
- Overload Protection
- Short Circuit Protection
- No Load Operation
- IP42 Enclosure

Electrical Specifications

Input

Input Voltage	90-264VAC
Input Frequency	47-63 Hz
Input Current	3A max at 115VAC 1.5A max at 230VAC
Inrush Current	<35A peak at 115VAC, <70A peak at 230VAC, cold start, 25°C
Power Factor	>0.95 at 115VAC full load >0.90 at 230VAC full load

Output

Total Output	300W
Output Voltage	See table
Hold Up Time	>10mS at full load and 115VAC nominal
Touch Current	<100uA At 264VAC, 60Hz
Average Active Efficiency	>88% with 115VAC/60Hz & 230Vac/50Hz input voltage (meets DOE level VI requirements)
No Load Power Consumption	<500mW
Turn on Delay	<3 seconds

Protection

Overvoltage	110%-150% of nominal. Auto recovery
Overload	105%-150% of maximum output current. Auto recovery
Short Circuit	Hiccup mode. Auto recovery
Ingress	IP42 Compliant

Environmental & Operating

Operating Temperature	-30°C to 60°C (refer to derating curve)
Storage Temperature	-20°C to +85°C
Humidity	0% - 90% non-condensing
Altitude	<5000m operational and storage
MTBF:	>200,000 hours per Bellcore TR-32 at full load and 25°C ambient

Compliance

Safety Approvals

USA	ANSI/AAMI ES60601-1
Canada	cUL ES60601-1
Europe	TUV EN60601-1 4th edition
Isolation	CB Report 4000VAC input to output, 2 x MOPP 1500 VAC input to ground, 1 x MOPP

EMC:	FCC Class B Radiated & Conducted CISPR11 Class B Radiated & Conducted EN55011 Class B Radiated & Conducted IEC 61000-3-2: Class A and D
Harmonic Currents	IEC 61000-3-3
Voltage Flicker	IEC 61000-4-2
Electrostatic Discharge	IEC 61000-4-3
Radiated Immunity	IEC 61000-4-4
EFT/Burst	IEC 61000-4-5
Surge Immunity	IEC 61000-4-6
Conducted Immunity	IEC 61000-4-8
Magnetic Field	IEC 61000-4-8
Dips / Interruptions	IEC 61000-4-11

General

Dimensions	8.74"(222mm)L x 4.4"(112mm)W x 1.77"(45mm)H
AC Input Receptacle	IEC60320 C14, C18
DC output Plug	10-pin Molex mini-fit, 4.2mm pitch. Others available upon request
Weight	3.46lb (1.57kg)

Your Partners in Power.....

Power Partners, Inc. | 43 Broad Street | Hudson, MA 01749

Tel: (978)567-9600 | Fax: (978)567-9601

Website: www.powerpartners-inc.com

Specifications subject to change.
PPWAMD300: April 3, 2018

Models and Ratings Chart


Model ^{1,2}	Voltage	Current	Total Power	Load Regulation	Ripple & Noise (P-P) ³	Efficiency Level
PPWAMD300-12	12VDC	25A	300W	±5%	240mV	VI
PPWAMD300-13-2	19VDC	15.79A	300W	±5%	300mV	VI
PPWAMD300-14	24VDC	12.5A	300W	±5%	300mV	VI
PPWAMD300-15	28VDC	10.71A	300W	±5%	300mV	VI
PPWAMD300-18	48VDC	6.25A	300W	±5%	300mV	VI
PPWAMD300-18-1	54VDC	5.56A	300W	±5%	300mV	VI

¹C14 Standard Receptacle. For C18 input receptacle, model numbers are PPWAMD300F, For Example PPWAMD300F-12.



²For switch option model numbers are PPWAMD300-XX-S, for example PPWAMD300-12-S.

³Ripple and noise are measured at 20MHz bandwidth with a 47uF electrolytic capacitor and a 1uF ceramic capacitor in parallel at output connector.


Mechanical Outline



Connector Detail




Front View (IEC320-C14)



Front View (IEC320-C18)



Derating Chart



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9