

# Chip Inductors - 0302CS (0805)



- 0302 size – 20% smaller than our 0402CS inductors
- 35 inductance values from 0.67 to 34 nH
- High Q values – up to 131 at 2.4 GHz!

Request free evaluation samples by contacting Coilcraft or visiting [www.coilcraft.com](http://www.coilcraft.com).

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>(nH) | Percent<br>tolerance | 900 MHz |                    | 1.7 GHz |                    | 2.4 GHz |                    | SRF<br>typ <sup>4</sup><br>(GHz) | DCR<br>max <sup>5</sup><br>(Ohms) | Irms <sup>6</sup><br>(mA) |
|--------------------------|---------------------------------|----------------------|---------|--------------------|---------|--------------------|---------|--------------------|----------------------------------|-----------------------------------|---------------------------|
|                          |                                 |                      | L typ   | Q typ <sup>3</sup> | L typ   | Q typ <sup>3</sup> | L typ   | Q typ <sup>3</sup> |                                  |                                   |                           |
| 0302CS-N67XKL_           | 0.67                            | <b>10</b>            | 0.66    | 42                 | 0.66    | 56                 | 0.67    | 70                 | >26                              | 0.021                             | 1600                      |
| 0302CS-1N7XJL_           | 1.7                             | <b>5</b>             | 1.7     | 57                 | 1.7     | 78                 | 1.7     | 95                 | 16.14                            | 0.038                             | 1140                      |
| 0302CS-1N9XJL_           | 1.9                             | <b>5</b>             | 1.9     | 42                 | 1.9     | 65                 | 1.9     | 83                 | 16.06                            | 0.065                             | 910                       |
| 0302CS-2N1XJL_           | 2.1                             | <b>5</b>             | 2.1     | 38                 | 2.1     | 57                 | 2.1     | 72                 | 15.94                            | 0.082                             | 830                       |
| 0302CS-3N0XJL_           | 3.0                             | <b>5</b>             | 3.0     | 56                 | 3.0     | 92                 | 3.0     | 131                | 15.10                            | 0.060                             | 950                       |
| 0302CS-3N3XJL_           | 3.3                             | <b>5</b>             | 3.3     | 56                 | 3.3     | 88                 | 3.3     | 129                | 11.50                            | 0.060                             | 950                       |
| 0302CS-3N5XJL_           | 3.5                             | <b>5</b>             | 3.5     | 60                 | 3.5     | 84                 | 3.5     | 110                | 11.53                            | 0.070                             | 870                       |
| 0302CS-3N8XJL_           | 3.8                             | <b>5</b>             | 3.8     | 60                 | 3.8     | 89                 | 3.8     | 105                | 10.67                            | 0.090                             | 830                       |
| 0302CS-4N0XJL_           | 4.0                             | <b>5</b>             | 4.0     | 52                 | 4.0     | 80                 | 4.1     | 98                 | 11.21                            | 0.100                             | 760                       |
| 0302CS-4N7XJL_           | 4.7                             | <b>5</b>             | 4.6     | 55                 | 4.6     | 88                 | 4.7     | 120                | 12.07                            | 0.074                             | 830                       |
| 0302CS-5N1XJL_           | 5.1                             | <b>5</b>             | 5.1     | 62                 | 5.1     | 92                 | 5.2     | 118                | 9.65                             | 0.074                             | 830                       |
| 0302CS-5N6XJL_           | 5.6                             | <b>5</b>             | 5.5     | 50                 | 5.5     | 71                 | 5.6     | 108                | 6.40                             | 0.120                             | 730                       |
| 0302CS-6N0XJL_           | 6.0                             | <b>5</b>             | 6.0     | 58                 | 6.0     | 82                 | 6.2     | 105                | 8.60                             | 0.140                             | 700                       |
| 0302CS-6N3XJL_           | 6.3                             | <b>5</b>             | 6.3     | 56                 | 6.3     | 80                 | 6.5     | 100                | 9.34                             | 0.155                             | 620                       |
| 0302CS-6N5XJL_           | 6.5                             | <b>5</b>             | 6.5     | 56                 | 6.5     | 80                 | 6.8     | 100                | 8.19                             | 0.200                             | 620                       |
| 0302CS-7N0XJL_           | 7.0                             | <b>5</b>             | 7.0     | 62                 | 7.1     | 84                 | 7.2     | 112                | 8.50                             | 0.103                             | 760                       |
| 0302CS-7N2XJL_           | 7.2                             | <b>5</b>             | 7.2     | 60                 | 7.2     | 82                 | 7.4     | 110                | 9.12                             | 0.112                             | 690                       |
| 0302CS-7N4XJL_           | 7.4                             | <b>5</b>             | 7.3     | 60                 | 7.4     | 82                 | 7.6     | 110                | 7.98                             | 0.112                             | 690                       |
| 0302CS-8N3XJL_           | 8.3                             | <b>5</b>             | 8.2     | 58                 | 8.3     | 80                 | 8.5     | 104                | 8.19                             | 0.150                             | 590                       |
| 0302CS-9N2XJL_           | 9.2                             | <b>5</b>             | 8.9     | 58                 | 9.0     | 83                 | 9.2     | 120                | 7.92                             | 0.115                             | 690                       |
| 0302CS-10NXJL_           | 10.0                            | <b>5</b>             | 10.0    | 58                 | 10.1    | 91                 | 10.2    | 119                | 7.45                             | 0.140                             | 620                       |
| 0302CS-11NXJL_           | 11.0                            | <b>5</b>             | 11.0    | 57                 | 11.2    | 83                 | 11.6    | 105                | 6.85                             | 0.210                             | 590                       |
| 0302CS-12NXJL_           | 12.0                            | <b>5</b>             | 12.0    | 59                 | 12.6    | 88                 | 12.7    | 110                | 6.86                             | 0.170                             | 560                       |
| 0302CS-13NXJL_           | 13.0                            | <b>5</b>             | 13.0    | 53                 | 13.3    | 83                 | 13.8    | 104                | 6.94                             | 0.230                             | 480                       |
| 0302CS-15NXJL_           | 15.0                            | <b>5</b>             | 15.0    | 55                 | 15.4    | 84                 | 15.9    | 106                | 6.20                             | 0.174                             | 560                       |
| 0302CS-16NXJL_           | 16.0                            | <b>5</b>             | 16.0    | 54                 | 16.4    | 85                 | 17.0    | 102                | 6.13                             | 0.210                             | 480                       |
| 0302CS-17NXJL_           | 17.0                            | <b>5</b>             | 16.9    | 52                 | 17.4    | 82                 | 18.2    | 118                | 6.26                             | 0.280                             | 440                       |
| 0302CS-18NXJL_           | 18.0                            | <b>5</b>             | 17.9    | 55                 | 18.5    | 80                 | 19.3    | 111                | 6.03                             | 0.350                             | 390                       |
| 0302CS-19NXJL_           | 19.0                            | <b>5</b>             | 18.9    | 53                 | 19.6    | 85                 | 20.5    | 104                | 5.79                             | 0.260                             | 480                       |
| 0302CS-20NXJL_           | 20.0                            | <b>5</b>             | 19.9    | 56                 | 20.2    | 88                 | 20.8    | 112                | 5.68                             | 0.300                             | 430                       |
| 0302CS-21NXJL_           | 21.0                            | <b>5</b>             | 20.9    | 53                 | 22.0    | 82                 | 24.1    | 95                 | 5.16                             | 0.370                             | 370                       |
| 0302CS-22NXJL_           | 22.0                            | <b>5</b>             | 22.0    | 52                 | 23.1    | 79                 | 25.2    | 94                 | 4.95                             | 0.420                             | 340                       |
| 0302CS-23NXJL_           | 23.5                            | <b>5</b>             | 23.5    | 54                 | 24.6    | 84                 | 27.4    | 92                 | 5.18                             | 0.400                             | 430                       |
| 0302CS-29NXJL_           | 29.0                            | <b>5</b>             | 29.0    | 51                 | 30.5    | 75                 | 33.0    | 90                 | 4.83                             | 0.470                             | 330                       |
| 0302CS-34NXJL_           | 34.0                            | <b>5</b>             | 34.0    | 55                 | 35.5    | 78                 | 38.1    | 94                 | 4.45                             | 0.530                             | 310                       |

1. When ordering, please specify **termination** and **packaging** codes:

**0302CS-34NXJLW**

- Termination:** L = RoHS compliant silver-platinum-glass frit.  
E = Halogen free component. RoHS compliant silver-platinum-glass frit terminations.
- Packaging:** W = 7" machine-ready reel. EIA-481 punched paper tape (2000 parts per full reel).  
U = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter W instead.

- Inductance measured at 250 MHz using a Coilcraft SMD-F fixture in an Agilent/HP 4286 impedance analyzer with Coilcraft-provided correlation pieces.
  - Q measured using an Agilent/HP 4287A with an Agilent/HP 16193 test fixture.
  - SRF measured using an Agilent/HP 8722ES network analyzer and a test fixture with a 0.017" air gap.
  - DCR measured on a micro-ohmmeter and a Coilcraft CCF858 test fixture.
  - Current that causes a 30°C temperature rise from 25°C ambient.
  - Electrical specifications at 25°C.
- Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)  
**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)  
**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)  
**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)  
**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 302-1 Revised 11/01/12

© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

**COILCRAFT** ACCURATE  
**PRECISION** REPEATABLE  
 MEASUREMENTS  
 SEE WEB SITE **TEST FIXTURES**



# 0302CS Series (0805)

## Typical L vs Frequency



**S-Parameter files**  
ON OUR WEB SITE  
**SPICE models**  
ON OUR WEB SITE

## Typical Q vs Frequency



## Irms Derating



**Designer's Kit C370** contains 20 each of all values

**Core material** Ceramic

**Environmental** RoHS compliant, halogen free optional

**Terminations** RoHS compliant silver-platinum-glass frit.

**Weight** 0.4 – 0.5 mg

**Ambient temperature** -40°C to +125°C with Irms current, +125°C to +155°C with derated current

**Storage temperature** Component: -40°C to +155°C. Tape and reel packaging: -40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Temperature Coefficient of Inductance (TCL)** +25 to +125 ppm/°C

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

One per billion hours / one billion hours, calculated per Telcordia SR-332

**Packaging** 2000 per 7" reel. Paper tape: 8 mm wide, 0.5 mm thick, 2 mm pocket spacing

**PCB washing** Tested with pure water or alcohol only. For other solvents, see Doc787\_PCB\_Washing.pdf.



| Amax  | Bmax  | Cmax  | D     | E     | F     | G     | H     |
|-------|-------|-------|-------|-------|-------|-------|-------|
| 0.034 | 0.021 | 0.018 | 0.006 | 0.015 | 0.010 | 0.014 | 0.021 |
| 0,86  | 0,53  | 0,45  | 0,20  | 0,38  | 0,25  | 0,36  | 0,53  |



**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 302-2 Revised 11/01/12  
 © Coilcraft Inc. 2013  
 This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9