

TR-490 Ratchet

Tool Capability:
Crimps barrel and insulation grip independently on No. 22–10 AWG (0,35–6,0 mm²) insulated and non-insulated terminals and connectors: nylon or vinyl insulated, butted or brazed seam.

Crimping Dies:
Insulated No. 22–18 AWG (0,35–0,97 mm²) red color coded.
Insulated no. 16–14 AWG (1,3–25 mm²) blue color coded.
Insulated No. 12–10 AWG (4,0–6,0 mm²) yellow color coded.
Non-Insulated No. 22–14 AWG (0,35–2,5 mm²).
Non-Insulated No. 12–10 (4,0–6,0 mm²).

Field Re-calibration: Calibration adjustment of ratchet can be accomplished in the field. See calibration and maintenance instructions packaged with the tool.

Positive Closure: Ratchet requires full closure of handles to ensure proper crimp. Ratchet release lever allows removal of misplaced terminals.


Materials and Finish: Hardened steel jaws and handles with corrosion resistant finish.

Weight: 0.8 lbs.

Grip: Plastic, red color.

Specifications:
Non-insulated and insulated terminals and connectors from 22–10 AWG shall be crimped with a positive action (ratchet) tool and be UL Listed with that tool. Non-insulated die shall be of an indent shape and insulated die shall be of a flat, smooth shape capable of crimping pre-insulated vinyl and nylon terminals and connectors. Dies shall be marked with the appropriate wire range and insulated dies shall be color coded: red for 22–18 AWG, blue for 16–14 AWG, and yellow for 12–10 AWG. The tool shall be compound lever type with a ratchet mechanism to insure positive closure for full crimping cycle. Tool shall be capable of field adjustment to proper calibration with common tools and materials specified in the maintenance and calibration section of the instruction booklet provided with the tool. The manufacturer shall provide a guide for maintenance procedure and instructions to field inspect for specified die gaps. Jaws shall be hardened steel and coated with a corrosion resistant finish. Tool shall be a 3M Scotchlok TR-490.

3M Terminals and Connectors are ULListed and CSACertified with the TR-490. For specific tooling information, see Tool Selection Guide in the the Appendix.



Product	UPC (054007-)	Wire Range	Tools/ Carton	Tools/ Case
TR-490	70481	22-10	1	10

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9