


# PIN RECEPTACLES

**FOR .048" - .064" DIAMETER PINS (#13 CONTACT)  
FOR .045" - .065" DIAMETER PINS (#23 CONTACT)**

## 0496

**0496-0-15-XX-23-XX-10-0**


Press-fit in .106 mounting hole



## 0368

**0368-0-33-XX-13-XX-10-0**


Wire crimp termination. Accepts wire sizes 16 AWG Max. / 20 AWG Min.



## 8067

**8067-0-19-XX-13-XX-10-0**


Wire Termination. Accepts wire sizes 24 AWG Max. / 28 AWG Min.



## 1105

**1105-0-15-XX-13-XX-04-0**


Press-fit in .080 mounting hole



## 8730

**8730-0-19-XX-23-XX-10-0**


Wire crimp termination. Accepts wire sizes 22 AWG Max. / 26 AWG Min.



## 3667

**3667-0-19-XX-23-XX-10-0**


Wire crimp termination. Accepts wire sizes 18 AWG Max. / 22 AWG Min.



## 9372

**9372-0-15-XX-23-XX-10-0**


Solder mount in .102 min. mounting hole



## 4582

**4582-0-15-XX-23-XX-10-0**


Square press-fit in .040 plated through-hole



## 5834

**5834-0-15-XX-23-XX-10-0**


Press-fit in .107 mounting hole



## 9401

**9401-0-15-XX-23-XX-10-0**


Solder mount in .102 min. mounting hole  
Also available on 24mm wide carrier tape:  
1,100 parts per 13" reel  
See page 194.14 for Tape & Reel details



## 9801

**9801-0-15-XX-23-XX-10-0**


Solder mount in .102 min. mounting hole  
Also available on 16mm wide carrier tape:  
1,200 parts per 13" reel  
See page 194.14 for Tape & Reel details



## 8829

**8829-0-15-XX-23-XX-10-0**

Solder mount in .102 min. mounting hole  
Also available on 24mm wide carrier tape:  
950 parts per 13" reel  
See page 194.14 for Tape & Reel details



### SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$

Diameters:  $\pm .002$

Angles:  $\pm 2^\circ$



**ORDER CODE: XXXX - X - XX - XX - XX - XX - XX - 0**

**BASIC PART #**

**SPECIFY SHELL FINISH:**

**01** 200  $\mu$ " TIN/LEAD OVER NICKEL

◆ **80** 200  $\mu$ " TIN OVER NICKEL (RoHS)

◆ **15** 10  $\mu$ " GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

**01** 200  $\mu$ " TIN/LEAD OVER NICKEL

◆ **80** 200  $\mu$ " TIN OVER NICKEL (RoHS)

◆ **27** 30  $\mu$ " GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#13 or #23 CONTACT (DATA ON PAGE 260)**

(For alternate contact choices, see group G on page 248)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9