





LOC	DIST	REVISIONS						
		P	LTR	DESCRIPTION	DATE	DWN	APVD	
ES	00		G9	ADD NEW DASH NUMBER 2-9	04MAY2012	CZ	SZ	
			H2	REV PER ECR-12-020199	22NOV2012	CZ	SZ	
			H4	ADDED THE NEW DASH NUMBER -33	28DEC2012	ML	SZ	



- 1 "AMP", PART NUMBER, AND DATECODE TO BE MARKED IN AREA SHOWN. PARTS UNDER 2.00 LONG MAY BE MARKED ON BOTH SIDES.
- 2 MATERIAL:
HOUSING - GLASS FILLED HIGH TEMP THERMO PLASTIC,BLACK, UL94 V-0
SIGNAL CONTACT - COPPER ALLOY
POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY.
- 3 CONTACT PLATING - NOBLE METAL PLATING ON CONTACT FUNCTIONAL AREA OF POWER AND SIGNAL CONTACTS
- 4 MECHANICAL CONNECTOR KEEP OUT ZONE.
- 5 DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 6 PCB - HOLE DIAMETERS ARE FINISHED HOLE SIZE.
- 7 PCB - .0453±.0010 DRILLED HOLES PLATED WITH .0003 MIN Sn OVER .001 TO .003 Cu PLATING TO ACHIEVE A .040 DIA HOLE.
- 8 TO GENERAL POWER CONTACT (WITHOUT LP POWER CONTACT), VARIABLE DIMENSIONS PLEASE SEE SHEET 2.
- 9 PLEASE REFER TO PAGE 5 FOR DETAIL DIMENSIONS.
- 10 PLEASE REFER TO PAGE 7 FOR SPECIAL DIMENSIONS.
- 11 FOR LP/S/P CONFIGURATION, OR SPECIAL DIMENSIONS FOR PART 2-6450840-1, PLEASE REFER TO SHEET 2.




THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ALEX SHOAL CHK Sunny Zhao APVD Sunny Zhao	14DEC2007 20DEC2007 20DEC2007	TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC 108-2292 APPLICATION SPEC 114-13251	NAME RIGHT ANGLE HEADER W/ LP CONTACT AND SHORT END MODULES MULTI-BEAM XLE	
MATERIAL 2		0 PLC ±" 1 PLC ±.01 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0050 ANGLES ±2° FINISH 3	SIZE 100779	CAGE CODE C=6450840	RESTRICTED TO -
Customer Drawing		SCALE 4:1	SHEET 1	OF 16	REV H4

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-

.250	2.315	1.535	.860	2.205	.230	2.415	2.555	.1275	6LP + 24S + 3P	3-6450840-3
-	1.135	.8075	.375	1.025	-	1.235	1.375	.1025	2LP + 16S + 2LP	3-6450840-1
.250	2.300	1.520	.845	2.190	.250	2.400	2.540	.170	3P + 24S + 3P	2-6450840-9
.250	3.800	2.270	1.595	3.690	.250	3.900	4.040	.170	6P + 24S + 6P	2-6450840-7
.250	4.400	2.370	2.095	4.290	.250	4.500	4.640	.170	8P + 8S + 8P	1-6450840-6
.250	1.700	1.145	.645	1.590	.250	1.800	1.940	.195	2P + 16S + 2P	2-6450840-5
.250	6.000	3.970	2.095	5.890	.250	6.100	6.240	.170	8P + 72S + 8P	2-6450840-3
.250	2.500	1.470	1.095	2.390	.250	2.600	2.740	.170	4P + 12S + 4P	2-6450840-2
.230	5.585	1.5025	.645	5.475	.250	5.685	5.825	.170	2P + 32S + 4LP + 14P	2-6450840-1
.250	3.520	2.990	2.265	3.410	.230	3.620	3.760	.1525	18LP + 24S + 2P	2-6450840-0
-	1.300	1.020	.345	1.190	-	1.400	1.540	.170	1P + 24S + 1P	1-6450840-5
.200	3.300	2.020	1.345	3.190	.200	3.400	3.540	.170	6HDP + 24S + 6HDP	1-6450840-2
.200	2.400	1.520	.945	2.290	.200	2.500	2.640	.170	4HDP + 20S + 4HDP	1-6450840-1
.250	2.400	1.370	1.095	2.290	.250	2.500	2.640	.170	4P + 8S + 4P	1-6450840-0
.200	2.100	1.220	.945	1.990	.200	2.200	2.340	.170	4HDP + 8S + 4HDP	6450840-9
-	8	-	-	-	-	-	-	-	4P+16S+24S+2HDP	6450840-8
-	1.300	1.020	.345	1.190	-	1.400	1.540	.170	1P + 24S + 1P	6450840-7
-	2.480	2.1525	1.345	2.370	.250	2.580	2.720	.170	5P + 32S + 2LP	6450840-6
.250	3.400	2.120	1.395	3.290	.250	3.500	3.640	.170	5P + 24S + 5P	6450840-5
.200	5.150	2.670	1.345	5.040	.300	5.250	5.390	.195	4ACP + 48S + 12HDP	6450840-4
.230	5.495	4.4275	3.170	5.385	.250	5.595	5.735	.195	12P + 48S + 8LP	6450840-3
-	2.315	-	-	2.205	-	2.415	2.555	.170	3P+ 1LP + 24S + 3HDP	6450840-2
DIM T	DIM V	DIM R	DIM W	DIM U	DIM S	DIM D	DIM L	DIM K	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±"

1 PLC ±.01

2 PLC ±.01

3 PLC ±.005

4 PLC ±.0050

ANGLES ±7°

FINISH

MATERIAL

-

DWN
ALEX SHOAL

CHK
Suryy Zhao

APVD
Suryy Zhao

14DEC2007

20DEC2007

20DEC2007

NAME

RIGHT ANGLE HEADER
W/ LP CONTACT AND SHORT END MODULES
MULTI-BEAM XLE

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

100779

6450840

2

16

H4

Customer Drawing

SCALE

1:1

SHEET


2

OF

16


REV

H4




LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER												SIGNAL												POWER									
			P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	1	2	3	4	5	6	7	8	9	10	11	12	LP1	LP2	LP3	LP4	LP5	LP6	LP7	LP8		
6450840-3	D		TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	LT	LT	LT	LT	LT	LT	LT	LT			
	Y5													Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5									Y5		
	R5													R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5									R5		
	O5													O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5									O5		
12P + 48S + 8LP																																				



PART NUMBER	ROWS		POWER				SIGNAL												POWER																
			P1	P2	P3	P4	1	2	3	4	5	6	7	8	9	10	11	12	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15	P16					
6450840-4	D		TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT					
	Y5						Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5														Y5	Y5		
	R5						R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5														R5	R5	R5	
	O5						O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5														O5	O5	O5	
4ACP + 48S + 12HDP		HD																															HD		




HOLD DOWN	HD
.120 SIGNAL PRESS FIT CON, ROW A,MLBF	O1
.120 SIGNAL PRESS FIT CON, ROW B,MLBF	R1
.120 SIGNAL PRESS FIT CON, ROW C,MLBF	Y1
.120 SIGNAL PRESS FIT CON, ROW D,MLBF	Z1
.120 SIGNAL PRESS FIT CON, ROW A,STD	O5
.120 SIGNAL PRESS FIT CON, ROW B,STD	R5
.120 SIGNAL PRESS FIT CON, ROW C,STD	Y5
.120 SIGNAL PRESS FIT CON, ROW D,STD	Z5
.120 PRESS FIT LOWER POWER CON	LT
.120 PRESS FIT POWER CON	TT
DESCRIPTION	IDENTIFIER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ALEX SHOAL CHK Sunny Zhao APVD Sunny Zhao	14DEC2007 20DEC2007 20DEC2007	 TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	RIGHT ANGLE HEADER W/ LP CONTACT AND SHORT END MODULES MULTI-BEAM XLE
		0 PLC ±.01			
		1 PLC ±.01			
		2 PLC ±.01			
MATERIAL	FINISH	3 PLC ±.005		SIZE	CAGE CODE
		4 PLC ±.0050			
		ANGLES ±.2°			
		WEIGHT			
		DRAWING NO		RESTRICTED TO	
		A100779C=6450840			
Customer Drawing		SCALE		SHEET	OF
		1:1		4	16
				REV	H4


LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER	SIGNAL						POWER	
			P1	1	2	3	4	5	6	P2	
6450840-7	D C B A			Z5	Z5	Z5	Z5	Z5	Z5		
				Y5	Y5	Y5	Y5	Y5	Y5		
				R5	R5	R5	R1	R5	R5		
				05	05	05	05	05	05		
IP + 24S + IP											




PART NUMBER	ROWS		POWER	SIGNAL						POWER	
			P1	1	2	3	4	5	6	P2	
1-6450840-5	D C B A			Z5	Z5	Z5	Z5	Z5	Z5		
				Y5	Y5	Y5	Y5	Y5	Y5		
				R5	R5	R5	R5	R5	R5		
				05	05	01	05	05	05		
IP + 24S + IP											

LAYOUT OF 1-6450840-5 IS SAME AS 6450840-7.



PART NUMBER: 6450840-8

PART NUMBER	ROWS		POWER				SIGNAL				BLANK	SIGNAL						POWER		
			P1	P2	P3	P4	1	2	3	4		5	6	7	8	9	10	P5	P6	
6450840-8	D C B A						Z5	Z5	Z5	Z5	BLANK	Z5	Z5	Z5	Z5	Z5	Z5			
							Y5	Y5	Y5	Y5		Y5	Y5	Y5	Y5	Y5	Y5			
							R5	R5	R5	R5		R5	R5	R5	R5	R5	R5			
							05	05	05	05		05	05	05	05	05	05			
4P + 16S + 24S + 2HDP																				



THIS DRAWING IS A CONTROLLED DOCUMENT.

OWN
ALEX SHOAL
CHK
Sunny Zhao
APVD
Sunny Zhao

14DEC2007
20DEC2007
20DEC2007

DIMENSIONS:
INCHES

0 PLC ±
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.0050
ANGLES ±.2°
FINISH

TOLERANCES UNLESS OTHERWISE SPECIFIED:

PRODUCT SPEC
108-2292
APPLICATION SPEC
114-13251
WEIGHT
Customer Drawing

NAME
RIGHT ANGLE HEADER
W/ LP CONTACT AND SHORT END MODULES
MULTI-BEAM XLE

SIZE
A100779

CAGE CODE
C=6450840

DRAWING NO
REV
H4


RESTRICTED TO

SCALE
1:1


SHEET
6

OF
16


REV
H4

[illegible]4805 (3/11)


This technical drawing shows a side elevation of a 1200mm wide door assembly. The door is composed of 12 glass panes arranged in a 4x3 grid. The panes are separated by a grid of muntins. The door is shown in a closed position, with a handle on the right side. The drawing includes dimensions for the overall width (1200mm) and the height of the glass panes (1000mm). The door is shown with a frame and a handle.


[illegible]4805 (3/11)

PART NUMBER	ROWS		LOW POWER																SIGNAL						POWER				
			LP1	LP2	LP3	LP4	LP5	LP6	LP7	LP8	LP9	LP10	LP11	LP12	LP13	LP14	LP15	LP16	LP17	LP18	1	2	3	4	5	6		P1	P2
2-6450840-0	D		LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT		
	Y5																			Y5	Y5	Y5	Y5	Y5					
	R5																			R5	R5	R5	R5	R5					
	O5	O5																		O5	O5	O5	O5						
	A	HD																										HD	
18LP + 24S + 2P																													

4805 (3/11)


PART NUMBER	ROWS		POWER								SIGNAL		POWER								
			P1	P2	P3	P4	P5	P6	P7	P8	1	2	P9	P10	P11	P12	P13	P14	P15	P16	
1-6450840-6	D C B A									Z5	Z5										
										Y5	Y5										
										R5	R5										
										Q5	Q5										
8P + 8S + 8P																					



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ALEX SHOI	14DEC2007		
DIMENSIONS: INCHES		CW Sunny Zhao	20DEC2007	TE Connectivity	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD Sunny Zhao	20DEC2007	NAME	
		PRODUCT SPEC		RIGHT ANGLE HEADER W/ LP CONTACT AND SHORT END MODULES MULTI-BEAM XLE	
1 P/LC ±. 2 P/LC ±. 3 P/LC ±.01 4 P/LC ±.005 5 P/LC ±.0050 ANGLES ±°		APPLICATION SPEC		SIZE CAGE CODE DRAWING NO RESTRICTED TO	
FINISH		WEIGHT -		A 00779 ©=6450840 -	
MATERIAL		Customer Drawing		SCALE 1:1	SHEET 10 OF 16 REV H4

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER		SIGNAL								LOW POWER				POWER																		
			P1	P2	I	2	3	4	5	6	7	8	LP1	LP2	LP3	LP4	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15	P16					
2-6450840-1	D		TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	LT	LT	LT	LT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT				
	Y5				Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5																					Y5	Y5	Y5
	R5				R5	R5	R5	R5	R5	R5	R5	R5																					R5	R5	R5
	A	HD			O5	O5	O5	O5	O5	O5	O5	O5	O5																				HD		
2P + 32S + 4LP + 14P																																			



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
ALEX SHOAL
CHK
Sunny Zhao
APVD
Sunny Zhao

14DEC2007
20DEC2007
20DEC2007

DIMENSIONS:
INCHES

0 PLC ±"
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.0050
ANGLES #2°
FINISH -

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

PRODUCT SPEC
108-2292
APPLICATION SPEC
114-13251
WEIGHT -

MATERIAL -

Customer Drawing

SCALE 1:1

NAME
RIGHT ANGLE HEADER
W/ LP CONTACT AND SHORT END MODULES
MULTI-BEAM XLE

SIZE
A1

CAGE CODE
00779

DRAWING NO
C=6450840

RESTRICTED TO
-

SHEET 11 OF 16

REV H4



TE Connectivity

4805 (3/11)

LOC		DIST		REVISONS			
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-


PART NUMBER	ROWS		POWER				SIGNAL			POWER				
			P1	P2	P3	P4	1	2	3	P5	P6	P7	P8	
2-6450840-2	D		TT	TT	TT	TT	Z5	Z5	Z5	TT	TT	TT	TT	
	C						Y5	Y5	Y5					
	B						R5	R5	R5					
		A	HD				O5	O5	O5					HD
4P + 12S + 4P														

PART NUMBER	ROWS		POWER		SIGNAL				POWER		
			P1	P2	1	2	3	4	P3	P4	
2-6450840-5	D		TT	TT	Z5	Z5	Z5		TT	TT	
	C				Y5	Y5	Y5				
	B				R5	R5	R5				
		A	HD		O5	O5	O5				HD
2P + 16S + 2P											



LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER								SIGNAL																		POWER													
			P1	P2	P3	P4	P5	P6	P7	P8	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	P9	P10	P11	P12	P13	P14	P15	P16						
2-6450840-3	D C B A		TT	TT	TT	TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	TT	TT	TT	TT	TT						
										Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5									Y5	Y5	Y5	Y5	Y5	Y5
										R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5									R5	R5	R5	R5	R5	R5
										O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5									O5	O5	O5	O5	O5	O5
8P + 72S + 8P																																					HD					




THIS DRAWING IS A CONTROLLED DOCUMENT.			DWN ALEX SHOAL	14DEC2007	TE Connectivity		
			CHK Sunny Zhao	20DEC2007			
DIMENSIONS: INCHES			APVD Sunny Zhao	20DEC2007	NAME RIGHT ANGLE HEADER W/ LP CONTACT AND SHORT END MODULES MULTI-BEAM XLE		
			TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		
					108-2292		
					APPLICATION SPEC		
					114-13251		
					WEIGHT		
					-		
					Customer Drawing		
					SCALE 1:1		
					SHEET 13 OF 16		
					REV H4		

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER						SIGNAL						POWER						
			P1	P2	P3	P4	P5	P6	1	2	3	4	5	6	P7	P8	P9	P10	P11	P12	
2-6450840-7	D		TT	TT	TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	TT	TT	TT	
	C								Y5	Y5	Y5	Y5	Y5	Y5							
	B								R5	R5	R5	R5	R5	R5							
	A	HD							O1	O5	O5	O5	O5	O5							HD
6P + 24S + 6P																					

G7



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
ALEX SHOAL
CHK
Sunny Zhao
APVD
Sunny Zhao

14DEC2007
20DEC2007
20DEC2007

DIMENSIONS:
INCHES

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ±"
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.0050
ANGLES ±2°
FINISH

MATERIAL

-

Customer Drawing

NAME

RIGHT ANGLE HEADER
W/ LP CONTACT AND SHORT END MODULES
MULTI-BEAM XLE

SIZE

A1

CAGE CODE

100779

DRAWING NO

6450840

RESTRICTED TO

-

SCALE

1:1

SHEET

14

OF


16


REV

H4

TE Connectivity


LOC	DIST	REVISONS			
ES	00	P	LTR	DESCRIPTION	DATE
		-		SEE SHEET 1	-

PART NUMBER	ROWS		POWER			SIGNAL						POWER			
			P1	P2	P3	1	2	3	4	5	6	P4	P5	P6	
2-6450840-9	D		TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	
	Y5					Y5	Y5	Y5	Y5	Y5					
	R5					R5	R5	R5	R5	R5					
	01					05	05	05	05	05					
3P + 24S + 3P															




H2

PART NUMBER	ROWS		LOW POWER		SIGNAL				LOW POWER		
			LP1	LP2	1	2	3	4	LP3	LP4	
3-6450840-1	D		LT	LT	Z1	Z5	Z5	Z5	LT	LT	
	C				Y5	Y5	Y5	Y5			
	B				R5	R5	R5	R5			
	A				05	05	05	05			
2LP + 16S + 2LP											



LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN
ES	00	-	-	SEE SHEET 1	-	-

PART NUMBER	ROWS		POWER						SIGNAL						POWER				
			LP1	LP2	LP3	LP4	LP5	LP6	1	2	3	4	5	6	P1	P2	P3		
3-6450840-3	D C B A			LT	LT	LT	LT	LT	LT	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	
										Y5	Y5	Y5	Y5	Y5	Y5				
										R5	R5	R5	R5	R5	R5				
										O5	O5	O5	O5	O5	O5				
6LP + 24S + 3P																			



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ALEX SHOAL	14DEC2007	TE Connectivity	
		CHK Sunny Zhao	20DEC2007		
DIMENSIONS: INCHES		APVD Sunny Zhao	20DEC2007	NAME RIGHT ANGLE HEADER W/ LP CONTACT AND SHORT END MODULES MULTI-BEAM XLE	
		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	
		0 PLC ±.01 1 PLC ±.01 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0050 ANGLES ±2° FINISH		108-2292 APPLICATION SPEC	
MATERIAL -		WEIGHT -		SIZE A100779	
		Customer Drawing		CAGE CODE 6450840	
				RESTRICTED TO -	
				SCALE 1:1	
				SHEET 16	
				OF 16	
				REV H4	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9