

Fluke 971

Temperature Humidity Meter

Technical Data



Quickly take accurate humidity and temperature readings in the air. Temperature and humidity are two important factors in maintaining optimal comfort levels and good indoor air quality. The Fluke 971 is

invaluable for facility maintenance and utility technicians, HVAC-service contractors, and specialists who assess indoor air quality (IAQ). Lightweight, rugged, and easy to hold, the Fluke 971 is the perfect tool for monitoring problem areas.

The Fluke 971 has:

- Backlit dual display of humidity and temperature
- 99 record storage capacity
- Ergonomic design with belt clip and protective holster
- Quick-response capacitance sensor with twist-open protective cover

General Features

- Compact and lightweight (190 g/6.7 oz)
- Temperature range from -20 °C to 60 °C (-4 °F to 140 °F)
- Measures dew point and wet bulb
- Relative humidity from 5 % to 95 %
- Min/Max/Avg data hold
- Low battery indicator

Specifications

| | |
|--------------------------------------|---|
| Temperature range | -20 °C to 60 °C (-4 °F to 140 °F) |
| Temperature accuracy | |
| 0 °C to 45 °C | ± 0.5 °C |
| -20 °C to 0 °C and 45 °C to 60 °C | ± 1.0 °C |
| 32 °F to 113 °F | ± 1.0 °F |
| -4 °F to 32 °F and 113 °F to 140 °F | ± 2.0 °F |
| Resolution | 0.1 °C / 0.1 °F |
| Temperature update rate | 500 ms |
| Temperature sensor type | NTC |
| Relative humidity range | 5 % to 95 % R.H. |
| Relative humidity accuracy | |
| 10 % to 90 % R.H. @ 23 °C (73.4 °F) | ± 2.5 % R.H. |
| <10 %, > 90 % R.H. @ 23 °C (73.4 °F) | ± 5.0 % R.H. |
| Resolution | 0.1 % R.H. |
| Response time (humidity) | For 90 % of total range - 60 sec. with 1 m/s air movement |
| Humidity sensor | Electronic capacitance polymer film sensor |
| Data storage | 99 points |

Specifications cont.

| | |
|------------------------------|---|
| Operating temperature | |
| Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| Humidity | 0 °C to 55 °C (32 °F to 131 °F) |
| Storage temperature | -20 °C to 60 °C (-4 °F to 140 °F) at < 80 % R.H. (with battery removed) |
| Weight | 190 g (6.7 oz) |
| Dimensions (HxWxD) | 194 mm x 60 mm x 34 mm (7.6 in x 2.4 in x 1.3 in) |
| Battery type | 4 AAA alkaline batteries |
| Battery life | 200 Hours |
| Safety approval | Electromagnetic compatibility: Complies with EN 61326-1 |
| Warranty | 12 months |

* Humidity sensor hysteresis (excursion of 10 % to 90 % to 10 % R.H.): ± 1 % R.H. with 1 m/s air movement
 * Temperature coefficient: 0.1 times the applicable accuracy specification per °C from 0 °C to 18 °C and 28 °C to 50 °C (32 °F to 64 °F and 83 °F to 122 °F)

Other IAQ Tools from Fluke

Fluke 983 Particle Counter

- Simultaneous display of six size channels on a bright, backlit LCD
- 5000 sample record capacity
- Logged samples include date, time, particle counts, sample volume, temperature and relative humidity
- Rechargeable NiMH battery providing up to 8 hours continuous operation
- Selectable sample time, count data, programmable delay
- Built-in relative humidity and temperature sensors



CO-210 Carbon Monoxide Probe

- Use as an accessory to a digital multimeter with DC millivolt inputs
- Displays CO level readings from 0 to 999 ppm, with a resolution of 1 ppm and accuracy of ± 3 %.
- Also used as a standalone device with an LED indicator and beeper that triggers with increasing frequency as CO levels rise.



CO-205 Aspirator Kit

The CO-205 flue gas sampling accessory kit contains all the components necessary to provide a clean sample for the Fluke family of gas measuring devices. The CO-205 accessory kit includes:

- Stainless steel sampling tube
- Industrial-grade hand operated aspirator to draw flue sample
- Easily replaceable particulate filter
- Specially designed nose cap for connection to the Fluke CO-210/CO-220.



CO-220 Carbon Monoxide Meter

- Standalone CO meter that does not require a digital multimeter
- Large backlit LCD displays CO levels from 0 to 1000 ppm.
- Beeper triggers with increasing frequency as CO levels rise.
- MAX hold function stores and displays the maximum CO level.
- Automatic sensor zeroing and self-test upon startup.



Fluke. *Keeping your world up and running.*

Fluke Corporation
 PO Box 9090, Everett, WA USA 98206
 Fluke Europe B.V.
 PO Box 1186, 5602 BD
 Eindhoven, The Netherlands
 For more information call:
 In the U.S.A. (800) 443-5853 or
 Fax (425) 446-5116
 In Europe/M-East/Africa (31 40) 2 675 200 or
 Fax (31 40) 2 675 222
 In Canada (800) 36-FLUKE or
 Fax (905) 890-6866
 From other countries +1 (425) 446-5500 or
 Fax +1 (425) 446-5116
 Web access: <http://www.fluke.com>

©2005 Fluke Corporation. All rights reserved.
 Printed in U.S.A. 11/2005 2457037 D-EN-N Rev C

Ordering Information

- Fluke-971** Temperature Humidity Meter
- Fluke-983** Particle Counter
- Fluke-CO-205** Aspirator Kit
- Fluke-CO-210** Carbon Monoxide Probe
- Fluke-CO-220** Carbon Monoxide Meter

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9