



Performance Masking Tape

233+

Technical Data

Product Description	A high performance crepe paper masking tape for most paint masking applications.			
Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Smooth crepe paper with a solvent resistant saturant	Rubber	Green	55m (60.17 yds.)

Typical Physical Properties **Note:** The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	38 oz./in. width (41 N/100mm)	D-3330
Tensile Strength:	25 lbs./in. width (438 N/100mm)	D-3759
Elongation at Break:	10%	D-3759
Tape Thickness:	6.7 mils (0.17mm)	D-3652
Temperature Use Range:	Up to 250°F (121°C) for up to 30 minutes	

- General Information**
- Removes cleanly when subject to temperatures up to 250°F (121°C) for up to 30 minutes
 - The heat and solvent resistance will provide excellent performance in most paint masking applications
 - Provides a balanced construction for applications where clean removal and conformability are critical requirements
 - Excellent transfer resistance to “difficult to remove from” surfaces like EPDM rubber moldings
 - Tape 233+ is better than most conventional masking tapes for sunlight resistance. However, it is still advised that it not be subjected to outdoor exposure or prolonged periods of sunlight. The tape may become difficult to remove.
 - Manufactured in an ISO 9002 registered plant to meet worldwide quality standards

Shelf Life To obtain best performance, use this product within 12 months from date of manufacture and store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

- Application Ideas**
- Excellent paint masking tape
 - Can be used for a variety of holding, bundling, protecting and a vast number of other difficult jobs where a pressure-sensitive tape is needed

Features	Features	Advantages	Benefits
	Proprietary adhesive	Instant adhesion	Sticks easily/allows fast application
		Good holding power	Resists lifting/curling
		Adhesive transfer resistance	Clean removal/helps minimize labor required to remove transferred adhesive

Features (cont.)	Features	Advantages	Benefits
	Bright green color	Improved visibility	Assists in improving edge

Scotch® Performance Masking Tape

233+

page 2 of 2

Controlled crepe paper backing	Smoothness	alignment Good surface contact/provides secure holding
	Thin	Sharp paint line/quality paint job
	Dead stretch	Resists recover
	Improved conformability	Easy handling/allows fast application
Backing saturant	Solvent and moisture resistant	Minimizes bleed-through and rework
Special backsize treatment	Controlled unwind	Easy to use/helps reduce waste
Unique components	Balanced construction	Excellent versatility/efficient tool – helps save time and money

Technical Information and Data The technical information and data, recommendations, and other statements provided in this document are based on tests or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be used with the 3M product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Limited Warranty and Limited Remedy The 3M product will be free from defects in material and manufacture for a period of one (1) year from the date of manufacture. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. If the 3M product is defective within the warranty period stated above, YOUR EXCLUSIVE REMEDY AND 3M'S SOLE OBLIGATION SHALL BE, AT 3M'S OPTION, TO REPLACE OR REPAIR THE 3M PRODUCT OR REFUND THE PURCHASE PRICE OF THE 3M PRODUCT.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, warranty, negligence, or strict liability.



This Industrial Tape and Specialties Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



Industrial Tape and Specialties Division

3M Center, Building 220-7W-03
St. Paul, MN 55144-1000
1 800 362 3550
1 800 223 7427 Fax on Demand
www.3M.com/industrialtape

© 3M 2002
All rights reserved.

70-0709-4841-2
July/17/2002

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9