


CoolSiC™ Automotive Schottky Diode 650V G5

650V/40A Silicon Carbide Schottky Diode in TO247-3

Features

- Revolutionary semiconductor material - Silicon Carbide
- Benchmark switching behavior
- No reverse recovery/ No forward recovery
- Temperature independent switching behavior
- High surge current capability
- Pb-free lead plating; RoHS compliant
- Junction Temperature range from -40°C to 175°C
- System efficiency improvement over Si diodes
- System cost / size savings due to reduced cooling requirements
- Enabling higher frequency / increased power density solutions
- Higher system reliability due to lower operating temperatures
- Reduced EMI



Potential Applications

- Traction inverter
- Booster / DCDC Converter
- On board Charger / PFC



Product Validation

“Qualified for Automotive Applications. Product Validation according to AEC-Q100/101”

Description

The 5th Generation CoolSiC™ Automotive Schottky Diode represents Infineon leading edge technology for Silicon Carbide Schottky Barrier diodes. Thanks to a compact design and a technology based on thin wafers, this family of products shows improved efficiency over all load conditions resulting from both its thermal characteristics and low figure of merit ($Q_C \times V_f$). This product family has been designed to complement Infineon's IGBT and CoolMOS™ portfolio. This ensures meeting the most stringent application requirements in the 650V voltage class.

Product Information	
Ordering Code	AIDW40S65C5
Marking	AD4065C5
Package	PG-TO247-3-41
SP Number	SP001725204

Parameter	Value/Unit
$V_{DC,max}$	650 V
$I_F; T_C < 117^\circ\text{C}$	40 A
$Q_C; V_R = 400\text{ V}$	56 nC
$E_C; V_R = 400\text{ V}$	12.9 μJ
$T_{j,max}$	175 $^\circ\text{C}$

Pin	Definition
Pin 2, case	Cathode
Pin 3	Anode



Table of Contents

Table of Contents

Features..... 1

Potential Applications..... 1

Product Validation..... 1

Description..... 1

Table of Contents..... 2

1 Maximum Ratings..... 3

2 Thermal Characteristics..... 4

3 Electrical Characteristics..... 5

4 Electrical Characteristics Diagrams..... 6

5 Package Outlines..... 9

Revision History..... 10

Maximum Ratings

1 Maximum Ratings

Table 1 Maximum ratings¹

Parameter	Symbol	Value	Unit
Repetitive peak reverse voltage	V_{RRM}	650	V
Continuous forward current for $R_{thJC,max}$ $T_C = 117^\circ\text{C}$, $D=1$	I_F	40	A
Surge non-repetitive forward current, sine halfwave $T_C = 25^\circ\text{C}$, $t_p=10\text{ms}$ $T_C = 150^\circ\text{C}$, $t_p=10\text{ms}$	$I_{F,SM}$	182 153	A
Non-repetitive peak forward current $T_C = 25^\circ\text{C}$, $t_p=10\mu\text{s}$	$I_{F,max}$	1432	A
i^2t value $T_C = 25^\circ\text{C}$, $t_p=10\text{ms}$ $T_C = 150^\circ\text{C}$, $t_p=10\text{ms}$	$\int i^2 dt$	166 118	A^2s
Diode dv/dt ruggedness $V_R=0\ldots 480\text{V}$	dv/dt	100	V/ns
Power dissipation $T_C = 25^\circ\text{C}$	P_{tot}	183	W
Operating temperature	T_j	$-40\ldots 175$	$^\circ\text{C}$
Storage temperature	T_{stg}	$-55\ldots 150$	$^\circ\text{C}$
ESD Human body model, $R=1.5\text{ k}\Omega$, $C=100\text{ pF}$ Charged device model		8 2	kV
Soldering temperature, wavesoldering only allowed at leads, 1.6mm (0.063 in.) from case for 10 s	T_{sold}	260	$^\circ\text{C}$
Mounting Torque (M3 and M4 screws)		70	Ncm

Thermal Characteristics

2 Thermal Characteristics

Table 2 Thermal Characteristics¹

Parameter	Symbol	Values			Unit	Note/Test condition
		Min.	Typ.	Max.		
Thermal resistance, junction–case ²	R_{thJC}	-	0.6	0.8	K/W	
Thermal resistance, junction-ambient ²	R_{thJA}	-	-	62	K/W	

Electrical Characteristics

3 Electrical Characteristics

Table 3 Static Characteristics

Parameter	Symbol	Values			Unit	Note/Test condition
		Min.	Typ.	Max.		
DC blocking voltage	V_{DC}	650	-	-	V	$T_j = 25^{\circ}\text{C}$, $I_R = 0.12\text{ mA}$
Diode forward voltage ³	V_F	-	1.5	1.7		$T_j = 25^{\circ}\text{C}$, $I_F = 40\text{ A}$
		-	1.8	2.1		$T_j = 150^{\circ}\text{C}$, $I_F = 40\text{ A}$
Reverse current	I_R	-	7	120	μA	$V_R = 650\text{ V}$, $T_j = 25^{\circ}\text{C}$
		-	47	-		$V_R = 650\text{ V}$, $T_j = 150^{\circ}\text{C}$

Table 4 Dynamic Characteristics at $T_j=25^{\circ}\text{C}$ unless noted otherwise

Parameter	Symbol	Values			Unit	Note/Test condition
		Min.	Typ.	Max.		
Total capacitive charge	Q_C	-	56	-	nC	$V_R = 400\text{ V}$, $di/dt = 200\text{ A}/\mu\text{s}$, $I_F \leq I_{F,MAX}$, $T_j = 150^{\circ}\text{C}$
Total capacitance	C	-	1138	-	pF	$V_R = 1\text{ V}$, $f = 1\text{ MHz}$
		-	148	-		$V_R = 300\text{ V}$, $f = 1\text{ MHz}$
		-	145	-		$V_R = 600\text{ V}$, $f = 1\text{ MHz}$

Footnotes:

¹ The parameter is not subject to production test- verified by design/characterization.

² $R_{th,JC}$ defined as per JESD-51-14. $R_{th,JA}$ defined as per JESD-51-2.

³ Only the value at 25°C is subject to production test. The value at 150°C is only verified by design/characterization.

Electrical Characteristics Diagrams

4 Electrical Characteristics Diagrams




Figure 1 (LEFT) Power dissipation; $P_{\text{tot}} = f(T_c)$; $R_{\text{thJC,max}}$
(RIGHT) Diode forward current; $I_F = f(T_c)$; $T_j \leq 175$ °C; $R_{\text{thJC,max}}$; parameter: D =duty cycle




Figure 2 (LEFT) Typical forward characteristic; $I_F = f(V_F)$; $t_p = 200$ μs; parameter: T_j
(RIGHT) Typical forward characteristics in surge current; $I_F = f(V_F)$; $t_p = 200$ μs; parameter: T_j

Electrical Characteristics Diagrams




Figure 3 (LEFT) Typical capacitive charge versus current slope (only capacitive charge, guaranteed by design); $Q_C = f(di_F/dt)$; $T_j = 150^\circ\text{C}$; $V_R = 400\text{V}$; $I_F \leq I_{F,max}$
(RIGHT) Typical reverse current versus reverse voltage; $I_R = f(V_R)$; parameter: T_j




Figure 4 (LEFT) Max. Transient thermal impedance; $Z_{thJC} = f(t_p)$; parameter: $D = t_p/T$
(RIGHT) Typ. Capacitance vs. Reverse voltage; $C = f(V_R)$; $T_j = 25^\circ\text{C}$; $f = 1\text{ MHz}$

Electrical Characteristics Diagrams




Figure 5 Typical capacitance stored energy; $E_C = f(V_R)$




Figure 6 Simplified forward characteristics model $V_F = f(I_F)$;
 $-40^\circ\text{C} < T_j < 175^\circ\text{C}$; $I_F < 80\text{ A}$

Package Outlines

5 Package Outlines




Figure 6 Package outline of PG-TO247-3-41 led (Dimensions in mm)



Revision History

Revision History

Document Version	Date of Release	Description of changes
V3.0	26.11.2018	1st release of Data Sheet

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

IMPORTANT NOTICE	
Edition 2017-07-07	
Published by Infineon Technologies AG 81726 München, Germany	The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics technology, delivery terms and conditions and ("Beschaffenhheitsgarantie"). prices please contact your nearest Infineon Technologies office (www.infineon.com).
© 2017 Infineon Technologies AG. All Rights Reserved.	With respect to any examples, hints or any typical values stated herein and/or any information regarding the WARNINGS application of the product, Infineon Technologies hereby Due to technical requirements products may disclaims any and all warranties and liabilities of any kind, contain dangerous substances. For information including without limitation warranties of non- on the types in question please contact your infringement of intellectual property rights of any third nearest Infineon Technologies office. party.
Do you have a question about this document? Email: erratum@infineon.com	
Document reference	In addition, any information given in this document is Except as otherwise explicitly approved by subject to customer's compliance with its obligations Infineon Technologies in a written document stated in this document and any applicable legal signed by authorized representatives of Infineon requirements, norms and standards concerning Technologies, Infineon Technologies' products customer's products and any use of the product of may not be used in any applications where a Infineon Technologies in customer's applications. failure of the product or any consequences of the use thereof can reasonably be expected to
	The data contained in this document is exclusively result in personal injury. intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9