

Features

- Incremental encoder / quadrature output
- Exceptionally long operating life
- Sturdy construction
- Bushing mount
- Available with PC board mounting bracket (optional)
- RoHS compliant*

ECW - Digital Contacting Encoder

Electrical Characteristics

Output ..... 2-bit quadrature code, Channel A leads Channel B by 90 º electrically turning clockwise (CW)
Closed Circuit Resistance ..... 5 ohms maximum
Open Circuit Resistance ..... 100 K ohms minimum
Contact Rating ..... 10 milliamp @ 10 VDC or 0.1 watt maximum
Insulation Resistance (500 VDC) ..... 1,000 megohms minimum
Dielectric Withstanding Voltage (MIL-STD-202 Method 301)
  Sea Level ..... 1,000 VAC minimum
Electrical Travel ..... Continuous
Contact Bounce (15 RPM) ..... 5 milliseconds maximum
RPM (Operating) ..... 120 maximum
Phase Tolerance (CH A to CH B) ..... 90 ° ± 72 °

Environmental Characteristics

Operating Temperature Range ..... -40 ºC to +85 ºC (-40 °F to 185 °F)
Storage Temperature Range ..... -40 ºC to +85 ºC (-40 °F to +185 °F)
Humidity ..... MIL-STD-202, Method 103B, Condition B
Vibration ..... 15 G
  Contact Bounce ..... 0.1 millisecond maximum
Shock ..... 50 G
  Contact Bounce ..... 0.1 millisecond maximum
Rotational Life ..... 200,000 shaft revolutions
IP Rating ..... IP 40

Mechanical Characteristics

Mechanical Angle ..... Continuous
Running Torque (Detented) ..... 0.5 to 1.5 N-cm (0.75 to 2.25 oz-in.)
Undetented Torque ..... 0.17 to 1.0 N-cm (0.25 to 1.50 oz-in)
Mounting Torque ..... 79 N-cm (7 lb.-in.) maximum
Shaft Side Load (Static) ..... 4.5 kg (10 lbs.) minimum
Weight ..... Approximately 21 gms. (0.75 oz.)
Terminals ..... PC pin or solder lug
Soldering Condition
  Manual Soldering ..... 96.5Sn/3.0Ag/0.5Cu solid wire or no-clean rosin cored wire
    370 °C (700 °F) max. for 3 seconds
  Wave Soldering ..... 96.5Sn/3.0Ag/0.5Cu solder with no-clean flux
    260 °C (500 °F) max. for 5 seconds
  Wash processes ..... Not recommended
Marking ..... Manufacturer's name and trademark, part number, and date code.
Hardware ..... One lockwasher and one mounting nut are shipped with each encoder, except where noted in the part number.

Quadrature Output Table – This table is intended to show available outputs as currently defined.

1/4 CYCLE PER DETENT



FULL CYCLE PER DETENT (Normally Open in Detent Shown)



RECOMMENDED INCREMENTAL CONTROL DIAGRAM FOR USE WITH A DEBOUNCE CIRCUIT



*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Dimensional Drawings

BUSHING MOUNTED - HOUSING **A**
Rear-Facing Terminals



PANEL HOLE DIMENSIONS
Bushing Mounted



PCB BRACKET MOUNTED - HOUSING **B**
Dimensions not given are the same as Bushing Mounted.



PCB MOUNTING DIMENSIONS
(Housing Styles B and E)



SOLDER HOLES - HOUSING **C**
Dimensions not given are the same as Bushing Mounted.



SNAP-IN MOUNT - Housing **G**



PCB MOUNTING DIMENSIONS



Shaft Style **B**



Shaft Style **C**



Shaft Style **J**



"D" DIMENSION EXTENDS FROM SHAFT END TO BUSHING FACE
"D" = (SHAFT LENGTH, FMS) – (BUSHING LENGTH)

Shaft Style **R**



Shaft Style **Y**



SLOT DEPTH ("Y" SHAFT) 9.65 (.380) FOR SHAFTS < 1 " LENGTH
14.7 (.578) FOR SHAFTS ≥ 1 " LENGTH

BUSHING MOUNTED - HOUSING **H**
Front-Facing Terminals







FOR TOLERANCES NOT SHOWN
.XX = ± .25 (.010) .XXX = ± .13 (.005)
SHAFT DIMENSIONS ± 1/32"
DIMENSIONS: MM (IN)



Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

ECW - Digital Contacting Encoder

BOURNS®

How to Order

PART NUMBERING SYSTEM

E	C	W	1	J	-	B	2	4	-	B	C	0	0	2	4	L

Code	Rotational Life
C	**200,000 Revolutions**

BUSHING CONFIGURATION	
Code	**Description**
W	**9 mm x 1/4 " Length. Threaded M9x0.75**
L	9 mm x 3/8 " Length. Threaded M9x0.75 (Use B shaft only.)
T	9 mm x 1/4 ". No Thread.

SWITCHING CONFIGURATION (In Detent Position) Applies to performance codes B0012 and C0024 only, use code "0" for all other performance codes.	
Code	**Description**
0	Not Applicable
1	**Normally Open**

ANTI-ROTATION LUG POSITION	
Code	**Description**
J	**9:00 Position**
D	None

SHAFT STYLE (See Outline Drawing for Details)	
Code	**Description**
B	**Plain with Inserted Slot (1/4 " Dia.)**
C	Single Flatted (1/4 " Dia.)
R	Plain with Cross Slot (6 mm Dia.)
Y	Split Shaft Version (.185 " Dia.)
J	Flatted Shaft (3/16 " Dia.)

The sample part number demonstrates the identification code for Bourns contacting encoders.

Boldface features are Bourns standard options. All others are available with higher minimum order quantities.

RoHS IDENTIFIER	
Code	**Description**
L	**Compliant**

PERFORMANCE CODE		
Code	**Detents**	**Cycles/Rev.**
E0006	0	6
E0009	0	9
E0012	0	12
E0024	0	24
E0036	0	36
B0012	12	12
C0006	**24**	6
C0024		**24**
D0009	36	9

HOUSING TERMINAL CONFIGURATION (X indicates "Equipped With"									
	Code								
Features	**A**	**B**	**C**	**D**	**E**	**F**	**G***	**H**	**K**
Terminal Cover	X	**X**			X		X		
Rear-Facing Terminals	X	**X**			X		X		
Solder Holes			X	X		X			
PCB Bracket		**X**		X	X	X			
Hardware Included	X		X		X	X		X	
Snap-In Mount							X		
Forward-Facing Terminals								X	X

*Bushing code T only.

SHAFT LENGTH (FMS)		
Code	**Description**	**Available Shaft Styles**
16	1/2 " Length	B
20	5/8 " (15.9 mm) Length	J
24	**3/4 " (19 mm) Length**	**B, C, J, Y**
28	7/8 " (22.2 mm) Length	B, C, J, Y
32	1 " (25.4 mm) Length	B, C, J, Y
36	1-1/8 " (28.6 mm) Length	B, C, J, Y
	Metric	
19	19 mm Length	R
22	22 mm Length	R
24	24 mm Length	R

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9