TDK·Lambda ZWQ Series

80-170W Quad Output Power Supplies

Features

- Universal Input (85 - 265VAC)
- Power Factor Corrected
- Floating Adjustable Fourth Output
- Low Profile <1U High

Key Market Segments & Applications

Industrial Test COMM Broadcast

RoHS

Specifications

Model		ZWQ80 -5222	ZWQ80 -5223	ZWQ80 -5224	ZWQ80 -5225	ZWQ130 -5222	ZWQ130 -5223	ZWQ130 -5224	ZWQ130 -5225
Input Voltage	-	85-265VAC (47-63Hz), 120-370VDC*							
Input Current (1)	A	1.6 / 0.8				2.6 / 1.3			
Inrush Current (1)	A	14/28							
Power Factor	-	Meets EN61000-3-2							
Temperature Coefficient	-	<0.02%/°C							
Max Output Power (convection)	W	80				130			
Max Output Power (forced air)	W	104	88.7	104	104	170	149.6	170	170
Overpower Protection (2)	W	>109	>93	>109	>109	>173	>152	>173	>173
Minimum Load	A	V1: 0.9A Conv, 1.4A Forced Air				V1: 1.5A Conv, 2.1A Forced Air			
Output Voltage Accuracy	%	±5% for outputs V2 and V3							
Efficiency (Typ)	%	72							
Hold Up Time (1)	ms	20							
Leakage Current	-	0.75mA max, 0.2mA (Typ) at 100VAC / 0.44mA(Typ) at 230VAC							
Remote On / Off	-	See installation manual (Not available with /A cover option)							
Oper Temp (convection cooled)	°C	-10°C to 60°C, derate linearly to 50% load from 40°C to 60°C. (3)							
Oper Temp (forced air cooled)	°C	-10°C to 70°C, derate linearly to 50% load from 50°C to 70°C. (>30cfm airflow)(3)							
Storage Temperature	°C	-30° to +85°C							
Humidity (non condensing)	-	Operating: 30 - 90% RH; Non-operating 10-95% RH							
Withstand Voltage	-	I/P~Grnd 2kVAC (20mA), I/P~O/P 3kVAC (20mA), O/P~Grnd 500VAC (100mA) for 1 min.							
Isolation Resistance	-	>100M at 25°C & 70%RH, Output to Ground 500VDC							
Vibration (non operating)	-	10 - 55Hz (1 minute sweep), 19.6m/s^2 constant X, Y, Z 1 hour							
Shock	-	< 196.1 m/s^2							
Safety Agency Approvals	-	UL60950-1, CSA60950-1, EN60950-1, CE Mark, EN50178							
Conducted & Radiated EMI	-	EN55011, EN55022-B, FCC Class B, VCCI-B							
Immunity	-	EN61000-4-2,-3,-4,-5,-6,-8,-11							
Weight (Typ)	g	550				730			
Size (W x H x D)	mm	93.5 x 35 x 210 (refer to outline drawing)				106 x 35 x 225 (refer to outline drawing)			
Warranty	yrs	One Year							

(1) 100/200VAC
(2) Avoid prolong operation in overload
(3) /A version - additional derating, see installation manual

*Safety certified for AC input only

Model Selector

Model	Output	Voltage (V)	Voltage Adjust Range (V)	Convect. (A)	Peak or Forced Air (A)(4)	Max Load Reg (mV)	Max Line Reg (mV)	Ripple Noise (mV)	OVP (V)(5)
ZWQ80-5222	V1	5	5.0-5.25	8.0	10.0	100	20	120	5.7-7.0
	V2	+12/15*	+12/+15	2.0	2.5	300	48	150	16.5-22.5
	V3	-12/15*	-12/-15	2.0	2.5	300	48	150	16.5-22.5
	V4	12	11.4-12.6	3.0	4.0	300	48	150	13.8-16.2
ZWQ80-5223	V1	5	5.0-5.25	8.0	10.0	100	20	120	5.7-7.0
	V2	+12/15*	+12/+15	2.0	2.5	300	48	150	16.5-22.5
	V3	-12/15*	-12/-15	2.0	2.5	300	48	150	16.5-22.5
	V4	3.3	2.0-3.63	7.0	9.0	100	20	120	3.79-4.95
ZWQ80-5224	V1	5	5.0-5.25	8.0	10.0	100	20	120	5.7-7.0
	V2	+12/15*	+12/+15	2.0	2.5	300	48	150	16.5-22.5
	V3	-12/15*	-12/-15	2.0	2.5	300	48	150	16.5-22.5
	V4	24	22.8-25.2	1.5	2.0	400	96	200	27.6-32.4
ZWQ80-5225	V1	5	5.0-5.25	8.0	10.0	100	20	120	5.7-7.0
	V2	+12/15*	+12/+15	2.0	2.5	300	48	150	16.5-22.5
	V3	-12/15*	-12/-15	2.0	2.5	300	48	150	16.5-22.5
	V4	5	2.0-5.25	7.0	9.0	100	20	120	5.7-7.0
ZWQ130-5222	V1	5	5.0-5.25	15.0	19.0	100	20	120	5.7-7.0
	V2	+12/15*	+12/+15	4.0	5.0	300	48	150	16.5-22.5
	V3	-12/15*	-12/-15	4.0	5.0	300	48	150	16.5-22.5
	V4	12	11.4-12.6	4.0	5.0	300	48	150	11.4-12.6
ZWQ130-5223	V1	5	5.0-5.25	15.0	19.0	100	20	120	5.7-7.0
	V2	+12/15*	+12/+15	4.0	5.0	300	48	150	16.5-22.5
	V3	-12/15*	-12/-15	4.0	5.0	300	48	150	16.5-22.5
	V4	3.3	2.0-3.63	10.0	12.0	100	20	120	3.79-4.95
ZWQ130-5224	V1	5	5.0-5.25	15.0	19.0	100	20	120	5.7-7.0
	V2	+12/15*	+12/+15	4.0	5.0	300	48	150	16.5-22.5
	V3	-12/15*	-12/-15	4.0	5.0	300	48	150	16.5-22.5
	V4	24	22.8-25.2	2.0	2.5	400	96	200	27.6-32.4
ZWQ130-5225	V1	5	5.0-5.25	15.0	19.0	100	20	120	5.7-7.0
	V2	+12/15*	+12/+15	4.0	5.0	300	48	150	16.5-22.5
	V3	-12/15*	-12/-15	4.0	5.0	300	48	150	16.5-22.5
	V4	5	2.0-5.25	10.0	12.0	100	20	120	5.7-7.0

* User selectable via connector or PCB. Outputs are floating from V1 & V4. Can be connected in series for 24/30V.

Other Industrial Products

ZWS/ZWD	5W to 480W Single and dual output
SC	30W to 120W Single, dual, & triple output
NV	175 to 700W Single and multiple output
HWS	15 to 1500W Single output

Options

Suffix	Description
blank	No cover or L Bracket
/L	L Bracket
/A	Cover and L Bracket

(4) The peak current draw must not exceed a 10 sec. duration with a duty cycle of 35%.

(5) An overvoltage condition on any output will shut down all outputs, the power supply must be re-set by cycling the AC input.

For Additional Information, please visit
https://product.tdk.com/info/en/products/power/index.html

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9