


1700A Multi-Conductor - Enhanced Category 5E Bonded-Pair Cable



For more Information
please call

1-800-Belden1



General Description:

CAT5e+ (350MHz), 4-Bonded-Pair, U/UTP-Unshielded, Riser-CMR, Premise Horizontal Cable, 24 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Ripcord, PVC Jacket

Usage (Overall)

Suitable Applications: Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Noisy Environments, CMR, Riser

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 24 | Solid | BC - Bare Copper |

Total Number of Conductors: 8

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Outer Jacket Diameter:

| Nom. Dia. (in.) |
|-----------------|
| 0.200 |

Outer Jacket Ripcord: Yes

Overall Cable

Overall Nominal Diameter: 0.200 in.

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | White/Blue Stripe & Blue |
| 2 | White/Orange Stripe & Orange |
| 3 | White/Green Stripe & Green |
| 4 | White/Brown Stripe & Brown |

Mechanical Characteristics (Overall)

Storage Temperature Range: -20°C To +75°C

Installation Temperature Range: 0°C To +60°C

Operating Temperature Range: -20°C To +60°C

Bulk Cable Weight: 21 lbs/1000 ft.

Max. Recommended Pulling Tension: 40 lbs.

Min. Bend Radius/Minor Axis: 0.500 in.

Min. Bend/Installation: 2 in.

1700A Multi-Conductor - Enhanced Category 5E Bonded-Pair Cable

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|--|
| NEC(UL) Specification: | CMR |
| CEC/C(UL) Specification: | CMR |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Telecommunications Standards: | Category 5e - TIA 568.C.2 |
| Other Specification: | NEMA WC-63.1 Category 5e, UL Verified to Category 5e |

Applicable Patents:

| |
|------------------|
| Country |
| www.belden.com/p |

Flame Test

| | |
|-------------------|-------------------------|
| UL Flame Test: | UL 1666 Vertical Riser |
| C(UL) Flame Test: | FT4 |
| IEC Flame Test: | 60332-3-24 (Category C) |
| IEEE Flame Test: | 1202 |

Plenum/Non-Plenum

| | |
|----------------|-------|
| Plenum (Y/N): | No |
| Plenum Number: | 1701A |

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

| |
|---------------------|
| Capacitance (pF/ft) |
| 15 |

| | |
|---|----|
| Maximum Capacitance Unbalance (pF/100 m): | 66 |
|---|----|

Nominal Velocity of Propagation:

| |
|--------|
| VP (%) |
| 70 |

Maximum Delay:

| |
|------------------|
| Delay (ns/100 m) |
| 510 |

Max. Delay Skew:

| |
|-----------------------|
| Delay Skew (ns/100 m) |
| 25 |

Maximum Conductor DC Resistance:

| |
|------------------------|
| DCR @ 20°C (Ohm/100 m) |
| 9 |

Max. Operating Voltage - UL:

| |
|-----------|
| Voltage |
| 300 V RMS |

Maximum DCR Unbalanced:

| |
|--------------------------|
| DCR Unbalance @ 20°C (%) |
| 3 |

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. PSNEXT (dB) | Min. PSACR (dB) | Min RL (dB) |
|-------------|-----------------------------|------------------|-----------------|-------------|
| 1 | 2.000 | 69.3 | 67.3 | 20.000 |
| 4 | 4.000 | 60.3 | 56.3 | 23.000 |

1700A Multi-Conductor - Enhanced Category 5E Bonded-Pair Cable

| | | | | |
|-------|--------|------|------|--------|
| 8 | 5.700 | 55.8 | 50.1 | 24.500 |
| 10 | 6.400 | 54.3 | 47.9 | 25.000 |
| 16 | 8.100 | 51.2 | 43.1 | 25.000 |
| 20 | 9.100 | 49.8 | 40.7 | 25.000 |
| 25 | 10.200 | 48.3 | 38.2 | 25.000 |
| 31.25 | 11.400 | 46.9 | 35.5 | 25.000 |
| 62.5 | 16.400 | 42.4 | 26.0 | 25.000 |
| 100 | 21.000 | 39.3 | 18.3 | 25.000 |
| 155 | 26.600 | 36.4 | 9.8 | 19.000 |
| 200 | 30.400 | 34.8 | 4.4 | 19.000 |
| 250 | 34.400 | 32.3 | >0 | 18.000 |
| 300 | 38.000 | 28.1 | | 18.000 |
| 350 | 41.400 | 27.1 | | 17.000 |
| 400 | 44.500 | 26.3 | | 17.000 |
| 450 | 47.600 | 25.5 | | 17.000 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. PSACRF (dB) |
|-------------|------------------------------|------------------|------------------|
| 1 | 100 ± 12 | 105 ± 10 | 65.8 |
| 4 | 100 ± 12 | 100 ± 10 | 53.8 |
| 8 | 100 ± 12 | 100 ± 10 | 47.7 |
| 10 | 100 ± 12 | 100 ± 10 | 45.8 |
| 16 | 100 ± 12 | 100 ± 10 | 41.7 |
| 20 | 100 ± 12 | 100 ± 10 | 39.8 |
| 25 | 100 ± 15 | 100 ± 10 | 37.8 |
| 31.25 | 100 ± 15 | 100 ± 10 | 35.9 |
| 62.5 | 100 ± 15 | 100 ± 10 | 29.9 |
| 100 | 100 ± 15 | 100 ± 10 | 25.8 |
| 155 | 100 ± 18 | 100 ± 10 | 22.0 |
| 200 | 100 ± 18 | 100 ± 10 | 19.8 |
| 250 | 100 ± 20 | 100 ± 10 | 17.8 |
| 300 | 100 ± 20 | 100 ± 10 | 14.3 |
| 350 | 100 ± 22 | 100 ± 10 | 12.9 |
| 400 | 100 ± 22 | 100 ± 10 | 11.8 |
| 450 | 100 ± 22 | 100 ± 10 | 10.7 |

Premise Cable Electrical Table 4:

| Frequency (MHz) | Min. TCL (dB) | Min. ELTCTL (dB) |
|-----------------|---------------|------------------|
| 1.000 | 40.000 | 35.000 |
| 4.000 | 40.000 | 23.000 |
| 8.000 | 40.000 | 16.900 |
| 10.000 | 40.000 | 15.000 |
| 16.000 | 38.000 | 10.900 |
| 20.000 | 37.000 | 9.000 |
| 25.000 | 36.000 | 7.000 |
| 31.250 | 35.100 | |
| 62.500 | 32.000 | |
| 100.000 | 30.000 | |
| 155.000 | 28.100 | |
| 200.000 | 27.000 | |
| 250.000 | 26.000 | |

Notes (Overall)

Notes: Belden IBDN. Jacket sequentially marked at 2 ft. intervals. Third party verified to ANSI/TIA-568-C.2 Category 5e. Values above 350 MHz are for Engineering Information Only

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|----------|-------------|-----------|-------|----------------------------|
| 1700A B02U1000 | 1,000 FT | 22.000 LB | PURPLE | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A B021000 | 1,000 FT | 22.000 LB | PURPLE | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A F2VU1000 | 1,000 FT | 22.000 LB | GRAY, DEC | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A F2V1000 | 1,000 FT | 22.000 LB | GRAY, DEC | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A F2V3000 | 3,000 FT | 66.000 LB | GRAY, DEC | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A 002U1000 | 1,000 FT | 22.000 LB | RED | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A 0021000 | 1,000 FT | 22.000 LB | RED | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A 0023000 | 3,000 FT | 66.000 LB | RED | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A 003U1000 | 1,000 FT | 22.000 LB | ORANGE | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A 0031000 | 1,000 FT | 22.000 LB | ORANGE | C | CAT5E+ 4PRB U/UTP CMR REEL |

1700A Multi-Conductor - Enhanced Category 5E Bonded-Pair Cable

| | | | | | |
|----------------|----------|-----------|-------------|---|----------------------------|
| 1700A 004U1000 | 1,000 FT | 22.000 LB | YELLOW | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A 005U1000 | 1,000 FT | 22.000 LB | GREEN, DARK | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A 0051000 | 1,000 FT | 22.000 LB | GREEN, DARK | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A 006U1000 | 1,000 FT | 22.000 LB | BLUE, LIGHT | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A 0061640 | 1,640 FT | 36.080 LB | BLUE, LIGHT | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A 0063000 | 3,000 FT | 66.000 LB | BLUE, LIGHT | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A 008U1000 | 1,000 FT | 21.000 LB | GRAY | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A 009U1000 | 1,000 FT | 22.000 LB | WHITE | C | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A 0091000 | 1,000 FT | 22.000 LB | WHITE | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A 0093000 | 3,000 FT | 66.000 LB | WHITE | C | CAT5E+ 4PRB U/UTP CMR REEL |
| 1700A 010U1000 | 1,000 FT | 22.000 LB | BLACK | | CAT5E+ 4PRB U/UTP CMR BOX |
| 1700A 0101000 | 1,000 FT | 22.000 LB | BLACK | C | CAT5E+ 4PRB U/UTP CMR REEL |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 10 Revision Date: 02-28-2014

© 2014 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9