



Electrical Details	
Electrical Configuration	C Filter
Capacitance Measurement	@ 1000hr Point
Current Rating	10A
Insulation Resistance (IR)	10GΩ or 1000ΩF
Temperature Rating	-55°C to +125°C
Ferrite Inductance (Typical)	Not Applicable
Mechanical Details	
Head Diameter	4.4mm (0.173")
Nut A/F	N/a. For use in tapped hole
Washer Diameter	N/a
Mounting Torque	0.15Nm (1.32lbf in) max.
Mounting Hole	6-32 UNC Class 2B
Max. Panel Thickness	N/a
Weight (Typical)	0.8g (0.03oz)
Finish	Silver plate on copper undercoat

Product Code	Capacitance (±20%) UOS	Dielectric	Rated Voltage (Vdc)	DWV (Vdc)	Typical No-Load Insertion Loss (dB)								
					0.01MHz	0.1MHz	1MHz	10MHz	100MHz	1GHz			
*SFKBC5000100ZC	10pF -20% / +80%	COG/NPO	500#	750						4			
SFKBC5000150ZC	15pF -20% / +80%										7		
SFKBC5000220ZC	22pF -20% / +80%										10		
SFKBC5000330ZC	33pF -20% / +80%										12		
*SFKBC5000470ZC	47pF -20% / +80%									1	15		
*SFKBC5000680MC	68pF									2	18		
*SFKBC5000101MC	100pF									4	22		
SFKBC5000151MC	150pF									7	25		
*SFKBC5000221MC	220pF									10	29		
*SFKBC5000331MC	330pF									13	33		
*SFKBC5000471MX	470pF		†X7R		500#				1	16	35		
SFKBC5000681MX	680pF				500#				2	19	36		
*SFKBC5000102MX	1.0nF	X7R	500#	500				4	23	41			
SFKBC5000152MX	1.5nF								7	26	45		
*SFKBC5000222MX	2.2nF								10	30	50		
SFKBC5000332MX	3.3nF								13	33	52		
*SFKBC5000472MX	4.7nF								1	16	36	55	
SFKBC5000682MX	6.8nF								2	19	39	57	
*SFKBC5000103MX	10nF								4	22	41	60	
*SFKBC5000153MX	15nF								7	25	44	62	
*SFKBC5000223MX	22nF								10	29	46	65	
SFKBC5000333MX	33nF								13	33	48	68	
*SFKBC2000473MX	47nF				200	500			1	16	35	70	
SFKBC2000683MX	68.0nF				200					2	19	39	>70
*SFKBC1000104MX	100nF				100		250			4	22	41	>70
*SFKBC0500154MX	150nF				50	125			7	25	45	60	>70

Also rated for operation at 115Vac 400Hz. Self-heating will occur – evaluation in situ recommended. * Recommended values. † Also available in COG/NPO.

Ordering Information - SFKBC range

SF	K	B	C	500	0101	M	C	0
Type	Case style	Thread	Electrical configuration	Voltage (dc)	Capacitance in picofarads (pF)	Tolerance	Dielectric	Nuts & Washers
Syfer Filter	4.4mm O.D.	6-32 UNC	C = C Filter	050 = 50V 100 = 100V 200 = 200V 500 = 500V	First digit is 0. Second and third digits are significant figures of capacitance code. The fourth digit is number of zeros following Example: 0101 = 100pF 0332 = 3300pF	M = ±20% Z = -20+80%	C = COG/NPO X = X7R	0 = Without

Note: Installation tool available on request
 Note: The addition of a 4-digit numerical suffix code can be used to denote changes to the standard part. Options include for example: change of finish / alternative voltage rating / non-standard intermediate capacitance values / test requirements. Please refer specific requests to the factory.



Electrical Details

Electrical Configuration	L-C Filter
Capacitance Measurement	@ 1000hr Point
Current Rating	10A
Insulation Resistance (IR)	10GΩ or 1000ΩF
Temperature Rating	-55°C to +125°C
Ferrite Inductance (Typical)	50nH



Mechanical Details

Head Diameter	4.4mm (0.173")
Nut A/F	N/a. For use in tapped hole
Washer Diameter	N/a
Mounting Torque	0.15Nm (1.32lbf in) max.
Mounting Hole	6-32 UNC Class 2B
Max. Panel Thickness	N/a
Weight (Typical)	0.8g (0.03oz)
Finish	Silver plate on copper undercoat

Product Code	Capacitance (±20%) UOS	Dielectric	Rated Voltage (Vdc)	DWV (Vdc)	Typical No-Load Insertion Loss (dB)							
					0.01MHz	0.1MHz	1MHz	10MHz	100MHz	1GHz		
* SFKBL5000100ZC	10pF -20% / +80%	COG/NP0	500#	750						6		
SFKBL5000150ZC	15pF -20% / +80%										9	
SFKBL5000220ZC	22pF -20% / +80%										12	
SFKBL5000330ZC	33pF -20% / +80%									1	15	
* SFKBL5000470ZC	47pF -20% / +80%									2	19	
* SFKBL5000680MC	68pF									4	20	
* SFKBL5000101MC	100pF									7	24	
SFKBL5000151MC	150pF									10	27	
* SFKBL5000221MC	220pF									12	30	
* SFKBL5000331MC	330pF											
* SFKBL5000471MX	470pF	†X7R	500#	750				1	16	34		
SFKBL5000681MX	680pF							2	19	38		
* SFKBL5000102MX	1.0nF	X7R	500#	750				2	19	38		
SFKBL5000152MX	1.5nF							3	22	41		
* SFKBL5000222MX	2.2nF							6	25	44		
SFKBL5000332MX	3.3nF							9	29	48		
* SFKBL5000472MX	4.7nF							12	31	51		
SFKBL5000682MX	6.8nF							15	35	54		
* SFKBL5000103MX	10nF								1	18	39	57
SFKBL5000153MX	15nF								2	21	41	60
* SFKBL5000223MX	22nF								4	23	43	63
SFKBL5000333MX	33nF								7	27	46	66
* SFKBL2000473MX	47nF		200	500			10	30	48	68		
SFKBL2000683MX	68nF		200				13	34	50	70		
*SFKBL1000104MX	100nF		100		250			1	17	37	51	>70
*SFKBL0500154MX	150nF		50	125			2	20	40	55	>70	
							4	22	44	60	>70	
							7	25	47	62	>70	

Also rated for operation at 115Vac 400Hz. Self heating will occur – evaluation in situ recommended. * Recommended values. † Also available in COG/NP0.

Ordering Information - SFKBL range

SF	K	B	L	500	0101	M	C	0
Type	Case style	Thread	Electrical configuration	Voltage (dc)	Capacitance in picofarads (pF)	Tolerance	Dielectric	Nuts & Washers
Syfer Filter	4.4mm O.D.	6-32 UNC	L = L-C Filter	050 = 50V 100 = 100V 200 = 200V 500 = 500V	First digit is 0. Second and third digits are significant figures of capacitance code. The fourth digit is number of zeros following Example: 0101 = 100pF 0332 = 3300pF	M = ±20% Z = -20+80%	C = COG/NP0 X = X7R	0 = Without

Note: Installation tool available on request
Note: The addition of a 4-digit numerical suffix code can be used to denote changes to the standard part.
Options include for example: change of finish / alternative voltage rating / non-standard intermediate capacitance values / test requirements. Please refer specific requests to the factory.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9