

## ATDS3534UV365B

3.45 x 3.45 mm UV LED With Ceramic Substrate



### FEATURES

- High power UV-A LED
- Dimensions: 3.45 mm x 3.45 mm x 2.0 mm
- Small package with high efficiency
- Surface mount technology
- Package: 1000pcs / reel
- Soldering methods: IR reflow soldering
- Moisture sensitivity level: 1
- RoHS compliant

### APPLICATIONS

- Photocatalytic Purification
- Blood and Counterfeit money detection
- UV curing in nail salon, dental, and poster printing applications
- UV Sensor Light

### PACKAGE MATERIALS


- Material as follows:  
Package: Ceramics  
Encapsulating resin: Silicone resin  
Electrodes: Au plating

### ATTENTION

Observe precautions for handling electrostatic discharge sensitive devices




### PACKAGE DIMENSIONS



### RECOMMENDED SOLDERING PATTERN

(units : mm; tolerance :  $\pm 0.1$ )



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.2(0.008)$  unless otherwise noted.
3. The specifications, characteristics and technical data described in the datasheet are subject to change without prior notice.
4. The device has a single mounting surface. The device must be mounted according to the specifications.

### SELECTION GUIDE

| Part Number    | Emitting Color (Material) | Lens Type   | $\Phi_e(\text{mW})^{[2]}$ @500mA |      |      |      | Viewing Angle <sup>[1]</sup> |
|----------------|---------------------------|-------------|----------------------------------|------|------|------|------------------------------|
|                |                           |             | Code.                            | Min. | Max. | Typ. | 2 $\theta$ 1/2               |
| ATDS3534UV365B | Ultraviolet (InGaN)       | Water Clear | C12                              | 490  | 560  | 620  | 120°                         |
|                |                           |             | C13                              | 560  | 640  |      |                              |
|                |                           |             | C14                              | 640  | 740  |      |                              |

Notes:  
1.  $\theta$ 1/2 is the angle from optical centerline where the radiant intensity is 1/2 of the optical peak value.  
2. Radiant Flux:  $\pm 15\%$ .  
3. Radiant flux value is traceable to CIE127-2007 standards.

**ELECTRICAL / OPTICAL CHARACTERISTICS at  $T_A=25^{\circ}\text{C}$** 

| Parameter  | Symbol                  | Value | Unit                   |
|--|-------------------------|-------|------------------------|
| Wavelength at Peak Emission $I_F = 500\text{mA}$ [Min.]  | $\lambda_{\text{peak}}$ | 360   | nm                     |
| Wavelength at Peak Emission $I_F = 500\text{mA}$ [Typ.]  |                         | 365   |                        |
| Wavelength at Peak Emission $I_F = 500\text{mA}$ [Max.]  |                         | 370   |                        |
| Spectral Bandwidth at 50% $\Phi$ REL MAX $I_F = 500\text{mA}$ [Typ.]   | $\Delta\lambda$         | 10    | nm                     |
| Forward Voltage $I_F = 500\text{mA}$ [Typ.]  | $V_F^{[1]}$             | 3.4   | V                      |
| Forward Voltage $I_F = 500\text{mA}$ [Max.]  |                         | 3.9   |                        |
| Allowable Reverse Current [Max.]   | $I_R$                   | 85    | mA                     |
| Temperature Coefficient of $V_F$<br>$I_F = 500\text{mA}$ , $-10^{\circ}\text{C} \leq T \leq 100^{\circ}\text{C}$ | $\text{TC}_V$           | -3.0  | mV/ $^{\circ}\text{C}$ |

Notes:

1. Forward voltage:  $\pm 0.1\text{V}$ .

2. Wavelength value is traceable to CIE127-2007 standards.

3. Excess driving current and / or operating temperature higher than recommended conditions may result in severe light degradation or premature failure.

**ABSOLUTE MAXIMUM RATINGS at  $T_A=25^{\circ}\text{C}$** 

| Parameter                                    | Symbol                   | Value       | Unit                 |
|--|--------------------------|-------------|----------------------|
| Power Dissipation                            | $P_D$                    | 1.95        | W                    |
| Reverse Voltage                              | $V_R$                    | 5           | V                    |
| Junction Temperature                         | $T_j^{[1]}$              | 115         | $^{\circ}\text{C}$   |
| Operating Temperature                        | $T_{\text{op}}$          | -40 to +100 | $^{\circ}\text{C}$   |
| Storage Temperature                          | $T_{\text{stg}}$         | -40 to +115 | $^{\circ}\text{C}$   |
| DC Forward Current                           | $I_F^{[1]}$              | 500         | mA                   |
| Peak Forward Current                         | $I_{\text{FM}}^{[2]}$    | 800         | mA                   |
| Electrostatic Discharge Threshold (HBM)      | -                        | 8000        | V                    |
| Thermal Resistance (Junction / Ambient)      | $R_{\text{th JA}}^{[1]}$ | 20          | $^{\circ}\text{C/W}$ |
| Thermal Resistance (Junction / Solder point) | $R_{\text{th JS}}^{[1]}$ | 10          | $^{\circ}\text{C/W}$ |

Notes:


1. Results from mounting on metal core PCB, mounted on pc board-metal core PCB is recommend for lowest thermal resistance.

2. 1/10 Duty Cycle, 0.1ms Pulse Width.


3. Relative humidity levels maintained between 40% and 60% in production area are recommended to avoid the build-up of static electricity – Ref JEDEC/JESD625-A and JEDEC/J-STD-033.

## TECHNICAL DATA

### RELATIVE INTENSITY vs. WAVELENGTH




### SPATIAL DISTRIBUTION




## ULTRAVIOLET


Forward Current vs. Forward Voltage




Radiant Flux vs. Forward Current




Forward Current Derating Curve




Radiant Flux vs. Ambient Temperature




Peak Wavelength vs. Ambient Temperature




Forward Voltage vs. Ambient Temperature




Permissible Forward Current vs. Duty Cycle



### TAPE SPECIFICATIONS (units : mm)




### REEL DIMENSION (units : mm)





## HANDLING PRECAUTIONS

Compare to epoxy encapsulant that is hard and brittle, silicone is softer and flexible. Although its characteristic significantly reduces thermal stress, it is more susceptible to damage by external mechanical force. As a result, special handling precautions need to be observed during assembly using silicone encapsulated LED products. Failure to comply might lead to damage and premature failure of the LED.

1. Handle the component along the side surfaces by using forceps or appropriate tools.




2. Do not directly touch or handle the silicone lens surface. It may damage the internal circuitry.



3. Do not stack together assembled PCBs containing exposed LEDs. Impact may scratch the silicone lens or damage the internal circuitry.




- 4-1. There should be enough space inside the nozzle to avoid contact with the dome lens during pick up.
- 4-2. The inner diameter of the SMD pickup nozzle should not exceed the size of the LED to prevent air leaks.
- 4-3. A pliable material is suggested for the nozzle tip to avoid scratching or damaging the LED surface during pickup.
- 4-4. The dimensions of the component must be accurately programmed in the pick-and-place machine to insure precise pickup and avoid damage during production.
5. As silicone encapsulation is permeable to gases, some corrosive substances such as  $H_2S$  might corrode silver plating of lead-frame. Special care should be taken if an LED with silicone encapsulation is to be used near such substances.




## Designing the Position of LED on a Board

1. No twist / warp / bent / or other stress shall be applied to the board after mounting LED with solder to avoid a crack of LED package. Refer to the following recommended position and direction of LED.


No good



Recommended Direction



2. Depending on the position and direction of LED, the mechanical stress on the LED package can be changed. Refer to the following figure.



Appropriate LED mounting is to place perpendicularly against the stress affected side.

3. Do not split board by hand. Split with exclusive special tool.
4. If an aluminum circuit board is used, a large stress by thermal shock might cause a solder crack. For this reason, it is recommended an appropriate verification should be taken before use.

## JEDEC Moisture Sensitivity

| Level | Floor Life |   | Soak Requirements |                                      |                        |            |
|-------|------------|---|-------------------|--------------------------------------|------------------------|------------|
|       |            |   | Standard          |                                      | Accelerated Equivalent |            |
|       | Time       | Conditions                                | Time (hours)      | Conditions                           | Time (hours)           | Conditions |
| 1     | Unlimited  | $\leq 30^\circ\text{C} / 85\% \text{ RH}$ | 168<br>+ 5 / - 0  | $85^\circ\text{C} / 85\% \text{ RH}$ | -                      | -          |

Kingbright recommends keeping the LEDs in the sealed moisture-barrier packaging until immediately prior to use. Any unused LEDs should be returned to the moisture-barrier bag and closed immediately after use.

## ESD Protection During Production

Electric static discharge can result when static-sensitive products come in contact with the operator or other conductors.

The following procedures may decrease the possibility of ESD damage:

1. Minimize friction between the product and surroundings to avoid static buildup.
2. All production machinery and test instruments must be electrically grounded.
3. Operators must wear anti-static bracelets.
4. Wear anti-static suit when entering work areas with conductive machinery.
5. Set up ESD protection areas using grounded metal plating for component handling.
6. All workstations that handle IC and ESD-sensitive components must maintain an electrostatic potential of 150V or less.
7. Maintain a humidity level of 50% or higher in production areas.
8. Use anti-static packaging for transport and storage.
9. All anti-static equipment and procedures should be periodically inspected and evaluated for proper functionality.

## Heat Generation

1. Thermal design of the end product is of paramount importance. Please consider the heat generation of the LED when making the system design.

The coefficient of temperature increase per input electric power is affected by the thermal resistance of the circuit board and density of LED placement on the board, as well as other components. It is necessary to avoid intense heat generation and operate within the maximum ratings given in this specification.

2. Please determine the operating current with consideration of the ambient temperature local to the LED and refer to the plot of Permissible Forward Current vs. Ambient temperature on characteristics in this specification.

Please also take measures to remove heat from the area near the LED to improve the operational characteristics on the LED.

3. The equation ① indicates correlation between  $T_j$  and  $T_a$ , and the equation ② indicates correlation between  $T_j$  and  $T_s$ .

$$T_j = T_a + R_{th JA} * W \quad \text{..... ①}$$

$$T_j = T_s + R_{th JS} * W \quad \text{..... ②}$$

$T_j$  = dice junction temperature: °C

$T_a$  = ambient temperature: °C


$T_s$  = solder point temperature: °C

$R_{th JA}$  = heat resistance from dice junction temperature to ambient temperature: °C / W

$R_{th JS}$  = heat resistance from dice junction temperature to  $T_s$  measuring point: °C / W

$W$  = inputting power ( $I_F \times V_F$ ): W

### REFLOW SOLDERING PROFILE for LEAD-FREE SMD PROCESS



#### Notes:

1. Don't cause stress to the LEDs while it is exposed to high temperature.
2. The maximum number of reflow soldering passes is 2 times.
3. Reflow soldering is recommended. Other soldering methods are not recommended as they might cause damage to the product.

**RELIABILITY TEST ITEMS AND CONDITIONS**

The reliability of products shall be satisfied with items listed below

**Lot Tolerance Percent Defective (LTPD) : 10%**

| No. | Test Item                                       | Standards              | Test Condition  | Test Times / Cycles            | Number of Damaged |
|-----|---|------------------------|---|--------------------------------|-------------------|
| 1   | Continuous operating test                       | -                      | $T_a = 25^{\circ}\text{C} + 10/-5^{\circ}\text{C}$ , RH = 55+/-20%RH<br>$I_F$ = maximum rated current*  | 1,000 h                        | 0 / 22            |
| 2   | High Temp. operating test                       | -                      | $T_a = 100^{\circ}\text{C} (+/-10^{\circ}\text{C})$<br>$I_F$ = maximum rated current*   | 1,000 h                        | 0 / 22            |
| 3   | Low Temp. operating test                        | -                      | $T_a = -40^{\circ}\text{C} + 3/-5^{\circ}\text{C}$<br>$I_F$ = maximum rated current*  | 1,000 h                        | 0 / 22            |
| 4   | High temp. storage test                         | JEITA ED-4701/200 201  | $T_a = 100^{\circ}\text{C} (+/-10^{\circ}\text{C})$<br>$T_a$ = maximum rated storage temperature  | 1,000 h                        | 0 / 22            |
| 5   | Low temp. storage test                          | JEITA ED-4701/200 202  | $T_a = -40^{\circ}\text{C} + 3/-5^{\circ}\text{C}$  | 1,000 h                        | 0 / 22            |
| 6   | High temp. & humidity storage test              | JEITA ED-4701/100 103  | $T_a = 60^{\circ}\text{C} + 5/-3^{\circ}\text{C}$ , RH = 90+5/-10%RH  | 1,000 h                        | 0 / 22            |
| 7   | High temp. & humidity operating test            | -                      | $T_a = 60^{\circ}\text{C} + 5/-3^{\circ}\text{C}$ , RH = 90+5/-10%RH<br>$I_F$ = maximum rated current*  | 1,000 h                        | 0 / 22            |
| 8   | Resistance to Soldering Heat (Reflow Soldering) | JEITA ED-4701/300 301  | $T_{\text{slid}} = 260^{\circ}\text{C}$ , 10sec   | 2 times                        | 0 / 22            |
| 9   | Solderability (Reflow Soldering)                | JEITA ED-4701/303 303A | $T_{\text{slid}} = 245^{\circ}\text{C} +/- 5^{\circ}\text{C}$ , 5+/-1sec  | 1 time over 95%                | 0 / 22            |
| 10  | Temperature Cycle operating test                | -                      | $-40^{\circ}\text{C}(30\text{min}) \sim 25^{\circ}\text{C}(5\text{min}) \sim 100^{\circ}\text{C}$<br>(30min) $\sim 25^{\circ}\text{C}(5\text{min})$<br>$I_F$ = derated current at $100^{\circ}\text{C}$ | 10 cycles                      | 0 / 22            |
| 11  | Temperature Cycle                               | JEITA ED-4701/100 105  | $-40^{\circ}\text{C}(30\text{min}) \sim 25^{\circ}\text{C}(5\text{min}) \sim 100^{\circ}\text{C}$<br>(30min) $\sim 25^{\circ}\text{C}(5\text{min})$   | 100 cycles                     | 0 / 22            |
| 12  | Thermal shock test                              | MIL-STD-202G           | $T_a = -40^{\circ}\text{C}(15\text{min}) \sim 100^{\circ}\text{C}(15\text{min})$  | 500 cycles                     | 0 / 22            |
| 13  | Electric Static Discharge (ESD)                 | JEITA ED-4701/300 304  | $C = 100\text{pF}$ , $R = 1.5\text{K}\Omega$ $V = 8000\text{V}$   | 3 times<br>Negative / Positive | 0 / 22            |
| 14  | Vibration test                                  | JEITA ED-4701/400 403  | 100 ~ 2000 ~ 100HZ Sweep 4min.<br>200m/s <sup>2</sup><br>3directions, 4cycles   | 48 min.                        | 0 / 22            |


Note: Refer to forward current vs. derating curve diagram.

**Criteria For Judging Damage**

| Item            | Symbol   | Test Conditions      | Criteria for Judgement |                     |
|-----------------|----------|----------------------|------------------------|---------------------|
|                 |          |                      | Min.                   | Max.                |
| Forward Voltage | $V_F$    | $I_F = 500\text{mA}$ | -                      | Initial Level x 1.1 |
| Radiant Flux    | $\Phi_e$ | $I_F = 500\text{mA}$ | Initial Level x 0.7    | -                   |

Note: The test is performed after the board is cooled down to the room temperature.

## PACKING & LABEL SPECIFICATIONS



### Packaging

1. The LEDs are packed in cardboard boxes after taping.
2. The label on the minimum packing unit shows: Part Number, Lot Number, Ranking, Quantity.
3. In order to protect the LEDs from mechanical shock, we pack them in cardboard boxes for transportation.
4. The LEDs may be damaged if the boxes are dropped or receive a strong impact against them, so precautions must be taken to prevent any damage.
5. The boxes are not water resistant and therefore must be kept away from water and moisture.
6. When the LEDs are transported, we recommend that you use the same packing methods as Kingbright's.

### PRECAUTIONARY NOTES

1. The information included in this document reflects representative usage scenarios and is intended for technical reference only.
2. The part number, type, and specifications mentioned in this document are subject to future change and improvement without notice. Before production usage customer should refer to the latest datasheet for the updated specifications.
3. When using the products referenced in this document, please make sure the product is being operated within the environmental and electrical limits specified in the datasheet. If customer usage exceeds the specified limits, Kingbright will not be responsible for any subsequent issues.
4. The information in this document applies to typical usage in consumer electronics applications. If customer's application has special reliability requirements or have life-threatening liabilities, such as automotive or medical usage, please consult with Kingbright representative for further assistance.
5. The contents and information of this document may not be reproduced or re-transmitted without permission by Kingbright.
6. All design applications should refer to Kingbright application notes available at <https://www.KingbrightUSA.com/ApplicationNotes>

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9