

## 3M™ Metal-Out Static Shielding Bag 1500


This transparent metal-out static shielding bag is designed to provide a static safe environment for sensitive electronic devices. Bags are printed with an ESD warning symbol and a lot code for traceability. Open top and ZipTop styles are available. The bags are heat sealable.

3M Static Shielding Bags are manufactured from a top coat, metal, polyester, polyethylene laminate. The proprietary top coating is designed to protect the metal layer. Polyester dielectric, in concert with the metal layer, is intended to provide shielding of Electrostatic Discharge (ESD) and to help minimize the penetration of electric field.

These bags are tested to meet or exceed certain electrical and physical requirements of ANSI/ESD S541 and to be ANSI/ESD S20.20 program compliant. Bags are RoHS Compliant\* and lead-free\*\*.



3M™ Metal-Out Static Shielding Bag 1500



| Physical            | Typical Value           | Testing Method            |
|---------------------|-------------------------|---------------------------|
| Tensile Strength    | 4900 PSI, 34 MPa        | ASTM D882                 |
| Puncture Resistance | 10 lbs, 44 N            | MIL-STD-3010C Method 2065 |
| Seal Strength       | 14 lbs, 62 N            | ASTM D882                 |
| Thickness           | 3 mils, .0762 mm +/-15% | MIL-STD-3010C Method 1003 |
| Marking Adhesion    | Pass                    | IPC-TM-650 2.4.1          |
| Transparency        | 40%                     | Tobias                    |

| Electrical                    | Typical Value            | Testing Method    |
|-------------------------------|--------------------------|-------------------|
| ESD Shielding                 | <10 nJ                   | ANSI/ESD STM11.31 |
| Surface Resistance - Interior | <1x10 <sup>11</sup> ohms | ANSI/ESD STM11.11 |
| Surface Resistance - Exterior | <1x10 <sup>6</sup> ohms  | ANSI/ESD STM11.11 |
| Static Decay                  | < 2 seconds              | ETS 406D          |
| Charge Retention              | <100 volts               | CPM-3M TP.21XX    |

| Cleanliness | Typical Value | Testing Method |
|-------------|---------------|----------------|
| Silicone    | Not Detected  | FTIR           |

| Heat Sealing Conditions | Typical Value                |
|-------------------------|------------------------------|
| Temperature             | 300°F – 375°F, 149°C – 190°C |
| Time                    | 0.5 – 3.5 seconds            |
| Pressure                | 30 – 70 PSI, 206 – 482 KPa   |

This product is intended for commercial use only. This product is not on the Qualified Product Listing under the Defense Standardization Program.

## 3M™ Metal-Out Static Shielding Bag 1500

### 3M Metal-Out Static Shielding Bags, Open Top 1500

| Dimensions<br>(W x L in.) | Part No. | Dimensions<br>(W x L in.) | Part No. | Dimensions<br>(W x L in.) | Part No. |
|---------------------------|----------|---------------------------|----------|---------------------------|----------|
| 3 x 5                     | 15035    | 8 x 12                    | 150812   | 12 x 18                   | 1501218  |
| 4 x 6                     | 15046    | 9 x 12                    | 150912   | 14 x 18                   | 1501418  |
| 5 x 8                     | 15058    | 10 x 12                   | 1501012  | 15 x 18                   | 1501518  |
| 6 x 8                     | 15068    | 10 x 14                   | 1501014  | 16 x 24                   | 1501624  |
| 6 x 10                    | 150610   | 10 x 24                   | 1501024  | 18 x 18                   | 1501818  |
| 6 x 30                    | 150630   | 11 x 15                   | 1501115  | 18 x 24                   | 1501824  |
| 7 x 15                    | 150715   | 12 x 16                   | 1501216  |                           |          |

Custom Sizes and Printing Available.

### 3M Metal-Out Static Shielding Bags, ZipTop 1500

| Dimensions<br>(W x L in.) | Part No. | Dimensions<br>(W x L in.) | Part No. | Dimensions<br>(W x L in.) | Part No. |
|---------------------------|----------|---------------------------|----------|---------------------------|----------|
| 3 x 5                     | 150Z35   | 6 x 8                     | 150Z68   | 10 x 12                   | 150Z1012 |
| 4 x 4                     | 150Z44   | 6 x 10                    | 150Z610  | 12 x 18                   | 150Z1218 |
| 4 x 6                     | 150Z46   | 8 x 10                    | 150Z810  | 12 x 18                   | 1911218  |

Custom Sizes and Printing Available.

3M is a trademark of 3M Company. All other trademarks are owned by their respective companies.

**\* RoHS 2011/65/EU Compliant** means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty section.


\*\*Lead-free means that the product has less than 2 ppm of lead when tested by ICP-AES, with reference to EPA method 3051A/3052.



#### Electronic Solutions Division Static Control Products

926 JR Industrial Drive  
Sanford, NC 27332  
Toll-Free: 866-722-3736  
International: 919-718-0000  
Email: 3mstaticinfo@mmm.com  
www.3Mstatic.com

Please recycle. Printed in USA.  
© 3M 2014. All rights reserved.  
98-0799-1154-5 JHA



- Standard sizes stocked for prompt shipment (usually same day).
- Width is measured from inside seam to inside seam.
- Length is measured from the top edge to the bottom fold.
- Opening is in the "width" dimension.
- Custom bag sizes, custom printing, and custom hot stamping are available.
- Most sizes are packed 100 per case.
- Small sizes are packed 500 or 1,000 per case.

Tolerance (inches): Width -0, +0.250  
Length +/- 0.125 Offset 0 to 0.250  
Seal width +/- 0.125

#### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9