SIPMOS® Power-Transistor

Feature

- N-Channel
- Enhancement mode
- Logic Level
- d*v*/d*t* rated
- Pb-free lead plating; RoHS compliant
- Qualified according to AEC Q101
- Halogen-free according to IEC61249-2-21

Product Summary

V_{DS}	600	V
$R_{DS(on)}$	45	Ω
I_D	0.12	A

PG-SOT223

Type	Package	RoHS compliant	Tape and Reel Information	Marking	Packaging
BSP125	PG-SOT223	Yes	H6433: 4000 pcs/reel	BSP125	Non dry
BSP125	PG-SOT223	Yes	H6327: 1000 pcs/reel	BSP125	Non dry

Maximum Ratings, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current T_A=25°C T_A=70°C	I_D	 0.12 0.1	A
Pulsed drain current T_A=25°C	$I_{D\ puls}$	0.48	
Reverse diode d*v*/d*t* I_S=0.12A, V_{DS}=480V, d*i*/d*t*=200A/µs, T_{jmax}=175°C	d*v*/d*t*	6	kV/µs
Gate source voltage	V_{GS}	±20	V
ESD Class (JESD22-A114-HBM)		1A (>250V, <500V)	
Power dissipation T_A=25°C, T_A=25	P_{tot}	1.8	W
Operating and storage temperature	T_j , T_{stg}	-55... +150	°C
IEC climatic category; DIN IEC 68-1		55/150/56	

Thermal Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Characteristics					
Thermal resistance, junction - soldering point (Pin 4)	R_{thJS}	-	-	25	K/W
SMD version, device on PCB:	R_{thJA}				
@ min. footprint		-	-	115	
@ 6 cm^2 cooling area [1)]		-	-	70	

Electrical Characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Static Characteristics					
Drain-source breakdown voltage V_{GS}=0, I_D=0.25mA	$V_{(BR)DSS}$	600	-	-	V
Gate threshold voltage, V_{GS} = V_{DS} I_D=94µA	$V_{GS(th)}$	1.3	1.9	2.3	
Zero gate voltage drain current	I_{DSS}				µA
V_{DS}=600V, V_{GS}=0, T_j=25°C		-	-	0.1	
V_{DS}=600V, V_{GS}=0, T_j=125°C		-	-	5	
Gate-source leakage current V_{GS}=20V, V_{DS}=0	I_{GSS}	-	10	100	nA
Drain-source on-state resistance V_{GS}=4.5V, I_D=0.11A	$R_{DS(on)}$	-	26	60	Ω
Drain-source on-state resistance V_{GS}=10V, I_D=0.12A	$R_{DS(on)}$	-	25	45	

[1]Device on 40mm*40mm*1.5mm epoxy PCB FR4 with 6cm² (one layer, 70 µm thick) copper area for drain connection. PCB is vertical without blown air.

Electrical Characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic Characteristics						
Transconductance	g_{fs}	V_{DS}≥2*I_D*$R_{DS(on)max}$, I_D=0.1A	0.06	0.18	-	S
Input capacitance	C_{iss}	V_{GS}=0, V_{DS}=25V, f=1MHz	-	100	150	pF
Output capacitance	C_{oss}		-	8.2	12.3	
Reverse transfer capacitance	C_{rss}		-	3.2	4.8	
Turn-on delay time	$t_{d(on)}$	V_{DD}=300V, V_{GS}=10V, I_D=0.13A, R_G=6Ω	-	7.7	11.6	ns
Rise time	t_r		-	14.4	21	
Turn-off delay time	$t_{d(off)}$		-	20	30	
Fall time	t_f		-	110	165	
Gate Charge Characteristics						
Gate to source charge	Q_{gs}	V_{DD}=400V, I_D=0.13A	-	0.27	0.3	nC
Gate to drain charge	Q_{gd}		-	2.3	3.5	
Gate charge total	Q_g	V_{DD}=400V, I_D=0.13A, V_{GS}=0 to 10V	-	4.4	6.6	
Gate plateau voltage	$V_{(plateau)}$	V_{DD}=400V, I_D=0.13A	-	3.44	-	V
Reverse Diode						
Inverse diode continuous forward current	I_S	T_A=25°C	-	-	0.12	A
Inv. diode direct current, pulsed	I_{SM}		-	-	0.48	
Inverse diode forward voltage	V_{SD}	V_{GS}=0, I_F=0.12A	-	0.8	1.2	V
Reverse recovery time	t_{rr}	V_R=300V, I_F=I_S, di_F/dt=100A/µs	-	156	235	ns
Reverse recovery charge	Q_{rr}		-	165	250	nC

1 Power dissipation

$P_{tot} = f(T_A)$

2 Drain current

$I_D = f(T_A)$

parameter: $V_{GS} \geq 10$ V

3 Safe operating area

$I_D = f(V_{DS})$

parameter : $D = 0$, $T_A = 25$

4 Transient thermal impedance

$Z_{thJA} = f(t_p)$

parameter : $D = t_p/T$

5 Typ. output characteristic

$I_D = f(V_{DS})$

parameter: T_j = 25 °C, V_{GS}

6 Typ. drain-source on resistance

$R_{DS(on)} = f(I_D)$

parameter: T_j = 25 °C, V_{GS}

7 Typ. transfer characteristics

$I_D = f(V_{GS})$; $V_{DS} \geq 2 \times I_D \times R_{DS(on)max}$

parameter: T_j = 25 °C

8 Typ. forward transconductance

$g_{fs} = f(I_D)$

parameter: T_j = 25 °C

9 Drain-source on-state resistance

$R_{DS(on)} = f(T_j)$

parameter : I_D = 0.12 A, V_{GS} = 10 V

(.) Typ. gate threshold voltage

$V_{GS(th)} = f(T_j)$

parameter: $V_{GS} = V_{DS}$; I_D =94µA

11 Typ. capacitances

$C = f(V_{DS})$

parameter: V_{GS}=0, f=1 MHz, T_j = 25 °C

12 Forward character. of reverse diode

$I_F = f(V_{SD})$

parameter: T_j

13 Typ. gate charge

$V_{GS} = f\ (Q_G)$; parameter: V_{DS} ,

I_D = 0.12 A pulsed, T_j = 25 °C

14 Drain-source breakdown voltage

$V_{(BR)DSS} = f\ (T_j)$

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2008 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9