



ENTERPRISE-GRADE DEVICE SERVER FOR SECURLY INTEGRATING 'EDGE' EQUIPMENT INTO A NETWORK

The EDS4100 is a combination Ethernet terminal and multi-port device server that delivers unprecedented levels of integration, intelligence, and security, and enables new ways to network-enable legacy equipment. Designed with enterprise-grade networking applications in mind, the EDS4100 provides a hassle-free and inexpensive way to add secure network connectivity to virtually any device with a serial interface.

Available in a four-port configuration, and equipped with flexible power options including Power Over Ethernet (PoE), the EDS4100 is ideal for applications where multiple pieces of equipment need to be connected, remotely accessed, and managed. Featuring Lantronix' powerful Evolution OS™ and a mature protocol stack, each EDS4100 device server offers robust security options like SSL/SSH, AES, 3DES, and RC4 encryption to defend against hostile Internet attacks.

The EDS4100 supports a flexible "Cisco-like" CLI and is equipped with a built-in web server that simplifies configuration and control, making it easier to integrate 'edge' devices such as medical devices, kiosks, POS/retail terminals, or security equipment into the enterprise network.



- + Provides a safe and secure network connectivity solution for virtually any device with an RS-232/422/485 serial interface
- + Simplifies deployment with a standards based, programmable computing platform which supports a Cisco-like CLI, XML, and RSS
- + Defends against hostile attacks with a versatile collection of ready-to-use security algorithms and encryption modules
- + Delivers flexible power configurations, eliminating the need for costly power converters
- + Provides new business intelligence from network-enabled equipment

FEATURES**+ Serial Interface**

- Connectors: 4 x DB9M; 2 x RS232, 2 x RS232/422/485
- Baud rate: 300 bps to 921.6 Kbps
- Characters: 7 or 8 data bits
- Stop Bits: 1 or 2
- Parity: odd, even, none
- Flow Control: CTS/RTS, XON/XOFF

+ Ethernet Interface

- Interface: 10Base-T/100Base-T
- Speed: 10/100/Auto Mbps
- Connector: RJ45
- Protocols: ARP, UDP, TCP, ICMP, Telnet, SNMP, DHCP, BOOTP, TFTP, Auto IP, SMTP, FTP, DNS, Traceroute and HTTP

+ Security

- SSL v3, SSH v2
- MD5, SHA-1, Base-64
- AES 128-bit encryption
- 3DES encryption
- RC4 128-bit encryption
- Password protection, IP filtering

+ LED Indicators

- Power, Link, Activity, RX Activity, TX Activity

+ Processor

- CPU: Intel XScale IXP420 @ 266MHz
- Memory: 32 MB SDRAM, 8 MB Flash

+ Power Requirements

- Barrel Connector: 9-30 VDC
- Screw Terminal: 42-56 VDC
- PoE: 802.3af compliant

+ Environmental Limits

- Operating temperature: 0° to 55°C (32° to 131°F)
- Storage temperature: -40° to 70°C (-40 to 158°F)
- Operating Humidity: 10% to 90%
- Storage Humidity: 10% to 90%

+ Form Factor

- Housing: Metal enclosure with removable wall mounts
 - Dimensions: 3.81 x 17.65* x 12.7 cm (1.5 x 6.95* x 5 in)
 - Weight: 0.86kg (1.9lbs)
- * With wall mounts = 20.14 cm (7.93 in)

+ Agency Approvals

- FCC, CUL, UL, VCCI, CE, CSA, TUV, C-Tick, GS, CB Scheme

+ Warranty

- 2-year limited warranty

+ Shipping Dimensions

- Dimensions: 242 x 191 x 115 mm (9.5 x 7.5 x 4.5 in)
- Weight: 1.44kg (3.19lbs)

+ Software

- Windows 98/ME/NT/2000/XP/Vista (32-bit versions) DeviceInstaller configuration software, Com Port Redirector software and related utilities
- Management Options: Web browser, Telnet client, Serial Terminal, SNMP v2 (MIBII, RS232MIB), XML

+ Regulatory

- FCC Part 15 Subpart B Class A
- ICES-003 Issue 4 February 2004 Class A
- AS/NZS CISPR 22: 2004 Class A
- EN55022: 1998 + A1: 2000 + A2: 2003 Class A
- VCCI V-3/2006.4 Class A
- EN61000-3-2: 2000 Class A
- EN61000-3-3: 1995 + A1: 2001
- EN55024: 1998 +A1: 2001 +A2: 2003
- IEC_61000-4-2: 1995 8kV Air, 4kV Contact
- IEC_61000-4-3: 1995 3.0V/m, 1kHz AM Sine Wave at 80%
- IEC_61000-4-4: 1995 1.0kV Power Lines, 0.5kV I/O Lines
- IEC_61000-4-5: 1995 1.0kV Common, 1.0 KV Differential
- IEC_61000-4-6: 1996 3.0 Vrms, 80% AM Modulated (1kHz)
- IEC_61000-4-8: 1993 50Hz 1.0 Arms/m
- IEC_61000-4-11: 1994 (>95%,0.5), (30%,25), (>95%,250)

+ Isolation

- Power Input: 2kV common mode and 1kV differential mode power surge protection
- Serial Port(s): 15 kV ESD protection
- Ethernet Port: 1500 VAC isolation shielded

ORDERING INFORMATION**+ Part Number**

ED4100Po-01

+ Description**EDS4100 four-port device server**

- No power supply
- CD Includes: User Guide and Software utilities (DeviceInstaller and Com Port Redirector)
- Quick Start Guide

ED4100Po-02

EDS4100 four-port device server

- 100-240 VAC International power supply with regional adapters
- CD Includes: User Guide and Software utilities (DeviceInstaller and Com Port Redirector)
- Quick Start Guide

**LANTRONIX®****CORPORATE HEADQUARTERS**

15353 Barranca Parkway | Irvine | CA 92618 | USA | t: 800.422.7055 | f: 949.450.7232 | sales@lantronix.com | www.lantronix.com

©2009, Lantronix, Inc. Lantronix is a registered trademark, and DeviceInstaller, Evolution OS and Com Port Redirector are trademarks of Lantronix, Inc.

All other trademarks are the property of their respective owners. Specifications subject to change without notice. All rights reserved.

920-007 08/09

Данный компонент на территории Российской Федерации**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибуторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ Р В 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru
moschip.ru_4

moschip.ru_6
moschip.ru_9