

3M™ Shrunk Delta Ribbon (SDR) Cable Assembly

.80 mm High Speed Digital Data Transmission, 26 position

1SF26-L1XX-00C-XXX



- Supports AIA Industrial Camera Link® Standard for Mini C/L camera to frame grabber applications
- 11 shielded, twisted twinax pairs with four drain wires
- Double overall shield with inner foil and outer braid
- Rugged ribbon contact type
- Rugged thumbscrew retention
- EMI shielded overmolded junction shell
- Optional R/A overmolded backshells eliminate bend radius
- See the Regulatory Information Appendix (RIA) in the “RoHS compliance” section of www.3M.com/Interconnect for compliance information (RIA E1 & C1 apply)

Date Modified: August 10, 2009

TS-2120-D
Sheet 1 of 4

Physical

Connector Contact Plating:

Wiping Area: 30 μ " [0.76 μ m] Min Gold

Underplating: 100 μ " [2.55 μ m] Nickel

Overmolded Shell:

Color: Black

Material: Polyvinyl Chloride (PVC)

Cable:

Color: Beige

Jacket Material: Polyvinyl Chloride (PVC)

Flammability: AWM VW-1

Marking: 3M Logo

Electrical

Voltage Rating: 30 V

Current Rating: 0.5 A

Insulation Resistance: 1 X 10⁸ Ω min at 100 V_{DC}

Withstanding Voltage: 125 V_{AC} RMS for 1 minute

Individually Shielded Twisted Pairs

Characteristic Impedance: 100 \pm 10 Ω

Conductor Size: 28 AWG Stranded

Propagation Velocity: 1.25 ns/ft [4.1 ns/m]

Skew (within pair): 50 ps / meter maximum

Skew (channel skew per chipset): 50 ps / meter maximum

Environmental

Temperature Rating: 0°C to +70°C

UL File No.: E86982

Camera Link is a certification mark of Automated Imaging Association

3M

Electronic Solutions Division
Interconnect Solutions
<http://www.3M.com/interconnects/>

3M is a trademark of 3M Company.
For technical, sales or ordering information call
800-225-5373

3M™ Shrunk Delta Ribbon (SDR) Cable Assembly

.80 mm High Speed Digital Data Transmission, 26 position

1SF26-L1XX-00C-XXX



Figure 1
Straight SDR to Straight SDR Cable Assembly
Option 20



Figure 2
Straight SDR to Straight SDR Cable Assembly

| mm [inch] | | |
|------------------------|------|-------|
| Tolerance Unless Noted | | |
| | .0 | .00 |
| mm | ± .1 | ± .01 |

[] Dimensions used for Reference Only

Note:

1. For length dimension, refer to the product ordering number.



TS-2120-D
Sheet 2 of 4

3M™ Shrunk Delta Ribbon (SDR) Cable Assembly

.80 mm High Speed Digital Data Transmission, 26 position

1SF26-L1XX-00C-XXX



Figure 3
R/A SDR to SDR Cable Assembly
Options 36 & 37




Figure 4
Overmolded R/A SDR Connector




Figure 5
Overmolded R/A SDR Connector
(36 option)



Figure 6
Overmolded R/A SDR Connector
(37 option)

| mm [inch] | | |
|------------------------|------|-------|
| Tolerance Unless Noted | | |
| | .0 | .00 |
| mm | ± .1 | ± .01 |

[] Dimensions used for Reference Only

TS-2120-D
Sheet 3 of 4

3M™ Shrunk Delta Ribbon (SDR) Cable Assembly

.80 mm High Speed Digital Data Transmission, 26 position

1SF26-L1XX-00C-XXX

| CN-1 Conn. Pos. | Base Configuration | | | | | CN-2 Conn. Pos. |
|-----------------------|-----------------------------|--------------|------------|--------------|--------------|-----------------------|
| | Full / Medium configuration | | | | | |
| | Cable | | | | | |
| 2 | XO- | YO- | TWINAX 1 | YO- | XO- | 25 |
| 15 | XO+ | YO+ | | YO+ | XO+ | 12 |
| 3 | X1- | Y1- | TWINAX 2 | Y1- | X1- | 24 |
| 16 | X1+ | Y1+ | | Y1+ | X1+ | 11 |
| 4 | X2- | Y2- | TWINAX 3 | Y2- | X2- | 23 |
| 17 | X2+ | Y2+ | | Y2+ | X2+ | 10 |
| 5 | XC- | Yclk- | TWINAX 4 | Yclk- | XC- | 22 |
| 18 | XC+ | Yclk+ | | Yclk+ | XC+ | 9 |
| 6 | X3- | Y3- | TWINAX 5 | Y3- | X3- | 21 |
| 19 | X3+ | Y3+ | | Y3+ | X3+ | 8 |
| 7 | Ser TC+ | 100 ohm | TWINAX 6 | 100 ohm | Ser TC+ | 20 |
| 20 | Ser TC- | Terminated | | Terminated | Ser TC- | 7 |
| 8 | Ser TFG- | ZO- | TWINAX 7 | ZO- | Ser TFG- | 19 |
| 21 | Ser TFG+ | ZO+ | | ZO+ | Ser TFG+ | 6 |
| 9 | CC1- | Z1- | TWINAX 8 | Z1- | CC1- | 18 |
| 22 | CC1+ | Z1+ | | Z1+ | CC1+ | 5 |
| 10 | CC2+ | Z2- | TWINAX 9 | Z2- | CC2+ | 17 |
| 23 | CC2- | Z2+ | | Z2+ | CC2- | 4 |
| 11 | CC3- | Zclk- | TWINAX 10 | Zclk- | CC3- | 16 |
| 24 | CC3+ | Zclk+ | | Zclk+ | CC3+ | 3 |
| 12 | CC4+ | Z3- | TWINAX 11 | Z3- | CC4+ | 15 |
| 25 | CC4- | Z3+ | | Z3+ | CC4- | 2 |
| 1 | INNER SHIELD | INNER SHIELD | DRAIN WIRE | INNER SHIELD | INNER SHIELD | 1 |
| 14 | INNER SHIELD | INNER SHIELD | | INNER SHIELD | INNER SHIELD | 14 |
| 13 | INNER SHIELD | INNER SHIELD | | INNER SHIELD | INNER SHIELD | 13 |
| 26 | INNER SHIELD | INNER SHIELD | | INNER SHIELD | INNER SHIELD | 26 |
| Shell | BRAID SHIELD | | | | | Shell |

Table 1
Cable Assembly Wiring Diagram

Ordering Information

1SF26-L1XX-00C-XXX (RIA E1 & C1 apply)

20 = SDR straight to SDR straight backshell.

36 = The direction of the cable for the RA SDR connector dresses down with respect to a horizontal board mount connector. The topology for the 36 option is a straight overmolded SDR backshell to a R/A overmolded SDR backshell.

37 = The direction of the cable for the RA SDR connector dresses up with respect to a horizontal board mount connector. The topology for the 37 option is a straight overmolded SDR backshell to a R/A overmolded SDR backshell.

Length :
100 = 1m
200 = 2m
500 = 5m
A00 = 10m

Refer to length dimension in figures 1 & 3
Reference notes 1 & 2 for cable length tolerance

Notes:

- For a cable length of less than 2m, the length tolerance is +50mm / -0mm
- For a cable length of 2m or more, the length tolerance is +3% / -0% of cable length

TS-2120-D
Sheet 4 of 4

3M

Electronic Solutions Division
Interconnect Solutions

<http://www.3M.com/interconnects/>

3M is a trademark of 3M Company.
For technical, sales or ordering information call
800-225-5373

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

**3M Electronics Solutions Division**

6801 River Place Blvd.
Austin, TX 78726-9000
U.S.A.
1-800-225-5373
www.3mconnectors.com

Please recycle. Printed in USA.
© 3M 2009. All rights reserved.

3M is a trademark of 3M Company.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9