

1.8V CMOS COMPATIBLE SMD CRYSTAL CLOCK OSCILLATOR

ASFL3



RoHS
Compliant



5.0 x 3.2 x 1.6 mm

FEATURES:

- Tri-state function
- Suitable for high density SMT
- Available tight stability option, +/-20ppm
- Seam sealed package assures high reliability
- Suitable for RoHS reflow

APPLICATIONS:

- CCD clock for VTR camera
- Equipment connected to PC or PC cards
- Thin equipment
- Wireless communication

STANDARD SPECIFICATIONS:

PARAMETERS

ABRACON P/N:	ASFL3 Series
Frequency:	0.5 MHz to 125 MHz
Operating temperature:	-10°C to +70°C (see option)
Storage temperature:	- 55°C to + 125°C
Overall Frequency Stability:	±100 ppm max. (see option)
Supply voltage (Vdd):	1.8 Vdc ± 10%
Supply Current (Idd):	See table below
Symmetry at 1/2 Vdd:	40/60% max. (see option)
Rise and Fall Times(Tr/Tf):	See table below
Output load:	15pF max.*
Output Voltage:	VOH = 0.9*Vdd min., VOL = 0.1*Vdd max.
Tri-state Function:	"1" or open;; Oscillation; VIH > 0.7*Vdd, "0": Output disabled (HI-Z); VIL < 0.3*Vdd
Start-up-time:	See table below
Aging (First year):	±3 ppm max. @25°C
Period Jitter:	See table below


Table:

* 30pF max is available. Please contact ABRACON.

Frequency range (MHz)	Idd mA (Typ)	Idd mA (Max)	Tr/Tf ns (Typ)	Tr/Tf ns (max)	Start-up time ms (Typ)	Start-up time ms (Max)	Period Jitter RMS ps (Typ)	Period Jitter RMS ps (Max)
0.5~9.999	2	5	5	10	3	5	2	3
10.000~29.999	5	8	3	6	3	5	2	3
30.000~49.999	8	10	3	6	3	5	2	3
50.000~69.999	5	10	2	5	3	5	2	3
70.000~99.999	8	15	2	5	4	10	2	3
100.000~125.000	12	20	2	4	4	10	2	3

OPTIONS AND PART IDENTIFICATION:

(Left blank if standard)



ABRACON IS
ISO9001:2008
CERTIFIED



ABRACON
CORPORATION

Visit www.abracon.com for Terms & Conditions of Sale **Revised: 06.30.10**
30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

1.8V CMOS COMPATIBLE SMD CRYSTAL CLOCK OSCILLATOR

ASFL3





RoHS
Compliant



5.0 x 3.2 x 1.6 mm

OUTLINE DRAWING:





PIN	FUNCTION
1	Tri-State
2	GND
3	Output
4	VDD

Note: It is recommended to use an approximately 0.01 μ F bypass capacitor between PIN 2 and 4.

TAPE & REEL: Tape and reel 1,000pcs/reel

REFLOW PROFILE:



Need a test socket for the ASFL3 Series? To view compatible **PRECISION TEST & BURN-IN SOCKETS** for these parts, [click here](#).

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS
ISO9001:2008
CERTIFIED



Visit www.abracon.com for Terms & Conditions of Sale **Revised: 06.30.10**
 30332 Esperanza, Rancho Santa Margarita, California 92688
 tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9