

USB3F TV - Reduced Flange

Smaller and Lighter



Dataspeed
10 x higher than USB2.0

Description

Derived from standard USB3F TV, Reduced Flange USB3F TV is ideal for applications where small dimensions and lower weight are critical.

With USB field, you can insert a standard USB 3.0 cordset into a metallic plug which will protect it from shocks, dust and fluids. No hazardous on-field cabling and grounding!

Main Features

- Smaller: **40% footprint surface reduction**
- Lighter: **15% lighter than standard USB3F TV receptacles**
- MIL-DTL-38999 coupling mechanism
- Mates with standard USB3F TV plugs & caps
- 3 platings: Olive Drab Cadmium, Nickel, Black Zn Ni
- USB3.0
- Reduced Flange Deviation (to be added at the end of your part number):
 - **F312** for standard versions (**F311** with safety castle nut*)
 - **F059** for Stand Off versions (**F058** with safety castle nut*)



standard
castle nut



* safety
castle nut

Main characteristics

Sealed against fluids and dust (IP68)

Shock, vibration and traction resistant

No cabling operation in field and no tools required

Improved EMI protection

Tri start thread coupling mechanism (MIL-DTL-38999 series III type) with anti-decoupling device - shell size 15

2 mechanical coding / polarization possibilities (receptacle insert rotation)

Mating cycles: 500 minimum

Environmental protection

Sealing: IP68 when mated with cap or potted version without cap

Salt spray:

> 48h with aluminium shell - Nickel ✓

> 500h with aluminium shell - Olive drab cadmium plating

> 500 h with aluminium shell - Black zinc nickel ✓

Fire retardant / low smoke: UL94 V0 and EN45545

Vibrations:

10 – 500 Hz, 10 g, 3 axes: no discontinuity > 1micro s

Shocks: IK06: weight of 250 g drop from 40 cm [15.75 in] onto connectors (mated pair)

Temperature range: - 40°C / +85°C

Data transmission

USB specification 3.0

Data rate: up to 5Gb/s for high speed USB

Power supply: up to 4.5 W

Markets & Applications



C4ISR, Battlefield, Ground vehicles



Navy



Railway












Applications:

- › Embedded computers, data acquisition and transmission in harsh environment, battlefield communication

USB3F TV - Reduced Flange

Smaller Dimensions and 15% lighter

Product	Length (mm)		Footprint (mm)	Panel dimension
Standard USB3F TV 	Standard USB3F TV 	Standard stand off USBF TV 	Standard USB3F TV 	Standard USB3F TV 
Reduced Flange USB3F TV 	Reduced Flange USB3F TV (F312) 	Stand off Reduced Flange USB3F TV (F059) 	Reduced Flange USB3F TV 	Reduced Flange USB3F TV 
	Increase of internal length by 1,37 mm	Reduction of internal length by 4mm and increase of external length by 4mm	40% footprint surface reduction	

Footprint Saving

40% footprint surface reduction:

Shell Size	USB3F TV standard diameter ØA max (mm)	USB3F TV Reduced Flange diameter ØK max (mm)	Footprint surface reduction Reduced Flange vs standard
15	41,6	32,1	40%

Panel Dimension


	USB3F TV Standard		USB3F TV Reduced Flange	
Size	B ⁰ _{-0,25} (mm)	ØC ^{+0,25} ₀ (mm)	ØG ^{+0,1} ₀ (mm)	H ^{+0,1} ₀ (mm)
15	27,56	28,83	27	25,5

Tools

Need of a specific tool for castle nut:


Size	Tool Part Number
15	809684

Max torque value: 8.5 N.m




USB3F TV - Reduced Flange

Receptacle




USB3F TV 7 X X F312




Panel Drilling


Stand off receptacle



USB3F TV 7S X X F059



Panel Drilling





PCB Layout

USB3F TV - Reduced Flange

Coding

To be specified in the part number: A or B.



How to order


Series	USB3F TV	7	A	ZN	F312
Shell type 7: Jam nut receptacle 7S: Transversally sealed jam nut receptacle for F059 or F058 only					
Coding A or B					
Shells material & Finish (inserts are metallized) N: Aluminium shell - nickel plating ✓ G: Aluminium shell - olive drab cadmium plating ZN: Aluminium shell - black zinc nickel plating ✓					
Deviation F312: Reduced Flange F059: Stand off Reduced Flange (only in transversally sealed version) F311: Reduced Flange with safety castle nut F058: Stand off Reduced Flange with safety castle nut (only in transversally sealed version)					

Examples: USB3FTV7AZNF312 ; USB3FTV7SBGF059

✓ : RoHS compliant

Watch our video

Rugged USB Plug Assembly



<http://opn.to/a/Azd09>

Scan
& discover !



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9