128K x 8 Static RAM

Features

- **High Speed**
  - **55ns and 70ns availability**
- **Voltage range**
  - **2.7V–3.6V**
- **Ultra low active power**
  - **Typical active current: 20 mA @ f = f_{max} (70ns speed)**
- **Low standby power**
- **Easy memory expansion with $\overline{CE}$ and $\overline{OE}$ features**
- **Automatic power-down when deselected**
- **CMOS for optimum speed/power**

Functional Description

The WCMA1008U1X is a high-performance CMOS static RAM organized as 128K words by 8 bits. Easy memory expansion is provided by an active LOW Chip Enable ($\overline{CE_1}$), an active HIGH Chip Enable (CE_2), an active LOW Output Enable ($\overline{OE}$) and three-state drivers. These devices have an automatic power-down feature, reducing the power consumption by over 99% when deselected.


Writing to the device is accomplished by taking Chip Enable one ($\overline{CE_1}$) and Write Enable ($\overline{WE}$) inputs LOW and the Chip Enable two (CE_2) input HIGH. Data on the eight I/O pins (I/O_0 through I/O_7) is then written into the location specified on the address pins (A_0 through A_{16}).

Reading from the device is accomplished by taking Chip Enable one ($\overline{CE_1}$) and Output Enable ($\overline{OE}$) LOW while forcing Write Enable ($\overline{WE}$) and Chip Enable two (CE_2) HIGH. Under these conditions, the contents of the memory location specified by the address pins will appear on the I/O pins.


The eight input/output pins (I/O_0 through I/O_7) are placed in a high-impedance state when the device is deselected ($\overline{CE_1}$ HIGH or CE_2 LOW), the outputs are disabled ($\overline{OE}$ HIGH), or during a write operation ($\overline{CE_1}$ LOW, CE_2 HIGH, and $\overline{WE}$ LOW).


The WCMA1008U1X is available in a 32 Lead TSOP and STSOP packages.

Logic Block Diagram



Pin Configurations





Maximum Ratings

(Above which the useful life may be impaired. For user guidelines, not tested.)

Storage Temperature .....–65°C to +150°C

Ambient Temperature with Power Applied.....55°C to +125°C

Supply Voltage to Ground Potential..... .....–0.5V to +4.6V

DC Voltage Applied to Outputs in High Z State[1].....0.5V to V_{CC} + 0.5V

DC Input Voltage[1].....–0.5V to V_{CC} + 0.5V

Output Current into Outputs (LOW).....20 mA

Static Discharge Voltage .....>2001V (per MIL-STD-883, Method 3015)

Latch-Up Current .....>200 mA

Operating Range

Product	Range	Ambient Temperature	V_{CC}
WCMA1008U1X	Industrial	–40°C to +85°C	2.7V to 3.6V

Product Portfolio

Product	V_{CC} Range			Speed	Power Dissipation (Industrial)			
					Operating, I_{CC}		Standby (I_{SB2})	
					$f = f_{max}$		Typ.[2]	Max.
	Min.	Typ.[2]	Max.		Typ.[2]	Max.		
WCMA1008U1X	2.7V	3.0V	3.6V	70 ns	20 mA	40 mA	0.4 µA	30 µA
				55 ns				

Notes:

1. $V_{IL(min.)}$ = –2.0V for pulse durations less than 20 ns.
2. Typical values are included for reference only and are not guaranteed or tested. Typical values are measured at $V_{CC} = V_{CC(typ.)}$, T_A = 25°C.

Electrical Characteristics Over the Operating Range

Parameter	Description	Test Conditions			WCMA1008U1X-70/55 Min.	Typ.[2]	Max.	Unit
V_{OH}	Output HIGH Voltage	I_{OH} = –1.0 mA	V_{CC} = 2.7V		2.4			V
V_{OL}	Output LOW Voltage	I_{OL} = 2.1 mA	V_{CC} = 2.7V				0.4	V
V_{IH}	Input HIGH Voltage				2		V_{CC} + 0.5V	V
V_{IL}	Input LOW Voltage				–0.5		0.8	V
I_{IX}	Input Leakage Current	GND ≤ V_I ≤ V_{CC}			–1		+1	µA
I_{OZ}	Output Leakage Current	GND ≤ V_O ≤ V_{CC}, Output Disabled			–1		+1	µA
I_{CC}	V_{CC} Operating Supply Current	f = f_{MAX} = $1/t_{RC}$	V_{CC} = 3.6V I_{OUT} = 0 mA CMOS Levels	70ns		20	40	mA
				55ns		23	50	
I_{SB1}	Automatic CE Power-Down Current— TTL Inputs	Max. V_{CC}, $\overline{CE}_1 \geq V_{IH}$, $CE_2 < V_{IH}$ $V_{IN} \geq V_{IH}$ or $V_{IN} \leq V_{IL}$, f = f_{MAX}		70ns		15	300	µA
				55ns		17	350	
I_{SB2}	Automatic CE Power-Down Current— CMOS Inputs	Max. V_{CC}, $\overline{CE}_1 \geq V_{CC}$ – 0.3V, CE_2 <0.3 $V_{IN} \geq V_{CC}$ – 0.3V or $V_{IN} \leq$ 0.3V, f = 0				0.4	30	

Capacitance[3]

Parameter	Description	Test Conditions	Max.	Unit
C_{IN}	Input Capacitance	T_A = 25°C, f = 1 MHz, V_{CC} = $Vcc_{(typ)}$	6	pF
C_{OUT}	Output Capacitance		8	pF


Thermal Resistance


Description	Test Conditions	Symbol	BGA	Unit
Thermal Resistance[3] (Junction to Ambient)	Still Air, soldered on a 4.25 x 1.125 inch, 4-layer printed circuit board	Θ_{JA}	55	°C/W
Thermal Resistance[3] (Junction to Case)		Θ_{JC}	16	°C/W

Note:


3. Tested initially and after any design or process changes that may affect these parameters.

AC Test Loads and Waveforms





Equivalent to: THÉVENIN EQUIVALENT




Parameters	3.3V	Unit
R1	1213	Ohms
R2	1378	Ohms
R_{TH}	645	Ohms
V_{TH}	1.75	Volts

Data Retention Characteristics (Over the Operating Range)

Parameter	Description	Conditions	Min.	Typ.[2]	Max.	Unit
V_{DR}	V_{CC} for Data Retention		1.6			V
I_{CCDR}	Data Retention Current	V_{CC} = 2V, $\overline{CE_1} \geq V_{CC} - 0.3V$, $CE_2 < 0.3V$ $V_{IN} \geq V_{CC} - 0.3V$ or $V_{IN} \leq 0.3V$		0.4	20	µA
t_{CDR}[3]	Chip Deselect to Data Retention Time		0			ns
t_R[4]	Operation Recovery Time		t_{RC}			ns

Data Retention Waveform



Note:

4. Full Device AC operation requires linear V_{CC} ramp from V_{DR} to $V_{CC(min.)} \geq 100\,\mu s$ or stable at $V_{CC(min.)} \geq 100\,\mu s$.

Switching Characteristics Over the Operating Range[5]


Parameter	Description	WCMA1008U1X-55		WCMA1008U1X-70		Unit
		Min.	Max.	Min.	Max.	
READ CYCLE						
t_{RC}	Read Cycle Time	55		70		ns
t_{AA}	Address to Data Valid		55		70	ns
t_{OHA}	Data Hold from Address Change	5		10		ns
t_{ACE}	$\overline{CE}_1$ LOW and CE_2 HIGH to Data Valid		55		70	ns
t_{DOE}	$\overline{OE}$ LOW to Data Valid		20		35	ns
t_{LZOE}	$\overline{OE}$ LOW to Low Z[6]	10		10		ns
t_{HZOE}	$\overline{OE}$ HIGH to High Z[6, 7]		20		25	ns
t_{LZCE}	$\overline{CE}_1$ LOW and CE_2 HIGH to Low Z[6]	10		10		ns
t_{HZCE}	$\overline{CE}_1$ HIGH or CE_2 LOW to High Z[6, 7]		20		25	ns
t_{PU}	$\overline{CE}_1$ LOW and CE_2 HIGH to Power-Up	0		0		ns
t_{PD}	$\overline{CE}_1$ HIGH or CE_2 LOW to Power-Down		55		70	ns
WRITE CYCLE[8,]						
t_{WC}	Write Cycle Time	55		70		ns
t_{SCE}	$\overline{CE}_1$ LOW and CE_2 HIGH to Write End	45		60		ns
t_{AW}	Address Set-Up to Write End	45		60		ns
t_{HA}	Address Hold from Write End	0		0		ns
t_{SA}	Address Set-Up to Write Start	0		0		ns
t_{PWE}	$\overline{WE}$ Pulse Width	45		55		ns
t_{SD}	Data Set-Up to Write End	25		30		ns
t_{HD}	Data Hold from Write End	0		0		ns
t_{HZWE}	$\overline{WE}$ LOW to High Z[6, 7]		20		25	ns
t_{LZWE}	$\overline{WE}$ HIGH to Low Z[6]	5		5		ns

Notes:


5. Test conditions assume signal transition time of 5 ns or less, timing reference levels of $V_{CC(typ.)}/2$, input pulse levels of 0 to $V_{CC(typ.)}$, and output loading of the specified I_{OL}/I_{OH} and 30 pF load capacitance.
6. At any given temperature and voltage condition, t_{HZCE} is less than t_{LZCE}, t_{HZOE} is less than t_{LZOE}, and t_{HZWE} is less than t_{LZWE} for any given device.
7. t_{HZOE}, t_{HZCE}, and t_{HZWE} transitions are measured when the outputs enter a high impedance state.
8. The internal write time of the memory is defined by the overlap of $\overline{WE}$, $\overline{CE}_1 = V_{IL}$ and $CE_2 = V_{IH}$. All signals must be ACTIVE to initiate a write and any of these signals can terminate a write by going INACTIVE. The data input set-up and hold timing should be referenced to the edge of the signal that terminates the write.

Switching Waveforms

Read Cycle No. 1 (Address Transition Controlled) [9, 10]



Read Cycle No. 2 ($\overline{OE}$ Controlled) [10, 11]




Notes:


9. Device is continuously selected. $\overline{OE}$, $\overline{CE}_1$ = V_{IL}, CE_2 = V_{IH}.
10. $\overline{WE}$ is HIGH for read cycle.
11. Address valid prior to or coincident with $\overline{CE}_1$ transition LOW and CE_2 transition HIGH.

Switching Waveforms (continued)

Write Cycle No. 1($\overline{WE}$ Controlled) [8, 12, 14]



Write Cycle No. 2 ($\overline{CE_1}$ or CE_2 Controlled) [8, 12, 14]




Notes:

12. Data I/O is high impedance if $\overline{OE} = V_{IH}$.
13. During this period, the I/Os are in output state and input signals should not be applied.
14. If $\overline{CE_1}$ goes HIGH and CE_2 goes LOW simultaneously with WE HIGH, the output remains in a high-impedance state.

Switching Waveforms (continued)

Write Cycle No. 3 ($\overline{WE}$ Controlled, $\overline{OE}$ LOW) [14]



Truth Table


$\overline{CE_1}$	CE_2	$\overline{WE}$	$\overline{OE}$	Inputs/Outputs	Mode	Power
H	X	X	X	High Z	Deselect/Power-Down	Standby (I_{SB})
X	L	X	X	High Z	Deselect/Power-Down	Standby (I_{SB})
L	H	H	L	Data Out	Read	Active (I_{CC})
L	H	L	X	Data In	Write	Active (I_{CC})
L	H	H	H	High Z	Output Disabled	Active (I_{CC})

Ordering Information

Speed (ns)	Ordering Code	Package Name	Package Type	Operating Range
70	WCMA1008U1X-TF70	T32	32-Lead TSOP	Industrial
	WCMA1008U1X-SF70	S32	32-Lead STSOP	
55	WCMA1008U1X-TF55	T32	32-Lead TSOP	
	WCMA1008U1X-SF55	S32	32-Lead STSOP	


Package Diagrams

32-Lead Thin Small Outline Package, T32



Package Diagrams (continued)

32-Lead Shrunk Thin Small Outline Package, S32



Document Title: WCMA1008U1X, 128K x 8 Static RAM					
REV.	**Spec #**	**ECN #**	**Issue Date**	**Orig. of Change**	**Description of Change**
**	38-14023	115246	4/24/2002	MGN	New Data Sheet

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9