

REFERENCE SPECIFICATIONS

-NFC 93425 (in compliance with HE 507)

PHYSICAL CHARACTERISTICS

- INSULATOR MATERIAL: THERMOPLASTIC ,UL94V0
- ACCESSORIES: BRASS
- SHELLS: STEEL

ELECTRICAL CHARACTERISTICS

- CONTACT/CONTACT : >=1000 V
- CONTACT/GROUND : >=1200 V
- INSULATION RESISTANCE: >=5000 MOhms

ENVIRONMENTAL CHARACTERISTICS



- CLIMATIC CATEGORY: 55/125/21
- TEMPERATURE RANGE -55°C TO +125°C
- DAMP HEAT STEADY STATE 21 DAYS
- SALT SPRAY 24 HOURS

MECHANICAL CHARACTERISTICS


- RETENTION AGAINST TORQUE:
 - Threaded insert: 0.7 N.m minimum
 - Female screw : 0.5 N.m minimum

NOTE ROHS INFORMATION

- The “LF” products meet european union Directives and other country regulations as described in GS-22-008.
- Shell plating :2 to 4µm Cu+ Ni + 3 to 10µmm Sn(pure bright)
- Accessories: Sn pure bright + nickel
- Packaging spec: See GS-14-920



spec ref				dr	Pro Engineer 1	2015/06/16			size	A2	scale	2:1
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	J Dalibard	2016/09/13			ecn no	ECN-ELX-F-24942-1		
				chr	J Dalibard	2016/09/19			product family - rel level Released			
				appr	Aymeric Soudy	2016/09/20						
surface 	linear	0.X	±0.3	Amphenol FCi	title SUB FEMALE DW full power without contact				dwg no	C01-8639-2311		rev E
		0.XX	±0.10									
		0.XXX	±0.05									
		angular	0°									
				cat. no.	-	Product - Customer Drw				sheet 1 of 4		



FRONT ACCESSORY	Blank without	L insert M3 O insert UNC 4.40	V Female screw UNC 4-40
PCB ACCESSORIES	A without	A without	A without

PART NUMBER	FRONT ACCESSORY	PCB ACCESSORY
D*W xSA00LF	WITHOUT	WITHOUT
D*VxW xSA00LF	Female screw UNC 4-40	WITHOUT
D*LxW xSA00LF	Insert M3	WITHOUT
D*OxW xSA00LF	Insert UNC 4-40	WITHOUT

shell size LAYOUTS

E	2V2
A	3V3
A	3W3
B	5W5
C	8W8

SCALE:4

spec ref				dr	Pro Engineer 1	2015/06/16			size	scale			
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	J Dalibard	2016/09/13			A2	2:1			
				chr	J Dalibard	2016/09/19			ecn no	ECN-ELX-F-24942-1			
				appr	Aymeric Soudy	2016/09/20			product family		-	rel level	Released
surface		linear	0.X	±0.3		title SUB FEMALE DW			dwg no	C01-8639-2311		rev	
			0.XX	±0.10									
			0.XXX	±0.05									
			angular	0°									±2°
						cat. no.	-	Product - Customer Drw				sheet 2 of 4	

FIRST ANGLE PROJECTION

C

D

E

F

A

B

C

D




E

FIRST ANGLE PROJECTION








2V2

3V3



3W3



SIDE VIEW FOR LAYOUTS: E A B C



spec ref				dr		Pro Engineer 1		2015/06/16		projection		mm		size		scale													
tolerance std				eng		J Dalibard		2016/09/13						A2		2:1													
TOLERANCES UNLESS OTHERWISE SPECIFIED				chr		J Dalibard		2016/09/19		ecn no				ECN-ELX-F-24942-1															
				appr		Aymeric Soudy		2016/09/20		product family				- rel level		Released													
surface 				linear		0.X		±0.3		Amphenol FCI		title		SUB FEMALE DW				dwg no		C01-8639-2311		rev		E					
																										0.XX		±0.10	
																										0.XXX		±0.05	
																										angular		0°	
										cat. no.		-		Product - Customer Drw				sheet 3 of 4											



spec ref				dr	Pro Engineer 1	2015/06/16			size	A2	scale	2:1		
tolerance std				eng	J Dalibard	2016/09/13			ecn no	ECN-ELX-F-24942-1				
TOLERANCES UNLESS OTHERWISE SPECIFIED				chr	J Dalibard	2016/09/19			rel levelReleased					
				appr	Aymeric Soudy	2016/09/20	product family							
surface	linear	0.X	±0.3	Amphenol FCi	title	SUB FEMALE DW			dwg no	C01-8639-2311			rev	E
		0.XX	±0.10											
		0.XXX	±0.05											
	angular	0°	±2°											

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9