



CRYSTEK MICROWAVE

A DIVISION OF CRYSTEK CORPORATION

50 GHZ LOW LOSS RF COAX CABLE ASSEMBLIES WITH 2.4mm STAINLESS STEEL CONNECTORS



50 GHz Low Loss Coaxial Cables

Features:

Strain Relief:	Heavy duty adhesive strain relief
Center Conductor:	Silver-plated solid copper
Inner Shield:	Flat silver-plated copper strip
Middle Shield:	High temp. aluminum polyimide foil
Outer Shield:	PC (Round Silver-Plated Copper Braid)
Dielectric:	Expanded PTFE, Type F (Polytetrafluoroethylene)
Jacket:	ETFE, Type X per ASTM D3159
Cable Outer Diameter:	0.122" (3.10mm)
Connectors:	SST, corrosion-resistant 303 stainless steel per ASTM-A582 (Passivated finish per SAE-AMS-2700)
Center Pin:	GPBC (Gold-Plated Beryllium Copper)
Jacket Color:	Grey
Operating Temperature:	-40°C to +85°C
Minimum Bend Radius:	0.40"

Electrical Specifications:

Impedance:	50 Ohms
Frequency:	Up to 50 GHz
Insertion Loss:	<1.44 dB/ft at 50 GHz
VSWR:	<1.35 to 50 GHz
Max Oper. Voltage:	500V RMS
Nominal Capacitance:	27.0 pF/ft
Velocity of Propagation:	78%
Shield Effectiveness:	Greater than 90 dB
Attenuation (dB/ft):	0.11 Max at 500 MHz
*connector loss not included	0.17 Max at 1 GHz
	0.43 Max at 6 GHz
	0.63 Max at 12 GHz
	0.79 Max at 18 GHz
	0.97 Max at 26 GHz
	1.26 Max at 40 GHz
	1.44 Max at 50 GHz

Mechanical Specifications:

Connector Corrosion (salt spray):

MIL-STD-202, method 101, test cond. B 5% salt solution.


Connector Durability:

500 connections Minimum

Electrical Test Data Supplied With Each Cable Assembly

Custom Lengths Available

2.4mm / 2.4mm [Straight/Straight]



Part Number	Description	Length
CC2450-MM-150-24	50 GHz Low Loss Coax Cable, 2.4mm Male/Male, Straight/Straight	24"
CC2450-MM-150-39.4	50 GHz Low Loss Coax Cable, 2.4mm Male/Male, Straight/Straight	39.4"
CC2450-MM-150-48	50 GHz Low Loss Coax Cable, 2.4mm Male/Male, Straight/Straight	48"



CRYSTEK
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913





PHONE: 239-561-3311 • 800-237-3061 Rev.: C

FAX: 239-561-1025 • WWW.CRYSTEK.COM Date: 04-07-14



CRYSTEK
MICROWAVE
A DIVISION OF CRYSTEK CORPORATION

**50 GHZ LOW LOSS RF
COAX CABLE ASSEMBLIES
WITH 2.4mm
STAINLESS STEEL
CONNECTORS**



CRYSTEK
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913
PHONE: 239-561-3311 • 800-237-3061
FAX: 239-561-1025 • WWW.CRYSTEK.COM

Rev.: C
Date: 04-07-14

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9