



## Main

Range of product	OsiSense XX
Sensor type	Ultrasonic sensor
Sensor name	XX9
Material	PBT (polybutylene terephthalate)
Sensor design	Ø 18 mm
Product specific application	Analog output
Type of output signal	Analogue
Wiring technique	4 wires
[Us] rated supply voltage	15...24 V DC with reverse polarity protection
Electrical connection	Cable 6.56 ft (2 m)
[Sd] sensing range	2.75...4 in (69.9...101.6 mm)
Beam angle	10 °
IP degree of protection	IP67 conforming to IEC 60529

## Complementary

Enclosure material	ULTEM
Front material	Silicone
ISO thread	M18 x 1
Supply voltage limits	10...28 V DC
Analogue output range	0...10 V inverse
[Sn] nominal sensing distance	4 in (101.6 mm)
Sensing window	69.9
Type of sensing window	Fixed
[Sa] assured operating distance	0.13...9 in (3.18...228.6 mm) (no teach mode)
Blind zone	2.01 in (51 mm)
Transmission frequency	500 kHz
Repeat accuracy	1.27 %
Minimum size of detected object	Cylinder diameter 1.6 mm up to 63.5 mm sensing distance
Status LED	2 LEDs (green/yellow (flashing)) setting-up assistance 2 LEDs (green/yellow) output state
Current consumption	50 mA
Maximum switching current	100 mA with overload and short-circuit protection
Maximum switching capacity	1 kOhm with overload and short-circuit protection
Delay response	2.5 ms
Delay recovery	1000 ms
Marking	CE
Height	0.71 in (18 mm)
Width	0.71 in (18 mm)
Depth	0.71 in (18 mm)
Length	2.55 in (64.77 mm)
CAD overall height	0.71 in (18 mm)
CAD overall width	0.71 in (18 mm)
CAD overall depth	0.71 in (18 mm)
Product weight	0.37 lb(US) (0.17 kg)

## Environment

standards	IEC 60947-5-2
product certifications	UL

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

NEMA degree of protection	NEMA 4X indoor use only
ambient air temperature for operation	32...140 °F (0...60 °C)
ambient air temperature for storage	-40...212 °F (-40...100 °C)
vibration resistance	+/-1 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
shock resistance	30 gn 11 ms (in all 3 axes) conforming to IEC 60068-2-27
resistance to electrostatic discharge	8 kV, level 4 conforming to IEC 61000-4-2
resistance to electromagnetic fields	9.14 V/yd (10 V/m), level 3 conforming to IEC 61000-4-3
resistance to fast transients	1 kV, level 3 conforming to IEC 61000-4-4

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1140 - Schneider Electric declaration of conformity	Compliant - since 1140 - Schneider Electric declaration of conformity
Reference contains SVHC above the threshold - go to CaP for more details	Reference contains SVHC above the threshold
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9