

DESCRIPTION

Demonstration circuit 1531A is a two-terminal current source featuring LT®3092. It requires only two resistors to set an output current between 0.5mA and 200mA. It is stable without input and output capacitors, offering high DC and AC impedance. It can be used in many applications such as 2-terminal floating current source, GND referred current source, variable current source, in-line limiter and intrinsic safety circuits.

A key feature of the LT3092 is the capability to supply a wide output current range. By using two external resistors, the output current can be programmed to any level between 0.5mA and 200mA, while the input-to-output difference voltage is limited to 40V and the power dissipation is limited below the thermal limit.

Internal protection circuitry includes reverse-battery and reverse-current protection, current limiting and thermal limiting.

LT3092 regulator is offered in the thermally enhanced 8-lead TSOT-23, 3-lead SOT-223 and 8-lead 3mm×3mm DFN packages.

The LT3092 datasheet gives a complete description of the part, operation and application information. The datasheet should be read in conjunction with this quick start guide for working on or modifying the demo circuit 1531A.

Design files for this circuit board are available. Call the LTC factory.

 , LTC, LTM, LT and uModule are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

Table 1. Performance Summary ($T_A = 25^\circ\text{C}$)

PARAMETER	CONDITION	VALUE
Minimum Vin-Vout Voltage	$I_{OUT}=1\text{mA}$	1.2V
Maximum Vin-Vout Voltage		40V
Output Current	JP1, $I_{OUT}=200\text{mA}$	200mA $\pm 3\%$
	JP1, $I_{OUT}=100\text{mA}$	100mA $\pm 3\%$
	JP1, $I_{OUT}=50\text{mA}$	50mA $\pm 3\%$
	JP1, $I_{OUT}=\text{ADJ}$	0.5mA~110mA

QUICK START PROCEDURE

The DC1531A is easy to set up to evaluate the performance of the LT3092. Refer to Figure 1. for proper measurement equipment setup and following the procedures below:

1. Before proceeding to test, use jumper JP1 for the desired output current (200mA, 100mA or 50mA). If the output current is different from the above values, use the ADJ option.

2. Assume 200mA is the desired output. Apply 2V across VIN (to VOUT). The measured I_{OUT} should be $200mA \pm 3\%$ (195mA to 207mA).
3. Vary Vin-Vout from 2V to 40V. I_{OUT} should measure $200mA \pm 3\%$ (195mA to 207mA).

Note: Minimum Vin-Vout depends on I_{OUT} . See datasheet for dropout curves.




Figure 1. Proper Measurement Equipment Setup

ADDITIONAL NOTE

Although the LT3092's design strives to be stable without any capacitors over a wide variety of operating conditions, it is not possible to test for all possible combinations of input and output impedances that the LT3092 will encounter. These impedances may include resistive, capacitive and inductive components and may be complex distributed networks. In addition, the current source's value will differ between applications and its connection may be GND referenced, power supply referenced or floating in a signal line path. **Linear Technology strongly recommends that stability be tested in circuits for any LT3092 application.**

When operating with a capacitor across the SET pin resistor, external compensation is usually required to maintain stability and compensate for the introduced pole. Optional input capacitor, output capacitor or RC compensation can be installed on the back side of the DC1531A if necessary. See datasheet for details.



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9