





LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			A	RELEASE PER ECO-16-002978	3MAR2016	RG	SH



DETAIL A
SCALE 20:1

- 1 CAGE ASSEMBLY MATERIAL: NICKEL SILVER, 0.25 THICK
HEAT SINK MATERIAL: ALUMINUM
HEAT SINK CLIP MATERIAL: STAINLESS STEEL
EMI SPRING MATERIAL: COPPER ALLOY
EMI GASKET MATERIAL: CONDUCTIVE RUBBER,UL 94V-0 RATED
EMI GASKET PLATE MATERIAL: STAINLESS STEEL
- 2 PITCH BETWEEN PORTS OF ONE 1X4 CAGE ASSEMBLY.
- 3 SPACING BETWEEN CAGES ON THE SAME PC BOARD, TO BE SPECIFIED BY CUSTOMER, MUST COMPLY WITH MINIMUM DIMENSIONS SHOWN.
- 4 REFERENCE APPLICATION SPEC 114-13217 FOR RECOMMENDED DRILL HOLE DIAMETER AND PLATING THICKNESS.
- 5 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 6 DIMENSION F IS THE NOMINAL THICKNESS OF CUSTOMER SUPPLIED PC BOARD,
SINGLE SIDED PC BOARD MINIMUM THICKNESS = 1.45mm
DOUBLE SIDED PC BOARD MINIMUM THICKNESS = 5.0mm PER CUSTOM.
- 7 HEAT SINKS, LIGHT PIPES, AND HEAT SINK CLIPS SHIPPED ASSEMBLED TO CAGE ASSEMBLY. CAGE ASSEMBLY MAY BE PRESSED INTO THE PCB AS SHIPPED.
- 8 DATUM **-A-** IS TOP SURFACE OF PC BOARD.
- 9 DIMENSION APPLIES WITH MODULE INSERTED IN CAGE.
- 10 UNPLATED THRU HOLE.

11. MATES WITH QSFP MSA COMPATIBLE TRANSCEIVER.
- 12 SURFACE TRACES PERMITTED WITHIN THIS AREA EXCEPT WHERE CAGE STANDOFFS, SHOWN IN DETAIL A, CONTACT PC BOARD.
- 13 BASELINE FOR THESE DIMENSIONS IS THE CENTER OF COMPLIANT PIN HOLE.
- 14 DATE CODE (YYWWD) MARKED ON TOP OF CAGE AND CONCEALED BY HEAT SINKS APPLIES TO CAGE ASSEMBLY ONLY.
- 15 REFERENCE APP SPEC 114-13217 FOR GASKET THICKNESS CALCULATION.
- 16 EMI SPRING FINISH: TIN PLATING OVER NICKEL
HEAT SINK FINISH: ANODIZED OR NICKEL PLATING.




SECTION B-B
SCALE 10:1

2170287-4, 2170287-5, 2170287-6
SCALE 2:1

1-2170287-0
SCALE 2:1

1-2170287-1
SCALE 2:1





2170287-1, 2170287-2, 2170287-3
SCALE 2:1

2170287-7, 2170287-8, 2170287-9
SCALE 2:1



1		
13.7	PCI(FIN TYPE)	1-2170287-1
15.0	CUSTOMIZED HEAT SINK	1-2170287-0
23.0	NETWORKING(FIN TYPE)	2170287-9
16.0	SAN(FIN TYPE)	2170287-8
13.7	PCI(FIN TYPE)	2170287-7
23.0	NETWORKING(FIN TYPE)	2170287-6
16.0	SAN(FIN TYPE)	2170287-5
13.7	PCI(FIN TYPE)	2170287-4
23.0	NETWORKING(PIN TYPE)	2170287-3
16.0	SAN(PIN TYPE)	2170287-2
13.7	PCI(PIN TYPE)	2170287-1
B	HEAT SINK PROFILE	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN KINSEN SUN CHK DENNY ZHU APVD ALEX CAI	29FEB2012 29FEB2012 29FEB2012	TE Connectivity	
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
mm		0 PLC ±.35 1 PLC ±0.25 2 PLC ±.25 3 PLC ±.25 4 PLC ±.25 ANGLES ±.25		PRODUCT SPEC	
MATERIAL		FINISH		APPLICATION SPEC	
1		16		114-13217	
CUSTOMER DRAWING		WEIGHT		SIZE CAGE CODE DRAWING NO	
				A100779C=2170287	
				RESTRICTED TO	
				SCALE 4:1 SHEET 1 OF 8 REV A	



LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00	-	-	SEE SHEET 1	-	-	-





1-2170287-0 shown
SCALE 4:1



1-2170287-0
ONE SIDED CONFIGURATION
SCALE 5:2




1-2170287-1 SHOWN
SCALE 4:1




1-2170287-1
ONE SIDED CONFIGURATION
SCALE 5:2


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN KINSEN SUN CHK DENNY ZHU APVD ALEX CAI	29FEB2012 29FEB2012 29FEB2012	TE Connectivity	
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
mm		0 PLC ±.35 1 PLC ±0.35 2 PLC ±0.25 3 PLC ±.35 4 PLC ±.35 ANGLES ±.35 FINISH		1X4 CAGE ASSEMBLY, THRU BEZEL, W/ELASTOMERIC GASKET AND HEAT SINKS, QSFP	
MATERIAL		WEIGHT		SIZE CAGE CODE DRAWING NO	
-		-		A100779C=2170287	
CUSTOMER DRAWING		SCALE		SHEET 2 OF 8	
		1:1		REV A	

LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-




THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN KINSEN SUN 29FEB2012	 TE Connectivity	
DIMENSIONS:		CHK DENNY ZHU 29FEB2012		
mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD ALEX CAI 29FEB2012	NAME 1X4 CAGE ASSEMBLY, THRU BEZEL, W/ELASTOMERIC GASKET AND HEAT SINKS, QSFP	
	0 PLC	±0.35	PRODUCT SPEC	SIZE
	1 PLC	±0.25	108-2286	CAGE CODE
	2 PLC	±	APPLICATION SPEC	DRAWING NO
	3 PLC	±	114-13217	RESTRICTED TO
MATERIAL	FINISH	WEIGHT	A100779C=2170287	-
-	-	CUSTOMER DRAWING	SCALE 1:1	SHEET 3 OF 8 REV A

LOC		DIST		REVISIONS					
GP		00		P	LTR	DESCRIPTION	DATE	DWN	APVD
				-	-	SEE SHEET 1	-	-	-





ONE SIDED CONFIGURATION
SCALE 5:2




BELLY TO BELLY CONFIGURATION
SIMILAR TO ONE SIDED
EXCEPT WHERE NOTED
SCALE 5:2


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN KINSEN SUN CHK DENNY ZHU APVD ALEX CAI	29FEB2012 29FEB2012 29FEB2012	TE Connectivity	
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
mm		0 PLC ±.35 1 PLC ±0.35 2 PLC ±0.25 3 PLC ± 4 PLC ± ANGLES ± FINISH		PRODUCT SPEC 108-2286 APPLICATION SPEC 114-13217	
MATERIAL		WEIGHT		SIZE CAGE CODE DRAWING NO	
-		-		A100779C=2170287	
CUSTOMER DRAWING		SCALE		SHEET 4 OF 8	
		1:1		REV A	







DETAIL M
SCALE 10:1



DETAIL J
3 PLACES
SCALE 8:1

— 3.75 MIN $\triangle 3$
 ⌀ OF FINAL ROW OF HOLES
 TO ⌀ OF FIRST ROW OF HOLES
 FOR NEXT ADJACENT CAGE

—CROSS-HATCHED AREA DENOTES
COMPONENT AND TRACE KEEP-OUT
(EXCEPT CHASSIS GROUND)

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN KINSEN SUN	29FEB2012	 TE Connectivity					
		CHK DENNY ZHU	29FEB2012						
		APPR ALEX CAI	29FEB2012						
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	IX4 CAGE ASSEMBLY, THRU BEZEL, W/ELASTOMERIC GASKET AND HEAT SINKS, QSFP				
mm		0 PLC ±. 1 PLC ±0.35 2 PLC ±0.25 3 PLC ± 4 PLC ±		PRODUCT SPEC	108-2286				
		ANGLES ±.		APPLICATION SPEC	114-13217				
MATERIAL	FINISH			SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO		
-	-			WEIGHT	A100779C=2170287		-		
CUSTOMER DRAWING				SCALE	1:1	SHEET	7	OF	8
								REV	A



THIS DRAWING IS A CONTROLLED DOCUMENT.			OWN KINSEEN SUN 29FEB2012		 TE Connectivity	
			CHK DENNY CHAI 29FEB2012			
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME IX4 CAGE ASSEMBLY, THRU BEZEL, W/ELASTOMERIC GASKET AND HEAT SINKS, OSFP		
mm						
		Ø PLC	±	PRODUCT SPEC 108-2286 APPLICATION SPEC 114-13217		
		PLC	±0.35			
		PLC	±0.25			
		PLC	±			
		PLC	±			
ANGLES		±		SIZE CAGE CODE DRAWING NO. A100779C-2170287		
MATERIAL		FINISH				
-		-		CUSTOMER DRAWING		
-		-				
-		-		SCALE 1:1		
-		-				
-		-		REV A		

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9