
# Dual Common-Cathode Ultrafast Plastic Rectifier




## FEATURES

- Glass passivated chip junction
- Ultrafast recovery time
- Low switching losses, high efficiency
- High forward surge capability
- AEC Q101 qualified
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245 °C (for TO-263AB package)
- Solder dip 260 °C, 40 s (for TO-220AB and ITO-220AB package)
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

RoHS COMPLIANT

## TYPICAL APPLICATIONS

For use in high frequency rectifier of switching mode power supplies, inverters, freewheeling diodes, dc-to-dc converters, and other power switching application.

| PRIMARY CHARACTERISTICS | |
|---|---|
| $I_{F(AV)}$ | 8.0 A x 2 |
| $V_{RRM}$ | 50 V to 600 V |
| $I_{FSM}$ | 200 A, 125 A |
| $t_{rr}$ | 35 ns, 50 ns |
| $V_F$ | 0.95 V, 1.30 V, 1.50 V |
| $T_J$ max. | 150 °C |

## MECHANICAL DATA

**Case:** TO-220AB, ITO-220AB, TO-263AB

Epoxy meets UL 94V-0 flammability rating

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test

**Polarity:** As marked

**Mounting Torque:** 10 in-lbs maximum

**MAXIMUM RATINGS** ($T_C$ = 25 °C unless otherwise noted)

| PARAMETER | SYMBOL | FEP 16AT | FEP 16BT | FEP 16CT | FEP 16DT | FEP 16FT | FEP 16GT | FEP 16HT | FEP 16JT | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|
| Maximum repetitive peak reverse voltage | $V_{RRM}$ | 50 | 100 | 150 | 200 | 300 | 400 | 500 | 600 | V |
| Maximum RMS voltage | $V_{RMS}$ | 35 | 70 | 105 | 140 | 210 | 280 | 350 | 420 | V |
| Maximum DC blocking voltage | $V_{DC}$ | 50 | 100 | 150 | 200 | 300 | 400 | 500 | 600 | V |
| Maximum average forward rectified current at $T_C$ = 100 °C | $I_{F(AV)}$ | 16 | | | | | | | | A |
| Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load per diode | $I_{FSM}$ | 200 | | | | 125 | | | | A |
| Operating storage and temperature range | $T_J$, $T_{STG}$ | - 55 to +150 | | | | | | | | °C |
| Isolation voltage (ITO-220AB only) from terminal to heatsink t = 1 min | $V_{AC}$ | 1500 | | | | | | | | V |

| **ELECTRICAL CHARACTERISTICS** ($T_C$ = 25 °C unless otherwise noted) | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITIONS** | | **SYMBOL** | **FEP 16AT** | **FEP 16BT** | **FEP 16CT** | **FEP 16DT** | **FEP 16FT** | **FEP 16GT** | **FEP 16HT** | **FEP 16JT** | **UNIT** |
| Maximum instantaneous forward voltage per diode (1) | 8.0 A | | $V_F$ | 0.95 | | | | 1.30 | | 1.50 | | V |
| Maximum DC reverse current per diode at rated DC blocking voltage | | $T_C$ = 25 °C<br>$T_C$ = 100 °C | $I_R$ | 10<br>500 | | | | | | | | µA |
| Maximum reverse recovery time per diode | $I_F$ = 0.5 A, $I_R$ = 1.0 A, $I_{rr}$ = 0.25 A | | $t_{rr}$ | 35 | | | | 50 | | | | ns |
| Typical junction capacitance per diode | 4.0 V, 1 MHz | | $C_J$ | 85 | | | | | | 60 | | pF |

**Note:**

(1) Pulse test: 300 µs pulse width, 1 % duty cycle

| **THERMAL CHARACTERISTICS** ($T_C$ = 25 °C unless otherwise noted) | | | | | |
|---|---|---|---|---|---|
| **PARAMETER** | **SYMBOL** | **FEP** | **FEPF** | **FEPB** | **UNIT** |
| Typical thermal resistance from junction to case per diode | $R_{\theta JC}$ | 2.2 | 3.1 | 2.2 | °C/W |

| **ORDERING INFORMATION** (Example) | | | | | |
|---|---|---|---|---|---|
| **PACKAGE** | **PREFERRED P/N** | **UNIT WEIGHT (g)** | **PACKAGE CODE** | **BASE QUANTITY** | **DELIVERY MODE** |
| TO-220AB | FEP16JT-E3/45 | 1.85 | 45 | 50/tube | Tube |
| ITO-220AB | FEPF16JT-E3/45 | 1.97 | 45 | 50/tube | Tube |
| TO-263AB | FEPB16JT-E3/45 | 1.35 | 45 | 50/tube | Tube |
| TO-263AB | FEPB16JT-E3/81 | 1.35 | 81 | 800/reel | Tape and reel |
| TO-220AB | FEP16JTHE3/45 (1) | 1.85 | 45 | 50/tube | Tube |
| ITO-220AB | FEPF16JTHE3/45 (1) | 1.97 | 45 | 50/tube | Tube |
| TO-263AB | FEPB16JTHE3/45 (1) | 1.35 | 45 | 50/tube | Tube |
| TO-263AB | FEPB16JTHE3/81 (1) | 1.35 | 81 | 800/reel | Tape and reel |

**Note:**

(1) Automotive grade AEC Q101 qualified

## RATINGS AND CHARACTERISTICS CURVES

($T_A$ = 25 °C unless otherwise noted)





Figure 1. Forward Current Derating Curve





Figure 4. Typical Reverse Characteristics Per Diode





Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Diode





Figure 5. Typical Junction Capacitance Per Diode







Figure 3. Typical Instantaneous Forward Characteristics Per Diode

## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)


**TO-220AB**




**ITO-220AB**




**TO-263AB**



# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

**Данный компонент на территории Российской Федерации**

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

**Офис по работе с юридическими лицами:**

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9