



T H E R M O M E T R I C S  
A C O M M I T M E N T T O E X C E L L E N C E

# NTC Interchangeable Thermistor Series Type SC



## Features

- Precision, solid state temperature sensor
- Epoxy filled sleeve for controlled diameter
- Interchangeability down to  $\pm 0.18^{\circ}\text{F}$  ( $\pm 0.10^{\circ}\text{C}$ )
- Suitable for use over the range of:  
-40°F to 221°F (-40°C to 105°C)
- High sensitivity greater than:  
-4%/°C at 77°F (25°C)
- Most popular Resistance (R) vs Temperature (T) curves are available
- Suitable for temperature measurement, control and compensation
- Ideal for medical applications
- Fully insulated
- Polyimide sleeved for good mechanical strength and resistance to solvents
- 0.008 in (0.2 mm) diameter heavy isomid insulated bifilar copper lead wires for SC50
- 0.004 in (0.1 mm) diameter heavy isomid insulated bifilar nickel lead wires for SC30

**Amphenol**  
Advanced Sensors

# Type SC30

## Specifications

### NTC Interchangeable Type SC30

Polyimide sleeved, interchangeable chip thermistors with heavy isomid insulated nickel lead-wires.

### Options

#### Consult Factory for Availability of Options

- Other resistance values in the range of 1000  $\Omega$  to 100 k $\Omega$
- Other tolerances or ranges
- Alternative lead wires or lengths
- Non standard R vs T curves
- Controlled dimensions

### Thermal and Electrical Properties

#### Dissipation Constant

Still air: 0.4 mW/ $^{\circ}$ C  
 Stirred oil: 3 mW/ $^{\circ}$ C

#### Thermal Time Constant

Still air: 5 seconds  
 Stirred oil: 0.3 seconds

#### Maximum Power at 77°F (25°C)

~30 mW

De-rated from 100% at 77°F (25°C) to 0% at 212°F (100°C)



NTC Interchangeable Type SC30 dimensions

### Ordering Information

Select appropriate part number below for resistance and temperature tolerance desired.

| $R_{25^{\circ}\text{C}}$ | Material System | $\pm 0.18^{\circ}\text{F}$ ( $\pm 0.1^{\circ}\text{C}$ )<br>32°F to 158°F<br>(0°C to 70°C) | $\pm 0.36^{\circ}\text{F}$ ( $\pm 0.2^{\circ}\text{C}$ )<br>32°F to 158°F<br>(0°C to 70°C) |
|--------------------------|-----------------|--|--|
| 2252                     | F               | SC30F232V  | SC30F232W  |
| 3000                     | F               | SC30F302V  | SC30F302W  |
| 5000                     | F               | SC30F502V  | SC30F502W  |
| 10000                    | F               | SC30F103V  | SC30F103W  |
| 10000                    | Y               | SC30Y103V  | SC30Y103W  |
| 30000                    | H               | SC30H303V  | SC30H303W  |
| 50000                    | G               | SC30G503V  | SC30G503W  |
| 100000                   | Y               | SC30Y104V  | SC30Y104W  |
| 100000                   | G               | SC30G104V  | SC30G104W  |

#### Notes:

1. For RoHS compliant product, please add the suffix "N" to the part label. *Example: SC30F103VN*
2. For RoHS compliant product with applications below 0°C, please add the suffix "H" to the part label. *Example: SC30F103VH*

# Type SC50 Specifications

## NTC Interchangeable Type SC50

Polyimide sleeved, interchangeable chip thermistors with heavy isomid insulated copper lead wires.

### Options

#### Consult Factory for Availability of Options.

- Other resistance values in the range of 1000  $\Omega$  to 100 k $\Omega$
- Other tolerances or ranges
- Alternative lead wires or lengths
- Non standard R vs T curves
- Controlled dimensions

### Thermal and Electrical Properties

#### Dissipation Constant

Still air: 0.5 mW/ $^{\circ}$ C  
Stirred oil: 0.4 mW/ $^{\circ}$ C

#### Thermal Time Constant

Still air: 8 seconds  
Stirred oil: 0.5 seconds

#### Maximum Power at 77°F (25°C)

~50 mW

De-rated from 100% at 77°F (25°C) to 0% at 212°F (100°C)



NTC Interchangeable Type SC50 dimensions

### Ordering Information

Select appropriate part number below for resistance and temperature tolerance desired.

| R <sub>25°C</sub> | Material System | ±0.18°F (±0.1°C)<br>32°F to 158°F<br>(0°C to 70°C) | ±0.36°F (±0.2°C)<br>32°F to 158°F<br>(0°C to 70°C) |
|-------------------|-----------------|--|--|
| 2252              | F               | SC50F232V  | SC50F232W  |
| 3000              | F               | SC50F302V  | SC50F302W  |
| 5000              | F               | SC50F502V  | SC50F502W  |
| 10000             | F               | SC50F103V  | SC50F103W  |
| 10000             | Y               | SC50Y103V  | SC50Y103W  |
| 30000             | H               | SC50H303V  | SC50H303W  |
| 50000             | G               | SC50G503V  | SC50G503W  |
| 100000            | Y               | SC50Y104V  | SC50Y104W  |
| 100000            | G               | SC50G104V  | SC50G104W  |

#### Notes:

1. For RoHS compliant product, please add the suffix "N" to the part label. *Example: SC50F103VN*
2. For RoHS compliant product with applications below 0°C, please add the suffix "H" to the part label. *Example: SC50F103VH*

**Amphenol**  
**Advanced Sensors**

[www.amphenol-sensors.com](http://www.amphenol-sensors.com)

© 2018 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice.  
Other company names and product names used in this document are the registered trademarks or  
trademarks of their respective owners.

AAS-920-307E - 02/2018

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## [Amphenol:](#)

[SC50F103V](#) [SC30Y103W](#) [SC50F103W](#) [SC30F103W](#) [SC30F103V](#) [SC30F103A](#) [SC30F103AN](#) [SC30F103VN](#)  
[SC30F103WN](#) [SC30Y103WN](#) [SC50F103WN](#) [SC50F103VN](#) [SC30F232V](#) [SC303F302V](#) [SC30F502V](#) [SC30Y103V](#)  
[SC30H303V](#) [SC30G503V](#) [SC30Y104V](#) [SC30G104V](#) [SC30F232W](#) [SC30F302W](#) [SC30F502W](#) [SC30H303W](#)  
[SC30Y503W](#) [SC30Y104W](#) [SC30G104W](#) [SC50F232V](#) [SC50F302V](#) [SC50Y103V](#) [SC50H303V](#) [SC50G503V](#)  
[SC50Y104V](#) [SC50G104V](#) [SC50F302W](#) [SC50F232W](#) [SC50F502W](#) [SC50Y103W](#) [SC50H303W](#) [SC50Y503W](#)  
[SC50Y104W](#) [SC50G104W](#) [SC30Y503V](#) [SC50F502V](#) [SC50F303W](#) [SC50Y503V](#) [SC30F302V](#) [SC30G503W](#)  
[SC50G503W](#)

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9