| | |
|---|---|
| L1553HDT BRIGHT RED | L1553GDT GREEN |
| L1553IDT HIGH EFFICIENCY RED | L1553EDT ORANGE |
| L1553SRDT SUPER BRIGHT RED | L1553YDT YELLOW |

## Features

- ●LOW POWER CONSUMPTION.
- ●ULTRA BRIGHTNESS IS AVAILABLE.
- ●WIDE VIEWING ANGLE.
- ●RELIABLE AND RUGGED.
- ●EXCELLENT UNIFORMITY OF LIGHT OUTPUT.
- ●IDEAL AS FLUSH MOUNTED PANEL INDICATORS.
- ●LONG LIFE - SOLID STATE RELIABILITY.

## Description

The Bright Red source color devices are made with Gallium Phosphide Red Light Emitting Diode.


The High Efficiency Red and Orange source color devices are made with Gallium Arsenide Phosphide on Gallium Phosphide Orange Light Emitting Diode.

The Green source color devices are made with Gallium Phosphide Green Light Emitting Diode.

The Yellow source color devices are made with Gallium Arsenide Phosphide on Gallium Phosphide Yellow Light Emitting Diode.

The Super Bright Red source color devices are made with Gallium Aluminum Arsenide Red Light Emitting Diode.

## Package Dimensions




Notes:
1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25(0.01") unless otherwise noted.
3. Lead spacing is measured where the lead emerge package.
4. Specifications are subject to change without notice.

Kingbright

## Selection Guide

| Part No. | Dice | Lens Type | Iv (mcd) @ 10 mA *20mA | | Viewing Angle |
|---|---|---|---|---|---|
| | | | Min. | Typ. | 2θ1/2 |
| L1553HDT | BRIGHT RED (GaP) | RED DIFFUSED | 0.5 | 1 | 110° |
| L1553IDT | HIGH EFFICIENCY RED (GaAsP/GaP) | RED DIFFUSED | 3 | 8 | 110° |
| L1553EDT | ORANGE (GaAsP/GaP) | ORANGE DIFFUSED | 3 | 8 | 110° |
| L1553GDT | GREEN (GaP) | GREEN DIFFUSED | 1 | 5 | 110° |
| L1553YDT | YELLOW (GaAsP/GaP) | YELLOW DIFFUSED | 1 | 5 | 110° |
| L1553SRDT | SUPER BRIGHT RED (GaAlAs) | RED DIFFUSED | *36 | *80 | 110° |

Notes:
1. θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.
2. * Luminous intensity with asterisk is measured at 20mA.


## Electrical / Optical Characteristics at $T_A$=25°C

| Symbol | Parameter | Device | Typ. | Max. | Units | Test Conditions |
|---|---|---|---|---|---|---|
| λpeak | Peak Wavelength | Bright Red<br>High Efficiency Red<br>Orange<br>Green<br>Yellow<br>Super Bright Red | 700<br>627<br>627<br>565<br>590<br>660 | | nm | IF=20mA |
| λ D | Dominate Wavelength | Bright Red<br>High Efficiency Red<br>Orange<br>Green<br>Yellow<br>Super Bright Red | 660<br>625<br>625<br>568<br>588<br>640 | | nm | IF=20mA |
| Δλ1/2 | Spectral Line Halfwidth | Bright Red<br>High Efficiency Red<br>Orange<br>Green<br>Yellow<br>Super Bright Red | 45<br>45<br>45<br>30<br>35<br>20 | | nm | IF=20mA |
| C | Capacitance | Bright Red<br>High Efficiency Red<br>Orange<br>Green<br>Yellow<br>Super Bright Red | 40<br>15<br>15<br>15<br>20<br>45 | | pF | VF=0V;f=1MHz |
| $V_F$ | Forward Voltage | Bright Red<br>High Efficiency Red<br>Orange<br>Green<br>Yellow<br>Super Bright Red | 2.25<br>2.0<br>2.0<br>2.2<br>2.1<br>1.85 | 2.5<br>2.5<br>2.5<br>2.5<br>2.5<br>2.5 | V | IF=20mA |
| $I_R$ | Reverse Current | All | | 10 | uA | VR = 5V |

## Absolute Maximum Ratings at $T_A$=25°C


| Parameter | Bright Red | High Efficiency Red | Orange | Green | Yellow | Super Bright Red | Units |
|---|---|---|---|---|---|---|---|
| Power dissipation | 120 | 105 | 105 | 105 | 105 | 100 | mW |
| DC Forward Current | 25 | 30 | 30 | 25 | 30 | 30 | mA |
| Peak Forward Current [1] | 120 | 160 | 160 | 140 | 140 | 155 | mA |
| Reverse Voltage | 5 | 5 | 5 | 5 | 5 | 5 | V |
| Operating/Storage Temperature | -40°C To +85°C | | | | | | |
| Lead Solder Temperature [2] | 260°C For 5 Seconds | | | | | | |

Notes:
1. 1/10 Duty Cycle, 0.1ms Pulse Width.
2. 4mm below package base.




RELATIVE INTENSITY Vs. WAVELENGTH


## Bright Red L1553HDT




FORWARD CURRENT Vs. FORWARD VOLTAGE



LUMINOUS INTENSITY Vs. FORWARD CURRENT




FORWARD CURRENT DERATING CURVE




SPATIAL DISTRIBUTION


## High Efficiency Red L1553IDT





FORWARD CURRENT Vs
FORWARD VOLTAGE




LUMINOUS INTENSITY Vs.
FORWARD CURRENT





FORWARD CURRENT
DERATING CURVE





SPATIAL DISTRIBUTION


## Orange L1553EDT





FORWARD CURRENT Vs
FORWARD VOLTAGE




LUMINOUS INTENSITY Vs.
FORWARD CURRENT





FORWARD CURRENT
DERATING CURVE





SPATIAL DISTRIBUTION


## Green L1553GDT





FORWARD CURRENT Vs
FORWARD VOLTAGE




LUMINOUS INTENSITY Vs.
FORWARD CURRENT





FORWARD CURRENT
DERATING CURVE





SPATIAL DISTRIBUTION


## Yellow L1553YDT





FORWARD CURRENT Vs.
FORWARD VOLTAGE




LUMINOUS INTENSITY Vs.
FORWARD CURRENT





FORWARD CURRENT
DERATING CURVE





SPATIAL DISTRIBUTION


**Super Bright Red L1553SRDT**





FORWARD CURRENT Vs
FORWARD VOLTAGE




LUMINOUS INTENSITY Vs.
FORWARD CURRENT




FORWARD CURRENT
DERATING CURVE




SPATIAL DISTRIBUTION

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

**Данный компонент на территории Российской Федерации**

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

**Офис по работе с юридическими лицами:**

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9