

Power Latching Relay EW60

- 1 pole 60A, 1 form A (NO) contact
- Polarized bistable (latching) with 1 or 2 coils
- NEMA 410-2011, 16A, 277VAC, electronic ballast; 20A branch circuit
- 480A inrush, 2.1m sec

Typical applications

Lighting control, bus actuator, power distribution, circuit protection, inverter

Approvals

UL

Contact Data

Contact arrangement	1 form A (NO)
Rated voltage	250VAC
Max. switching voltage	440VAC
Rated current	60A
Breaking capacity max.	15kVA
Contact material	AgSnO ₂
Initial voltage drop	≤1mΩ @ 3A, 12V
Frequency of operation with/without load	360/3600h ⁻¹

Contact ratings

Type	Contact	Load	Cycles
UL508			
EW60-1A3	NO	60A, 250VAC, resistive, 70°C	1x10 ⁴ 1)
EW60-1A3	NO	60A, 250VAC, general use, 70°C	6x10 ³
EW60-1A3	NO	120VAC, 1HP (horsepower) 23°C	1x10 ⁴
EW60-1A3	NO	16 or 20A, electr. ballast, 70°C	50x10 ³

1) in Process

Coil Data

Magnetic system	polarized, bistable (latching)
Number of coils	1 or 2
Coil voltage range	12VDC
Min./Max. energization duration	100ms/1min at <10% duty factor

Coil versions, bistable coil

Coil code	Rated voltage VDC	Set voltage VDC	Reset voltage VDC	Coil resistance Ω±10%	Rated coil power W
bistable 1 coil					
BL12	12	9.6	9.6	96	1.5
bistable 2 coil					
CL12	12	9.6	9.6	48	3/3

All figures are given for coil without preenergization, at ambient temperature +23°C

Max. coil power: 130% of rated coil power

Other coil voltages on request

Coil operation

coil terminals	1 coil		2 coils		
	A1	A2	A1	A2	A3
Set	-	+	-	+	
Reset	+	-	-		+

Contact position not defined at delivery

Insulation Data

Initial dielectric strength	
between open contacts	1500V _{rms}
between contact and coil	4000V _{rms}
Initial surge withstand voltage	
between contact and coil	10000V (1.2/50μs)
Clearance/creepage	
between contact and coil	≥6/9mm



Material group of insulation parts

IIIa

Tracking index of relay base

PTI 175V

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customer-support/rohssupportcenter

Ambient temperature

-40 to 70°C

Category of environmental protection

IEC 61810

RTI (dust protected)

Vibration resistance (functional)

1.5mm double amplitude¹⁾

Shock resistance (functional)

50g

Shock resistance (destructive)

100g

Terminal type

PCB Mounting

Weight


appr. 37.5g

Packaging/unit

200pcs/carton

¹⁾ 10...55Hz


Dimensions




Power Latching Relay EW60 (Continued)

Wire Connection drawing


bistable 1 coil:



bistable 2 coils:



PCB Drilling (Copper Side)



1) if 2 coil version

Product code structure

Typical product code

EW 6 0 -1 A 3 -B L12 D 0 4

Type (product family)

Version - Current class / Model

6 60A

Version - Orientation and Performance Class

0 vertical (Bottom-right), standard performance

Number of Contact Poles

1 1 pole

Contact configuration

A form A (NO Contact)

Contact material

3 AgSnO₂

Coil version

B bistable 1 coil
C bistable 2 coils

Coil voltage

L12 Low Sensitivity, 12V,

Category of Protection

D RTI (dust proof)

Mechanical feature

0 standard

Terminals

4 pcb terminals

Product code	Design	Coil	Contact material	Part Number
EW60-1A3-BL12D04	Vertical	12V Bistable, 1 Coil, 1.5W	AgSnO ₂	2071366-1
EW60-1A3-CL12D04	Vertical	12V Bistable, 2 Coils 3W	AgSnO ₂	2071366-2

Other types on request

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9