

10GX33 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable



For more Information
please call

1-800-Belden1

**Description:**

23 AWG Solid Bare Copper Bonded-Pair Conductors, FEP Insulation, Patented H-spline Center Member, Rip Cord, Flamarrest® Jacket.

Usage (Overall)**Suitable Applications:**

Premise Horizontal Cable, 10 Gigabit Ethernet, 100BaseTX, 100BaseVG
 ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video,
 AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, PoE

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Total Number of Conductors:

8

Insulation**Insulation Material:**

Insulation Material
FEP - Fluorinated Ethylene Propylene

Outer Shield**Outer Shield Material:**

Outer Shield Material
Unshielded

Outer Jacket**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Ripcord:

Yes

Overall Cable**Overall Cabling Separator Material:**

Patented RoundFlex H-Spline Center Member

Overall Nominal Diameter:

0.295 in.

Pair**Pair Color Code Chart:**

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall)**Storage Temperature Range:**

-20°C To +75°C

Installation Temperature Range:

+5°C To +50°C

Operating Temperature Range:

-20°C To +60°C

10GX33 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable

Bulk Cable Weight: 40 lbs/1000 ft.

Max. Recommended Pulling Tension: 45 lbs.

Min. Bend Radius/Minor Axis: 2 in.

Min. Bend/Installation: 3.100 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 08/20/2008

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Telecommunications Standards: Category 6A - TIA 568.C.2

Applicable Patents:

Country	Patent
US	5606151
US	5734126
US	6074503
US	7772494
US	7838773
US	8030571

Flame Test

UL Flame Test: NFPA 262 Plenum Flame Test (UL910)(FT6)

C(UL) Flame Test: FT6

CSA Flame Test: FT6

Suitability

Suitability - Outdoor: No

Suitability - Burial: No

Plenum/Non-Plenum

Plenum (Y/N): Yes

Non-Plenum Number: 10GX32

Electrical Characteristics (Overall)**Nom. Mutual Capacitance:**

Capacitance (pF/ft)
17.000

Maximum Capacitance Unbalance (pF/100 m): 90

Nominal Velocity of Propagation:

VP (%)
68.000

Maximum Delay:

Delay (ns/100 m)
538 @ 100MHz

10GX33 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable

Max. Delay Skew:

Delay Skew (ns/100 m)
30.000

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
7.500

Max. Operating Voltage - UL:

Voltage
300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)
2.000

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
1	2.100	75.3	73.3	73.3	71.3	20.000
4	3.800	66.3	64.3	62.5	60.5	23.000
8	5.300	61.8	59.8	56.4	54.4	24.500
10	5.900	60.3	58.3	54.4	52.4	25.000
16	7.500	57.2	55.2	49.8	47.8	25.000
20	8.400	55.8	53.8	47.4	45.4	25.000
25	9.400	54.3	52.3	45.0	43.0	25.000
31.25	10.500	52.9	50.9	42.4	40.4	25.000
62.5	15.000	48.4	46.4	33.4	31.4	25.000
100	19.100	45.3	43.3	26.2	24.2	25.000
200	27.600	40.8	38.8	13.2	11.2	21.000
250	31.100	39.3	37.3	8.3	6.3	20.500
300	34.300	38.1	36.1	3.9	1.9	20.100
350	37.200	37.1	35.1	N/A	N/A	19.800
400	40.100	36.3	34.3	N/A	N/A	19.500
450	42.700	35.5	33.5	N/A	N/A	18.900
500	45.300	34.8	32.8	N/A	N/A	18.400
550	47.700	34.2	32.2	N/A	N/A	18.000
600	50.100	33.6	31.6	N/A	N/A	17.600
625	51.200	33.4	31.4	N/A	N/A	17.400
750	56.700	32.2	30.2	N/A	N/A	16.500
860	61.200	31.3	29.3	N/A	N/A	15.800

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ACRF (dB)	Min. PSACRF (dB)
1	100 ± 15	100 ± 15	70.8	68.8
4	100 ± 15	100 ± 10.4	58.8	56.8
8	100 ± 15	100 ± 8	52.7	50.7
10	100 ± 15	100 ± 7.3	50.8	48.8
16	100 ± 15	100 ± 5.7	46.7	44.7
20	100 ± 15	100 ± 5	44.8	42.8
25	100 ± 15	100 ± 5	42.8	40.8
31.25	100 ± 15	100 ± 5	40.9	38.9
62.5	100 ± 15	100 ± 5	34.9	32.9
100	100 ± 15	100 ± 5	30.8	28.8
200	100 ± 22	100 ± 5	24.8	22.8
250	100 ± 32	100 ± 5	22.8	20.8
300	100 ± 32	100 ± 5	21.3	19.3
350	100 ± 32	100 ± 5	19.9	17.9
400	100 ± 32	100 ± 5	18.8	16.8
450	100 ± 32	100 ± 5	17.7	15.7
500	100 ± 32	100 ± 5	16.8	14.8
550	100 ± 32	100 ± 5	16.0	14.0

10GX33 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable

600	100 ± 32	100 ± 5	15.2	13.2
625	100 ± 32	100 ± 5	14.9	12.9
750			13.3	11.3
860			12.1	10.1

Premise Cable Electrical Table 4:

Frequency (MHz)	Min. PSANEXT (dB)	Min. PSAACRF (dB)	Min. TCL (dB)	Min. ELTCTL (dB)
1.000	67.000	67.000	48.000	43.000
4.000	67.000	67.000	48.000	41.000
8.000	67.000	61.100	48.000	24.900
10.000	67.000	59.200	48.000	23.000
16.000	67.000	55.100	46.000	18.900
20.000	67.000	5.200	45.000	17.000
25.000	67.000	51.200	44.000	15.000
31.250	67.000	49.300	43.100	
62.500	66.600	43.300	40.000	
100.000	63.500	39.200	38.000	
200.000	59.000	33.200	35.000	
250.000	57.500	31.200	34.000	
300.000	56.300	29.700	33.200	
350.000	55.300	28.300	32.600	
400.000	54.500	27.200	32.000	
450.000	53.700	26.100	31.500	
500.000	53.000	25.200	31.000	
550.000	52.400	2.400		
600.000	51.800	23.600		
625.000	51.600	23.300		
750.000	50.400	21.700		
860.000	49.500	20.500		

Notes (Overall)

Notes: Jacket sequentially marked at 2 ft/1m. intervals. 0.295" cable dimension per TIA 6@1 equivalent diameter. Third party channel verified to TIA/EIA-568-C.2, Category 6A

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
10GX33 D151000	1,000 FT	43.000 LB	BLUE	C	CAT6A 4PRB U/UTP CMP REEL
10GX33 0041000	1,000 FT	43.000 LB	YELLOW	C	CAT6A 4PRB U/UTP CMP REEL
10GX33 0081000	1,000 FT	43.000 LB	GRAY	C	CAT6A 4PRB U/UTP CMP REEL
10GX33 0091000	1,000 FT	43.000 LB	WHITE	C	CAT6A 4PRB U/UTP CMP REEL

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 9 Revision Date: 09-28-2012

© 2012 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

10GX33 Multi-Conductor - Enhanced Category 6A Bonded-Pair Cable

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9