BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Key Features

- Industry standard five pin Quarter-brick 57.9 x 36.8 x 11.6 mm (2.28 x 1.45 x 0.46 in.)
- Optional digital PMBus interface
- Fully regulated intermediate bus converter
- High efficiency, typ. 96% at half load, 12 Vout
- +/- 2% output voltage tolerance band
- 1500 Vdc input to output isolation
- 2.5 million hours MTBF
- Optional baseplate
- Optional output voltage Droop for parallel operation
- ISO 9001/14001 certified supplier
- PMBus Revision 1.1 compliant

Power Management

- Configurable soft start/stop
- Precision delay and ramp-up
- Voltage sequencing and margining
- Voltage/current/temperature monitoring
- Configurable output voltage
- Power good
- Synchronization
- Voltage track





Þ

Safety Approvals



Design for Environment



Meets requirements in hightemperature lead-free soldering processes.

Contents

Ordering Information	2
General Information	2
Safety Specification	
Absolute Maximum Ratings	5
Functional Description	
Electrical Specification	
3.3 V, 60 A / 198 W	BMR 453 0002/0037
5 V, 60 A / 300 W	BMR 453 0002/004
9 V, 33 A / 297 W	BMR 453 0000/002
12 V, 33 A / 396 W	BMR 453 0000/00116
EMC Specification	
Operating Information	
Thermal considerations	
Connections	
PMBus communications	
Mechanical Information	
Soldering Information	32
Delivery Information	33
Product Qualification Specification	

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Ordering Information

Product program	Output
BMR4530002/003	3.3 V / 60 A, 198 W
BMR4530002/004	5 V / 60 A, 300 W
BMR4530000/002	9 V / 33 A, 297 W
BMR4530006/012	9.6 V / 33 A, 297 W
BMR4530000/001	12 V / 33 A, 396 W
BMR4530006/013	12 V / 33 A, 376 W
BMR4530006/014	12.45 V / 33 A, 391 W

Product Number and Packaging

BMR453	n ₁	n ₂	n ₃	n ₄	/	n ₅	n ₆	n ₇
Mechanical pin option	х				/			
Mechanical option		x			/			
Hardware option			х	х	/			
Configuration file					/	х	х	х
Optional designation	Desc	cription	1					
n ₁	0 = 9 1 = 9 2 = L 3 = L 4 = L 5 = L	Standa Surface Lead le Lead le Lead le Lead le	rd pin e mour ength 3 ength 4 ength 2 ength 2 off 6.7 i	length nt optic 3.69 mr 4.57 mr 4.79 mr 1.79 mr mm	5.33 n on ^{note 1} n (0.14 n (0.15 n (0.17 n (021	nm (0. 45 in.) 80 in.) 10 in.) 0 in.)	210 in (cut)	.)
n ₂	0 = Open frame 1 = Baseplate 2 = Baseplate with GND-pin							
n ₃ n ₄	00 = 8.1-13.2 Vout With digital interface 01 = 8.1-13.2 Vout Without digital interface 02 = $3-6.7$ Vout With digital interface 03 = $3-6.7$ Vout Without digital interface 06 = $8.1-13.2$ Vout With 0.6 V droop load sharing function Without digital interface 07 = $8.1-13.2$ Vout With 0.6 V droop load sharing function With digital interface							
n ₅ n ₆ n ₇	001 = 12 V Standard configuration 002 = 9 V Standard configuration 003 = 3.3 V Standard configuration 004 = 5 V Standard configuration 007 = 9 V with positive RC logic configuration 008 = 12 V with positive RC logic configuration 009 = 3.3 V with positive RC logic configuration 010 = 5 V with positive RC logic configuration 012 = 9.6 V with 0.6 V droop load sharing function configuration (available only for n3n4 = 06 or 07) 013 = 12 V with 0.6 V droop load sharing function configuration (Vin 40-75,available, only for n3n4 = 06 or 07) 014 = 12.45 V with 0.6 V droop load sharing function configuration							

(Vin 40-75, available only for n3n4 = 06 or 07)

xxx = Application Specific Configuration

Packaging	20 converters/tray/box PE foam dissipative

Example: Product number BMR4532000/002 equals an Through hole mount lead length 3.69 mm (cut), open frame, digital interface with 9 V standard configuration variant.

Note 1: Surface mount option available for 8.1-13.2Vout open frame version. Can not be combined with base plate option.

For application specific configurations contact your local Ericsson Power Modules sales representative.

General Information

Reliability

The failure rate (λ) and mean time between failures (MTBF= 1/ λ) is calculated at max output power and an operating ambient temperature (T_A) of +40°C. Ericsson Power Modules uses Telcordia SR-332 Issue 2 Method 1 to calculate the mean steady-state failure rate and standard deviation (σ).

Telcordia SR-332 Issue 2 also provides techniques to estimate the upper confidence levels of failure rates based on the mean and standard deviation.

Mean steady-state failure rate, λ	Std. deviation, σ
403 nFailures/h	61 nFailures/h

MTBF (mean value) for the BMR453 series = 2.5 Mh. MTBF at 90% confidence level = 2.1 Mh

Compatibility with RoHS requirements

The products are compatible with the relevant clauses and requirements of the RoHS directive 2011/65/EU and have a maximum concentration value of 0.1% by weight in homogeneous materials for lead, mercury, hexavalent chromium, PBB and PBDE and of 0.01% by weight in homogeneous materials for cadmium.

Exemptions in the RoHS directive utilized in Ericsson Power Modules products are found in the Statement of Compliance document.

Ericsson Power Modules fulfills and will continuously fulfill all its obligations under regulation (EC) No 1907/2006 concerning the registration, evaluation, authorization and restriction of chemicals (REACH) as they enter into force and is through product materials declarations preparing for the obligations to communicate information on substances in the products.

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Quality Statement

The products are designed and manufactured in an industrial environment where quality systems and methods like ISO 9000, Six Sigma, and SPC are intensively in use to boost the continuous improvements strategy. Infant mortality or early failures in the products are screened out and they are subjected to an ATE-based final test. Conservative design rules, design reviews and product qualifications, plus the high competence of an engaged work force, contribute to the high quality of the products.

Warranty

Warranty period and conditions are defined in Ericsson Power Modules General Terms and Conditions of Sale.

Limitation of Liability

Ericsson Power Modules does not make any other warranties, expressed or implied including any warranty of merchantability or fitness for a particular purpose (including, but not limited to, use in life support applications, where malfunctions of product can cause injury to a person's health or life).

© Ericsson AB 2014

The information and specifications in this technical specification is believed to be correct at the time of publication. However, no liability is accepted for inaccuracies, printing errors or for any consequences thereof. Ericsson AB reserves the right to change the contents of this technical specification at any time without prior notice.

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Safety Specification

General information

Ericsson Power Modules DC/DC converters and DC/DC regulators are designed in accordance with the safety standards IEC 60950-1, EN 60950-1 and UL 60950-1 Safety of Information Technology Equipment.

IEC/EN/UL 60950-1 contains requirements to prevent injury or damage due to the following hazards:

- Electrical shock
- Energy hazards
- Fire
- Mechanical and heat hazards
- Radiation hazards
- Chemical hazards

On-board DC/DC converters and DC/DC regulators are defined as component power supplies. As components they cannot fully comply with the provisions of any safety requirements without "conditions of acceptability". Clearance between conductors and between conductive parts of the component power supply and conductors on the board in the final product must meet the applicable safety requirements. Certain conditions of acceptability apply for component power supplies with limited stand-off (see Mechanical Information and Safety Certificate for further information). It is the responsibility of the installer to ensure that the final product housing these components complies with the requirements of all applicable safety standards and regulations for the final product.

Component power supplies for general use should comply with the requirements in IEC/EN/UL 60950-1 *Safety of Information Technology Equipment*. Product related standards, e.g. IEEE 802.3af *Power over Ethernet*, and ETS-300132-2 *Power interface at the input to telecom equipment, operated by direct current (dc)* are based on IEC/EN/UL 60950-1 with regards to safety.

Ericsson Power Modules DC/DC converters, Power interface modules and DC/DC regulators are UL 60950-1 recognized and certified in accordance with EN 60950-1. The flammability rating for all construction parts of the products meet requirements for V-0 class material according to IEC 60695-11-10, *Fire hazard testing, test flames* – 50 W horizontal and vertical flame test methods.

Isolated DC/DC converters & Power interface modules

The product may provide basic or functional insulation between input and output according to IEC/EN/UL 60950-1 (see Safety Certificate), different conditions shall be met if the output of a basic or a functional insulated product shall be considered as safety extra low voltage (SELV). output is considered as safety extra low voltage (SELV) if one of the following conditions is met:

- The input source provides supplementary or double or reinforced insulation from the AC mains according to IEC/EN/UL 60950-1.
- The input source provides functional or basic insulation from the AC mains and the product's output is reliably connected to protective earth according to IEC/EN/UL 60950-1.

For functional insulated products (see Safety Certificate) the output is considered as safety extra low voltage (SELV) if one of the following conditions is met:

- The input source provides double or reinforced insulation from the AC mains according to IEC/EN/UL 60950-1.
- The input source provides basic or supplementary insulation from the AC mains and the product's output is reliably connected to protective earth according to IEC/EN/UL 60950-1.
- The input source is reliably connected to protective earth and provides basic or supplementary insulation according to IEC/EN/UL 60950-1 and the maximum input source voltage is 60 Vdc.

Galvanic isolation between input and output is verified in an electric strength test and the isolation voltage (V_{iso}) meets the voltage strength requirement for basic insulation according to IEC/EN/UL 60950-1.

It is recommended to use a slow blow fuse at the input of each DC/DC converter. If an input filter is used in the circuit the fuse should be placed in front of the input filter. In the rare event of a component problem that imposes a short circuit on the input source, this fuse will provide the following functions:

- Isolate the fault from the input power source so as not to affect the operation of other parts of the system
- Protect the distribution wiring from excessive current and power loss thus preventing hazardous overheating

Non - isolated DC/DC regulators

The DC/DC regulator output is SELV if the input source meets the requirements for SELV circuits according to IEC/EN/UL 60950-1.

For basic insulated products (see Safety Certificate) the

Technical Specification 5

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Absolute Maximum Ratings

Characte	ris tics	min	typ	max	Unit
T _{P1}	Operating Temperature (see Thermal Consideration section)	-40		+125	°C
Ts	Storage temperature	-55		+125	°C
Vi	Input voltage	-0.5		80	V
V _{iso}	Isolation voltage (input to output test voltage), see note 1			1500	Vdc
V _{tr}	Input voltage transient (Tp 100 ms)			100	V
V _{RC}	Remote Control pin voltage	-0.3		18	V
V Logic I/O	SALERT, CTRL, SYNC, SCL, SDA, SA(0,1)	-0.3		3.6	V

Stress in excess of Absolute Maximum Ratings may cause permanent damage. Absolute Maximum Ratings, sometimes referred to as no destruction limits, are normally tested with one parameter at a time exceeding the limits of Output data or Electrical Characteristics. If exposed to stress above these limits, function and performance may degrade in an unspecified manner.

Note 1: Isolation voltage (input/output to base-plate) max 750 Vdc.

Fundamental Circuit Diagram



BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Functional Description

 $T_{P1} = -40 \text{ to } +90^{\circ}\text{C}, \ V_1 = 36 \text{ to } 75 \text{ V}, \ \text{sense pins connected to output pins unless otherwise specified under Conditions.} \\ Typical values given at: \\ T_{P1} = +25^{\circ}\text{C}, \ V_1 = 53 \text{ V}, \ \text{max } I_0, \ \text{unless otherwise specified under Conditions} \\ \text{Configuration File: } 190 \text{ 10-CDA } 102 \text{ 935/001 rev } D \\ \end{array}$

Characteristics		Conditions	min	typ	max	Unit
PMBus monitoring	accuracy	· · · · · ·				
VIN_READ	Input voltage		-3	+0.4	3	%
VOUT_READ	Output voltage	V ₁ = 53 V	-1.0	-0.3	1.0	%
IOUT_READ Output current		$V_{\rm I}$ = 53 V, 50-100% of max $I_{\rm O}$	-6	±1	6	%
IOUT_READ	Output current	$V_1 = 53 V$, 10% of max I_0	-0.7	-	0.7	Α
TEMP_READ	Temperature		-5	-	5	°C
Fault Protection Ch	aracteristics					
	Factory default		-	33	-	V
Input Under Voltage	Setpoint accuracy		-3	-	3	%
Lockout,		Factory default	-	1.8	-	V
UVLO	Hysteresis	Configurable via PMBus of threshold range, Note 1	0	-	-	V
	Delay		-	200	-	μS
	VOUT_UV_FAULT_LIMIT	Factory default	-	0	-	V
(Output voltage)		Configurable via PMBus, Note 1	0	-	16	V
Over/Under Voltage	VOUT_OV_FAULT_LIMIT	Factory default	-	15.6	-	V
OVP/UVP		Configurable via PMBus, Note 1	Vолт	-	16	V
	fault response time		-	200	-	μS
	Setpoint accuracy	ю	-6		6	%
Over Current	IOUT_OC_FAULT_LIMIT	Factory default	-	38	-	А
OCP		Configurable via PMBus, Note 1	0	-	100	
	fault response time		-	200	-	μS
	OTP FALLET LIMIT	Factory default	-	135	-	
Over Temperature		Configurable via PMBus, Note 1	-50		135	
Protection,	OTP hysteresis	Factory default		10	405	
OIF	foult response time	Configurable via Pivibus, Note 1	0	200	165	
Logic Input/Output	Characteristics		-	200	-	μs
					0.8	V
		CTRL_CS, SAU, SA1, PG_SYNC,		-	0.0	V
Logic input high (VIH)		CTPL CS PG SYNC SALEPT	2.0	-	-	v
Logic output low (V $_{\alpha}$)		SCL, SDA $l_{0L} = 5 \text{ mA}$	-	-	0.4	V
Logic output high (V _{OH})		CTRL_CS, PG_SYNC, SALERT, SCL, SDA $I_{OH} = -5 \text{ mA}$	2.8	-	-	V
Setup time, SMBus			100	-		ns
Hold time, SMBus			300	-		ns
Bus free time T(BUF)		Note 2	200	-		US

Note 1: See Operating Information section.

Note 2: It is recommended that a PMBus master read back written data for verification i.e. do not rely on the ACK/NACK bit since this bit are as susceptible to errors as any other bit^{*}. However, under very rare operating conditions, it is possible to get intermittent read backfailures. It is therefore recommended to implement error handling in the master that also deals with those situations.

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

3.3V, 60A / 198W Electrical Specification

 $T_{P1} = -40 \text{ to } +90^{\circ}\text{C}, \ V_{I} = 36 \text{ to } 75 \text{ V}, \ \text{sense pins connected to output pins unless otherwise specified under Conditions.} \\ Typical values given at: \ T_{P1} = +25^{\circ}\text{C}, \ V_{I} = 53 \text{ V}, \ \text{max } I_{0}, \ \text{unless otherwise specified under Conditions.} \\ \text{Additional } C_{out} = 0.1 \text{ mF}, \ \text{Configuration File: 190 10-CDA 102 935/003 rev B}$

Charact	eristics	Conditions	min	typ	max	Unit	
Vi	Input voltage range		36		75	V	
Vloff	Turn-off input voltage	Decreasing input voltage	32	33	34	V	
Vlan	Turn-on input voltage	Increasing input voltage	34	35	36	V	
Ci	Internal input capacitance			10		μF	
Po	Output pow er		0		198	W	
	Efficiency	50% of max I _o		94.7		%	
n		max I _o		93.3			
'1		50% of max $I_{\rm O}$, $V_{\rm I}$ = 48 V		94.9			
		max I_0 , $V_1 = 48 V$		93.3			
Pd	Pow er Dissipation	max I _o		14.1	20.8	W	
Pli	Input idling pow er	$I_0 = 0 A, V_1 = 53 V$		1.7		W	
P _{RC}	Input standby power	$V_1 = 53 V$ (turned off with RC)		123		mW	
fs	Default switching frequency	0-100% of max Io see Note 1	171	180	189	kHz	

V _{Oi}	Output voltage initial setting and accuracy	$T_{P1} = +25^{\circ}C, V_1 = 53 V, I_0 = 60 A$	3.26	3.3	3.36	V
	Output adjust range	See operating information	3.0		6.7	V
	Output voltage tolerance band	0-100% of max I ₀	3.22		3.38	V
VO	Line regulation	max I _o		4	16	mV
	Load regulation	$V_{\rm I}$ = 53 V, 1-100% of max $I_{\rm O}$		4	12	mV
V_{tr}	Load transient voltage deviation	V_1 = 53 V, Load step 25-75-25% of max I_0 , di/dt = 1 A/µs, see Note 2		±0.2		V
t _{tr}	Load transient recovery time			250		μs
tr	Ramp-up time (from 10-90% of V _{Oi})	10-100% of max $I_{0,}$		8		ms
ts	Start-up time (f rom V ₁ connection to 90% of V _{Oi})	see Note 3		140		ms
t,	Vin shutdown fall time	max I _o		0.2		mS
7	(from V_1 off to 10% of V_0)	$I_0 = 0 A$		4.5		S
	RC start-up time	max I _o		52		ms
t _{RC}	RC shutdow n fall time	max I ₀		3		ms
	(from RC off to 10% of V_0)	$I_0 = 0 A$		4.5		S
b	Output current		0		60	А
l _{lim}	Current limit threshold	$V_0 = 3.0 V, T_{P1} < max T_{P1}$	61	66	82	А
l _{sc}	Short circuit current	$T_{P1} = 25^{\circ}C, V_{O} < 0.2 V$, see Note 4		11		А
Cout	Recommended Capacitive Load	$T_{P1} = 25^{\circ}C$, see Note 5	0.1	6	10	mF
V_{Oac}	Output ripple & noise	See ripple & noise section, max I _o , V _{oi}		30	100	mVp-p
OVP	Over voltage protection	T _{P1} = +25°C, V ₁ = 53 V, 10-100% of max I ₀ , see Note 6		4.6		V

Note 1: Frequency may be adjusted via PMBus, see Operating Information section.

Note 2: Cout = 6 mF used at load transient test.

Note 3: Start-up and R amp-up time can be increased via PMBus, see Operation Information section.

Note 4: RMS current in hiccup mode.

Note 5: Low ESR-value.

Note 6: OVP-level can be adjusted via PMBus, see Operation Information.

ERICSSON 📕

Technical Specification 8

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

3.3V, 60A / 198W Electrical Specification

Efficiency





Output Current Derating, open frame



Thermal Resistance, base plate option



Output Current Derating, base plate option



ERICSSON 📕

Technical Specification 9

BMR 453 0002/003

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

3.3V, 60A / 198W Electrical Specification

Output Characteristics



Current Limit Characteristics



Output voltage vs. load current at $I_0 > max I_0$, $T_{P1} = +25^{\circ}C$

Start-up



Output Ripple & Noise



Shut-down





BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

5.0V, 60A / 300W Electrical Specification

 $T_{P1} = -40 \text{ to } +90^{\circ}\text{C}, \ V_{I} = 36 \text{ to } 75 \text{ V}, \ \text{sense pins connected to output pins unless otherwise specified under Conditions.} \\ Typical values given at: \ T_{P1} = +25^{\circ}\text{C}, \ V_{I} = 53 \text{ V}, \ \text{max } I_{0}, \ \text{unless otherwise specified under Conditions.} \\ \text{Additional } C_{out} = 0.1 \text{ mF}, \ \text{Configuration File: } 190 \text{ 10-CDA } 102 \text{ 935/004 rev B} \\ \end{array}$

Charact	eristics	Conditions	min	typ	max	Unit	
Vi	Input voltage range		36		75	V	
V _{loff}	Turn-off input voltage	Decreasing input voltage	32	33	34	V	
Vlan	Turn-on input voltage	Increasing input voltage	34	35	36	V	
Ci	Internal input capacitance			10		μF	
Po	Output pow er		0		300	W	
	Efficiency	50% of max lo		96.0		%	
n		max I _o		94.8			
1		50% of max I_0 , $V_1 = 48$ V		96.1			
		max I_0 , $V_1 = 48$ V		94.8			
Pd	Pow er Dissipation	max I _o		16.5	22.8	W	
Pli	Input idling pow er	$I_0 = 0 A, V_1 = 53 V$		1.9		W	
P _{RC}	Input standby power	$V_1 = 53 V$ (turned off with RC)		143		mW	
fs	Default switching frequency	0-100% of max Io see Note 1	171	180	189	kHz	

V _{Oi}	Output voltage initial setting and accuracy	$T_{P1} = +25^{\circ}C, V_1 = 53 V, I_0 = 60 A$	4.95	5.0	5.05	V
	Output adjust range	See operating information	3.0		6.7	V
V	Output voltage tolerance band	0-100% of max I ₀	4.9		5.1	V
VO	Line regulation	max I _o		3	19	mV
	Load regulation	$V_{\rm I}$ = 53 V, 1-100% of max $I_{\rm O}$		6	12	mV
V _{tr}	Load transient voltage deviation	$V_1 = 53 V$, Load step 25-75-25% of max I_0 , di/dt = 1 A/ μ s, see Note 2		±0.2		V
t _{tr}	Load transient recovery time			200		μs
tr	Ramp-up time (from 10-90% of V _{Oi})	10-100% of max I _{o,}		8		ms
ts	Start-up time (from V ₁ connection to 90% of V _{0i})	see Note 3		140		ms
t,	Vin shutdown fall time	max I _o		0.2		mS
-1	(from V_1 off to 10% of V_0)	$I_0 = 0 A$		4.5		S
	RC start-up time	max I _o		53		ms
t _{RC}	RC shutdow n fall time	max I _o		2		ms
	(from RC off to 10% of V_0)	I _O = 0 A		4.5		S
b	Output current		0		60	А
l _{lim}	Current limit threshold	$V_0 = 4.5 V, T_{P1} < max T_{P1}$	61	66	82	А
l _{sc}	Short circuit current	$T_{P1} = 25^{\circ}C, V_{O} < 0.2 V$, see Note 4		11		А
Cout	Recommended Capacitive Load	$T_{P1} = 25^{\circ}C$, see Note 5	0.1	6	10	mF
V_{Oac}	Output ripple & noise	See ripple & noise section, max I _o , V _{Oi}		25	100	mVp-p
OVP	Over voltage protection	T _{P1} = +25°C, V ₁ = 53 V, 10-100% of max I ₀ , see Note 6		6.8		V

Note 1: Frequency may be adjusted via PMBus, see Operating Information section.

Note 2: Cout = 6 mF used at load transient test.

Note 3: Start-up and R amp-up time can be increased via PMBus, see Operation Information section.

Note 4: RMS current in hiccup mode.

Note 5: Low ESR-value.

Note 6: OVP-level can be adjusted via PMBus, see Operation Information.

Technical Specification 11

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

5.0V, 60A / 300W Electrical Specification

Efficiency





Output Current Derating, open frame



Thermal Resistance, base plate option



Output Current Derating, base plate option



Technical Specification 12

BMR 453 0002/004

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

5.0V, 60A / 300W Electrical Specification

Output Characteristics



Current Limit Characteristics



Output v oltage v s. load current at I_{O} > max I_{O} , T_{P1} = +25°C

Start-up





Output Ripple & Noise



Output Load Transient Response



BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

9.0V, 33A / 297W Electrical Specification

 $T_{P1} = -40 \text{ to } +90^{\circ}\text{C}, \ V_{I} = 36 \text{ to } 75 \text{ V}, \ \text{sense pins connected to output pins unless otherwise specified under Conditions.} \\ Typical values given at: \ T_{P1} = +25^{\circ}\text{C}, \ V_{I} = 53 \text{ V}, \ \text{max } I_{0}, \ \text{unless otherwise specified under Conditions.} \\ \text{Additional } C_{out} = 0.1 \text{ mF}, \ \text{Configuration File: 190 10-CDA 102 935/002 rev D}$

Charact	eristics	Conditions	min	typ	max	Unit
Vi	Input voltage range		36		75	V
V _{loff}	Turn-off input voltage	Decreasing input voltage	32	33	34	V
Vlan	Turn-on input voltage	Increasing input voltage	34	35	36	V
Ci	Internal input capacitance			18		μF
Po	Output pow er		0		297	W
	Efficiency	50% of max lo		96		%
n		max I _o		95		
11		50% of max I_0 , $V_1 = 48 V$		96		
		max I_0 , $V_1 = 48$ V		95		
Pd	Pow er Dissipation	max I _o		15.5	24.7	W
Pli	Input idling pow er	$I_0 = 0 A, V_1 = 53 V$		2.1		W
P _{RC}	Input standby power	$V_1 = 53 V$ (turned off with RC)		190		mW
fs	Default switching frequency	0-100% of max Io see Note 1	133	140	145	kHz

V _{Oi}	Output voltage initial setting and accuracy	$T_{P1} = +25^{\circ}C, V_1 = 53 V, I_0 = 17 A$	8.90	9.0	9.10	V
	Output adjust range	See operating information	8.1		13.2	V
V.	Output voltage tolerance band	0-100% of max I ₀	8.82		9.18	V
VO	Line regulation	max I _o		15	50	mV
	Load regulation	$V_{\rm I}$ = 53 V, 1-100% of max $I_{\rm O}$		60	85	mV
V_{tr}	Load transient voltage deviation	V_1 = 53 V, Load step 25-75-25% of max I_0 , di/dt = 1 A/µs, see Note 2		±0.35		V
t _{tr}	Load transient recovery time			250		μs
tr	Ramp-up time (from 10-90% of V _{Oi})	10-100% of max $I_{0,}$		8		ms
ts	Start-up time (f rom V ₁ connection to 90% of V _{Oi})	see Note 3		140		ms
t,	Vin shutdown fall time	max I ₀		0.4		mS
4	(from V_1 off to 10% of V_0)	$I_0 = 0 A$		8		S
	RC start-up time	max I _o		53		ms
t _{RC}	RC shutdow n fall time	max Io		3.2		ms
	(from RC off to 10% of Vo)	$I_0 = 0 A$		8		S
Ь	Output current		0		33	А
l _{lim}	Current limit threshold	$V_0 = 8.1 V$, $T_{P1} < max T_{P1}$	34	38	43	А
lsc	Short circuit current	$T_{P1} = 25^{\circ}C, V_{O} < 0.2 V$, see Note 4		6		А
Cout	Recommended Capacitive Load	$T_{P1} = 25^{\circ}C$, see Note 5	0.1	3.3	6	mF
V _{Oac}	Output ripple & noise	See ripple & noise section, max I _o , V _{Oi}		50	120	mVp-p
OVP	Over voltage protection	T _{P1} = +25°C, V ₁ = 53 V, 10-100% of max I ₀ , see Note 6		15.6		V

Note 1: Frequency may be adjusted via PMBus, see Operating Information section.

Note 2: Cout = 3.3 mF used at load transient test.

Note 3: Start-up and R amp-up time can be increased via PMBus, see Operation Information section.

Note 4: RMS current in hiccup mode.

Note 5: Low ESR-value.

Note 6: OVP-level can be adjusted via PMBus, see Operation Information.

Technical Specification 14

BMR 453 0000/002

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

9.0V, 33A / 297W Electrical Specification

Efficiency





Output Current Derating, open frame



Thermal Resistance, base plate option



Output Current Derating, base plate option



Technical Specification 15

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

9.0V, 33A / 297W Electrical Specification

Output Characteristics





Current Limit Characteristics





 $\begin{array}{l} \mbox{Start-up enabled by connecting } V_1 \mbox{ at:} \\ T_{P1} = +25^{\circ}C, \ V_1 = 53 \ V, \\ I_0 = 33 \ A \ resistive \ load. \end{array}$

Top trace: output voltage (5 V/di v.). Bottom trace: input voltage (50 V/di v.). Time scal e: (50 ms/di v.).

Output Ripple & Noise



Shut-down



Shut- down enabled by disconnecting V₁ at: T_{P1} = +25°C, V₁ = 53 V, I_0 =33 A resistive load.

Top trace: output voltage (2 V/div.). Bottom trace: input voltage (50 V/div.). Time scale: (0.2 ms/div.).

Output Load Transient Response



BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

12.0V, 33A / 396W Electrical Specification

 $\begin{array}{l} T_{P1}=-40 \text{ to } +90^{\circ}\text{C}, \ V_{I}=36 \text{ to } 75 \text{ V}, \ \text{sense pins connected to output pins unless otherwise specified under Conditions.} \\ Typical values given at: \\ T_{P1}=+25^{\circ}\text{C}, \ V_{I}=53 \text{ V}, \ \text{max } I_{0}, \ \text{unless otherwise specified under Conditions.} \\ \text{Additional } C_{out}=0.1 \text{ mF}, \ \text{Configuration File: 190 10-CDA 102 935/001 rev D} \end{array}$

Charact	eristics	Conditions	min	typ	max	Unit
Vi	Input voltage range		36		75	V
V _{loff}	Turn-off input voltage	Decreasing input voltage	32	33	34	V
Vlan	Turn-on input voltage	Increasing input voltage	34	35	36	V
Cı	Internal input capacitance			18		μF
Po	Output pow er		0		396	W
	Efficiency	50% of max I _o		96.5		%
		max I _o		95.5		
''		50% of max $I_{\rm O}$, $V_{\rm I}$ = 48 V		96.5		
		max I_0 , $V_1 = 48$ V		95.5		
Pd	Pow er Dissipation	max I _o		18.3	27.1	W
Pli	Input idling pow er	$I_0 = 0 A, V_1 = 53 V$		2.4		W
P _{RC}	Input standby power	$V_1 = 53 V$ (turned off with RC)		190		mW
fs	Default switching frequency	0-100% of max Io see Note 1	133	140	145	kHz

Voi	Output voltage initial setting and	T _{P1} = +25°C, V ₁ = 53 V, I ₀ = 17 A	11.88	12.0	12.12	V
-	Accuracy	See operating information	0 1		12.2	V
	Output adjust range	See operating information	0.1		13.2	v
Vo	Output voltage tolerance band	0-100% of max I ₀	11.76		12.24	V
vo	Line regulation	max I_0 at 40-75V input, see Note 7		20	60	mV
	Load regulation	$V_1 = 53 V$, 1-100% of max I_0		60	90	mV
V_{tr}	Load transient voltage deviation	V_1 = 53 V, Load step 25-75-25 % of max I _o , di/dt = 1 A/µs, see Note 2		±0.4		V
t _{tr}	Load transient recovery time			250		μs
tr	Ramp-up time (from 10–90% of V _{Oi})	10-100% of max $I_{0,}$		8		ms
ts	Start-up time (from V _I connection to 90% of V _{Oi})	see Note 3		140		ms
t,	Vin shutdown fall time	max I _o		0.4		mS
u;	(from V_1 off to 10% of V_0)	$I_0 = 0 A$		7		S
	RC start-up time	max Io		53		ms
t _{RC}	RC shutdow n fall time	max Io		3.2		ms
	(from RC off to 10% of $V_{O})$	I ₀ = 0 A		7		S
lo	Output current		0		33	А
l _{lim}	Current limit threshold	$V_{O} = 10.8 V, T_{P1} < max T_{ref}$	34	38	43	А
sc	Short circuit current	$T_{P1} = 25^{\circ}C$, see Note 4		-		А
Cout	Recommended Capacitive Load	$T_{P1} = 25^{\circ}C$, see Note 5	0.1	3.3	6	mF
V_{Oac}	Output ripple & noise	See ripple & noise section, max $I_{\rm O}$		60	120	mVp-p
OVP	Over voltage protection	T _{P1} = +25°C, V ₁ = 53 V, 10-100% of max I ₀ , see Note 6		15.6		V

Note 1: Frequency may be adjusted with PMBus communication. See Operating Information section

Note 2: Cout = 3.3mF used at load transient test.

Note 3: Start-up and R amp-up time can be increased via PMBus, see Operation Information section.

Note 4: OCP in latch mode

Note 5: Low ESR-value

Note 6: OVP-level can be adjusted via PMBus, see Operation Information.

Note 7: Line regulation characteristics at 36 to 75V input are presented on the next page.

Technical Specification 17

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

12.0V, 33A / 396W Electrical Specification

Efficiency





Output Current Derating, open frame



Thermal Resistance, base plate option



Output Current Derating, base plate option



Technical Specification 18

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

12.0V, 33A / 396W Electrical Specification

Output Characteristics



Output v oltage v s. load current at $T_{P1} = +25^{\circ}C$ The output v oltage range is limited at 36V input v oltage.

Start-up



Bottom trace: input voltage (50 V/div.). Time scal e: (50 ms/div.).

 $\begin{array}{l} \mbox{Start-up enabled by connecting V_1 at:} \\ T_{ref} = +25^\circ C, \ V_l = 53 \ V, \\ I_O = 33 \ A \ resistive \ load. \end{array}$

Output Ripple & Noise



Current Limit Characteristics



Shut-down



Shut- down enabled by disc onnecting V₁ at: $T_{P1} = +25^{\circ}C$, V₁ = 53 V, $I_0 = 33$ A resistive load.

Top trace: output voltage (5 V/di v.). Bottom trace: input voltage (50 V/di v.). Time scal e: (1 ms/di v.).

Output Load Transient Response



 $\begin{array}{l} \mbox{Output voltage response to load current} \\ \mbox{step-change (8.25-24.75-8.25 A) at:} \\ \mbox{T}_{P1} = + 25^\circ C, \ V_1 = 53 \ V, \ C_0 = 3.3 mF \,. \end{array}$

Top trace: output voltage (0.2 V/div.). Bottom trace: output current (10 A/div.). Time scale: (0.5 ms/div.).

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

EMC Specification

Conducted EMI measured according to EN55022, CISPR 22 and FCC part 15J (see test set-up). See Design Note 009 for further information. The fundamental switching frequency is 140 kHz for BMR 453 @ $V_I = 53 V$, max I_O .

Conducted EMI Input terminal value (typ)



EMI without filter

External filter (class B)

Suggested external input filter in order to meet class B in EN 55022, CISPR 22 and FCC part 15J.







Layout recommendation

The radiated EMI performance of the product will depend on the PWB layout and ground layer design. It is also important to consider the stand-off of the product. If a ground layer is used, it should be connected to one of the output terminals and the equipment ground or chassis.

A ground layer will increase the stray capacitance in the PWB and improve the high frequency EMC performance.

Output ripple and noise

Output ripple and noise measured according to figure below. See Design Note 022 for detailed information.



Output ripple and noise test setup

EMI with filter

30

Frequency (Hz)

(VL(B)) Iana,

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Operating information

Input Voltage

The input voltage range 36 to 75 Vdc meets the requirements of the European Telecom Standard ETS 300 132-2 for normal input voltage range in -48 and -60 Vdc systems, -40.5 to -57.0 V and -50.0 to -72 V respectively. At input voltages exceeding 75 V, the power loss will be higher than at normal input voltage and T_{P1} m ust be limited to absolute max+125°C. The absolute maximum continuous

Turn-off Input Voltage

input voltage is 80 Vdc.

The product monitors the input voltage and will turn on and turn off at predetermined levels. The turn on and turn off level and the hysteresis in between can be configured via the PMBus. The default hysteresis between turn on and turn off input voltage is set to 2 V.

Remote Control (RC)



The products are fitted with a configurable remote control function. The primary remote control is referenced to the primary negative input connection (-In). The RC function allows the converter to be turned on/off by an external device like a semiconductor or mechanical switch. The RC pin has an internal pull up resistor. The remote control functions can also be configured using the PMBus.

The device should be capable of sinking 0.7 mA. When the RC pin is left open, the voltage generated on the RC pin is max 6 V. The standard product is provided with "negative logic" remote control and will be off until the RC pin is connected to the -In. To turn on the product the voltage between RC pin and -In should be less than 1 V. To turn off the product the RC pin should be left open. In situations where it is desired to have the product to power up automatically without the need for control signals or a switch, the RC pin can be wired directly to -In. The logic option for the primary remote control is configured using the PMBus.

Remote Control (secondary side)

The CTRL CS pin can be configured as remote control via the PMBus interface. In the default configuration the CTRL CS pin is disabled and the output has an internal pull-up to 3.3 V. The CTRL CS pin can be left open when not used. The logic options for the secondary remote control can be positive or negative logic.

Input and Output Impedance

The impedance of both the input source and the load will interact with the impedance of the product. It is important that the input source has low characteristic impedance. Minimum recommended external input capacitance is 100 uF. The performance in some applications can be enhanced by addition of external capacitance as described under External Decoupling Capacitors.

External Decoupling Capacitors

When powering loads with significant dynamic current requirements, the voltage regulation at the point of load can be improved by addition of decoupling capacitors at the load. The recommended minimum capacitance on the output is 100 uF. The most effective technique is to locate low ESR ceramic and electrolytic capacitors as close to the load as possible, using several parallel capacitors to lower the effective ESR. The ceramic capacitors will handle high-frequency dynamic load changes while the electrolytic capacitors are used to handle low frequency dynamic load changes. Ceramic capacitors will also reduce any high frequency noise across the load. It is equally important to use low resistance and low inductance PWB layouts and cabling.

External decoupling capacitors will become part of the product's control loop. The control loop is optimized for a wide range of external capacitance and the maximum recommended value that could be used without any additional analysis is found in the Electrical specification.

The ESR of the capacitors is a very important parameter. Stable operation is guaranteed with a verified ESR value of >10 m Ω across the output connections.

For further information please contact your local Ericsson Power Modules representative.

PMBus configuration and support

The products provide a PMBus digital interface that enables the user to configure many aspects of the device operation as well as monitor the input and output parameters. Please contact your local Ericsson Power Modules representative for appropriate SW tools to down-load new configurations.

Output Voltage Adjust using PMBus

The output voltage of the product can be reconfigured using the PMBus interface. BMR 453 xx00/001 and /002 can be adjusted from 8.1 V to 13.2 V. The BMR 453 xx02/003 and /004 can be adjusted from 3.0 V to 6.7 V.



The output voltage will be fully regulated for all operating combinations within the shaded area in the plot above.

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Operation outside of this area is not recommended for normal use.

Margin Up/Down Controls

These controls allow the output voltage to be momentarily adjusted, either up or down, by a nominal 10%. This provides a convenient method for dynamically testing the operation of the load circuit over its supply margin or range. It can also be used to verify the function of supply voltage supervisors. The margin up and down levels of the product can be reconfigured using the PMBus interface.

Soft-start Power Up

The soft-start control introduces a time-delay (default setting 40 ms) before allowing the output voltage to rise. The default rise time of the ramp up is 10 ms. Power-up is hence completed within 50 ms in default configuration using remote control. When starting by applying input voltage the control circuit boot-up time adds an additional 100 ms delay. The soft-start power up of the product can be reconfigured using the PMBus interface.

Remote Sense

The products have remote sense that can be used to compensate for voltage drops between the output and the point of load. The sense traces should be located close to the PCB ground layer to reduce noise susceptibility. The remote sense circuitry will compensate for up to 10% voltage drop between +Out pin and the point of load (+Sense). The -Sense pin should be always connected to -Out. When activating remote sense, connect the +Sense pin to the +Input of the load. If the remote sense is not needed +Sense pin should be connected to +Out of the BMR453 unit. To be able to use remote sense the converter must be equipped with a digital connector.

Temperature Protection (OTP, UTP)

The products are protected from thermal overload by an internal temperature shutdown protection.

When T_{P1} as defined in thermal consideration section is exceeded the product will shut down. The product will make continuous attempts to start up (non-latching mode) and resume normal operation automatically when the temperature has dropped below the temperature threshold, the hysteresis is defined in general electrical specification.

The OTP and hysteresis of the product can be re-configured using the PMBus interface. The product has also an under temperature protection. The OTP and UTP fault limit and fault response can be configured via the PMBus. Note: using the fault response "continue without interruption" may cause permanent damage of the product.

Over Voltage Protection (OVP)

The product has output over voltage protection that will shut down the converter in over voltage conditions (latching mode) The OVP fault level and fault response can be re-configured using the PMBus interface.

Over Current Protection (OCP)

The product includes current limiting circuitry for protection at continuous overload. The module needs RC cycle operation at least once before enters hiccup mode if the maximum output current is exceeded and the output voltage is below $0.3 \times Vout$. The load distribution should be designed for the maximum output short circuit current specified. If for some reason the output should be short circuited, minimum resistance should not be lower than 6 m Ω . The OCP level and fault response can be re-configured using the PMBus interface. The default configuration is set to hiccup mode for the OCP, except for BMR453xxx/001 (latching OCP). Brick wall OCP mode is also supported in BMR453 series for option. For further information please contact your local Ericsson Power Modules representative.

RC recycle operation as below:



Input Over/Under voltage protection

The input of the product can be protected agains high input voltage and low input voltage. The over- and under-voltage fault level and fault response can be configured via the PMBus interface.

Pre-bias Start-up

The product has a Pre-bias start up functionality and will not sink current during start up if a pre-bias source is present at the output terminals.

Power Good

The PG SYNC pin can be configured as an output (POWER GOOD). The power good signal (TTL level) indicates proper operation of the product and can also be used as an error flag indicator. The PG SYNC pin has POWER GOOD as default configuration with the output set as active low. The PG SYNC pin is configured via the PMBus interface.

Tracking and External reference

The PG SYNC pin can be configured as an input for voltage tracking or an external analogue reference.

The PG SYNC pin is configured via the PMBus interface and has default setting Power Good.

Send command MFR_MULTI_PIN_CONFIG (0xF9h) with data 0x10h, the module will work in standalone tracking mode; Connect the PG_SYNC pin to the external reference voltage

(ground to -OUT), the output voltage will follow this reference voltage with a predefined scale.

The max reference voltage is 2.5 V which connects to digital controller's ADC port.

The reference voltage / Vout scale factor is stored in

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

MFR_VOUT_ANALOG_SCALE (0 xE8h) with default value 0.175(0 xA2CDh), end user can change it by using PMBus command.

End user can read the scaled value by command MFR_READ_VOUT_ANALOG_REF (0xE9h). Any changes of using PMBUS command should use command Store Default all (0x11h) to make the change permanent before power off.

Switching frequency adjust using PMBus

The switching frequency is set to 140 kHz as default but this can be reconfigured via the PMBus interface. The product is optimized at this frequency but can run at lower and higher frequency, (125 kHz - 150 kHz). However the output performance is not specified if the frequency is changed.

Input Transient

The BMR453 products have limited ability to react on sudden input voltage changes. As an example the 12 V module BMR453xxxx/001 can have an output voltage deviation of 5 V when a 20 V input step is applied (40 V to 60 V). This is tested with a slew rate of 0.1 V/us on the input voltage change and minimum output capacitance 100 uF. Increasing the output capacitance will improve the result.

Parallel Operation with Droop

The BMR 453 0006(or BMR4530007) with /012 or /013 or /014 configuration file are variants that can be connected in parallel. The products have a pre-configured voltage droop: The stated output voltage initial setting accuracy is within ± 35 mV at no load, The output voltage will decrease when the load current is increased, the voltage will droop 0.6V while load reaches max load. This feature allows the products to be connected in parallel and share the current with 10% accuracy. Up to 90% of max output current can be used from each module.



Fault protection at parallel operation with Droop If one of the two modules exceeds the OVP, OCP or OTP level, the module might turn off depends on its pre-set fault response action, and the other module might not handle more current than its max capability, that will lead to both modules can not recover until the protection trig condition removed, to secure a normal operation, both modules need a reset.

Typical Vout Vs. Vin characteristic at 33A load and TP1=25°C



The output voltage will be fully regulated for all operating combinations within the shaded area in the plot above. Operation outside of this area is not recommended for normal use.

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Thermal Consideration

General

The products are designed to operate in different thermal environments and sufficient cooling must be provided to ensure reliable operation. For products mounted on a PWB without a heat sink attached, cooling is achieved mainly by conduction, from the pins to the host board, and convection, which is dependant on the airflow across the product. Increased airflow enhances the cooling of the product. The Output Current Derating graph found in the Output section for each model provides the available output current vs. ambient air temperature and air velocity at $V_{1} = 53 V_{.}$

The product is tested on a 254 x 254 mm, 35 μ m (1 oz), 8-layer test board mounted vertically in a wind tunnel with a cross-section of 608 x 203 mm.



Definition of product operating temperature

The product operating temperatures is used to monitor the temperature of the product, and proper thermal conditions can be verified by measuring the temperature at positions P1, P2, P3, P4. The temperature at these positions (T_{P1} , T_{P2} , T_{P3} , T_{P4}) should not exceed the maximum temperatures in the table below. The number of measurement points may vary with different thermal design and topology. Temperatures above maximum T_{P1}, measured at the reference point P1 (P3 for base plate versions) are not allowed and may cause permanent damage.

Position	Description	Maxtemperature
P1	PWB (reference point)	T _{P1} =125° C
P2	Opto-coupler	T _{P2} =105° C
P3	PWB (reference point for base- plate version)	T _{P3} =125° C
P4	Primary MOSFET	T _{P4} =125° C



(Best airflow direction Negative to Positive.)

Bottom view

(base plate version)

Ambient Temperature Calculation

For products with base plate the maximum allowed ambient temperature can be calculated by using the thermal resistance.

1. The power loss is calculated by using the formula $((1/n) - 1) \times \text{output power} = \text{power losses (Pd)}.$ η = efficiency of product. E.g. 95% = 0.95

2. Find the thermal resistance (Rth) in the Thermal Resistance graph found in the Output section for each model. Note that the thermal resistance can be significantly reduced if a heat sink is mounted on the top of the base plate.

Calculate the temperature increase (ΔT). $\Delta T = Rth \times Pd$

3. Max allowed ambient temperature is: Max $T_{P1} - \Delta T$.

E.g. BMR 453 5100/001 at 2 m/s:

1.
$$\left(\left(\frac{1}{0.944}\right) - 1\right) \times 396 \text{ W} = 23.5 \text{ W}$$

2. 23.5 W × 3.1°C/W = 73°C

3. 125 °C – 73°C = max ambient temperature is 52°C

The actual temperature will be dependent on several factors such as the PWB size, number of layers and direction of airflow.

Technical Specification 24

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Connections (Top view)



Pin	Designation	Function
1	+ln	Positive Input
2	RC	Remote Control
3	Case	Case to GND (optional)
4	-In	Negative Input
5	-Out	Negative Output
6	S+	Positive Remote Sense
7	S-	Negative Remote Sense
8	SA0	Address pin 0
9	SA1	Address pin 1
10	SCL	PMBus Clock
11	SDA	PMBus Data
12	PG SYNC	Configurable I/O pin: Power Good output, SYNC-, tracking-, or ext ref-input
13	DGND	PMBus ground
14	SALERT	PMBus alert signal
15	CTRL CS	PMBus remote control or Currentshare
16	+Out	Positive Output

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

PMBus Communications

The products provide a PMBus digital interface that enables the user to configure many aspects of the device operation as well as monitor the input and output parameters. The products can be used with any standard two-wire I^2C or SMBus host device. In addition, the device is compatible with PMBus version 1.1 and includes an SALERT line to help mitigate bandwidth limitations related to continuous fault monitoring.

Monitoring via PMBus

A system controller can monitor a wide variety of different parameters through the PMBus interface. The controller can monitor for fault condition by monitoring the SALERT pin, which will be asserted when any number of pre-configured fault or warning conditions occur. The system controller can also continuously monitor for any number of power conversion parameters including but not limited to the following:

- Input voltage
- Output voltage
- Output current
- Internal junction temperature
- Switching frequency
- Duty cycle

Evaluation software

A Configuration Monitoring and Management (CMM) evaluation software, is available for the products. For more information please contact your local Ericsson Power Modules sales representative.

Addressing

The figure and table below show recommended resistor values with min and max voltage range for hard-wiring PMBus addresses (series E96, 1% tolerance resistors suggested):



SA0/SA1	R1 /R0 [kΩ]
0	24.9
1	49.9
2	75
3	100
4	124
5	150

The SA0 and SA1 pins can be configured with a resistor to GND according to the following equation.

PMBus Address = 8 x (SA0value) + (SA1 value)

If any one of those voltage applied to ADC0 and ADC1 is out of the range from the table above, PMBus address 127 is assigned. If the calculated PMBus address is 0 or 12, PMBus address 127 is assigned instead. PMBus address 11 is not to be used. The user shall also be aware of further limitations of the addresses as stated in the PMBus Specification.

BMR453 / BMR454 PMBus Specification Exception

Item	PMBus Standard	BMR453 /BMR454
#SMBALERT	Open Drain	Totem Pole
TLOW:EXT (Cumulative clock low extend time (slave device))	25 ms	6.25 ms
TBUF_min (Bus free time between Stop and Start Condition)	4.7 us	200 us

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

PMBus Commands

The DC/DC converter is PMBUS compliant. The following table lists the implemented PMBus commands. For more detailed information see PMBus Power System Management Protocol Specification; Part I – General Requirements, Transport and Electrical Interface and PMBus Power System Management Protocol; Part II – Command Language.

Designation	Cn	nd	Impl
Standard PMBus Commands			
Control Commands			
PAGE	001	ו	No
OPERATION	011	ו	Yes
ବିN_OFF_CONFIG	021	ı	Yes
WRITE_PROTECT	10	ו	Yes
Output Commands			
♥ OUT_MODE	201	ו	Yes
OUT_COMMAND	211	ו	Yes
₩OUT_TRIM	221	ו	Yes
∜OUT_GAIN	231	ו	Yes ^{note1}
VOUT_MAX	241	ו	Yes
VOUT_MARGIN_HIGH	25	ו	Yes
₩ÐUT_MARGIN_LOW	26	ו	Yes
₩DUT_TRANSITION_RATE	27	ו	Yes
₩OUT_DROOP	28	ו	No
VOUT_SCALE_LOOP	29	ו	Yes note1
₩OUT_SCALE_MONITOR	2A	h	Yes note1
COEFFICIENTS	301	٦	No
POUT_MAX	311	n	No
MAX_DUTY	321	n	Yes
FREQUENCY_SWITCH	331	n	Yes
VIN_ON	351	n	Yes
VIN_OFF	361	n	Yes
IOUT_CAL_GAIN	381	n	Yes note1
IOUT_CAL_OFFSET	391	า	Yes note1
Fault Limit Commands			
POWER_GOOD_ON	5E	h	Yes
POWER_GOOD_OFF	5F	h	Yes
VOUT_OV_FAULT_LIMIT	40	n	Yes
VOUT_UV_FAULT_LIMIT	44	n	Yes
IOUT_OC_FAULT_LIMIT	46	n	Yes
IOUT_OC_LV_FAULT_LIMIT	48	1	Yes
IOUT_UC_FAULT_LIMIT	4B	h	No
OT_FAULT_LIMIT	4F	h	Yes

Designation	Cmd	Impl
OT WARN LIMIT	51h	Yes
UT WARN LIMIT	52h	Yes
UT FAULT LIMIT	53h	Yes
VIN OV FAULT LIMIT	55h	Yes
VIN OV WARN LIMIT	57h	Yes
VIN UV WARN LIMIT	58h	Yes
VIN_UV_FAULT_LIMIT	59h	Yes
VOUT_OV_WARN_LIMIT	42h	Yes
VOUT_UV_WARN_LIMIT	43h	Yes
IOUT_OC_WARN_LIMIT	4Ah	Yes
IIN_OC_FAULT_LIMIT	5Bh	No
IIN OC WARN LIMIT	5Dh	No
Fault Response Commands		
VOUT_OV_FAULT_RESPONSE	41h	Yes
VOUT_UV_FAULT_RESPONSE	45h	Yes
OT_FAULT_RESPONSE	50h	Yes
UT_FAULT_RESPONSE	54h	Yes
VIN_OV_FAULT_RESPONSE	56h	Yes
VIN_UV_FAULT_RESPONSE	5Ah	Yes
IOUT_OC_FAULT_RESPONSE	47h	Yes
IOUT_UC_FAULT_RESPONSE	4Ch	No
IIN_OC_FAULT_RESPONSE	5Ch	No
Time setting Commands		
TON_DELAY	60h	Yes
TON_RISE	61h	Yes
TON_MAX_FAULT_LIMIT	62h	Yes
TON_MAX_FAULT_RESPONSE	63h	Yes
TOFF_DELAY	64h	Yes
TOFF_FALL	65h	Yes
TOFF_MAX_WARN_LIMIT	66h	Yes
Status Commands (Read Only)		
CLEAR_FAULTS	03h	Yes
STATUS_BYTES	78h	Yes
STATUS_WORD	79h	Yes
STATUS_VOUT	7Ah	Yes
STATUS_IOUT	7Bh	Yes
STATUS_INPUT	7Ch	Yes
STATUS_TEMPERATURE	7Dh	Yes
STATUS_CML	7Eh	Yes
STATUS_OTHER	7Fh	Yes
Monitor Commands (Read Only)		
READ_VIN	88h	Yes

BMR 453 series Fully regulated Intermediate Bus ConvertersEN/LZT 146 395 R9AMarch 2014Input 36-75 V, Output up to 60 A / 396 W© Ericsson AB

Designation	Cmd	Impl
READ_VOUT	8Bh	Yes
READ_IOUT	8Ch	Yes
READ_TEMPERATURE_1	8Dh	Yes
READ_TEMPERATURE_2	8Eh	Yes
READ_FAN_SPEED_1	90h	No
READ_DUTY_CYCLE	94h	Yes
READ_FREQUENCY	95h	Yes
READ_POUT	96h	No
READ_PIN	97h	No
Identification Commands (Read Only)		
PMBUS_REVISION	98h	Yes
MFR_ID	99h	Yes note1
MFR_MODEL	9Ah	Yes note1
MFR_REVISION	9Bh	Yes note1
MFR_LOCATION	9Ch	Yes note1
MFR_DATE	9Dh	Yes note1
MFR_SERIAL	9Eh	Yes note1
Group Commands		
INTERLEAVE	37h	No
Supervisory Commands		
STORE_DEFAULT_ALL	11h	Yes note2
RESTORE_DEFAULT_ALL	12h	Yes
STORE_USER_ALL	15h	No
RESTORE_USER_ALL	16h	No
BMR 453/454 Specific Commands		
MFR_POWER_GOOD_POLARITY	D0h	Yes
MFR_VOUT_UPPER_RESISTOR	D2h	Yes note1
MFR_VIN_SCALE_MONITOR	D3h	Yes note1
MFR_CLA_TABLE_NUM_ROW	D4h	Yes
MFR_CLA_ROW_COEFFICIENTS	D5h	Yes
MFR_STORE_CLA_TABLE	D6h	Yes
MFR_ACTIVE_COEFF_CLA_TABLE	D8h	Yes
MFR_SET_ROM_MODE	D9h	Yes note1
MFR_SELECT_TEMP_SENSOR	DCh	Yes
MFR_VIN_OFFSET	DDh	Yes note1
MFR_REMOTE_TEMP_CAL	E2h	Yes
MFR_REMOTE_CONTROL	E3h	Yes
MFR_DEAD_BAND_MODE	E4h	Yes note1
MFR_DEAD_BAND_DELAY	E5h	Yes note1
MFR_TEMP_COEFF	E7h	Yes note1
MFR_VOUT_ANALOG_SCALE	E8h	Yes
MFR_READ_VOUT_ANALOG_REF	E9h	Yes

Designation	Cmd	Impl
MFR_DEBUG_BUFF	F0h	Yes
MFR_SETUP_PASSWORD	F1h	Yes
MFR_DISABLE_SECURITY	F2h	Yes
MFR_DEAD_BAND_IOUT_THRESHOLD	F3h	Yes note1
MFR_SECURITY_BIT_MASK	F4h	Yes
MFR_PRIMARY_TURN	F5h	Yes note1
MFR_SECONDARY_TURN	F6h	Yes note1
MFR_SET_DPWM_POLARITY	F7h	Yes note1
MFR_ILIM_SOFTSTART	F8h	Yes
MFR_MULTI_PIN_CONFIG	F9h	Yes
MFR_DEAD_BAND_VIN_THRESHOLD	FAh	Yes note1
MFR_DEAD_BAND_VIN_IOUT_HYS	FBh	Yes note1
MFR_FIRMEWARE_VERSION	FCh	Yes note1
MFR_MESSAGE_CODE_DEVICE_ID	FDh	Yes note1

Notes:

Cmd is short for Command. Impl is short for Implemented.

Note1:

the content is protected for being overwritten to secure normal operation

Note 2:

Power must be kept on at least 700ms after sending STORE_DEFAULT_ALL command for data flash refresh.

ERICSSON 📕

Technical Specification 28

BMR 453 series Fully regulated Intermediate Bus ConvertersEN/LZT 146 395 R9AMarch 2014Input 36-75 V, Output up to 60 A / 396 W© Ericsson AB

Mechanical Information - Hole Mount, Open Frame Version



All component placements – whether shown as physical components or symbolical outline – are for reference only and are subject to change throughout the product's life cycle, unless explicitly described and dimensioned in this drawing.



Technical Specification 29





All component placements – whether shown as physical components or symbolical outline – are for reference only and are subject to change throughout the product's life cycle, unless explicitly described and dimensioned in this drawing.

ERICSSON 🔰

Technical Specification 30

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Mechanical Information - SMD mount, Open Frame Version







Pin positions according to recommended footprint

TOP VIEW



RECOMMENDED FOOTPRINT - TOP VIEW



NOTES

PIN SPECIFICATIONS Pin 1.2.4.5 & 16 - Material: Copper alloy Plating: Au 0.1 μm over 1-3 μm Ni. Pin 6-15 - Material: Brass Plating: Au 0.1 μm over 2 μm Ni.

Weight: Typical 46 g

All dimensions in mm (inch). Tolerances unless specified: x.x ±0.5 mm (0.02) x.xx±0.25 mm (0.01) (not applied on footprint or typical values)



All component placements – whether shown as physical components or symbolical outline – are for reference only and are subject to change throughout the product's life cycle, unless explicitly described and dimensioned in this drawing.



37.8 1.49]

Technical Specification 31

BMR 453 series Fully regulated Intermediate Bus Converters EN/LZT 146 395 R9A March 2014 Input 36-75 V, Output up to 60 A / 396 W © Ericsson AB

Mechanical Information - Hole mount, Open Frame Version, Non Digital Interface



The stand-off in combination with insulating material ensures that requirements as per IEC/EN/UL60950 are met and 1500 V isolation maintained even if open vias or traces are present under the DC/DC converter.

E D

All component placements - whether shown as physical components or symbolical outline - are for reference only and are subject to change throughout the product's life cycle, unless explicitly described and dimensioned in this drawing.

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Soldering Information – Surface Mounting

The surface mount product is intended for forced convection or vapor phase reflow soldering in SnPb and Pb-free processes.

The reflow profile should be optimised to avoid excessive heating of the product. It is recommended to have a sufficiently extended preheat time to ensure an even temperature across the host PCB and it is also recommended to minimize the time in reflow.

A no-clean flux is recommended to avoid entrapment of cleaning fluids in cavities inside the product or between the product and the host board, since cleaning residues may affect long time reliability and isolation voltage.

Minimum Pin Temperature Recommendations

Pin number 5 is chosen as reference location for the minimum pin temperature recommendation since this will likely be the coolest solder joint during the reflow process.

SnPb solder processes

For SnPb solder processes, a pin temperature (T_{PIN}) in excess of the solder melting temperature, (T_L, 183°C for Sn63Pb37) for more than 30 seconds and a peak temperature of 210°C is recommended to ensure a reliable solder joint.

For dry packed products only: depending on the type of solder paste and flux system used on the host board, up to a recommended maximum temperature of 245°C could be used, if the products are kept in a controlled environment (dry pack handling and storage) prior to assembly.

General reflow process specifications		SnPb eutectic	Pb-free
Average ramp-up (T _{PRODUCT})		3°C/s max	3°C/s max
Typical solder melting (liquidus) temperature	TL	183°C	221°C
Minimum reflow time above T_L		30 s	30 s
Minimum pin temperature	T _{PIN}	210°C	235°C
Peak product temperature	T _{PRODUC}	225°C	260°C
Average ramp-down (T _{PRODUCT})		6°C/s max	6°C/s max
Maximum time 25°C to peak		6 minutes	8 minutes



Lead-free (Pb-free) solder processes

For Pb-free solder processes, a pin temperature (T_{PIN}) in excess of the solder melting temperature (T_{L} , 217 to 221°C for SnAgCu solder alloys) for more than 30 seconds and a peak temperature of 235°C on all solder joints is recommended to ensure a reliable solder joint.

Maximum Product Temperature Requirements

Top of the product PCB near pin 2 is chosen as reference location for the maximum (peak) allowed product temperature ($T_{PRODUCT}$) since this will likely be the warmest part of the product during the reflow process.

SnPb solder processes

For SnPb solder processes, the product is qualified for MSL 1 according to IPC/JEDEC standard J-STD-020C.

During reflow T_{PRODUCT} must not exceed 225 °C at any time.

Pb-free solder processes

For Pb-free solder processes, the product is qualified for MSL 3 according to IPC/JEDEC standard J-STD-020C.

During reflow T_{PRODUCT} must not exceed 260 °C at any time.

Dry Pack Information

Products intended for Pb-free reflow soldering processes are delivered in standard moisture barrier bags according to IPC/JEDEC standard J-STD-033 (Handling, packing, shipping and use of moisture/reflow sensitivity surface mount devices).

Using products in high temperature Pb-free soldering processes requires dry pack storage and handling. In case the products have been stored in an uncontrolled environment and no longer can be considered dry, the modules must be baked according to J-STD-033.

Thermocoupler Attachment

Pin 2 for measurement of maximum product temperature T_PRODUCT



Pin 5 for measurement of minimum Pin (solder joint) temperature T_{PIN}

Technical Specification 33

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Delivery Package Information – Surface Mount Version

The products are delivered in antistatic injection molded trays (Jedec design guide 4.10D standard).

Tray Specifications			
Material	Antistatic PPE		
Surface resistance	10^{5} < Ohm/square < 10^{12}		
Bakability	The trays can be baked at maximum 125°C for 48 hours		
Tray thickness	14.50 mm 0.571 [inch]		
Box capacity	20 products (2 full trays/box)		
Tray weight	125 g empty, 574 g full tray		



JEDEC standard tray for 2x5 = 10 products. All dimensions in mm [inch] Tolerances: X.x ±0.26 [0.01], X.xx ±0.13 [0.005]

Note: pick up positions refer to center of pocket. See mechanical drawing for exact location on product.

Technical Specification ³⁴

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Soldering Information – Hole Mounting

The hole mounted product is intended for plated through hole mounting by wave or manual soldering. The pin temperature is specified to maximum to 270°C for maximum 10 seconds.

A maximum preheat rate of 4° C/s and maximum preheat temperature of 150°C is suggested. When soldering by hand, care should be taken to avoid direct contact between the hot soldering iron tip and the pins for more than a few seconds in order to prevent overheating.

A no-clean flux is recommended to avoid entrapment of cleaning fluids in cavities inside the product or between the product and the host board. The cleaning residues may affect long time reliability and isolation voltage.

Delivery Package Information – Hole Mount Version

The products are delivered in antistatic trays.

Tray Specifications			
Material	PE Foam		
Surface resistance	10^5 < Ohm/square < 10^{11}		
Bakability	The trays are not bakeable		
Tray capacity	20 converters/tray		
Box capacity	Product – Open frame /Base plate option 60 products (3 full trays /box)		
Weight	Product – Open frame 1100 g full tray, 140g empty tray Product – Base plate option 1480 g full tray, 140g empty tray		



35 **Technical Specification**

BMR 453 series Fully regulated Intermediate Bus Converters	EN/LZT 146 395 R9A	March 2014
Input 36-75 V, Output up to 60 A / 396 W	© Ericsson AB	

Product Qualification Specification

Characteristics			
External visual inspection	IPC-A-610		
Change of temperature (Temperature cycling)	IEC 60068-2-14 Na	Temperature range Number of cycles Dwell/transfer time	-40 to 100°C 1000 15 min/0-1 min
Cold (in operation)	IEC 60068-2-1 Ad	Temperature T _A Duration	-45°C 72 h
Damp heat	IEC 60068-2-67 Cy	Temperature Humidity Duration	85°C 85 % RH 1000 hours
Dry heat	IEC 60068-2-2 Bd	Temperature Duration	125°C 1000 h
Electrostatic discharge susceptibility	IEC 61340-3-1, JESD 22-A114 IEC 61340-3-2, JESD 22-A115	Human body model (HBM) Machine Model (MM)	Class 2, 2000 V Class 3, 200 V
Immersion in cleaning solvents	IEC 60068-2-45 XA, method 2	Water Glycol ether Isopropyl alcohol	55°C 35°C 35°C
Mechanical shock	IEC 60068-2-27 Ea	Peak acceleration Duration	100 g 6 ms
Moisture reflow sensitivity ¹	J-STD-020C	Level 1 (SnPb-eutectic) Level 3 (Pb Free)	225°C 260°C
Operational life test	MIL-STD-202G, method 108A	Duration	1000 h
Resistance to soldering heat ²	IEC 60068-2-20 Tb, method 1A	Solder temperature Duration	270°C 10-13 s
Robustness of terminations	IEC 60068-2-21 Test Ua1 IEC 60068-2-21 Test Ue1	Through hole mount products Surface mount products	All leads All leads
Solderability	IEC 60068-2-58 test Td ¹	Preconditioning Temperature, SnPb Eutectic Temperature, Pb-free	150°C dry bake 16 h 215°C 235°C
	IEC 60068-2-20 test Ta ²	Preconditioning Temperature, SnPb Eutectic Temperature, Pb-free	Steam ageing 235°C 245°C
Vibration, broad band random	IEC 60068-2-64 Fh, method 1	Frequency Spectral density Duration	10 to 500 Hz 0.07 g ² /Hz 10 min in each direction

Notes ¹ Only for products intended for reflow soldering (surface mount products) ² Only for products intended for wave soldering (plated through hole products)





Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.З, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж: moschip.ru moschip.ru_4

moschip.ru_6 moschip.ru_9