


## LFP100F

LF P 100 F - -

① ② ③ ④ ⑤ ⑥



RoHS

Recommended EMI/EMC Filter  
NAC-04-472

High voltage pulse noise type : NAP series  
Low leakage current type : NAM series

\* The EMI/EMC Filter is recommended to connect with several devices.

- ① Series name  
② Single output  
③ Output wattage  
④ Universal input  
⑤ Output voltage  
⑥ Optional \*1  
C : with Coating  
G : Low leakage current  
J1 : VH(J.S.T.)connector type  
R : with Remote ON/OFF  
R2 : with Remote ON/OFF  
S : with Chassis  
SN : with Chassis & cover

Please refer to Instruction manual 6.

This power supply is manufactured by SMD technology. The stress to P.C.B like twisting or bending causes the defect of the unit, so handle the unit with care.

| MODEL                 | LFP100F-24-Y       | LFP100F-36-Y    | LFP100F-48-Y    |
|-----------------------|--------------------|-----------------|-----------------|
| MAX OUTPUT WATTAGE[W] | *2 103.2 (206.4)   | 100.8 (201.6)   | 100.8 (201.6)   |
| DC OUTPUT             | *2 24V 4.3A (8.6A) | 36V 2.8A (5.6A) | 48V 2.1A (4.2A) |

## SPECIFICATIONS

|                                     | MODEL                                |                   | LFP100F-24-Y                                                                                           | LFP100F-36-Y      | LFP100F-48-Y      |
|-------------------------------------|--------------------------------------|-------------------|--------------------------------------------------------------------------------------------------------|-------------------|-------------------|
| INPUT                               | VOLTAGE[V]                           |                   | AC85 - 264 1 φ (Refer to Instruction Manual 1.1 and 3.2) *5                                            |                   |                   |
|                                     | CURRENT[A]                           | ACIN 100V         | 1.3typ (Io=100%)                                                                                       |                   |                   |
|                                     |                                      | ACIN 200V         | 0.7typ (Io=100%)                                                                                       |                   |                   |
|                                     | FREQUENCY[Hz]                        |                   | 50 / 60 (47 - 63)                                                                                      |                   |                   |
|                                     | EFFICIENCY[%]                        | ACIN 100V         | 84.0typ (Io=100%)                                                                                      | 84.0typ (Io=100%) | 84.0typ (Io=100%) |
|                                     |                                      | ACIN 200V         | 87.0typ (Io=100%)                                                                                      | 87.0typ (Io=100%) | 87.0typ (Io=100%) |
|                                     | POWER FACTOR                         | ACIN 100V         | 0.99typ (Io=100%)                                                                                      |                   |                   |
| ACIN 200V                           |                                      | 0.95typ (Io=100%) |                                                                                                        |                   |                   |
|                                     | INRUSH CURRENT[A]                    | ACIN 100V         | 15typ (Io=100%) (At cold start) (Ta=25℃)                                                               |                   |                   |
|                                     |                                      | ACIN 200V         | 30typ (Io=100%) (At cold start) (Ta=25℃)                                                               |                   |                   |
|                                     | LEAKAGE CURRENT[ma]                  |                   | 0.40 / 0.75max (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60950-1 and DEN-AN)                    |                   |                   |
| OUTPUT                              | VOLTAGE[V]                           |                   | 24                                                                                                     | 36                | 48                |
|                                     | CURRENT[A]                           |                   | *2 4.3 (Peak 8.6)                                                                                      | 2.8 (Peak 5.6)    | 2.1 (Peak 4.2)    |
|                                     | LINE REGULATION[mV]                  |                   | *7 96max                                                                                               | 144max            | 192max            |
|                                     | LOAD REGULATION[mV]                  |                   | *7 150max                                                                                              | 240max            | 240max            |
|                                     | RIPPLE[mVp-p]                        | 0 to +50℃         | 120max                                                                                                 | 150max            | 150max            |
|                                     |                                      | -10 - 0℃          | 160max                                                                                                 | 200max            | 200max            |
|                                     | RIPPLE NOISE[mVp-p]*3                | 0 to +50℃         | 150max                                                                                                 | 250max            | 250max            |
|                                     |                                      | -10 - 0℃          | 180max                                                                                                 | 300max            | 300max            |
|                                     | TEMPERATURE REGULATION[mV]           | 0 to +50℃         | 240max                                                                                                 | 360max            | 480max            |
|                                     |                                      | -10 to +50℃       | 290max                                                                                                 | 450max            | 600max            |
|                                     | DRIFT[mV]                            |                   | *4 96max                                                                                               | 144max            | 192max            |
|                                     | START-UP TIME[ms]                    |                   | 350typ (ACIN 100V, Io=100%)                                                                            |                   |                   |
|                                     | HOLD-UP TIME[ms]                     |                   | 20typ (ACIN 100V, Io=100%)                                                                             |                   |                   |
| PROTECTION<br>CIRCUIT AND<br>OTHERS | OUTPUT VOLTAGE ADJUSTMENT RANGE[V]   |                   | 21.60 to 27.50                                                                                         | 32.40 to 39.60    | 39.60 to 52.80    |
|                                     | OUTPUT VOLTAGE SETTING[V]            |                   | 24.00 to 24.96                                                                                         | 36.00 to 37.44    | 48.00 to 49.92    |
|                                     | OVERCURRENT PROTECTION               |                   | Works over 101% of rating and recovers automatically                                                   |                   |                   |
|                                     | OVERVOLTAGE PROTECTION[V]            |                   | 27.60 to 33.60                                                                                         | 41.40 to 50.40    | 55.20 to 67.20    |
|                                     | OPERATING INDICATION                 |                   | Not provided                                                                                           |                   |                   |
|                                     | REMOTE SENSING                       |                   | Not provided                                                                                           |                   |                   |
|                                     | REMOTE ON/OFF                        |                   | Option (Refer to Instruction Manual 6)                                                                 |                   |                   |
| ISOLATION                           | INPUT-OUTPUT-RC                      | *6                | AC3,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature)                         |                   |                   |
|                                     | INPUT-FG                             |                   | AC2,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature)                         |                   |                   |
|                                     | OUTPUT-RC-FG                         | *6                | AC500V 1minute, Cutoff current = 25mA, DC500V 50MΩ min (At Room Temperature)                           |                   |                   |
|                                     | OUTPUT-RC                            | *6                | AC100V 1minute, Cutoff current = 25mA, DC100V 10MΩ min (At Room Temperature)                           |                   |                   |
| ENVIRONMENT                         | OPERATING TEMP., HUMID. AND ALTITUDE |                   | *5 -10 to +70℃, 20 - 90%RH (Non condensing) (Refer to Instruction Manual 3.2), 3,000m (10,000feet) max |                   |                   |
|                                     | STORAGE TEMP., HUMID. AND ALTITUDE   |                   | -20 to +75℃, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max                                      |                   |                   |
|                                     | VIBRATION                            |                   | 10 - 55Hz, 19.6m/s <sup>2</sup> (2G), 3minutes period, 60minutes each along X, Y and Z axis            |                   |                   |
|                                     | IMPACT                               |                   | 196.1m/s <sup>2</sup> (20G), 11ms, once each X, Y and Z axis                                           |                   |                   |
| SAFETY AND<br>NOISE<br>REGULATIONS  | AGENCY APPROVALS (AT ONIY AC input)  |                   | UL60950-1, C-UL (CSA60950-1), EN60950-1, EN50178 Complies with DEN-AN                                  |                   |                   |
|                                     | CONDUCTED NOISE                      |                   | Complies with FCC-B, VCCI-B, CISPR22-B, EN55011-B, EN55022-B                                           |                   |                   |
|                                     | HARMONIC ATTENUATOR                  |                   | Complies with IEC61000-3-2 (Class A) *8                                                                |                   |                   |
| OTHERS                              | CASE SIZE/WEIGHT                     |                   | 62 X 33 X 155mm [2.44 X 1.30 X 6.10 inches] (W X H X D) / 290g max (with chassis & cover : 480g max)   |                   |                   |
|                                     | COOLING METHOD                       |                   | Convection (Refer to Instruction Manual 3.1 and 3.2) *5                                                |                   |                   |

\*1 Specification is changed at option, refer to Instruction Manual.

\*2 Peak loading for 10sec. And Duty 40% max, refer to Instruction Manual 5. In detail.

( ) means peak current. There is a possibility that an internal device is damaged when the specification is exceeded.

\*3 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.

Measured by 20MHz oscilloscope or Ripple-Noise meter (Equivalent to KEISOKU-GIKEN: RM103).

\*4 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25℃, with the input voltage held constant at the rated input/output.

\*5 Derating is required.

\*6 Applicable when remote control (optional) is added.

\*7 Please contact us about dynamic load and input response.

\*8 Please contact us about another class.


To meet the specifications. Do not operate over-loaded condition.

Parallel operation is not possible.

Derating is required when operated with chassis and cover.

Sound noise may be generated by power supply in case of pulse load.


## Block diagram




## External view

※ External size of option is different from standard model.

Standard type



Chassis and cover type



- ※ 4 Mounting holes are existing.
- ※ The back side of P.C.B. of the power supply is assembled some SMDs.
- Be attention not to bump against the attached area by vibration.
- ※ Use the spacer of 8mm length or more regarding insulation.
- And do not use press-fitting bush.
- ※ Point A, Point B are thermometry points. Please refer to Instruction Manual 3.

| I/O Connector   | Mating connector | Terminal        |
|-----------------|------------------|-----------------|
| CN1 1-1123724-3 | 1-1123722-5      | Chain 1123721-1 |
|                 |                  | Loose 1318912-1 |
| CN2 1-1123723-8 | 1-1123722-8      | Chain 1123721-1 |
|                 |                  | Loose 1318912-1 |

(Mfr:Tyco Electronics)

- ※ I/O Connector is Mfr. Tyco Electronics
- ※ Option:-J1:VH(J.S.T) connector type.

## &lt;PIN CONNECTION&gt;

CN1

| Pin No. | Input |
|---------|-------|
| 1       | AC(L) |
| 2       |       |
| 3       | AC(N) |
| 4       |       |
| 5       | FG    |

CN2

| Pin No. | Output |
|---------|--------|
| 1 to 4  | -V     |
| 5 to 8  | +V     |

- ※ Keep drawing current per pin below 5A for CN2.

- ※ Tolerance :  $\pm 1$  [ $\pm 0.04$ ]
- ※ Weight : 290g max (with chassis & cover : 480g max)
- ※ PCB material : CEM3
- ※ Optional chassis and cover material : Electric galvanizing steel board.
- ※ Dimensions in mm, [ ]=inches
- ※ Mounting torque (Mounting hole of chassis) :  $1.5N \cdot m$  (16kgf · cm) max

## Connector type

CN4 Option (Mfr:J.S.T)


| PIN No. | Contents |
|---------|----------|
| 1       | RC(+)    |
| 2       | RC(-)    |

## Barrier strip type

Model B2B-XH-A  
Mating Connector (Terminal)  
XHP-2  
(BXH-001T-P0.6  
or SXH-001T-P0.6)

# LFP150F

LF P 150 F - -



Recommended EMI/EMC Filter  
NAC-04-472



High voltage pulse noise type : NAP series  
Low leakage current type : NAM series  
\* The EMI/EMC Filter is recommended to connect with several devices.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑧ Optional \*1
- C : with Coating
- G : Low leakage current
- J1 : VH(J.S.T.)connector type
- R : with Remote ON/OFF
- R2 : with Remote ON/OFF
- S : with Chassis
- SN : with Chassis & cover

Please refer to Instruction manual 6.

This power supply is manufactured by SMD technology. The stress to P.C.B like twisting or bending causes the defect of the unit, so handle the unit with care.

| MODEL                 | LFP150F-24-Y        | LFP150F-36-Y    | LFP150F-48-Y    |
|-----------------------|---------------------|-----------------|-----------------|
| MAX OUTPUT WATTAGE[W] | *2 151.2 (302.4)    | 151.2 (302.4)   | 153.6 (307.2)   |
| DC OUTPUT             | *2 24V 6.3A (12.6A) | 36V 4.2A (8.4A) | 48V 3.2A (6.4A) |

## SPECIFICATIONS

|                               | MODEL                                |                                                                                     | LFP150F-24-Y                                                                                           | LFP150F-36-Y      | LFP150F-48-Y      |
|-------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-------------------|-------------------|
| INPUT                         | VOLTAGE[V]                           |                                                                                     | AC85 - 264 1 $\phi$ (Refer to Instruction Manual 1.1 and 3.2) *5                                       |                   |                   |
|                               | CURRENT[A]                           | ACIN 100V                                                                           | 2.0typ (Io=100%)                                                                                       |                   |                   |
|                               |                                      | ACIN 200V                                                                           | 1.0typ (Io=100%)                                                                                       |                   |                   |
|                               | FREQUENCY[Hz]                        |                                                                                     | 50 / 60 (47 - 63)                                                                                      |                   |                   |
|                               | EFFICIENCY[%]                        | ACIN 100V                                                                           | 85.5typ (Io=100%)                                                                                      | 85.5typ (Io=100%) | 85.5typ (Io=100%) |
|                               |                                      | ACIN 200V                                                                           | 88.0typ (Io=100%)                                                                                      | 88.0typ (Io=100%) | 88.0typ (Io=100%) |
|                               | POWER FACTOR                         | ACIN 100V                                                                           | 0.99typ (Io=100%)                                                                                      |                   |                   |
|                               |                                      | ACIN 200V                                                                           | 0.95typ (Io=100%)                                                                                      |                   |                   |
|                               | ACIN 100V                            | 15typ (Io=100%) (At cold start) (Ta=25℃)                                            |                                                                                                        |                   |                   |
|                               | ACIN 200V                            | 30typ (Io=100%) (At cold start) (Ta=25℃)                                            |                                                                                                        |                   |                   |
| LEAKAGE CURRENT[ma]           |                                      | 0.40 / 0.75max (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60950-1 and DEN-AN) |                                                                                                        |                   |                   |
| OUTPUT                        | VOLTAGE[V]                           |                                                                                     | 24                                                                                                     | 36                | 48                |
|                               | CURRENT[A]                           |                                                                                     | *2 6.3 (Peak 12.6)                                                                                     | 4.2 (Peak 8.4)    | 3.2 (Peak 6.4)    |
|                               | LINE REGULATION[mV]                  |                                                                                     | *7 96max                                                                                               | 144max            | 192max            |
|                               | LOAD REGULATION[mV]                  |                                                                                     | *7 150max                                                                                              | 240max            | 240max            |
|                               | RIPPLE[mVp-p]                        | *3 0 to +50℃                                                                        | 120max                                                                                                 | 150max            | 150max            |
|                               |                                      | -10 - 0℃                                                                            | 160max                                                                                                 | 200max            | 200max            |
|                               | RIPPLE NOISE[mVp-p]*3                | 0 to +50℃                                                                           | 150max                                                                                                 | 250max            | 250max            |
|                               |                                      | -10 - 0℃                                                                            | 180max                                                                                                 | 300max            | 300max            |
|                               | TEMPERATURE REGULATION[mV]           | 0 to +50℃                                                                           | 240max                                                                                                 | 360max            | 480max            |
|                               |                                      | -10 to +50℃                                                                         | 290max                                                                                                 | 450max            | 600max            |
|                               | DRIFT[mV]                            |                                                                                     | *4 96max                                                                                               | 144max            | 192max            |
|                               | START-UP TIME[ms]                    |                                                                                     | 350typ (ACIN 100V, Io=100%)                                                                            |                   |                   |
|                               | HOLD-UP TIME[ms]                     |                                                                                     | 20typ (ACIN 100V, Io=100%)                                                                             |                   |                   |
|                               | OUTPUT VOLTAGE ADJUSTMENT RANGE[V]   |                                                                                     | 21.60 to 27.50                                                                                         | 32.40 to 39.60    | 39.60 to 52.80    |
| OUTPUT VOLTAGE SETTING[V]     |                                      | 24.00 to 24.96                                                                      | 36.00 to 37.44                                                                                         | 48.00 to 49.92    |                   |
| PROTECTION CIRCUIT AND OTHERS | OVERCURRENT PROTECTION               |                                                                                     | Works over 101% of rating and recovers automatically                                                   |                   |                   |
|                               | OVERVOLTAGE PROTECTION[V]            |                                                                                     | 27.60 to 33.60                                                                                         | 41.40 to 50.40    | 55.20 to 67.20    |
|                               | OPERATING INDICATION                 |                                                                                     | Not provided                                                                                           |                   |                   |
|                               | REMOTE SENSING                       |                                                                                     | Not provided                                                                                           |                   |                   |
|                               | REMOTE ON/OFF                        |                                                                                     | Option (Refer to Instruction Manual 6)                                                                 |                   |                   |
|                               | INPUT-OUTPUT-RC                      |                                                                                     | *6 AC3,000V 1minute, Cutoff current = 10mA, DC500V 50M $\Omega$ min (At Room Temperature)              |                   |                   |
|                               | INPUT-FG                             |                                                                                     | AC2,000V 1minute, Cutoff current = 10mA, DC500V 50M $\Omega$ min (At Room Temperature)                 |                   |                   |
|                               | OUTPUT-RC-FG                         |                                                                                     | *6 AC500V 1minute, Cutoff current = 25mA, DC500V 50M $\Omega$ min (At Room Temperature)                |                   |                   |
| ISOLATION                     | OUTPUT-RC                            |                                                                                     | *6 AC100V 1minute, Cutoff current = 25mA, DC100V 10M $\Omega$ min (At Room Temperature)                |                   |                   |
|                               | OPERATING TEMP., HUMID. AND ALTITUDE |                                                                                     | *5 -10 to +70℃, 20 - 90%RH (Non condensing) (Refer to Instruction Manual 3.2), 3,000m (10,000feet) max |                   |                   |
|                               | STORAGE TEMP., HUMID. AND ALTITUDE   |                                                                                     | -20 to +75℃, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max                                      |                   |                   |
|                               | VIBRATION                            |                                                                                     | 10 - 55Hz, 19.6m/s <sup>2</sup> (2G), 3minutes period, 60minutes each along X, Y and Z axis            |                   |                   |
| ENVIRONMENT                   | IMPACT                               |                                                                                     | 196.1m/s <sup>2</sup> (20G), 11ms, once each X, Y and Z axis                                           |                   |                   |
|                               | AGENCY APPROVALS (AT ONIY AC input)  |                                                                                     | UL60950-1, C-UL (CSA60950-1), EN60950-1, EN50178 Complies with DEN-AN                                  |                   |                   |
|                               | CONDUCTED NOISE                      |                                                                                     | Complies with FCC-B, VCCI-B, CISPR22-B, EN55011-B, EN55022-B                                           |                   |                   |
|                               | HARMONIC ATTENUATOR                  |                                                                                     | Complies with IEC61000-3-2 (Class A) *8                                                                |                   |                   |
| SAFETY AND NOISE REGULATIONS  | CASE SIZE/WEIGHT                     |                                                                                     | 75 X 36.5 X 160mm [2.95 X 1.44 X 6.30 inches] (W X H X D) / 380g max (with chassis & cover : 610g max) |                   |                   |
|                               | COOLING METHOD                       |                                                                                     | Convection (Refer to Instruction Manual 3.1 and 3.2) *5                                                |                   |                   |
| OTHERS                        |                                      |                                                                                     |                                                                                                        |                   |                   |

\*1 Specification is changed at option, refer to Instruction Manual.

\*2 Peak loading for 10sec. And Duty 40% max, refer to Instruction Manual 5. In detail.

( ) means peak current. There is a possibility that an internal device is damaged when the specification is exceeded.

\*3 This is the value that measured on measuring board with capacitor of 22  $\mu$ F at 150mm from output terminal.

Measured by 20MHz oscilloscope or Ripple-Noise meter (Equivalent to KEISOKU-GIKEN: RM103).

\*4 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.

\*5 Derating is required.

\*6 Applicable when remote control (optional) is added.

\*7 Please contact us about dynamic load and input response.

\*8 Please contact us about another class.


\* To meet the specifications. Do not operate over-loaded condition.

\* Parallel operation is not possible.

\* Derating is required when operated with chassis and cover.


\* Sound noise may be generated by power supply in case of pulse load.

## Block diagram



## External view

※ External size of option is different from standard model.



- ※ 4 Mounting holes are existing.
- ※ The back side of P.C.B. of the power supply is assembled some SMDs.  
Be attention not to bump against the attached area by vibration.
- ※ Use the spacer of 8mm length or more regarding insulation.  
And do not use press-fitting bush.
- ※ Point A, Point B are thermometry points. Please refer to Instruction Manual 3.

| I/O Connector |             | Mating connector | Terminal |           |
|---------------|-------------|------------------|----------|-----------|
| CN1           | 1-1123724-3 | 1-1123722-5      | Chain    | 1123721-1 |
|               |             |                  | Loose    | 1318912-1 |
| CN2           | 1-1123723-6 | 1-1123722-6      | Chain    | 1123721-1 |
|               |             |                  | Loose    | 1318912-1 |
| CN3           | 1-1123723-7 | 1-1123722-7      | Chain    | 1123721-1 |
|               |             |                  | Loose    | 1318912-1 |

(Mfr:Tyco Electronics)

- ※ I/O Connector is Mfr. Tyco Electronics  
※ Option:-J1:VH(J.S.T) connector type.

### <PIN CONNECTION>

| Pin No. | Input |
|---------|-------|
| 1       | AC(L) |
| 2       |       |
| 3       | AC(N) |
| 4       |       |
| 5       | FG    |

| Pin No. | Output |
|---------|--------|
| 1 to 6  | +V     |

| Pin No. | Output |
|---------|--------|
| 1 to 7  | -V     |

- ※ Keep drawing current per pin below 5A for CN2,CN3.
- ※ Tolerance :  $\pm 1$  [ $\pm 0.04$ ]
- ※ Weight : 380g max (with chassis & cover : 610g max)
- ※ PCB material : CEM3
- ※ Optional chassis and cover material : Electric galvanizing steel board.
- ※ Dimensions in mm, [ ] =inches
- ※ Mounting torque (Mounting hole of chassis): 1.5N · m (16kaf · cm) max

## Connector type

| PIN No. | Contents |
|---------|----------|
| 1       | RC(+)    |
| 2       | RC(-)    |

## Barrier strip type

Model B2B-XH-A  
Mating Connector (Terminal)  
XHP-2  
( BXH-001T-P0.6  
or SXH-001T-P0.6 )

## LFP240F

LF

P

240

F

-

-

①



②

③

④

⑤

⑥

Recommended EMI/EMC Filter  
NAC-06-472High voltage pulse noise type : NAP series  
Low leakage current type : NAM series

- ① Series name  
② Single output  
③ Output wattage  
④ Universal input  
⑤ Output voltage  
⑥ Optional \*1  
C : with Coating  
G : Low leakage current  
J1 : VH(J.S.T.)connector type  
R : with Remote ON/OFF  
R2 : with Remote ON/OFF  
S : with Chassis  
SN : with Chassis & cover  
T : Vertical terminal block  
U1 : Can be attached the external capacitor unit

Please refer to Instruction manual 6.

This power supply is manufactured by SMD technology. The stress to P.C.B like twisting or bending causes the defect of the unit, so handle the unit with care.

| MODEL                 | LFP240F-24-Y                  | LFP240F-30-Y  | LFP240F-36-Y     | LFP240F-48-Y   |
|-----------------------|-------------------------------|---------------|------------------|----------------|
| MAX OUTPUT WATTAGE[W] | 300 (480)                     | 300 (480)     | 302.4 (482.4)    | 302.4 (480)    |
| DC OUTPUT             | Convection<br>24V 10A (20A)   | 30V 8A (16A)  | 36V 6.7A (13.4A) | 48V 5A (10A)   |
|                       | Forced air<br>24V 12.5A (20A) | 30V 10A (16A) | 36V 8.4A (13.4A) | 48V 6.3A (10A) |

## SPECIFICATIONS

|                                     | MODEL                                |                                    | LFP240F-24-Y                                                                                           | LFP240F-30-Y                  | LFP240F-36-Y      | LFP240F-48-Y      |        |
|-------------------------------------|--------------------------------------|------------------------------------|--------------------------------------------------------------------------------------------------------|-------------------------------|-------------------|-------------------|--------|
| INPUT                               | VOLTAGE[V]                           |                                    | AC85 - 264 1 φ (Refer to Instruction Manual 1.1 and 3.2) *5                                            |                               |                   |                   |        |
|                                     | CURRENT[A]                           | ACIN 100V                          | 3.6typ (Io=100%)                                                                                       |                               |                   |                   |        |
|                                     |                                      | ACIN 200V                          | 1.8typ (Io=100%)                                                                                       |                               |                   |                   |        |
|                                     | FREQUENCY[Hz]                        |                                    | 50 / 60 (47 - 63)                                                                                      |                               |                   |                   |        |
|                                     | EFFICIENCY[%]                        | ACIN 100V                          | 86.0typ (Io=100%)                                                                                      | 86.0typ (Io=100%)             | 86.0typ (Io=100%) | 86.0typ (Io=100%) |        |
|                                     |                                      | ACIN 200V                          | 88.5typ (Io=100%)                                                                                      | 88.5typ (Io=100%)             | 89.0typ (Io=100%) | 89.0typ (Io=100%) |        |
|                                     | POWER FACTOR                         | ACIN 100V                          | 0.99typ (Io=100%)                                                                                      |                               |                   |                   |        |
|                                     |                                      | ACIN 200V                          | 0.95typ (Io=100%)                                                                                      |                               |                   |                   |        |
|                                     | INRUSH CURRENT[A]                    | ACIN 100V                          | 15 / 30typ (Io=100%) (Primary inrush current /Secondary inrush current) (More than 3 sec. to re-start) |                               |                   |                   |        |
|                                     |                                      | ACIN 200V                          | 30 / 30typ (Io=100%) (Primary inrush current /Secondary inrush current) (More than 3 sec. to re-start) |                               |                   |                   |        |
|                                     |                                      | LEAKAGE CURRENT[ma]                | 0.40 / 0.75max (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60950-1 and DEN-AN)                    |                               |                   |                   |        |
| OUTPUT                              | VOLTAGE[V]                           |                                    | 24                                                                                                     | 30                            | 36                | 48                |        |
|                                     | CURRENT[A]                           | Convection *2                      | 10 (Peak 20)                                                                                           | 8 (Peak 16)                   | 6.7 (Peak 13.4)   | 5 (Peak 10)       |        |
|                                     |                                      | Forced air *2                      | 12.5 (Peak 20)                                                                                         | 10 (Peak 16)                  | 8.4 (Peak 13.4)   | 6.3 (Peak 10)     |        |
|                                     | LINE REGULATION[mV]                  |                                    | *7 96max                                                                                               | 144max                        | 144max            | 192max            |        |
|                                     | LOAD REGULATION[mV]                  |                                    | *7 150max                                                                                              | 240max                        | 240max            | 240max            |        |
|                                     | RIPPLE[mVp-p]                        | *3 0 to +50℃                       | 120max                                                                                                 | 150max                        | 150max            | 150max            |        |
|                                     |                                      | *3 -10 - 0℃                        | 160max                                                                                                 | 200max                        | 200max            | 200max            |        |
|                                     | RIPPLE NOISE[mVp-p]*3                | 0 to +50℃                          | 150max                                                                                                 | 250max                        | 250max            | 250max            |        |
|                                     |                                      | -10 - 0℃                           | 180max                                                                                                 | 300max                        | 300max            | 300max            |        |
|                                     | TEMPERATURE REGULATION[mV]           | 0 to +50℃                          | 240max                                                                                                 | 360max                        | 360max            | 480max            |        |
|                                     |                                      | -10 to +50℃                        | 290max                                                                                                 | 450max                        | 450max            | 600max            |        |
|                                     |                                      |                                    | DRIFT[mV]                                                                                              | *4 96max                      | 144max            | 144max            | 192max |
|                                     |                                      |                                    | START-UP TIME[ms]                                                                                      | 350typ (ACIN 100V, Io=100%)   |                   |                   |        |
|                                     |                                      |                                    | HOLD-UP TIME[ms]                                                                                       | *9 20typ (ACIN 100V, Io=100%) |                   |                   |        |
|                                     |                                      | OUTPUT VOLTAGE ADJUSTMENT RANGE[V] | 21.60 to 27.50                                                                                         | 27.00 to 33.00                | 32.40 to 39.60    | 39.60 to 52.80    |        |
|                                     |                                      | OUTPUT VOLTAGE SETTING[V]          | 24.00 to 24.96                                                                                         | 30.00 to 31.20                | 36.00 to 37.44    | 48.00 to 49.92    |        |
| PROTECTION<br>CIRCUIT AND<br>OTHERS | OVERCURRENT PROTECTION               |                                    | Works over 101% of rating and recovers automatically                                                   |                               |                   |                   |        |
|                                     | OVERVOLTAGE PROTECTION[V]            |                                    | 27.60 to 33.60                                                                                         | 34.50 to 42.00                | 41.40 to 50.40    | 55.20 to 67.20    |        |
|                                     | OPERATING INDICATION                 |                                    | Not provided                                                                                           |                               |                   |                   |        |
|                                     | REMOTE SENSING                       |                                    | Not provided                                                                                           |                               |                   |                   |        |
|                                     |                                      | REMOTE ON/OFF                      | Option (Refer to Instruction Manual 6)                                                                 |                               |                   |                   |        |
| ISOLATION                           | INPUT-OUTPUT-RC                      |                                    | *6 AC3,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature)                      |                               |                   |                   |        |
|                                     | INPUT-FG                             |                                    | AC2,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature)                         |                               |                   |                   |        |
|                                     | OUTPUT-RC-FG                         |                                    | *6 AC500V 1minute, Cutoff current = 25mA, DC500V 50MΩ min (At Room Temperature)                        |                               |                   |                   |        |
|                                     | OUTPUT-RC                            |                                    | *6 AC100V 1minute, Cutoff current = 25mA, DC100V 10MΩ min (At Room Temperature)                        |                               |                   |                   |        |
| ENVIRONMENT                         | OPERATING TEMP., HUMID. AND ALTITUDE |                                    | *5 -10 to +70℃, 20 - 90%RH (Non condensing) (Refer to Instruction Manual 3.2), 3,000m (10,000feet) max |                               |                   |                   |        |
|                                     | STORAGE TEMP., HUMID. AND ALTITUDE   |                                    | -20 to +75℃, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max                                      |                               |                   |                   |        |
|                                     | VIBRATION                            |                                    | 10 - 55Hz, 19.6m/s² (2G), 3minutes period, 60minutes each along X, Y and Z axis                        |                               |                   |                   |        |
|                                     |                                      | IMPACT                             | 196.1m/s² (20G), 11ms, once each X, Y and Z axis                                                       |                               |                   |                   |        |
| SAFETY AND<br>NOISE<br>REGULATIONS  | AGENCY APPROVALS (AT ONIY AC input)  |                                    | UL60950-1, C-UL (CSA60950-1), EN60950-1, EN50178 Complies with DEN-AN                                  |                               |                   |                   |        |
|                                     | CONDUCTED NOISE                      |                                    | Complies with FCC-B, VCCI-B, CISPR22-B, EN55011-B, EN55022-B                                           |                               |                   |                   |        |
|                                     | HARMONIC ATTENUATOR                  |                                    | Complies with IEC61000-3-2 (Class A) *8                                                                |                               |                   |                   |        |
| OTHERS                              | CASE SIZE/WEIGHT                     |                                    | 84 X 46 X 180mm [3.31 X 1.81 X 7.09 inches] (W X H X D) / 540g max (with chassis & cover : 860g max)   |                               |                   |                   |        |
|                                     | COOLING METHOD                       |                                    | Convection / Forced air (Refer to Instruction Manual 3.1 and 3.2) *5                                   |                               |                   |                   |        |

\*1 Specification is changed at option, refer to Instruction Manual.

\*2 Peak loading for 10sec. And Duty 40% max, refer to Instruction Manual 5. In detail.

( ) means peak current. There is a possibility that an internal device is damaged when the specification is exceeded.

\*3 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.

Measured by 20MHz oscilloscope or Ripple-Noise meter (Equivalent to KEISOKU-GIKEN: RM103).

\*4 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.

\*5 Derating is required.

\*6 Applicable when remote control (optional) is added.

\*7 Please contact us about dynamic load and input response.

\*8 Please contact us about another class.

\*9 By attaching an external capacitor unit, it is possible to extend the hold-up time.


\* To meet the specifications. Do not operate over-loaded condition.

\* Parallel operation is not possible.

\* Derating is required when operated with chassis and cover.

\* Sound noise may be generated by power supply in case of pulse load.


## Block diagram



## External view

※ External size of option is different from standard model.

Standard type




- ※ 5 Mounting holes are existing.
- ※ The back side of P.C.B. of the power supply is assembled some SMDs.  
Be attention not to bump against the attached area by vibration.
- ※ Use the spacer of 8mm length or more regarding insulation.  
And do not use press-fitting bush.
- ※ Point A, Point B, Point C are thermometry points. Please refer to Instruction Manual 3.

| I/O Connector   | Mating connector | Terminal                           |
|-----------------|------------------|------------------------------------|
| CN1 1-1123724-3 | 1-1123722-5      | Chain 1123721-1<br>Loose 1318912-1 |
| CN2 1-1123723-6 | 1-1123722-6      | Chain 1123721-1<br>Loose 1318912-1 |
| CN3 1-1123723-7 | 1-1123722-7      | Chain 1123721-1<br>Loose 1318912-1 |

(Mfr:Tyco Electronics)

- ※ I/O Connector is Mfr. Tyco Electronics
- ※ Option:-J1:VH(J.S.T) connector type.

Chassis and cover type



## &lt;PIN CONNECTION&gt;

| CN1     | CN2     | CN3     |
|---------|---------|---------|
| Pin No. | Pin No. | Pin No. |
| 1       | 1 to 6  | 1 to 7  |
| 2       |         |         |
| 3       |         |         |
| 4       |         |         |
| 5       |         |         |
| Input   | Output  | Output  |
| AC(L)   | +V      | -V      |
| AC(N)   |         |         |
| FG      |         |         |

※ Keep drawing current per pin below 5A for CN2,CN3.

- ※ Tolerance :  $\pm 1$  [ $\pm 0.04$ ]
- ※ Weight : 540g max (with chassis & cover : 860g max)
- ※ PCB material : CEM3
- ※ Optional chassis and cover material : Electric galvanizing steel board.
- ※ Dimensions in mm, [ ]=inches
- ※ Mounting torque (Mounting hole of chassis) :1.5N · m (16kgf · cm) max

## Connector type

CN4 Option (Mfr:J.S.T)

| PIN No. | Contents |
|---------|----------|
| 1       | RC(+)    |
| 2       | RC(-)    |

## Barrier strip type

Model B2B-XH-A  
Mating Connector (Terminal)  
XHP-2  
(BXH-001T-P0.6  
or SXH-001T-P0.6)


## LFP300F

LF P 300 F -□ -□

① ② ③ ④ ⑤ ⑥



RoHS

Recommended EMI/EMC Filter  
NAC-06-472High voltage pulse noise type : NAP series  
Low leakage current type : NAM series

- ① Series name  
② Single output  
③ Output wattage  
④ Universal input  
⑤ Output voltage  
⑥ Optional \*1  
C : with Coating  
G : Low leakage current  
J : EP (Tyco Electronics) connector type  
J1 : VH (J.S.T.) connector type  
R : with Remote ON/OFF  
R2 : with Remote ON/OFF  
S : with Chassis  
SN : with Chassis & cover  
SNF : with Chassis & cover & fan (Only 24V)  
T1 : Horizontal terminal block  
U1 : Can be attached the external capacitor unit

Please refer to Instruction manual 6.

This power supply is manufactured by SMD technology. The stress to P.C.B like twisting or bending causes the defect of the unit, so handle the unit with care.

| MODEL                 |            | LFP300F-24-TY   | LFP300F-30-TY | LFP300F-36-TY    | LFP300F-48-TY    |
|-----------------------|------------|-----------------|---------------|------------------|------------------|
| MAX OUTPUT WATTAGE[W] | *2         | 360 (600)       | 360 (600)     | 360 (604.8)      | 360 (604.8)      |
| DC OUTPUT             | Convection | 24V 12.5A (25A) | 30V 10A (20A) | 36V 8.4A (16.8A) | 48V 6.3A (12.6A) |
|                       | Forced air | 24V 15A (25A)   | 30V 12A (20A) | 36V 10A (16.8A)  | 48V 7.5A (12.6A) |

## SPECIFICATIONS

|                                     | MODEL                                |                                                                                                        | LFP300F-24-TY                                                                                                         | LFP300F-30-TY           | LFP300F-36-TY              | LFP300F-48-TY              |
|-------------------------------------|--------------------------------------|--------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|-------------------------|----------------------------|----------------------------|
| INPUT                               | VOLTAGE[V]                           |                                                                                                        | AC85 - 264 1 φ (Refer to Instruction Manual 1.1 and 3.2) *5                                                           |                         |                            |                            |
|                                     | CURRENT[A]                           | ACIN 100V                                                                                              | 4.3typ (Io=100%)                                                                                                      |                         |                            |                            |
|                                     |                                      | ACIN 200V                                                                                              | 2.2typ (Io=100%)                                                                                                      |                         |                            |                            |
|                                     | FREQUENCY[Hz]                        |                                                                                                        | 50 / 60 (47 - 63)                                                                                                     |                         |                            |                            |
|                                     | EFFICIENCY[%]                        | ACIN 100V                                                                                              | 85.0typ (Io=100%)                                                                                                     | 85.5typ (Io=100%)       | 85.5typ (Io=100%)          | 85.5typ (Io=100%)          |
|                                     |                                      | ACIN 200V                                                                                              | 88.0typ (Io=100%)                                                                                                     | 88.0typ (Io=100%)       | 88.0typ (Io=100%)          | 88.0typ (Io=100%)          |
|                                     | POWER FACTOR                         | ACIN 100V                                                                                              | 0.99typ (Io=100%)                                                                                                     |                         |                            |                            |
|                                     |                                      | ACIN 200V                                                                                              | 0.95typ (Io=100%)                                                                                                     |                         |                            |                            |
| INRUSH CURRENT[A]                   | ACIN 100V                            | 15 / 30typ (Io=100%) (Primary inrush current /Secondary inrush current) (More than 3 sec. to re-start) |                                                                                                                       |                         |                            |                            |
|                                     | ACIN 200V                            | 30 / 30typ (Io=100%) (Primary inrush current /Secondary inrush current) (More than 3 sec. to re-start) |                                                                                                                       |                         |                            |                            |
| LEAKAGE CURRENT[mA]                 |                                      | 0.45 / 0.75max (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60950-1 and DEN-AN)                    |                                                                                                                       |                         |                            |                            |
| OUTPUT                              | VOLTAGE[V]                           |                                                                                                        | 24                                                                                                                    | 30                      | 36                         | 48                         |
|                                     | CURRENT[A]                           | ACIN 100V *2                                                                                           | 12.5 (Peak 22) Convection                                                                                             | 10 (Peak 18) Convection | 8.4 (Peak 14.6) Convection | 6.3 (Peak 11) Convection   |
|                                     |                                      |                                                                                                        | 15 (Peak 22) Forced air                                                                                               | 12 (Peak 18) Forced air | 10 (Peak 14.6) Forced air  | 7.5 (Peak 11) Forced air   |
|                                     |                                      | ACIN 200V *2                                                                                           | 12.5 (Peak 25) Convection                                                                                             | 10 (Peak 20) Convection | 8.4 (Peak 16.8) Convection | 6.3 (Peak 12.6) Convection |
|                                     |                                      |                                                                                                        | 15 (Peak 25) Forced air                                                                                               | 12 (Peak 20) Forced air | 10 (Peak 16.8) Forced air  | 7.5 (Peak 12.6) Forced air |
|                                     | LINE REGULATION[mV]                  |                                                                                                        | *7 96max                                                                                                              | 144max                  | 144max                     | 192max                     |
|                                     | LOAD REGULATION[mV]                  |                                                                                                        | *7 150max                                                                                                             | 240max                  | 240max                     | 240max                     |
|                                     | RIPPLE[mVp-p]                        | *3 0 to +40℃                                                                                           | 120max                                                                                                                | 150max                  | 150max                     | 150max                     |
|                                     |                                      |                                                                                                        | -10 - 0℃                                                                                                              | 160max                  | 200max                     | 200max                     |
|                                     | RIPPLE NOISE[mVp-p]*3                | 0 to +40℃                                                                                              | 150max                                                                                                                | 250max                  | 250max                     | 250max                     |
|                                     |                                      |                                                                                                        | -10 - 0℃                                                                                                              | 180max                  | 300max                     | 300max                     |
|                                     | TEMPERATURE REGULATION[mV]           | 0 to +40℃                                                                                              | 240max                                                                                                                | 360max                  | 360max                     | 480max                     |
|                                     |                                      |                                                                                                        | -10 to +40℃                                                                                                           | 290max                  | 450max                     | 450max                     |
|                                     | DRIFT[mV]                            |                                                                                                        | *4 96max                                                                                                              | 144max                  | 144max                     | 192max                     |
|                                     | START-UP TIME[ms]                    |                                                                                                        | 350typ (ACIN 100V, Io=100%)                                                                                           |                         |                            |                            |
|                                     | HOLD-UP TIME[ms]                     |                                                                                                        | *9 20typ (ACIN 100V, Io=100%)                                                                                         |                         |                            |                            |
|                                     | OUTPUT VOLTAGE ADJUSTMENT RANGE[V]   |                                                                                                        | 21.60 to 27.50                                                                                                        | 27.00 to 33.00          | 32.40 to 39.60             | 39.60 to 52.80             |
| OUTPUT VOLTAGE SETTING[V]           |                                      | 24.00 to 24.96                                                                                         | 30.00 to 31.20                                                                                                        | 36.00 to 37.44          | 48.00 to 49.92             |                            |
| PROTECTION<br>CIRCUIT AND<br>OTHERS | OVERCURRENT PROTECTION               |                                                                                                        | Works over 101% of rating and recovers automatically                                                                  |                         |                            |                            |
|                                     | OVERVOLTAGE PROTECTION[V]            |                                                                                                        | 27.60 to 33.60                                                                                                        | 34.50 to 42.00          | 41.40 to 50.40             | 55.20 to 67.20             |
|                                     | OPERATING INDICATION                 |                                                                                                        | Not provided                                                                                                          |                         |                            |                            |
|                                     | REMOTE SENSING                       |                                                                                                        | Not provided                                                                                                          |                         |                            |                            |
| REMOTE ON/OFF                       |                                      | Option (Refer to Instruction Manual 6)                                                                 |                                                                                                                       |                         |                            |                            |
| ISOLATION                           | INPUT-OUTPUT-RC                      |                                                                                                        | *6 AC3,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature)                                     |                         |                            |                            |
|                                     | INPUT-FG                             |                                                                                                        | AC2,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature)                                        |                         |                            |                            |
|                                     | OUTPUT-RC-FG                         |                                                                                                        | *6 AC500V 1minute, Cutoff current = 25mA, DC500V 50MΩ min (At Room Temperature)                                       |                         |                            |                            |
|                                     | OUTPUT-RC                            |                                                                                                        | *6 AC100V 1minute, Cutoff current = 25mA, DC100V 10MΩ min (At Room Temperature)                                       |                         |                            |                            |
| ENVIRONMENT                         | OPERATING TEMP., HUMID. AND ALTITUDE |                                                                                                        | *5 -10 to +70℃, 20 - 90%RH (Non condensing) (Refer to Instruction Manual 3.2), 3,000m (10,000feet) max                |                         |                            |                            |
|                                     | STORAGE TEMP., HUMID. AND ALTITUDE   |                                                                                                        | -20 to +75℃, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max                                                     |                         |                            |                            |
|                                     | VIBRATION                            |                                                                                                        | 10 - 55Hz, 19.6m/s <sup>2</sup> (2G), 3minutes period, 60minutes each along X, Y and Z axis                           |                         |                            |                            |
| SAFETY AND<br>NOISE<br>REGULATIONS  | IMPACT                               |                                                                                                        | 196.1m/s <sup>2</sup> (20G), 11ms, once each X, Y and Z axis                                                          |                         |                            |                            |
|                                     | AGENCY APPROVALS (AT ONLY AC input)  |                                                                                                        | UL60950-1, C-UL (CSA60950-1), EN60950-1, EN50178 Complies with DEN-AN                                                 |                         |                            |                            |
|                                     | CONDUCTED NOISE                      |                                                                                                        | Complies with FCC-B, VCCI-B, CISPR22-B, EN55011-B, EN55022-B                                                          |                         |                            |                            |
| OTHERS                              | HARMONIC ATTENUATOR                  |                                                                                                        | Complies with IEC61000-3-2 (Class A) *8                                                                               |                         |                            |                            |
|                                     | CASE SIZE/WEIGHT                     |                                                                                                        | 95×52.5×222mm [3.74×2.07×8.74 inches] (W×H×D) (without terminal block) / 810g max (with chassis & cover : 1,270g max) |                         |                            |                            |
|                                     | COOLING METHOD                       |                                                                                                        | Convection / Forced air (Refer to Instruction Manual 3.1 and 3.2) *5                                                  |                         |                            |                            |

\*1 Specification is changed at option, refer to Instruction Manual.

\*2 Peak loading for 10sec. And Duty 40% max, refer to Instruction Manual 5. In detail.

( ) means peak current. There is a possibility that an internal device is damaged when the specification is exceeded.

\*3 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.

Measured by 20MHz oscilloscope or Ripple-Noise meter (Equivalent to KEISOKU-GIKEN: RM103).

\*4 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.

\*5 Derating is required.

\*6 Applicable when remote control (optional) is added.

\*7 Please contact us about dynamic load and input response.

\*8 Please contact us about another class.

\*9 By attaching an external capacitor unit, it is possible to extend the hold-up time.


\* To meet the specifications. Do not operate over-loaded condition.

\* Parallel operation is not possible.

\* Derating is required when operated with chassis and cover.

\* Sound noise may be generated by power supply in case of pulse load.


## Block diagram



## External view

※ External size of option is different from standard model.

|               |
|---------------|
| Standard type |
|---------------|



- ※ 5 Mounting holes are existing.
- ※ The back side of P.C.B. of the power supply is assembled some SMDs.  
Be attention not to bump against the attached area by vibration.
- ※ Use the spacer of 8mm length or more regarding insulation.  
And do not use press-fitting bush.
- ※ Point A, Point B, Point C, Point D are thermometry points.  
Please refer to Instruction Manual 3.
- ※ Keep drawing current per pin below 20A for TB2.

- ※ Tolerance :  $\pm 1$  [ $\pm 0.04$ ]
- ※ Weight : 810g max (with chassis & cover : 1,270g max)
- ※ PCB material : CEM3
- ※ Dimensions in mm, [ ]=inches
- ※ Screw tightening torque : M4 1.6N · m (16.9kgf · cm) max

| Connector type |
|----------------|
|----------------|

CN4 Option (Mfr:J.S.T)

| PIN No. | Contents |
|---------|----------|
| 1       | RC(+)    |
| 2       | RC(-)    |

## Barrier strip type

Model B2B-XH-A  
Mating Connector (Terminal)  
XHP-2  
( BXH-001T-P0.6  
or SXH-001T-P0.6 )

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Cosel:

[LFP150F-36-SNY](#) [LFP240F-30-Y](#) [LFP100F-36-SY](#) [LFP240F-24-TY](#) [LFP240F-48-R2Y](#) [LFP100F-48-GY](#) [LFP100F-24-RY](#) [LFP150F-48-Y](#) [LFP150F-24-R2Y](#) [LFP100F-36-J1Y](#) [LFP240F-48-SY](#) [LFP150F-24-SY](#) [LFP240F-30-RY](#) [LFP240F-30-GY](#) [LFP100F-48-RY](#) [LFP240F-36-J1Y](#) [LFP100F-36-SNY](#) [LFP150F-48-R2Y](#) [LFP150F-36-GY](#) [LFP240F-36-Y](#) [LFP150F-48-CY](#) [LFP240F-48-J1Y](#) [LFP240F-24-SY](#) [LFP150F-36-RY](#) [LFP100F-48-Y](#) [LFP100F-24-SY](#) [LFP150F-24-J1Y](#) [LFP240F-24-CY](#) [LFP150F-24-SNY](#) [LFP150F-36-Y](#) [LFP240F-36-GY](#) [LFP240F-30-CY](#) [LFP240F-36-TY](#) [LFP150F-48-J1Y](#) [LFP150F-36-R2Y](#) [LFP240F-30-R2Y](#) [LFP240F-24-SNY](#) [LFP150F-48-GY](#) [LFP240F-48-RY](#) [LFP150F-24-RY](#) [LFP240F-48-TY](#) [LFP150F-24-CY](#) [LFP100F-24-J1Y](#) [LFP100F-36-GY](#) [LFP240F-48-SNY](#) [LFP100F-48-R2Y](#) [LFP240F-36-CY](#) [LFP240F-30-SY](#) [LFP100F-36-Y](#) [LFP240F-24](#) [LFP150F-48-RY](#) [LFP100F-48-SNY](#) [LFP240F-30-SNY](#) [LFP240F-24-R2Y](#) [LFP150F-48-SY](#) [LFP240F-30-TY](#) [LFP150F-36-CY](#) [LFP240F-24-J1Y](#) [LFP240F-48-Y](#) [LFP150F-48-SNY](#) [LFP150F-24-GY](#) [LFP240F-36-R2Y](#) [LFP240F-24-Y](#) [LFP150F-24-Y](#) [LFP240F-36-SY](#) [LFP100F-36-R2Y](#) [LFP240F-48-CY](#) [LFP100F-24-Y](#) [LFP100F-24-CY](#) [LFP240F-36-SNY](#) [LFP240F-24-GY](#) [LFP100F-24-R2Y](#) [LFP100F-48-CY](#) [LFP100F-48-SY](#) [LFP240F-36-RY](#) [LFP100F-36-RY](#) [LFP100F-24-SNY](#) [LFP240F-48-GY](#) [LFP100F-48-J1Y](#) [LFP240F-30-J1Y](#) [LFP240F-24-J1RY](#) [LFP100F-36-CY](#) [LFP150F-36-SY](#) [LFP100F-24-GY](#) [LFP150F-36-J1Y](#) [LFP240F-24-RY](#)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9