


High Voltage Ceramic Disc Capacitors 10 kVDC & 15 kVDC

Fig. 1



LEAD OFFSET 'LO'	
10 kVDC series NOMINAL	0.20 (5.0 mm)
15 kVDC series NOMINAL	0.30 (7.6 mm)

INSULATION RESISTANCE:

min. 1000 Ω F or 200 000 M Ω

TOLERANCE ON CAPACITANCE:

$\pm 20\%$; +80 - 20%

DISSIPATION FACTOR:

0.2 % max. at 1 kHz; 1V (Class 1)
2.0 % max. at 1 kHz; 1V (Class 2)

CATEGORY TEMPERATURE RANGE:

(- 25 to + 85) °C

CLIMATIC CATEGORY ACC. TO EN60068-1:

25/085/21

OPERATING TEMPERATURE RANGE:

(- 25 to + 105) °C

FEATURES

- Low losses
- High capacitance in small size
- High stability



RoHS
COMPLIANT

APPLICATIONS

- TV & Monitors
- SMPS
- DC and Pulse High voltage
- X-Ray Equipment

DESIGN

The capacitors consist of a ceramic disc of which both sides are silver-plated. Connection leads are made of tinned copper having diameters of 0.032" (0.81 mm).

The capacitors may be supplied with straight leads having lead spacing of 0.375 (9.5 mm), 0.500" (12.7 mm) or 0.750" (10.1 mm)

The standard tolerances are $\pm 20\%$ or +80 - 20%.

Coating is made of flame retardant epoxy resin in accordance with "UL94V-0".

CAPACITANCE RANGE:

100 pF to 3300 pF

DIELECTRIC STRENGTH BETWEEN LEADS:

10 kVDC 15 000 VDC, 2 s
15 kVDC 24 000 VDC, 2 s
(in dielectric fluid)

CERAMIC DIELECTRIC:

T3M (Class 1)
X5F, Y5R, Y5U, Z5U (Class 2)

ORDERING INFORMATION, CERAMIC 10 kVDC								
C (pF)	TOL. (%)	D DIAMETER INCH (mm)	T THICKNESS INCH (mm)	LS LEAD SPACE	WIRE SIZE		ORDERING CODE	
					AWG	INCH (mm)		
T3M (N4700)								
250	± 20 %	0.490 (12.4)	0.290 (7.4)	0.375 (9.5)	20	0.032 (0.81)	615R100GATT25	
500		0.680 (17.3)	0.320 (8.1)	0.500 (12.7)			615R100GATT50	
680		0.750 (19.1)	0.300 (7.6)				615R100GATT68	
820		0.810 (20.6)	0.320 (8.1)				615R100GATT82	
1000		0.980 (24.9)	0.320 (8.1)	615R100GATD10				
X5F								
100	± 20 %	0.680 (17.3)	0.370 (9.4)	0.500 (12.7)	20	0.032 (0.81)	615R100GAT10	
250			0.300 (7.6)				615R100GAT25	
500			0.345 (8.8)				615R100GAT50	
Y5R								
100	± 20 %	0.490 (12.4)	0.330 (7.4)	0.375 (9.5)	20	0.032 (0.81)	615R100GAST10	
250			0.340 (8.6)				615R100GAST25	
500			0.310 (7.9)				615R100GAST50	
1000			0.750 (19.1)	0.320 (8.1)			0.500 (12.7)	615R100GAD10
2500			0.980 (24.9)	0.330 (7.4)				615R100GATD25
Y5U								
1000	+ 80/- 20 %	0.680 (17.3)	0.330 (7.4)	0.500 (12.7)	20	0.032 (0.81)	615R100GASD10	
Z5U								
2500	+ 80/- 20 %	0.750 (19.1)	0.350 (8.9)	0.500 (12.7)	20	0.032 (0.81)	615R100GAD25	
3300		0.980 (24.9)	0.390 (9.9)				615R100GAD33	

ORDERING INFORMATION, CERAMIC 15 kVDC								
C (pF)	TOL. (%)	D DIAMETER INCH (mm)	T THICKNESS INCH (mm)	LS LEAD SPACE	WIRE SIZE		ORDERING CODE	
					AWG	INCH (mm)		
T3M (N4700)								
100	± 20 %	0.490 (12.4)	0.470 (11.9)	0.500 (12.7)	20	0.032 (0.81)	615R150GATT10	
250		0.670 (17.0)	0.430 (10.9)	0.750 (19.1)			615R150GATT25	
390		0.750 (19.1)	0.425 (10.8)				615R150GATT39	
500		0.810 (20.6)	0.410 (10.4)				615R150GATT50	
750		0.980 (24.9)	0.350 (8.9)	615R150GATT75				
X5F								
100	± 20 %	0.670 (17.0)	0.430 (10.9)	0.750 (19.1)	20	0.032 (0.81)	615R150GAT10	
250			0.455 (11.6)				615R150GAT25	
Y5R								
100	± 20 %	0.490 (12.4)	0.490 (12.4)	0.500 (12.7)	20	0.032 (0.81)	615R150GAST10	
250			0.480 (12.2)				615R150GAST25	
500			0.670 (17.0)	0.430 (10.9)			0.750 (19.1)	615R150GAT50
1000			0.980 (24.9)	0.460 (11.7)				615R150GATD10
Y5U								
500	+ 80/- 20 %	0.490 (12.4)	0.375 (9.5)	0.500 (12.7)	20	0.032 (0.81)	615R150GAST50	
1000		0.670 (17.0)	0.420 (10.7)	0.750 (19.1)			615R150GAD10	
Z5U								
2200	+ 80/- 20 %	0.980 (24.9)	0.510 (13.0)	0.750 (19.1)	20	0.032 (0.81)	615R150GAD22	
2500			0.450 (11.4)				615R150GAD25	



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9