





REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
D		REV PER ECR-09-024937	12NOV2009	DZ	SY
E		ECO-15-006810	22JAN2016	LL	SH



ATCA PANEL AND
PRINTED CIRCUIT BOARD
ASSEMBLY LAYOUT



AMC PANEL AND
PRINTED CIRCUIT BOARD
ASSEMBLY LAYOUT

1. MATERIAL:
HOUSING:
PBT POLYESTER, BLACK, UL 94V-0
TERMINALS:
0.33 THICK PHOSPHOR BRONZE PLATED WITH 1.27µm MINIMUM THICK
HARD GOLD IN LOCALIZED AREA AND 2.0µm MINIMUM THICK
MATTE TIN IN COMPLIANT PIN TERMINAL AREA
OVER 1.27µm MINIMUM THICK NICKEL UNDERPLATE

SHIELD:
0.25 THICK COPPER ALLOY PLATED WITH 2.03µm MINIMUM TIN
OVER 1.27 µm MINIMUM NICKEL

GROUND CLIP: 0.25 THICK COPPER ALLOY PRE-PLATED WITH 2.03µm
MINIMUM MATTE TIN OVER 1.27µm MINIMUM NICKEL

LIGHT EMITTING DIODE (LED):
DIFFUSED EPOXY LENS, 12.95 CARBON STEEL WIREFRAME LEADS
PREPLATED WITH 8.89µm THICK Sn/Cu OVER 2.03µm THICK Ag
OVER 1.02µm THICK Cu OVER 3.56µm THICK Ni OVER
1.02µm THICK Cu UNDERPLATE


LED COMPLIANT PIN CONTACTS:
0.3 THICK BRASS PLATED WITH 2µm MINIMUM MATTE TIN OVER
1.27µm MINIMUM NICKEL UNDERPLATE.

2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS, PART 68
SUBPART F.

- 3 MAXIMUM PIN LENGTH 3.40 FROM TOP SURFACE OF PC BOARD
4 FINISHED PLATED THROUGH HOLE DIAMETER - ANNULAR RING
DIAMETER 1.3 TO 1.5
5 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
6 DATE CODE LOCATED ON REAR OF PART APPROXIMATELY AS SHOWN
7 CONTACTS ARE NOT INTENDED TO BE ALIGNED WITH EACH OTHER
8 SUGGESTED OPERATING CURRENT FOR LEDS IS 20mA


15.88	GREEN/YELLOW	GREEN/YELLOW	GREEN/YELLOW	GREEN/YELLOW	YES	WITH GROUND CLIP	1888655-7
16.13	YELLOW	YELLOW	GREEN/YELLOW	GREEN/YELLOW	YES	WITHOUT GROUND CLIP	1888655-6
16.13	YELLOW	YELLOW	GREEN	GREEN	YES	WITHOUT GROUND CLIP	1888655-5
15.88	GREEN	GREEN	GREEN	GREEN	NO	WITH GROUND CLIP	1888655-4
15.88	GREEN	GREEN	GREEN	GREEN	YES	WITH GROUND CLIP	1888655-3 (SHOWN)
16.13	GREEN	GREEN	GREEN	GREEN	YES	WITHOUT GROUND CLIP	1888655-2
16.13	GREEN	GREEN	GREEN	GREEN	NO	WITHOUT GROUND CLIP	1888655-1
M DIM	LED #4 (LOWER-RIGHT)	LED #3 (UPPER-RIGHT)	LED #2 (UPPER-LEFT)	LED #1 (LOWER-LEFT)	SHIELD SIDE ACTION PIN	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L.A.MAYER 31OCT2006	NAME STACKED MODULAR JACK ASSEMBLY, 2 X 8, 8 POSN, SHIELDED, PANEL GROUND, OFFSET, CAT 5	SIZE A1	CAGE CODE 00779	DRAWING NO 1888655	RESTRICTED TO -
DIMENSIONS:		CHK J.WESTMAN 31OCT2006					
mm		APVD S.FLICKINGER 31OCT2006					
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC 108-1854					
0 PLC ± 1 PLC ±0.13 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±1° FINISH -		APPLICATION SPEC 114-2160					
MATERIAL SEE NOTE 1		WEIGHT -					
		CUSTOMER DRAWING					
		SCALE 3:1					
		SHEET 1					
		OF 2					
		REV E					




AMC PANEL AND PRINTED CIRCUIT BOARD LAYOUT

SCALE 2:1



PC BOARD LAYOUT (COMPONENT SIDE

THIS DRAWING IS A CONTROLLED DOCUMENT.										
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWG. L.A. MAYER 310CT2006		 TE Connectivity				
				CHK. WESTMAN 310CT2006						
		0 PLC ±: 1 PLC ±: .10 2 PLC ±: .10 3 PLC ±: .10 4 PLC ±: .1 ANGLES ±: .1		APPROV. S. FLICKINGER 310CT2006		NAME				
				PRODUCT SPEC		STACKED MODULAR JACK ASSEMBLY, 2 X 8, 8 POSN, SHIELDED, PANEL GROUND, OFFSET, CAT 5				
				108-1854						
				APPLICATION SPEC						
				114-2160						
MATERIAL		FINISH		WEIGHT -		SIZE A1		CASE CODE 00779	DRAWING NO. C=1888655	RESTRICTED TO -
SEE NOTE 1						CUSTOMER DRAWING		SCALE 2:1	SHEET 2 OF 2	REV E

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9