

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0736443203](#)
Status: **Active**
Overview: [hdm](#)
Description: 2.00mm (.079") Pitch HDM® Board-to-Board Backplane Header, Vertical, SMC, Press-Fit, Guide Post Location A, Polarizing Key Position B, 144 Circuits

Documents:

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification


CSA LR19980
UL E29179

General

Product Family Backplane Connectors
Series [73644](#)
Application Backplane
Comments Standard Press-Fit, Tin/Lead (SnPb)
Component Type PCB Header
Overview [hdm](#)
Product Name HDM®
Style N/A

Physical

Circuits (Loaded) 144
Circuits (maximum) 144
Color - Resin Black, Natural
Durability (mating cycles max) 250
First Mate / Last Break No
Flammability 94V-0
Guide to Mating Part Yes
Keying to Mating Part Yes
Material - Metal Phosphor Bronze, Stainless Steel
Material - Plating Mating Gold
Material - Plating Termination Tin
Material - Resin High Temperature Thermoplastic
Number of Columns 24
Number of Pairs Open Pin Field
Number of Rows 6
Orientation Vertical
PC Tail Length (in) 0.138 In
PC Tail Length (mm) 3.50 mm
PCB Locator No
PCB Retention Yes
PCB Thickness Recommended (in) 0.098 In
PCB Thickness Recommended (mm) 2.50 mm
Packaging Type Tube
Pitch - Mating Interface (in) 0.079 In
Pitch - Mating Interface (mm) 2.00 mm
Pitch - Term. Interface (in) 0.079 In
Pitch - Term. Interface (mm) 2.00 mm
Plating min: Mating (µin) 30
Plating min: Mating (µm) 0.75
Plating min: Termination (µin) 15
Plating min: Termination (µm) 0.375
Polarized to PCB No



Series

image - Reference only

EU RoHS

RoHS Compliant by Exemption

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Halogen-Free

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[73644Series](#)

Mates With

[73632](#) HDM PLUS® Board-to-Board Daughtercard Receptacle. [73780](#) HDM® Board-to-Board Daughtercard Receptacle

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Flat Rock Tooling for Pneumatic Press	0622013700
HDM® Backplane Insertion Signal Contact Tool	0621001400
HDM® Backplane Insertion Head for 144 Positions	0622005703



Stackable	No	Extraction Tool	0621001000
Surface Mount Compatible (SMC)	Yes		
Temperature Range - Operating	-55°C to +105°C		
Termination Interface: Style	Through Hole - Compliant Pin		
Electrical			
Current - Maximum per Contact	1A		
Data Rate	1.0 Gbps		
Real Signals (per 25mm)	75		
Shielded	No		
Voltage - Maximum	250V AC		
Material Info			
Reference - Drawing Numbers			
Packaging Specification	PK-70873-0818		
Sales Drawing	SDA-73644-****		
HDM and High Density Metric are trademarks of Amphenol Corporation			

This document was generated on 05/14/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

NOTES:

1. MATERIALS: HOUSING - LIQUID CRYSTAL POLYMER (LCP), GLASS-FILLED, UL94V-0, COLOR: BLACK, TERMINAL - PHOSPHOR BRONZE.
2. FINISHES: SELECTIVE GOLD (Au) IN CONTACT AREA, 0.00076mm MINIMUM THICKNESS; NICKEL (Ni) AND GOLD FLASH OVERALL SELECTIVE GOLD (Au) IN CONTACT AREA, 0.00076mm MIN. THICKNESS; SELECTIVE TIN/LEAD (Sb/Pb) IN TAIL AREA; NICKEL (Ni) OVERALL.
3. THIS PART CONFORMS TO MOLEX PRODUCT SPECIFICATION PS-73670-9999.
4. FOR MIXED CONTACT MATING LENGTHS, CONSULT FACTORY FOR AVAILABILITY.
5. DIMENSIONS ARE IN MILLIMETERS.
6. FOR SPECIFIC MATERIAL NUMBERS, REFER TO SHEET 2.
7. PACKAGE PER PK-70873-0818.
8. PARTS MARKED WITH PART NUMBER AND DATE CODE, ON EITHER SIDE, APPROXIMATELY WHERE SHOWN.



2	D
1	J
MFG.	SH.
REV.	

PCB LAYOUT: COMPONENT SIDE
RECOMMENDED PCB THICKNESS: 2.50 MIN

DIMENSIONS SHOWN (METRIC) INCH

UNLESS OTHERWISE SPECIFIED
TOLERANCES: ANGULAR ± 1/2°

	INCH	METRIC
3 PLACE	± N/A	---
2 PLACE	± N/A	± 0.05
1 PLACE	---	± 0.10

DRAFT WHERE APPLICABLE MUST
REMAIN WITHIN DIMENSIONS

DRWG. BY	JRR	CHK'D. BY	SMR
APP'D. BY	CAB	SCALE	2 : 1

REVISIONS ONLY ON CAD SYSTEM

TITLE



SALES ASSY, HDM BACKPLANE
MODULE, POLAR/GUIDE OPTION

MOLEX INCORPORATED
LITSE,ILL. 60532
SHEET NO. 1 OF 2
DATE 96/12/18

PART NO. SEE CHART
SDA-73644-****

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO
MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

DIV. DA
SIZE B

	10	9	8	7	6	5	4	3	2	1	73644																																																			
	MATERIAL NUMBER	NUMBER OF SIGNAL CONTACTS	PLATING	DIM "A"	DIM "B"	DIM "M"																																																								
F	73644-00**	72	SELECTIVE GOLD/GOLD FLASH	31.60	22.00	5.00																																																								
	73644-01**	72	SELECTIVE GOLD/GOLD FLASH	31.60	22.00	5.50																																																								
	73644-02**	72	SELECTIVE GOLD/GOLD FLASH	31.60	22.00	6.00																																																								
	73644-10**	144	SELECTIVE GOLD/GOLD FLASH	55.60	46.00	5.00																																																								
	73644-11**	144	SELECTIVE GOLD/GOLD FLASH	55.60	46.00	5.50																																																								
E	73644-12**	144	SELECTIVE GOLD/GOLD FLASH	55.60	46.00	6.00																																																								
	73644-20**	72	SELECTIVE GOLD/SELECTIVE TIN-LEAD	31.60	22.00	5.00																																																								
	73644-21**	72	SELECTIVE GOLD/SELECTIVE TIN-LEAD	31.60	22.00	5.50																																																								
	73644-22**	72	SELECTIVE GOLD/SELECTIVE TIN-LEAD	31.60	22.00	6.00																																																								
	73644-30**	144	SELECTIVE GOLD/SELECTIVE TIN-LEAD	55.60	46.00	5.00																																																								
D	73644-31**	144	SELECTIVE GOLD/SELECTIVE TIN-LEAD	55.60	46.00	5.50																																																								
	73644-32**	144	SELECTIVE GOLD/SELECTIVE TIN-LEAD	55.60	46.00	6.00																																																								
							MATERIAL NUMBER ASSIGNMENT 73644- * * * * 0 = 72-CIRCUIT, GOLD/GOLD FLASH 1 = 144-CIRCUIT, GOLD/GOLD FLASH 2 = 72-CIRCUIT, GOLD/TIN-LEAD 3 = 144-CIRCUIT, GOLD/TIN-LEAD 0 = 5.00 MATING LENGTH 1 = 5.50 MATING LENGTH 2 = 6.00 MATING LENGTH																																																							
LOCATION A  LOCATION B 							<table><tr><th>NUMBER</th><th>GUIDE POST LOCATION</th><th>POLAR KEY POSITION</th></tr><tr><td>00</td><td>B</td><td rowspan="2">A</td></tr><tr><td>01</td><td>A</td></tr><tr><td>02</td><td>B</td><td rowspan="2">B</td></tr><tr><td>03</td><td>A</td></tr><tr><td>04</td><td>B</td><td rowspan="2">C</td></tr><tr><td>05</td><td>A</td></tr><tr><td>06</td><td>B</td><td rowspan="2">D</td></tr><tr><td>07</td><td>A</td></tr><tr><td>08</td><td>B</td><td rowspan="2">E</td></tr><tr><td>09</td><td>A</td></tr><tr><td>10</td><td>B</td><td rowspan="2">F</td></tr><tr><td>11</td><td>A</td></tr><tr><td>12</td><td>B</td><td rowspan="2">G</td></tr><tr><td>13</td><td>A</td></tr><tr><td>14</td><td>B</td><td rowspan="2">H</td></tr><tr><td>15</td><td>A</td></tr><tr><td>16</td><td>B</td><td rowspan="2">N/A</td></tr><tr><td>17</td><td>A</td></tr><tr><td>18</td><td>N/A</td><td></td></tr></table>					NUMBER	GUIDE POST LOCATION	POLAR KEY POSITION	00	B	A	01	A	02	B	B	03	A	04	B	C	05	A	06	B	D	07	A	08	B	E	09	A	10	B	F	11	A	12	B	G	13	A	14	B	H	15	A	16	B	N/A	17	A	18	N/A	
NUMBER	GUIDE POST LOCATION	POLAR KEY POSITION																																																												
00	B	A																																																												
01	A																																																													
02	B	B																																																												
03	A																																																													
04	B	C																																																												
05	A																																																													
06	B	D																																																												
07	A																																																													
08	B	E																																																												
09	A																																																													
10	B	F																																																												
11	A																																																													
12	B	G																																																												
13	A																																																													
14	B	H																																																												
15	A																																																													
16	B	N/A																																																												
17	A																																																													
18	N/A																																																													
REF. MATERIAL NUMBER 73644-0009 GUIDE PIN IS IN LOCATION A POLARIZING KEY IS IN LOCATION B, POSITION E							REF. MATERIAL NUMBER 73644-0008 GUIDE PIN IS IN LOCATION B POLARIZING KEY IS IN LOCATION A, POSITION E																																																							

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9