

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

PHYSICAL PROPERTIES:
HOUSING MATERIAL: PBT
FLAMMABILITY: UL94V-0
COLOR: BLACK
MAX BOW/WARP: .0056 IN/IN.

MECHANICAL:
PITCH (TERMINAL SPACING): .563"
WIRE RANGE: 10-22 AWG
RECOMMENDED TIGHTENING TORQUE: 14IN-LBS MAX.

ELECTRICAL PROPERTIES:
MAXIMUM CURRENT: 30A
OPERATING VOLTAGE: 300V

ENVIRONMENTAL PROPERTIES:
OPERATING TEMP RANGE: -40°C TO 120°C

TERMINAL:
TERMINALS: BRASS, TIN PLATED. (UNLESS OTHERWISE STATED)
SCREWS: 8-32 STEEL, NICKEL PLATED. (UNLESS OTHERWISE STATED)
Q.C. TABS: BRASS, NICKEL PLATED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	T5	PART STATUS UPDATED	22JAN2018	RK	PS

△

 STAINLESS STEEL SCREWS.

△

 WHITE INK STAMP.

△

 NICKEL PLATED BRASS TERMINALS.

△

 NICKEL PLATED BRASS SCREWS.

△

 SEE FIGURE.

△

 PRELIMINARY PART NUMBER.

△

 OBSOLETE PART NUMBER.

△

 TE CONNECTIVITY LOGO LOCATED APPROXIMATE AREA SHOWN.

△	5	-	-	-	-	-	-	-	-	-	7.886	8.323	13	1-1546310-3								
△	2	7	-	-	-	-	-	12	12	12	7.323	7.760	12	4-1546310-8								
△		-	8	-	-	-	12	12	12	-	7.323	7.760	12	4-1546310-7								
△		-	-	-	-	12	12	12	-	-	7.323	7.760	12	4-1546310-6								
	-	-	-	-	-	-	-	-	-	-	7.323	7.760	12	1-1546310-2								
	-	-	-	-	-	-	-	-	-	-	6.760	7.179	11	1-1546310-1								
	-	-	-	-	-	-	-	-	-	-	6.197	6.634	10	1-1546310-0								
	-	-	-	-	-	-	-	-	-	-	5.634	6.071	9	1546310-9								
△	4	7	-	-	-	-	-	-	-	-	8	5.071	5.508	8	4-1546310-5							
	-	8	8	-	-	-	-	-	-	-	5.071	5.508	8	2-1546310-9								
	-	-	-	-	-	-	-	-	-	-	5.071	5.508	8	1546310-8								
△		-	-	-	-	-	7	-	-	-	4.508	4.945	7	3-1546310-8								
	-	-	-	-	-	-	-	-	-	-	4.508	4.945	7	1546310-7								
△	4	7	-	-	-	-	-	-	-	-	6	3.945	4.382	6	4-1546310-4							
△	4	7	-	-	-	-	-	-	-	-	3.945	4.382	6	4-1546310-3								
△		-	-	-	-	-	-	-	-	-	6	3.945	4.382	6	4-1546310-2							
△	5	3	2	1	7	-	-	-	-	-	3.945	4.382	6	3-1546310-1								
	-	-	-	-	-	-	6	-	-	-	3.945	4.382	6	3-1546310-0								
	-	6	6	-	-	-	-	-	-	-	3.945	4.382	6	2-1546310-8								
△	5	4	3	7	-	-	5	1	-	-	3.945	4.382	6	2-1546310-6								
△	1	7	-	-	-	-	-	-	6	-	3.945	4.382	6	2-1546310-3								
△	1	7	-	-	-	6	-	-	-	-	3.945	4.382	6	2-1546310-2								
△	7	-	-	-	-	-	-	-	-	6	3.945	4.382	6	2-1546310-1								
△	5	2	7	-	-	-	-	-	6	6	3.945	4.382	6	1546636-1								
△	6	1	-	-	6	-	-	-	6	-	3.945	4.382	6	1-1546310-9								
△	1	-	-	-	6	-	-	-	-	-	3.945	4.382	6	1546589-1								
	-	-	-	-	-	-	-	-	-	-	3.945	4.382	6	1546310-6								
	-	-	-	-	-	5	-	-	-	-	3.382	3.819	5	3-1546310-7								
△	5	4	3	7	-	-	-	1	-	5	3.382	3.819	5	2-1546310-7								
	-	-	-	-	-	-	-	-	-	-	3.382	3.819	5	1546310-5								
△	2	6	-	-	-	-	-	-	4	4	2.819	3.256	4	5-1546310-0								
△	5	4	3	2	7	-	-	-	-	-	2.819	3.256	4	4-1546310-1								
△	4	-	-	-	-	-	-	-	-	-	2.819	3.256	4	4-1546310-0								
△	5	3	2	1	7	-	-	-	-	-	2.819	3.256	4	3-1546310-9								
	-	-	-	-	-	-	-	-	-	-	2.819	3.256	4	1546310-4								
	△	4	3	7	-	-	-	-	-	-	2.256	2.693	3	2-1546310-5								
	△	5	1	7	-	-	-	-	3	1	2.256	2.693	3	2-1546310-4								
△	6	5	1	-	1	2	-	-	1	-	2.256	2.693	3	2-1546310-0								
	-	-	-	-	-	-	-	-	-	-	2.256	2.693	3	1546310-3								
	-	-	-	-	-	-	-	2	-	2	1.693	2.130	2	5-1546310-1								
	-	-	-	-	-	-	-	-	-	-	1.693	2.130	2	1546310-2								
NOTES	9	OTB JUMPER	8	.250 QC TAB 90° DOUBLE SIDE	7	.250 QC TAB 90°/45° DOUBLE SIDE	6	.250 QC TAB 90° DOUBLE SIDE	5	.250 QC TAB 45° DOUBLE SIDE	4	.250 QC TAB STRAIGHT DOUBLE SIDE	3	.250 QC TAB 90° SINGLE SIDE	2	.250 QC TAB 45° SINGLE SIDE	1	.250 QC TAB STRAIGHT SINGLE SIDE	DIM B	DIM A	NO. OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES

MATERIAL
-

FINISH
-

TOLERANCES, UNLESS
OTHERWISE SPECIFIED:

0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -
ANGLES ± -

DWN
S SCHLEGEL
CHK
S YODER
APVD
S YODER
PRODUCT SPEC
APPLICATION SPEC
WEIGHT
CUSTOMER DRAWING

16FEB2007
2/16/07
2/16/07

TE Connectivity Ltd.

14.3 (.563) DBL ROW BARRIER STRIP
W/O WASHER

SIZE
A2

CAGE CODE
00779

DRAWING NO
C-1546310






RESTRICTED TO
-

SCALE
NTS

SHEET
1 OF 4

REV
T5

1471-9 (1/15)



	-	-	-	-	-	-	2	-	2	-	1.693	2.130		5-1546310-1
	-	-	-	-	-	-	-	-	-	-	10.701	11.138	18	1-1546310-8
	-	-	-	-	-	-	-	-	-	-	10.138	10.575	17	1-1546310-7
	-	-	-	-	-	-	-	-	-	-	9.575	10.012	16	1-1546310-6
	-	-	-	-	-	-	-	-	-	-	9.012	9.449	15	1-1546310-5
	-	-	-	-	-	-	-	-	14	14	8.449	8.886	14	4-1546310-9
	-	-	-	-	-	-	-	-	-	-	8.449	8.886	14	1-1546310-4
NOTES	9	8	7	6	5	4	3	2	1		DIM B	DIM A	NO. OF POSN	PART NUMBER
	OTB JUMPER	.250 QC TAB 90° DOUBLE SIDE	.250 QC TAB 90°/45° DOUBLE SIDE	.250 QC TAB 90° DOUBLE SIDE	.250 QC TAB 45° DOUBLE SIDE	.250 QC TAB STRAIGHT DOUBLE SIDE	.250 QC TAB 90° SINGLE SIDE	.250 QC TAB 45° SINGLE SIDE	.250 QC TAB STRAIGHT SINGLE SIDE					

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

MATERIAL

TOLERANCES, UNLESS OTHERWISE SPECIFIED:

0 PLC	±	-
1 PLC	±	-
2 PLC	±	-
3 PLC	±	-
4 PLC	±	-
ANGLES	±	-

FINISH

DWN 16FEB2007

CHK 2/16/07

APVD 2/16/07

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

TE Connectivity Ltd.

14.3 (.563) DBL ROW BARRIER STRIP W/O WASHER

SIZE A2

CAGE CODE 00779

DRAWING NO C-1546310

RESTRICTED TO


SCALE NTS

SHEET 2 OF 4


REV T5

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

D




2-1546310-0




2-1546310-6 OBSOLETE


C



OBSOLETE 2-1546310-1




2-1546310-4 OBSOLETE



OBSOLETE 2-1546310-7

B

A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S SCHLEGEL 16FEB2007	 TE Connectivity Ltd.		
DIMENSIONS: INCHES		CHK S YODER 2/16/07			
		APVD S YODER 2/16/07	NAME 14.3 (.563) DBL ROW BARRIER STRIP W/O WASHER		
		PRODUCT SPEC			
TOLERANCES, UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	SIZE A2	CAGE CODE 00779	DRAWING NO C-1546310
MATERIAL -		WEIGHT -	RESTRICTED TO -		
FINISH -		CUSTOMER DRAWING	SCALE NTS	SHEET 3 OF 4	REV T5

D

C

1546310

B

A


REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

D



4-1546310-7 OBSOLETE


C



5-1546310-1

B

A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 16FEB2007 S SCHLEGEL		 TE Connectivity Ltd.	
DIMENSIONS: INCHES		TOLERANCES, UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -			
		CHK 2/16/07 S YODER		NAME	
		APVD 2/16/07 S YODER		14.3 (.563) DBL ROW BARRIER STRIP W/O WASHER	
MATERIAL -		FINISH -		RESTRICTED TO -	
CUSTOMER DRAWING		WEIGHT -		SIZE CAGE CODE DRAWING NO	
		SCALE NTS		SHEET 4 OF 4	
		REV T5			

D

C

1546310

B

A

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9