

Power PCB Relay RT2

- 2 pole 8 A, 2 CO or 2 NO contacts
- DC- or AC-coil
- Sensitive coil 400 mW
- Reinforced insulation
- WG version: Product in accordance to IEC60335-1
- RoHS compliant (Directive 2002/95/EC)
as per product date code 0413

Applications

Domestic appliances, heating control, emergency lighting, modems



F0149-B

Approvals

VDE REG.-Nr. 6106, **C** **us** E214025, **REAR** C0786
Technical data of approved types on request

Contact data

Contact configuration	2 CO or 2 NO
Contact set	single contact
Type of interruption	micro disconnection
Rated current	8 A, UL: 10 A
Rated voltage / max.switching voltage AC	240/400 VAC
Limiting continuous current	UL: 10 A
Maximum breaking capacity AC	2000 VA
Limiting making capacity, max 4 s, duty factor 10%	15 A
Contact material	AgNi 90/10, AgNi 90/10 gold plated, AgSnO ₂
Mechanical endurance DC coil	> 30 x 10 ⁶ cycles
AC coil	> 5 x 10 ⁶ cycles
Rated frequency of operation with / without load	6 / 1200 min-1

Contact ratings

Type	Load	Cycles
RT424	8 A, 250 VAC, NO contact, 70°C, EN61810-1	100x10 ³
RT444	6(3) A, 250 VAC, NO contact, 85°C; EN60730-1	100x10 ³
RT424	6(2) A, 250 VAC, NO/NC contact, 85°C; EN60730-1	100x10 ³
RT424	10 A, 250 VAC, CO contact, 70°C; General purpose, UL508	30x10 ³
RT424	1/2hp @ 240 VAC, 1/4hp @ 120 VAC, UL508	
RT424	Pilot duty B300, UL508	
RT424	8 A, 30 VDC, General Purpose, UL508	
RT424	4 A, 230 VAC, cosφ=0.6, gas burner	150x10 ³

Coil data


Rated coil voltage range DC coil	5...110 VDC
AC coil	24...230 VAC
Coil power DC coil	typ 400 mW
AC coil	typ 0,75 VA
Operative range	2
Coil insulation system according UL1446	class F

Coil versions, DC-coil


Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω	Rated coil power mW
005	5	3.5	0.5	62±10%	403
006	6	4.2	0.6	90±10%	400
012	12	8.4	1.2	360±10%	400
024	24	16.8	2.4	1440±10%	400
048	48	33.6	4.8	5520±10%	417
060	60	42.0	6.0	8570±12%	420
110	110	77.0	11.0	28800±12%	420

All figures are given for coil without preenergization, at ambient temperature +23°C
Other coil voltages on request


Max. DC load breaking capacity



Electrical endurance



Coil operating range DC



Power PCB Relay RT2 (Continued)

Coil versions, AC-coil 50Hz

Coil code	Rated voltage	Operate voltage 50 Hz	Release voltage 50 Hz	Coil resistance	Rated coil power 50 Hz
	VAC	VAC	VAC	Ω	VA
524	24	18.0	3.6	$350 \pm 10\%$	0.76
615	115	86.3	17.3	$8100 \pm 15\%$	0.76
700	200	150.0	30.0	$24350 \pm 15\%$	0.76
730	230	172.5	34.5	$32500 \pm 15\%$	0.74

All figures are given for coil without preenergization, at ambient temperature +23°C

Insulation

Dielectric strength coil-contact circuit	5000 V _{rms}
open contact circuit	1000 V _{rms}
adjacent contact circuits	2500 V _{rms}
Clearance / creepage coil-contact circuit	$\geq 10 / 10$ mm
adjacent contact circuits	$\geq 3 / 4$ mm
Material group of insulation parts	$\geq IIIa$
Tracking index of relay base	PTI 250 V
Insulation to IEC 60664-1	
Type of insulation coil-contact circuit	reinforced
open contact circuit	functional
adjacent contact circuits	basic
Rated insulation voltage	250 V
Pollution degree	3
Rated voltage system	240 V
Overvoltage category	III


Other data

RoHS - Directive 2002/95/EC	compliant as per product date code 0413
Flammability class according to UL94	V-0
For WG version: GWFI to IEC 60335-1	$> 850^\circ\text{C}$
GWT to IEC 60335-1 current $\leq 0,2$ A	$> 650^\circ\text{C}$
current $> 0,2$ A	$> 750^\circ\text{C}$
Ambient temperature range	$-40 \dots +70^\circ\text{C}$
Operate- / release time DC coil	typ 7 / 2 ms
Bounce time DC coil NO / NC contact	typ 1 / 3 ms
Vibration resistance (function) NO / NC contact	20 / 5 g, 30 ... 300 Hz
Shock resistance (destruction)	100 g
Category of protection	RTII - flux proof, RTIII - wash tight
Mounting	pcb or on socket
Mounting distance DC / AC coils	0 mm
Resistance to soldering heat flux-proof version	$270^\circ\text{C} / 10$ s
wash-tight version	$260^\circ\text{C} / 5$ s
Relay weight	13 g
Packaging unit	20 / 500 pcs

Accessories


For details see datasheet	accessories RT
---------------------------	----------------

Dimensions



S0272-BA


Coil operating range AC



S0305-B

PCB layout / terminal assignment


Bottom view on solder pins



S0418-CA


*) With the recommended PCB hole sizes a grid pattern from 2.5 mm to 2.54 mm can be used.

2 CO contacts



S0163-BJ

2 NO contacts



S0163-BK

Power PCB Relay RT2 (Continued)

Product key

Product key		R	T	4					
Type									
Version									
4	8 A, pinning 5 mm, flux proof								
E	8 A, pinning 5 mm, wash tight								
Contact configuration									
2	2 CO contacts								
	4 2 NO contacts								
Contact material									
3	AgSnO ₂								
4	AgNi 90/10								
	5 AgNi 90/10 gold plated								
Coil									
Coil code: please refer to coil versions table									
Version									
Blank	Standard version								
WG	Product in accordance with IEC 60335-1 (domestic appliances)								

Preferred types in bold print

Product key	Version	Contacts	Cont. material	Coil	Coil	Part number			
RT424005	8 A pinning 5 mm flux proof	2 CO contacts	AgNi 90/10	DC-coil	5 VDC	5-1393243-9			
RT424006					6 VDC	6-1393243-1			
RT424012					12 VDC	6-1393243-3			
RT424024					24 VDC	6-1393243-8			
RT424048					48 VDC	7-1393243-0			
RT424060					60 VDC	7-1393243-3			
RT424110							110 VDC	7-1393243-5	
RT424524						AC-coil	24 VAC	7-1393243-6	
RT424615							115 VAC	7-1393243-8	
RT424730							230 VAC	7-1393243-9	
RT425005					AgNi 90/10 gold plated	DC-coil	5 VDC	8-1393243-0	
RT425012								12 VDC	8-1393243-2
RT425024								24 VDC	8-1393243-5
RT425524							AC-coil	24 VAC	9-1393243-1
RT425615				115 VAC	9-1393243-2				
RT425730				230 VAC	9-1393243-3				
RT444012		2 NO contacts	AgNi 90/10	DC-coil	12 VDC	9-1393243-7			
RT444024						24 VDC	9-1393243-9		
RTE24005	8 A pinning 5 mm wash tight	2 CO contacts			5 VDC	0-1393243-1			
RTE24006					6 VDC	0-1393243-2			
RTE24012					12 VDC	0-1393243-4			
RTE24024					24 VDC	1-1393243-0			
RTE24048					48 VDC	1-1393243-1			
RTE24060					60 VDC	1-1393243-3			
RTE24110						110 VDC	1-1393243-4		
RTE24524						AC-coil	24 VAC	1-1393243-5	
RTE24615							115 VAC	1-1393243-7	
RTE24730							230 VAC	1-1393243-8	
RTE25005						AgNi 90/10 gold plated	DC-coil	5 VDC	1-1393243-9
RTE25012								12 VDC	2-1393243-0
RTE25024								24 VDC	2-1393243-1

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9