

## LCM600

600 Watts

Bulk Front End

Total Power: 600 W  
# of Outputs: Single  
Output: 3.3 to 60 V  
Optional 5.0 V standby



## Special Features

- 600 W output power
- Low Cost
- 2.4" x 4.5" x 7.5"
- 7.41 W/cu-in
- Industrial/Medical safety
- -40 °C to 70 °C with derating
- Optional 5 V @ 2 A Housekeeping
- High Efficiency: 89% typical
- Variable speed "Smart Fans"
- DSP controlled front end
- Conformal coat option
- ± 20% adjustment range
- Margin programming
- OR-ing FET
- Terminal block input option

## Compliance

- EMI Class B
- EN61000 Immunity

## Safety


- UL 60950-1  
508/1598/1433  
60601-1
- CSA 60950-1
- VDE 60950-1  
60601
- China CCC
- CB Scheme Report/Cert

## Electrical Specifications

### Input

|                       |  |
|-----------------------|--|
| Input range:          | 85 - 264 Vac (Operating)<br>115/230 Vac (Nominal) Input through standard IEC connector |
| Frequency:            | 47 - 440 Hz, Nominal 50/60   |
| Input fusing:         | Internal 10 A fuses, both lines fused  |
| Inrush current:       | ≤ 25 A peak, either hot or cold start  |
| Power factor:         | 0.99 typical, meets EN61000-3-2  |
| Harmonics:            | Meets IEC 1000-3-2 requirements  |
| Input current:        | 8 A RMS max input current, at 100 Vac  |
| Hold up time:         | 20 ms minimum for Main O/P, at full rated load   |
| Efficiency:           | > 88% at full load   |
| Leakage current:      | < 0.3 mA at 264 Vac  |
| ON/OFF power switch:  | N/A  |
| Power line transient: | MOV directly after the fuse  |
| Isolation:            | PRI-Chassis 2500 Vdc Basic<br>PRI-SEC 2500 Vdc Reinforced<br>SEC-Chassis 500 Vdc       |

LCM600Q Efficiency Without the 5 Vsb and 24 V ORing FETS



## Output

|                               |                                      |   |
|-------------------------------|--------------------------------------|---|
| Output rating:                | See table 1                          | 85 - 264 Vac  |
| Set point:                    | ± 0.5%                               | 85 - 264 Vac  |
| Total regulation range:       | Main output ± 2%<br>5 Vsb ± 1%       | Combined line/load/transient when measured at output terminal   |
| Rated load:                   | 600 W maximum                        | Derate linear to 50% from 50 °C to 70 °C  |
| Minimum load:                 | Main output @ 0.0 A<br>5 Vsb @ 0.0 A | No loss of regulation   |
| Output noise (PARD):          | 1% max p-p<br>50 mV max p-p          | Main output<br>5 Vsb output<br>Measured with a 0.1 µF Ceramic and 10 µF Tantalum Capacitor on any output, 20 MHz                                |
| Output voltage overshoot:     |                                      | No overshoot/undershoot outside the regulation band during on or off cycle  |
| Transient response:           | < 300 µSec                           | 50% load step @ 1 A/µs<br>Step load valid between 10% to 100% of output rating<br>Recovery time to within 1% of set point at onset of transient |
| Max units in parallel:        |                                      | Up to 10  |
| Short circuit protection:     | Protected, no damage to occur        | Bounce mode   |
| Remote sense:                 |                                      | Compensation up to 500 mV   |
| Output isolation:             |                                      | Standard per safety requirements  |
| Forced load sharing:          | To within 10% of all shared outputs  | Analog sharing control  |
| Overload protection (OCP):    | 105% to 125%<br>120% to 170%         | Main output<br>5 Vsb output   |
| Overvoltage protection (OVP): | 125% to 145%<br>110% to 125%         | 12 V output<br>5 Vsb output   |
| Overtemp protection:          | 10 - 15 °C above safe operating area | Both PFC and output converter monitored   |

## Environmental Specifications

|                        |   |
|------------------------|---|
| Operating temperature: | -40 °C to +70 °C, linear derating to 50% from 50 °C to 70 °C          |
| Storage temperature:   | -40 °C to +85 °C  |
| Humidity:              | 20 to 90%, non-condensing. Operating. Conformal coat option available |
| Fan noise:             | < 45 dBA, 80% load at 30 °C   |
| Altitude:              | Operating - 15,000 feet<br>Storage - 30,000 feet                      |
| Shock:                 | MIL-STD-810F 516.5, Procedure I, VI. Storage                          |
| Vibration:             | MIL-STD-810F 514.5, Cat. 4, 10. Storage                               |

## Ordering Information

| Model Number* | Output | Nominal Output Voltage Set Point | Set Point Tolerance | Adjustment Range | Current |        | Output Ripple P/P | Power Max. | Combined Line/ Load Regulation | Status      |
|---------------|--------|----------------------------------|---------------------|------------------|---------|--------|-------------------|------------|--------------------------------|-------------|
|               |        |                                  |                     |                  | Min     | Max    |                   |            |                                |             |
| LCM600C       | 3 V    | 3 V                              | ± 0.5%              | 2.0 - 4.0 V      | 0 A     | 150 A  | 50 mV             | 600 W      | 2%                             | Coming Soon |
| LCM600E       | 5 V    | 5 V                              | ± 0.5%              | 4.0 - 6.0 V      | 0 A     | 120 A  | 50 mV             | 600 W      | 2%                             | Coming Soon |
| LCM600L       | 12 V   | 12 V                             | ± 0.5%              | 9.6 - 14.4 V     | 0 A     | 52 A   | 120 mV            | 600 W      | 2%                             | Released    |
| LCM600N       | 15 V   | 15 V                             | ± 0.5%              | 12.0 - 19.5 V    | 0 A     | 44 A   | 150 mV            | 600 W      | 2%                             | Coming Soon |
| LCM600Q       | 24 V   | 24 V                             | ± 0.5%              | 19.2 - 28.8 V    | 0 A     | 27 A   | 240 mV            | 600 W      | 2%                             | Released    |
| LCM600U       | 36 V   | 36 V                             | ± 0.5%              | 28.8 - 43.2 V    | 0 A     | 16.7 A | 240 mV            | 600 W      | 2%                             | Released    |
| LCM600W       | 48 V   | 48 V                             | ± 0.5%              | 38.4 - 57.6 V    | 0 A     | 14 A   | 280 mV            | 600 W      | 2%                             | Released    |

\*Note: Add "-T" for terminal block instead of IEC input.

| Pin Assignment |   |                |
|----------------|---|----------------|
| Signals        | Name Description  | Pin Number(s)  |
| +Vout          | Power rail  | SK4            |
| GND            | Power GND   | SK5            |
| Signals        | Name Description  | SK2 Pin Number |
| A2             | EEPROM Address  | 1              |
| -VPROG         | Return connection of external supply for Margin Programming   | 2              |
| A1             | EEPROM Address  | 3              |
| -Vsense        | Remote Sense Return   | 4              |
| ISHARE         | Load share voltage  | 5              |
| A0             | EEPROM Address  | 6              |
| SDA1           | Serial Data Signal (I2C)                                      | 7              |
| +VPROG         | Positive connection of external supply for Margin Programming | 8              |
| SCL1           | Serial Clock Signal (I2C)                                     | 9              |
| +Vsense        | Remote Sense Positive   | 10             |
| 5VSB           | 5V standby  | 11             |
| GND            | 5V standby Return   | 12             |
| 5VSB           | 5V standby  | 13             |
| G_DCOK_C       | Global DCOK Collector   | 14             |
| GPIOA6         | EEPROM Write Protect  | 15             |
| G_DCOK_E       | Global DCOK Emitter (GND)                                     | 16             |
| GND            | Return Ground for output signal and I2C communication         | 17             |
| G_ACOK_C       | Global ACOK Collector   | 18             |
| INH_EN         | Turn Off Main Output  | 19             |
| G_ACOK_E       | Global ACOK Emitter (GND)                                     | 20             |

Note: Mating connector for SK2 is LANDWIN CI0120P1HD0-LF



PSU Front View



Signal Output Signal Connectors (SK2)

### LED Indicators

2 provided are clearly visible up to a 45 degree offset from vertical with office environment ambient lighting. The status is reflected in the indicator color.

**The DC\_OK** LED is bicolor. It shall light green if the DC output is within specification, and amber if the output falls out of specification.

**The AC\_OK** LED is Green if the AC is within specification and off when out of specification. Note: With 5 V standby, Amber also indicates that PSU is in standby mode/output off.

### Control Signals

**AC\_OK** Open collector 0.5 V maximum at 10 mA. Both emitter and collector access provided.

**DC\_OK** Open collector 0.5 V maximum at 10 mA. Both emitter and collector access provided.

**PS\_INHIBIT/ENABLE Signal** 0.0 - 0.5 V contact closure, output OFF



# Mechanical Drawing - Terminal Block Input Weight: 2.84 lbs (1.29 Kg)



## Accessories



Order kit part number 73-788-001 for control connector interface with .3m wires attached



Order kit part number 73-788-002 for control connector interface with unloaded housing and 20 pins

## Miscellaneous Specifications

### Burn-In

100% Burn-in at 45 °C, at 80 - 90 % load. Duration of burn-in determined by Quality Assurance Procedures

### MTBF

The power supply has a minimum MTBF of 300K hours using the Bell core 332, issue 6 specification @ 25 °C and 40 °C, ambient, at full load. With the power supply installed in a system in a 25 °C ambient environment and operating at full load, capacitor life shall be 10 years, minimum for ALL electrolytic capacitors contained within this power supply. The power supply shall demonstrate a MTBF level of > 500,000 hours.

### Quality Assurance

Full QAV testing shall be conducted in accordance with Emerson Network Power Standards with reports available upon request.

### Warranty

Emerson Network Power shall warrant the power supply to be free of defects in materials and workmanship for a minimum period of **three years** from the date of shipment, when operated within specifications. The warranty shall be fully transferable to the end owner of the equipment powered by the supply.

### Americas

5810 Van Allen Way  
Carlsbad, CA 92008  
USA  
Telephone: +1 760 930 4600  
Facsimile: +1 760 930 0698

### Europe (UK)

Waterfront Business Park  
Merry Hill, Dudley  
West Midlands, DY5 1LX  
United Kingdom  
Telephone: +44 (0) 1384 842 211  
Facsimile: +44 (0) 1384 843 355

### Asia (HK)

14/F, Lu Plaza  
2 Wing Yip Street  
Kwun Tong, Kowloon  
Hong Kong  
Telephone: +852 2176 3333  
Facsimile: +852 2176 3888

For global contact, visit:

[www.Emerson.com/EmbeddedPower](http://www.Emerson.com/EmbeddedPower)  
[techsupport.embeddedpower@emerson.com](mailto:techsupport.embeddedpower@emerson.com)

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

### Emerson Network Power.

The global leader in enabling business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- **Embedded Power**
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

### EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. ©2011 Emerson Electric Co.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9