

## AX101747 Faceplates and Panels - MediaFlex Plate, Single gang



For more Information  
please call

1-800-Belden1



## General Description:

MediaFlex Plate, Single gang

## Usage (Overall)

|                        |                                                                                                                                         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | - Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800, 3600, 2400, 1200, Fiber and Coax. |
| Related Parts:         | Compatible with MediaFlex Inserts                                                                                                       |

## Physical Characteristics (Connectivity)

## Dimensions

Dimensions:

| Height (in.) | Width (in.) | Depth (in.) |
|--------------|-------------|-------------|
| 4.500        | 3.020       | 0.455       |

## Materials

Materials:

| Description | Material          |
|-------------|-------------------|
| Plate       | Plastic - UL94V-0 |

## Color

|        |             |
|--------|-------------|
| Color: | Elec. White |
|--------|-------------|

## Weight

|         |            |
|---------|------------|
| Weight: | 0.100 lbs. |
|---------|------------|

## Included Parts

|                 |                                                 |
|-----------------|-------------------------------------------------|
| Included Parts: | windows, paper, 6-32 screws, installation guide |
|-----------------|-------------------------------------------------|

## Packaging

|            |                                                 |
|------------|-------------------------------------------------|
| Packaging: | Individually packaged in a suitable plastic bag |
|------------|-------------------------------------------------|

## Mechanical Characteristics (Connectivity)

|                                 |                |
|---------------------------------|----------------|
| Storage Temperature Range:      | -40°C To +70°C |
| Installation Temperature Range: | -10°C To +60°C |
| Operating Temperature Range:    | -10°C To +60°C |

## Applicable Specifications and Agency Compliance (Overall)

## Applicable Standards &amp; Environmental Programs

|                                       |                                  |
|---------------------------------------|----------------------------------|
| EU Directive 2002/95/EC (RoHS):       | Yes                              |
| EU RoHS Compliance Date (mm/dd/yyyy): | 07/01/2006                       |
| MIL Order #39 (China RoHS):           | EUP 50                           |
| Safety Listing:                       | ACA, Bi-national Standard Listed |

## Suitability

|                       |     |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

## Notes (Overall)

**Notes:** For proper installation refer to Installation Guide PX102063 included with the product or visit our web site at <http://www.belden.com>

## Product Family

Part Numbers:

| ddescription                | Gray     | Almond   | Elec. White | Black    |
|-----------------------------|----------|----------|-------------|----------|
| MediaFlex Plate Single Gang | AX101745 | AX101746 | AX101747    | AX101748 |
| MediaFlex Plate Double Gang | AX101869 | AX101870 | AX101871    | AX101872 |

## Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|



AX101747 Faceplates and Panels - MediaFlex Plate, Single gang

|          |      |          |  |  |                                |
|----------|------|----------|--|--|--------------------------------|
| AX101747 | 1 EA | 0.062 LB |  |  | MEDIAFLEX FACEPLATE SG ELEC WH |
|----------|------|----------|--|--|--------------------------------|

Revision Number: 0    Revision Date: 05-31-2009

© 2015 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9