



**NEW!**

# High Frequency, High Current Power Inductors



- Excellent Q factors – up to 230 at 400 MHz!
- Current handling as high as 57 Amps
- Inductance values from 22 to 257 nH

**Environmental** RoHS compliant, halogen free

**Terminations** RoHS compliant tin-silver over copper

**Ambient temperature** –40°C to +125°C with Irms current, +125°C to +145°C with derated current

**Storage temperature** Component: –40°C to +145°C.  
Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Temperature Coefficient of Inductance (TCL)** +5 to +70 ppm/°C

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Mean Time Between Failures (MTBF)** 1 billion hours

**PCB washing** Tested with pure water or alcohol only. For other solvents, see Doc787\_PCB\_Washing.pdf.

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>±20%<br>(nH) | Q <sup>3</sup><br>typ | Q test<br>freq<br>(MHz) | SRF typ <sup>4</sup><br>(MHz) | DCR<br>(mOhm) |      | Irms (A) <sup>5</sup> |              | Weight<br>(g) |
|--------------------------|-----------------------------------------|-----------------------|-------------------------|-------------------------------|---------------|------|-----------------------|--------------|---------------|
|                          |                                         |                       |                         |                               | typ           | max  | 20°C<br>rise          | 40°C<br>rise |               |
| 1010VS-23NME_            | 23.5                                    | 95                    | 100                     | 923                           | 1.05          | 1.20 | 18.0                  | 26.0         | 0.49          |
| 1010VS-46NME_            | 46.5                                    | 150                   | 100                     | 526                           | 1.50          | 1.62 | 17.9                  | 25.5         | 0.65          |
| 1010VS-79NME_            | 79.0                                    | 135                   | 50                      | 386                           | 1.95          | 2.11 | 17.8                  | 25.0         | 0.82          |
| 1010VS-111ME_            | 111                                     | 150                   | 50                      | 382                           | 2.53          | 2.73 | 15.7                  | 22.0         | 0.98          |
| 1010VS-141ME_            | 146                                     | 140                   | 50                      | 433                           | 3.08          | 3.33 | 14.1                  | 19.3         | 1.23          |
| 1212VS-22NME_            | 22.0                                    | 200                   | 100                     | 918                           | 0.48          | 0.55 | 40.5                  | 57.0         | 2.20          |
| 1212VS-42NME_            | 42.0                                    | 195                   | 50                      | 557                           | 0.70          | 0.77 | 38.0                  | 52.0         | 2.70          |
| 1212VS-66NME_            | 66.0                                    | 200                   | 50                      | 480                           | 0.90          | 0.99 | 35.0                  | 48.0         | 3.20          |
| 1212VS-90NME_            | 90.0                                    | 175                   | 50                      | 444                           | 1.10          | 1.21 | 33.0                  | 45.0         | 3.70          |
| 1212VS-111ME_            | 117                                     | 165                   | 50                      | 399                           | 1.30          | 1.43 | 32.0                  | 44.0         | 4.20          |
| 2014VS-33NME_            | 33                                      | 230                   | 100                     | 620                           | 0.63          | 0.74 | 32.5                  | 43.0         | 1.60          |
| 2014VS-66NME_            | 66                                      | 200                   | 50                      | 413                           | 0.90          | 1.00 | 31.5                  | 42.5         | 2.30          |
| 2014VS-111ME_            | 108                                     | 210                   | 50                      | 320                           | 1.20          | 1.34 | 31.0                  | 42.0         | 3.10          |
| 2014VS-151ME_            | 155                                     | 205                   | 50                      | 296                           | 1.44          | 1.60 | 29.4                  | 39.7         | 3.60          |
| 2014VS-201ME_            | 202                                     | 200                   | 50                      | 262                           | 1.70          | 1.82 | 26.3                  | 35.8         | 4.40          |
| 2014VS-251ME_            | 257                                     | 200                   | 50                      | 230                           | 1.94          | 2.15 | 24.9                  | 34.5         | 5.00          |

1. When ordering, specify **packaging** code:

2014VS-251MEC

- Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape.
- B = Less than full reel. In tape, but not machine ready.  
To have a leader and trailer added (\$25 charge), use code letter C instead.
- D = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked.

2. Inductance measured at 1.0 MHz, 0.1 Vrms, 0 A using an Agilent/HP HP4291A impedance analyzer with an Agilent/HP 16193A test fixture or equivalents.
3. Q measured at the specified frequency using an Agilent/HP 4291A impedance analyzer or equivalent.
4. SRF measured using an Agilent/HP 8753 network analyzer or equivalent and a Coilcraft CCF1199 test fixture
5. Current that causes the specified temperature rise from 25°C ambient.
6. Electrical specifications at 25°C.
- Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 893-1 Revised 01/23/13


© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.







**NEW!**

# High Frequency, High Current Power Inductors – 1010VS, 1212VS, 2014VS

## L vs Frequency



## Q vs Frequency


[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)  
**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)  
**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)  
**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)  
**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 893-2 Revised 01/23/13



© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.


**NEW!**

# High Frequency, High Current Power Inductors – 1010VS, 1212VS, 2014VS

## 1010VS





**Recommended Land Pattern**




| Part number | Height |      | Weight (g) |
|-------------|--------|------|------------|
|             | inches | mm   |            |
| 1010VS-23N  | 0.142  | 3.60 | 0.49       |
| 1010VS-46N  | 0.161  | 4.10 | 0.65       |
| 1010VS-79N  | 0.189  | 4.80 | 0.82       |
| 1010VS-111  | 0.220  | 5.60 | 0.98       |
| 1010VS-141  | 0.240  | 6.10 | 1.23       |

## 1212VS





**Recommended Land Pattern**




| Part number | Height |      | Weight (g) |
|-------------|--------|------|------------|
|             | inches | mm   |            |
| 1212VS-22N  | 0.260  | 6.60 | 2.2        |
| 1212VS-42N  | 0.299  | 7.60 | 2.7        |
| 1212VS-66N  | 0.346  | 8.80 | 3.2        |
| 1212VS-90N  | 0.409  | 10.4 | 3.7        |
| 1212VS-111  | 0.445  | 11.3 | 4.2        |

All dimensions are in  $\frac{\text{inches}}{\text{mm}}$ .

## 2014VS



**Recommended Land Pattern**



| Part number | Height |      | Weight (g) |
|-------------|--------|------|------------|
|             | inches | mm   |            |
| 2014VS-33N  | 0.236  | 5.99 | 1.6        |
| 2014VS-66N  | 0.279  | 7.09 | 2.3        |
| 2014VS-111  | 0.327  | 8.31 | 3.1        |
| 2014VS-151  | 0.362  | 9.19 | 3.6        |
| 2014VS-201  | 0.409  | 10.4 | 4.4        |
| 2014VS-251  | 0.449  | 11.4 | 5.0        |

## Packaging

**1010VS-23N** 250/7" reel ; 1000/13" reel ; 3.81 mm pocket depth

**1010VS-46N** 250/7" reel ; 900/13" reel ; 4.32 mm pocket depth

**1010VS-79N** 200/7" reel ; 800/13" reel ; 5.05 mm pocket depth

Plastic tape: 24 mm wide, 0.35 mm thick, 16 mm pocket spacing

**1010VS-111** 175/7" reel ; 700/13" reel ; 5.84 mm pocket depth

**1010VS-141** 150/7" reel ; 600/13" reel ; 6.35 mm pocket depth

Plastic tape: 24 mm wide, 0.40 mm thick, 16 mm pocket spacing

**1212VS-22N** 450/13" reel ; 8.86 mm pocket depth

**1212VS-42N** 400/13" reel ; 7.87 mm pocket depth

**1212VS-66N** 350/13" reel ; 9.02 mm pocket depth

**1212VS-90N** 300/13" reel ; 10.67 mm pocket depth

**1212VS-111** 250/13" reel ; 11.68 mm pocket depth

Plastic tape: 24 mm wide, 0.50 mm thick, 20 mm pocket spacing

**2014VS-33N** 500/13" reel ; 6.22 mm pocket depth

**2014VS-66N** 450/13" reel ; 7.37 mm pocket depth

**2014VS-111** 400/13" reel ; 8.56 mm pocket depth

**2014VS-151** 350/13" reel ; 9.45 mm pocket depth

**2014VS-201** 350/13" reel ; 10.67 mm pocket depth

**2014VS-251** 250/13" reel ; 11.68 mm pocket depth

Plastic tape: 44 mm wide, 0.50 mm thick, 20 mm pocket spacing



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com

**UK** +44-1236-730595 sales@coilcraft-europe.com

**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw

**China** +86-21-6218 8074 sales@coilcraft.com.cn

**Singapore** +65-6484 8412 sales@coilcraft.com.sg

Document 893-3 Revised 01/23/13

© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9