

Standard Series Buccaneer

Tried and tested, the Standard Buccaneer is one of our most popular waterproof connectors in the industry today. IP68 and IP69K rated, these environmentally sealed power connectors have been designed into a wide range of markets such as Industrial, Automotive and Marine, setting the gold standard for dust and waterproof circular connectors.



- Flex Cable Connectors
- Water and dustproof to IP68 when mated with compatible connector
- 2, 3, 4, 6, 7, 9, 12, 25 Pole with leading Earth contact on 3 Pole Socket versions
- Screw, Crimp, Crimp/Solder Terminations depending on part code and number of Poles
- PX0734 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with PX07 Series In-Line Flange and Panel Mount Connectors
- Plug or Socket
- Screw contacts supplied fitted, Crimp contacts supplied loose (Crimp/Solder contacts and fitting tools available separately)
- Choice of cable acceptance 3.5mm-9mm diameter depending on part code (see data for details)
- Cable Support accessory 12237 available separately to provide extra support for smaller cables (5mm-9mm diameter)
- Colour choices and colour codes: Blue (BL), Green (GN), Grey (GY), Light Grey (LG), Red (RD), White (WH), Yellow (YL), Black (standard colour, no suffix code)


Standard Series Buccaneer

Flex Cable Connector



PX0731

- ⬡ Mates with In-Line Flex or Panel Mounting Versions
- ⬡ Screw Locking Ring
- ⬡ Leading Earth on 3 Pole Connectors
- ⬡ Standard Cable Acceptance (2 to 9 pole) 6-8mm, 3.5-9mm with Alternative Glands




Pin Contacts	Socket Contacts	Pole Count	Termination	Contacts
PX0736/P	PX0736/S	02	Screw	Supplied Fitted
PX0731/P	PX0731/S	03	Screw	Supplied Fitted
PX0776/P	PX0776/S	03	Crimp	Supplied Loose
PX0748/P	PX0748/S	04	Screw	Supplied Fitted
PX0739/P	PX0739/S	06	Screw	Supplied Fitted
PX0745/P	PX0745/S	07	Screw	Supplied Fitted
PX0728/P	PX0728/S	09	Crimp	Supplied Loose
PX0794/P	PX0794/S	12	Crimp / Solder	Order Separately
PX0820/P	PX0820/S	25	Crimp / Solder	Order Separately

Inline Flex Cable Connector




PX0732

- ⬡ Mates with Flex or Panel Mounting Versions
- ⬡ Screw Locking Ring
- ⬡ Leading Earth on 3 Pole Connectors
- ⬡ Standard Cable Acceptance (2 to 9 Pole) 6-8mm, 3.5-9mm with Alternative Glands



Pin Contacts	Socket Contacts	Pole Count	Termination	Contacts
PX0737/P	PX0737/S	02	Screw	Supplied Fitted
PX0732/P	PX0732/S	03	Screw	Supplied Fitted
PX0778/P	PX0778/S	03	Crimp	Supplied Loose
PX0749/P	PX0749/S	04	Screw	Supplied Fitted
PX0740/P	PX0740/S	06	Screw	Supplied Fitted
PX0746/P	PX0746/S	07	Screw	Supplied Fitted
PX0729/P	PX0729/S	09	Crimp	Supplied Loose
PX0795/P	PX0795/S	12	Crimp / Solder	Order Separately
PX0821/P	PX0821/S	25	Crimp / Solder	Order Separately

Standard Series Buccaneer

Pre Wired Flex Cable Connector  PX0700	- Overmoulded Cable Assemblies - Up to 14mm Dia Cable with PVC or PU Jackets - PX0700 Flex Cable Connector - Mates with In-Line Flex Connector & all Panel Connectors	
---	--	---

Front Panel Mounting Connector  PX0730/P	Mates with Flex Cable Connector Front Panel Mounting Single Hole Fixing Pin or Socket Versions Poles 2, 3, 4, 6, 7, 9, 12 & 25	3.18 3.05 28.83 28.7 Ø27.70 Ø27.15 13.5 Fixing Details. 5.2 Max. Panel 0.8 Min. Panel 13.5 9.6 A Ø38.1 DIMENSION A. POLE. PLUG. SOCKET. 2 11.0 3 14.3 3 CRIMP 9.6 4 11.8 6 14.95 7 20.0 9 21.65 12 19.8 25 9.6 BNC 9.6 11.4 10.0 16.0
---	---	--

Pin Contacts	Socket Contacts	Pole Count	Termination	Contacts
PX0735/P	PX0735/S	02	Screw	Supplied Fitted
PX0730/P	PX0730/S	03	Screw	Supplied Fitted
PX0779/P	PX0779/S	03	Crimp	Supplied Loose
PX0747/P	PX0747/S	04	Screw	Supplied Fitted
PX0738/P	PX0738/S	06	Screw	Supplied Fitted
PX0744/P	PX0744/S	07	Screw	Supplied Fitted
PX0727/P	PX0727/S	09	Crimp	Supplied Loose
PX0796/P	PX0796/S	12	Crimp / Solder	Order Separately
PX0822/P	PX0822/S	25	Crimp / Solder	Order Separately

Rear Panel Mounting Connector  PX0709/x/xx	⬡ Mates with Flex Cable Connector ⬡ Front Panel Mounting ⬡ Single Hole Fixing ⬡ Pin or Socket Versions ⬡ Poles 2, 3, 4, 6, 7, 9, 12 & 25	5.2 Max Panel 0.8 Min Panel 2.60-2.70 45.00 7.50 10.5 A 2.60-2.70 19.30 10.50 10.5
---	---	--

Pin Contacts	Socket Contacts	Pole Count	Termination	Contacts
PX0709/P/02	PX0709/S/02	02	Screw	Supplied Fitted
PX0709/P/03	PX0709/S/03	03	Screw	Supplied Fitted
PX0708/P/03	PX0708/S/03	03	Crimp	Supplied Loose
PX0709/P/04	PX0709/S/04	04	Screw	Supplied Fitted
PX0709/P/06	PX0709/S/06	06	Screw	Supplied Fitted
PX0709/P/07	PX0709/S/07	07	Screw	Supplied Fitted
PX0708/P/09	PX0708/S/09	09	Crimp	Supplied Loose
PX0708/P/12	PX0708/S/12	12	Crimp / Solder	Order Separately
PX0708/P/25	PX0708/S/25	25	Crimp / Solder	Order Separately


Standard Series Buccaneer

PCB Mounting Connector



PX0707/P/12

- ⬡ Mates with Flex Cable Connector
- ⬡ Rear Panel Mounting
- ⬡ No. Poles: 3, 4, 6, 9, 12 or 25
- ⬡ Pin or Socket Versions
- ⬡ Pre-loaded Gold Plated Contacts




Pin Contacts	Socket Contacts	Pole Count	Termination	Contacts
PX0707/P/03	PX0707/S/03	03	PCB	Supplied Fitted
PX0707/P/04	PX0707/S/04	04	PCB	Supplied Fitted
PX0707/P/06	PX0707/S/06	06	PCB	Supplied Fitted
PX0707/P/09	PX0707/S/09	09	PCB	Supplied Fitted
PX0707/P/12	PX0707/S/12	12	PCB	Supplied Fitted
PX0707/P/25	PX0707/S/25	25	PCB	Supplied Fitted

Bulkhead Flange Mounting Connector



PX0756/S

- ⬡ Mates with Flex Cable Connector
- ⬡ Rear Panel Mounting
- ⬡ No. Poles: 3, 4, 6, 9, 12 or 25
- ⬡ Pin or Socket Versions
- ⬡ Pre-loaded Gold Plated Contacts



Pin Contacts	Socket Contacts	Pole Count	Termination	Contacts
PX0757/P	PX0757/S	02	Screw	Supplied Fitted
PX0756/P	PX0756/S	03	Screw	Supplied Fitted
PX0787/P	PX0787/S	03	Crimp	Supplied Loose
PX0761/P	PX0761/S	04	Screw	Supplied Fitted
PX0758/P	PX0758/S	06	Screw	Supplied Fitted
PX0760/P	PX0760/S	07	Screw	Supplied Fitted
PX0762/P	PX0762/S	09	Crimp	Supplied Loose
PX0798/P	PX0798/S	12	Crimp/Solder	Order Separately
PX0823/P	PX0823/S	25	Crimp/Solder	Order Separately


Standard Series Buccaneer

Low Profile Flange Mounting Connector



PX0765/S

- ⬡ Screw Flange Fixing
- ⬡ Pin or Socket Versions
- ⬡ Poles 2, 3, 4, 6, 7, 9, 12 & 25
- ⬡ Mates with Flex Cable Connector
- ⬡ Supplied with Sealing Gasket & Screw Sealing Grommets



Pin Contacts	Socket Contacts	Pole Count	Termination	Contacts
PX0764/P	PX0764/S	02	Screw	Supplied Fitted
PX0765/P	PX0765/S	03	Screw	Supplied Fitted
PX0781/P	PX0781/S	03	Crimp	Supplied Loose
PX0766/P	PX0766/S	04	Screw	Supplied Fitted
PX0767/P	PX0767/S	06	Screw	Supplied Fitted
PX0768/P	PX0768/S	07	Screw	Supplied Fitted
PX0769/P	PX0769/S	09	Crimp	Supplied Loose
PX0797/P	PX0797/S	12	Crimp/Solder	Order Separately
PX0824/P	PX0824/S	25	Crimp/Solder	Order Separately


Standard Series Buccaneer

Sealing Cap and Assembling Tool



PX0734
PX0733

- Maintains IP68 Rating of Unmated Panel, Bulkhead & Flange Mount Connectors
- PX0734 for Flex Cable Connector
- PX0733 for In-line Flex Front
- PX0711 for PCB & Rear Panel Mount Connectors




Rear of Panel Back Shell



PX0799

- Environmental Seal for Panel Rear
- Standard Cable Acceptance 6-8mm, 3.5 to 9mm with Alternative Glands
- For Front Panel Mounting Connectors
- Replaces Mounting Nut in Panel Connector




PVC Insulation Boot



PNo. 12855

- Shock Protection for Rear of Connector
- Flammability Rating UL94V-0
- Fits Front Panel Mount Versions Only

12855 for panel mounting types only.




Cable Support Accessory



PNo. 12237

- Gives Extra Support to the Cable
- Suitable for 5-7mm and 7-9mm Cable Diameters

12237 provides additional cable support. Suitable for 5-7mm and 7-9mm cables.




Standard Series Buccaneer

Spring Loaded Sealing Cap



PX0713

- IP54 rated
- Spring loaded
- Clip shut to seal
- For use with front of panel mounting connector types



Coloured Contact Inserts



PX0941

- With or Without Matching Gland Nut
- Positive Visual Identification
- Available In:
Black, Blue, Green, Grey,
Light Grey, Red, White & Yellow

Part No.	Suffix Colour	Insert / Gland Nut Combinations
Blank	Black	1 = Insert and Gland Nut Coloured
BL	Blue	2 = Insert Only Coloured
GN	Green	
GY	Grey	Example:
LG	Light Grey	PX0731/P/YL1 = Yellow Insert and Gland Nut
RD	Red	
WH	White	
YL	Yellow	

Standard Series Buccaneer

Contacts for 12 & 25 Pole Inserts



12 & 25 Way Contacts

- ⬡ Crimp or Solder Pins & Sockets
- ⬡ Gold Plated
- ⬡ Current Ratings:
12 Way: 5A, 50V
25 Way: 1A, 50V

Part No.

Description

Crimp:

Solder:

Contacts (25 Pole) / Supplied In Packs of 10:

SA3180

SA3180/1

Pins

SA3179

SA 3179/1

Sockets

Contacts (12 Pole) / (Supplied In Packs of 10:

SA3348

SA3348/1

Pins

SA3347

SA3347/1


Sockets

Assembly Tools



14025
13027

- ⬡ Crimp Tools for 3, 9, 12 & 25 Pole Crimp Contacts
- ⬡ Insertion / Extraction Tool for 25 Pole Contacts



Part No.

Description

14232

Crimp Tool (3 pole)

13826

Crimp Tool (9 pole)

14025

Crimp Tool (12 pole)

14025/1AMP

Crimp Tool (25 pole)

14232/1

Positioner (3 pole)

14025/5AMP

Positioner (12 pole)

13027/3

Insertion / Extraction Tool (3 Pole)

13027/1

Insertion / Extraction Tool (12 Pole)

13027

Insertion / Extraction Tool (25 Pole)

Standard Series Buccaneer

Cable Glands



SA3253



Pack of Alternative Cable Glands to Suit Cables from 3.5 to 9mm Dia.

Cable Acceptance - Alternatives

Gland Diameter:	Gland Part:	Gland Colour:	Additional Suffix:
6-8mm	12023	Black	Standard for 2-12 Pole
3.5-5mm	SA3426	Grey	Suffix /04†
5-7mm	12023/1	White	Suffix /05
7-9mm	12023/2	Yellow	Suffix /07*
Gland Pack	SA3253	Pack of 3 Glands to Suit Cables 3.5-5mm, 5-7mm & 7-9mm dia†	

Note:

7-9mm Gland Standard for 25 Way, No Suffix Required.

† Includes Additional Black Gland Cage for 3.5-5mm Dia. Cable Range.

To Order Connector with Alternative Cable Gland add Suffix to Part No. e.g. PX0731/P/07 = PX0731 3 Pin Connector with Cable Gland to Suit 7-9mm Dia. Cable.

Cable Acceptance - Standard As Supplied

No. Contacts:	Cable Diameter or Type:
2-12 Pole	6-8mm
25 Pole	7-9mm

Standard Series Buccaneer

Technical Overview Data

Electrical:

No. Poles:	2, 3	4	6, 7	9	12	25
Current Rating:						
VDE:	12A	10A	5A	5A	5A	1A
UL, CSA:	10A	6A	3A	5A	5A	1A
Voltage Rating (ac/dc):	277V	277V	277V	150V	50V	50V
Contact Resistance:	<10mΩ (2-9 Pole) <5mΩ (12 Pole) <5mΩ (25 Pole)					

Insulation Resistance:	>10 ⁴ MΩ @ 500V d.c. (2-9 Pole)					
AC Breakdown voltage:	4kV Pole - Pole (2-9 Pole) 6kV Poles - Panel (Low Profile Flange and Panel Types - 2-9 Pole) 7.5kV Poles - Panel (Other Types - 2-9 Pole)					

Operating Temp. Range:	-20°C to +70°C
-------------------------------	----------------

Approvals

 UL	E93288 and E337507
 CSA	LR80968-30
 VDE	40023148

Overmoulded Cable Assemblies Approvals to Customer Requirements.

Materials:

Body Mouldings:	Glass Filled Polyamide UL94HB
Inserts (2-25 pole):	Polyamide UL94V-0
PX0707:	Polyamide UL94V-0
PX0708:	Polyamide UL94V-0
PX0709:	Polyamide UL94V-0

Overmoulded Types

Body Mouldings:	Polyurethane
Flammability Rating:	UL94V-HB

Contacts

Screw Terminal:	Brass, Nickel Plated
Crimp (9 pole):	Copper Alloy, Tin Plated
Crimp / Solder (12+25 Pole):	Copper Alloy, Gold Plated (0.1µm on Nickel)

BNC Inserts:	Brass, Nickel Plated
BNC Contacts:	Brass, Silver Plated

RoHS	Compliant
-------------	-----------

Mechanical:

Sealing:	IP69K, Tested in Accordance with DIN 40050/Part 9 IP6k9k
-----------------	--

IP68, EN 60529:1992+A2:2013 Tested @ 1.054kg/sq.cm. (15lb/sq.in.) 10m Depth for 2 Weeks.

EN 60529:1992 +A2:2013 Tested @ 9.84kg/sq.cm. (140lb/sq.in.) 100m Septh for 12 Hours.

Salt Mist:	EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1
-------------------	---

Cable Acceptance

2-12 Pole - Standard Gland:	6-8mm Dia
2-12 Pole - Alternative Glands:	3.5-9mm Dia
25 Pole - Standard Gland:	7-9mm Dim
25 Pole - Alternative Glands:	3.5-7mm Dim

Contact Accommodation

2 & 3 Pole Screw Terminals:	4mm ² (12AWG) Max
3 Pole Crimp:	1.0-1.5mm ² (14-18AWG) Max
4, 6 & 7 Pole:	1.5mm ² (16AWG) Max
9 Pole:	0.12-0.21mm ² (24-26AWG)
12 Pole:	0.32mm ² (22-26AWG) Max
25 Pole:	0.12-0.21mm ² (24-26AWG)

Terminations

2-7 Pole:	Screw Terminals
3 Pole:	Screw Terminals & Crimp
9 Pole:	Crimp Contacts
12 Pole:	Crimp & Solder Contacts
25 Pole:	Crimp & Solder Contacts

Tightening Torques:	Gland Nut: 1.13Nm (10lbf.in.)
Flex Mounting / In-Line:	Rear Fixing Nut: 1.7Nm (15lbf.in.)
Panel Mounting:	Front Fixing Nut: 1.4Nm (12.4lbf.in.)

Surface / Bulkhead and Low Profile Flange Mounting:	4 Fixing Screws (using Washers Supplied) 0.34Nm (3lbf.in.)
Sealings Caps / Locking Ring:	1.13Nm (10lbf.in.)

Rear Thread, Front Panel Connector:	M27 x 1.0-6H
--	--------------

Thread, Front Panel Connector:	M35 x 1.0-6H
---------------------------------------	--------------

Standard Series Buccaneer

PX0xxx	X	XX	XX	X
Body Styles	Contacts Type	Cable Acceptance or PCB / Rear Panel Mounting	Insert / Gland Nut Colour	Insert / Gland Nut Colour Combination
	P = Pin S = Socket	Flex Cable and In-line Flex Connectors cable acceptance use: Blank = 6-8mm (Black) standard for 2-12 pole 04 = 3.5-5mm (Grey) 05 = 5-7mm (White) 07 = 7-9mm (Yellow) (standard for 25 way, no suffix required) PCB (PX0707) and Rear Panel Mount connectors (PX0708 and PX0709) use: 02 = 2 pole 03 = 3 pole 04 = 4 pole 06 = 6 pole 07 = 7 pole 09 = 9 pole 12 = 12 pole 25 = 25 pole Front Panel, Bulkhead and Flange Mount - not required:	Blank = Black BL = Blue GN = Green GY = Grey LG = Light Grey RD = Red WH = White YL = Yellow	1 = Insert and Gland Nut Coloured 2 = Insert only Coloured

Example:

PX0707/P/06 = PCB Panel connector, pin contacts, 6 pole

PX0731/S = Flex Cable connector, socket contacts, 3 pole

PX0732/P/07/BL2 = In-Line Flex Cable connector, pin contacts, 3 pole, 7-9mm cable acceptance, blue insert


PCB Layouts:

Sockets:


Contact Nos viewed from rear of panel

Pins:


Contact Nos viewed from rear panel rear of panel




PX0707/S/03




PX0707/S/04




PX0707/P/03




PX0707/P/04




PX0707/S/06




PX0707/S/09




PX0707/P/06




PX0707/P/09




PX0707/S/12



PX0707/S/25




PX0707/P/12



PX0707/P/25

Sealed Inline Cable Joiner

Cable Joiner  PX0777	- Standard Cable Acceptance 6-8mm - Cable Range 3.5-9mm (Using Alternative Glands) - Supplied with 4, 6 or 8 Way - Terminal Block - Available Moulded in Black or Orange	
---	--	---

Technical Overview Data

Specifications:

Rating:
Wire Termination:
Conductor Accommodation:
Cable Acceptance:

Material:
Sealing:

Salt Mist:

Operating Temp. Range:

Colour:

RoHS

PX0777

16A, 250V a.c.
 3 Way Terminal Block
 2.5mm² Max (14AWG)
 6-8mm Dia
 Alternative Glands available on request

Glass Filled Polyamide UL94-HB
 IP68 to BSEN 60529 : 1992
 1.054kg/sq.cm. (15lbs/sq.in.)
 10m Depth for 2 Weeks

IP69k to DIN 40050-9

EN60068-2-52 Test Kb Salt Mist (Cyclic)
 Marine Severity Level 1

-20°C to +70°C

Black
 Orange (Add /OR to PNo.)

Compliant

PX0777/4POLE, 6POLE, 8POLE

10A, 250V a.c.
 4, 6, 8 Way Terminal Block
 1.5mm² Max (16AWG)
 6-8mm Dia
 Alternative Glands available on request

Glass Filled Polyamide UL94-V0
 IP68 to BSEN 60529 : 1992
 1.054kg/sq.cm. (15lbs/sq.in.)
 10m Depth for 2 Weeks

IP69k to DIN 40050-9


EN60068-2-52 Test Kb Salt Mist (Cyclic)
 Marine Severity Level 1

-20°C to +70°C

Black
 Orange (Add /OR to PNo.)


Compliant

POLE Configurations:



PX0777	/	XPOLE	/	XX	/	XX
Part No.		Blank = 3 Pole		Blank = 6-8mm		Blank = Black
		4POLE = 4 Pole		04 = 3.5-5mm		OR = Orange
		6POLE = 6 Pole		05 = 5-7mm		
		8POLE = 8 Pole		07 = 7-9mm		
Example:						
PX0777 = 3 Pole 6-8mm Black						
PX0777/04 = 3 Pole 3.5-5.0mm Black						
PX0777/04/OR = 3 Pole 3.5-5.0mm Orange						
PX0777/4POLE = 4 Pole 6-8mm Black						
PX0777/6POLE/04 = 6 Pole 3.5-5.0mm Black						
PX0777/8POLE/04/OR = 8 Pole 3.5-5.0mm Orange						


PX0777 Wiring & Assembly Instructions



1. Strip wires to dimensions shown.
2. Assemble components parts onto cable as shown, then connect wires to terminal block.

ENSURING WIRES CONNECTED INTO ONE SIDE OF TERMINAL BLOCK MATCH WIRES CONNECTED INTO THE OTHER SIDE.

E.g. **Brown to Brown (Live)**
Blue to Blue (Neutral)
Green / Yellow to Green / Yellow (Earth)



Wire Stripping Details

3. Bring the two body mouldings together ensuring the 'O' ring is correctly located in groove then lock together with locking ring, ensure ring is fully tightened.

Put gland cage over gland and push fully home into its appropriate body then fully tighten gland nuts.
4. To ensure a good seal, all surfaces must be completely free of dust, grease or any other contamination.

THIS CABLE CONNECTOR IS SUITABLE FOR USE WITH LOADS NOT EXCEEDING 16 AMPS USING 1.5mm² CABLE

ALWAYS USE WITH SUPPLY PROTECTED BY AN RCD, IF IN DOUBT CONSULT A QUALIFIED ELECTRICIAN.

DANGER

**DISCONNECT MAINS
SUPPLY BEFORE
DISMANTLING
CONNECTOR**

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9