



# Inductors for Power Circuits

Wound Ferrite

**VLS-EX Series**

# VLS6045EX<sub>Type</sub>

---

VLS6045EX

---

## REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

### SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

#### REMINDERS

- The storage period is less than 6 months. Be sure to follow the storage conditions (Temperature: 5 to 30°C, Humidity: 0 to 75% RH or less).  
If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Before soldering, be sure to preheat components.  
The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.  
If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- When embedding a printed circuit board where a chip is mounted to a set, be sure that residual stress is not given to the chip due to the overall distortion of the printed circuit board and partial distortion such as at screw tightening portions.
- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Carefully lay out the coil for the circuit board design of the non-magnetic shield type.  
A malfunction may occur due to magnetic interference.
- Use a wrist band to discharge static electricity in your body through the grounding wire.
- Do not expose the products to magnets or magnetic fields.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.  
The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.  
If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- (1) Aerospace/Aviation equipment
- (2) Transportation equipment (cars, electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

When designing your equipment even for general-purpose applications, you are kindly requested to take into consideration securing protection circuit/device or providing backup circuits in your equipment.

# Inductors for Power Circuits

## Wound Ferrite

Product compatible with RoHS directive  
Halogen-free  
Compatible with lead-free solders

## Overview of VLS6045EX Type

### FEATURES

- A magnetic shield type wound inductor for power circuits.
- High magnetic shield construction achieved by a ferrite magnetic material and compatible with high-density mounting.
- Larger current and lower Rdc have been achieved by optimizing the ferrite core figure.

### APPLICATION

TVs, STBs, game devices, and other audiovisual equipment

### PART NUMBER CONSTRUCTION

| VLS         |                       | 6045        |               | EX | - | R47             |      | N                    |      |
|-------------|-----------------------|-------------|---------------|----|---|-----------------|------|----------------------|------|
| Series name | L×W×H Dimensions (mm) |             | Internal code |    |   | Inductance (μH) |      | Inductance tolerance |      |
|             | 6045                  | 6.0×6.0×4.5 |               |    |   | R47             | 0.47 | M                    | ±20% |
|             |                       |             |               |    |   | 2R2             | 2.2  | N                    | ±30% |
|             |                       |             |               |    |   | 100             | 10   |                      |      |

### OPERATING TEMPERATURE RANGE, PACKAGE QUANTITY, PRODUCT WEIGHT

| Type      | Temperature range              |                               | Package quantity<br>(pieces/reel) | Individual weight<br>(g) |
|-----------|--------------------------------|-------------------------------|-----------------------------------|--------------------------|
|           | Operating temperature*<br>(°C) | Storage temperature**<br>(°C) |                                   |                          |
| VLS6045EX | -40 to 105                     | -40 to 105                    | 1500                              | 0.6                      |

\* Operating temperature range includes self-temperature rise.

\*\* The Storage temperature range is for after the circuit board is mounted.

- RoHS Directive Compliant Product: See the following for more details related to RoHS Directive compliant products. <http://product.tdk.com/en/environment/rohs/>
- Halogen-free: Indicates that Cl content is less than 900ppm, Br content is less than 900ppm, and that the total Cl and Br content is less than 1500ppm.

 Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use. Please note that the contents may change without any prior notice due to reasons such as upgrading.

# VLS6045EX Type

## RECOMMENDED REFLOW PROFILE



| Preheating |       |            | Soldering |      | Peak  |      |
|------------|-------|------------|-----------|------|-------|------|
| Temp.      | Time  |            | Temp.     | Time | Temp. | Time |
| T1         | T2    | t1         | T3        | t2   | T4    | t3   |
| 150°C      | 180°C | 60 to 120s | 220°C     | 40s  | 260°C | 5s   |

# VLS6045EX Type

## SHAPE & DIMENSIONS



Dimensions in mm

## RECOMMENDED LAND PATTERN



Dimensions in mm

# VLS6045EX Type

## ELECTRICAL CHARACTERISTICS

### CHARACTERISTICS SPECIFICATION TABLE

| L<br>( $\mu$ H) | Measuring frequency |       | DC resistance<br>( $\Omega$ ) $\pm$ 30% | Rated current*  |                 | Part No.       |
|-----------------|---------------------|-------|-----------------------------------------|-----------------|-----------------|----------------|
|                 | Tolerance           | (kHz) |                                         | Idc1<br>(A)max. | Idc2<br>(A)typ. |                |
| 0.47            | $\pm$ 30%           | 100   | 0.010                                   | 13.5            | 7.0             | VLS6045EX-R47N |
| 1.0             | $\pm$ 30%           | 100   | 0.012                                   | 12.0            | 6.0             | VLS6045EX-1R0N |
| 1.5             | $\pm$ 30%           | 100   | 0.017                                   | 8.2             | 5.3             | VLS6045EX-1R5N |
| 2.2             | $\pm$ 30%           | 100   | 0.019                                   | 7.5             | 5.1             | VLS6045EX-2R2N |
| 3.3             | $\pm$ 30%           | 100   | 0.023                                   | 6.5             | 4.95            | VLS6045EX-3R3N |
| 4.7             | $\pm$ 20%           | 100   | 0.027                                   | 5.8             | 4.2             | VLS6045EX-4R7M |
| 6.8             | $\pm$ 20%           | 100   | 0.036                                   | 4.7             | 3.6             | VLS6045EX-6R8M |
| 10              | $\pm$ 20%           | 100   | 0.047                                   | 3.9             | 3.4             | VLS6045EX-100M |
| 15              | $\pm$ 20%           | 100   | 0.075                                   | 3.1             | 2.5             | VLS6045EX-150M |
| 22              | $\pm$ 20%           | 100   | 0.105                                   | 2.4             | 1.9             | VLS6045EX-220M |
| 33              | $\pm$ 20%           | 100   | 0.175                                   | 1.9             | 1.5             | VLS6045EX-330M |

\* Rated current: smaller value of either Idc1 or Idc2.

Idc1: When based on the inductance change rate (30% below the initial L value)

Idc2: When based on the temperature increase (Temperature increase of 40°C by self heating)

#### Measurement equipment


| Measurement item   | Product No.         | Manufacturer                                           |
|--------------------|---------------------|--------------------------------------------------------|
| L                  | 4194A               | Keysight Technologies, Inc. (formerly Hewlett-Packard) |
| DC resistance      | VP-2941A            | Panasonic (formerly Matsushita Electric Industrial)    |
| Rated current Idc1 | 4284A+42841A+42842A | Keysight Technologies, Inc. (formerly Hewlett-Packard) |

\* Equivalent measurement equipment may be used.

# VLS6045EX Type

## ELECTRICAL CHARACTERISTICS

### L FREQUENCY CHARACTERISTICS GRAPH



○ Measurement equipment

Product No.

Manufacturer

4294A

Keysight Technologies, Inc. (formerly Hewlett-Packard)

\* Equivalent measurement equipment may be used.

# VLS6045EX Type

## ELECTRICAL CHARACTERISTICS

### INDUCTANCE VS. DC BIAS CHARACTERISTICS GRAPH



○ Measurement equipment

| Product No.                                     | Manufacturer                                           |
|-------------------------------------------------|--------------------------------------------------------|
| 4284A+42841A+42842A                             | Keysight Technologies, Inc. (formerly Hewlett-Packard) |
| * Equivalent measurement equipment may be used. |                                                        |

## ■ PACKAGING STYLE

\* These values are typical values.

Technical drawing of a multi-hole plate. The main view shows a plate with a width  $W$  and a thickness  $t$ . It features a series of holes with diameter  $\phi D0$ . The distance between the first two holes is  $P2$ , and the distance between the last two holes is  $P0$ . The distance between the first and last holes is  $P1$ . The distance from the first hole to the top edge is  $E$ , and the distance from the last hole to the bottom edge is  $F$ . A detail view shows the cross-section of the plate, indicating a width  $A$  and a thickness  $t$ . The dimensions are in mm.

| Type             | A   | B   | øD0        | E        | F        | P0      | P1      | P2       | W        | K   | t   |
|------------------|-----|-----|------------|----------|----------|---------|---------|----------|----------|-----|-----|
| <b>VLS6045EX</b> | 6.3 | 6.3 | 1.5+0.1/-0 | 1.75±0.1 | 5.5±0.05 | 4.0±0.1 | 8.0±0.1 | 2.0±0.05 | 12.0±0.3 | 4.7 | 0.4 |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9