

Amphenol® LTW®



Head Office (Taiwan):
Amphenol LTW Technology Co., Ltd.
 9F, No.657-12, Jungjeng Road, Shinjuang City,
 Taipei County 242, Taiwan
 Tel : +886-2-2908-5626
 Fax: +886-2-2902-9787~88
 e-mail: sales@ltw-tech.com

Branch Office (China):
Amphenol Zhengri Electronic (Kunshan) Co., Ltd.
 No. 62 Da Tung Road, Peng Lang Street, Kunshan City,
 Jiangsu Province 215333, China
 Tel : +86-512-5761-0501~2
 Fax: +86-512-5761-0515
 Sales Contact: (East China) +86-512-5761-0512
 (South China) +86-755-2823-2407
 137-1383-4316

Distributed by :

Amphenol® LTW®

Waterproof Connector Solutions

Amphenol® LTW® Innovation in Waterproof Solution




Complete Range of Waterproof Connectors & Cable Assembly

www.amphenolltw.com

Amphenol LTW reserves the right to improve, enhance and modify the design specifications and construction of Amphenol LTW products without prior notification. For additional product and technical information, please contact us.

Copyright by Amphenol LTW in Taiwan 05/2010


**SPECIFICATIONS**

No.	Specifications	Standard Value
01. Identifications		Power Connector
02. Description		Panel Mount, Molded with Cable and Field Installable
03. Current Rating / Pin Arrangements		8A : 5 to 7 12A : 2 to 4 16A : 3+PE (Screw in Type Termination) 20A : 3
04. Material		Contacts: Copper Alloy, Gold Plated 16A Available in Gold, Silver and Tin Plating Connector Body: Nylon + GF UL Recognized
05. Temperature Range		Cable: -20°C to +80°C Connector Body: -40°C to +105°C
06. Waterproof Rating		IP67
07. Contact Resistance		5mΩ
08. Insulation Resistance		≥100MΩ at DC 250V
09. Durability		500 Times
10. Breakdown Voltage		≥AC 1000V / 1 Minute
11. Standard Cable Length (for Molded Cable)		1–99M (Standard Cable: UL2464 PVC Jacket or Power Cable)
12. Field Installable		All Solder Contacts Unless And Otherwise Indicated

CONTACT PIN ARRANGEMENT


8A Current

Size is between C and D size



12A Current

Size is between C and D size



16A Current

Size is between C and D size



20A Current

C size



20A+2A Current

Size is over E size




25A Current

C size





○ 2A ● 8A ● 12A ● 16A ○ 20A ○ 25A







Female Connector Female Pin
Male Connector Male Pin







Female Connector Male Pin
Male Connector Female Pin



Panel (Chassis) Mount		Mating Parts		Accessories
CONNECTOR	P/N	CONNECTOR	P/N	
 LTWPWE-PMMS-SC7001 FEATURES: - Male Connector - Front Mounting - IP 67 - Solder Contacts 8A: 5 to 7 Pins - UL Approved	 PANEL CUT-OUT	 LTWPWE-AFFM-SL7AX FEATURES: - Female Connector - In-line Molded Type (Cable to Cable or Cable to Field Installable) - With SR - IP 67 8A: 5 to 7 Pins	LTWPWE-BFFA-SL7001 FEATURES: - Female Connector - Solder Contacts - In-line Field Installable (Field Installable to Field Installable or Cable to Field Installable) - Without SR - IP 67 8A: 5 to 7 Pins - UL Approved	
		 LTWPWE-AMMM-SL7AX FEATURES: - Male Connector - In-line Molded Type (Cable to Cable or Cable to Field Installable) - With SR - IP 67 8A: 5 to 7 Pins	LTWPWE-BMMA-SL7001 FEATURES: - Male Connector - Solder Contacts - In-line Field Installable (Field Installable to Field Installable or Cable to Field Installable) - Without Cable - IP 67 8A: 5 to 7 Pins - UL Approved	
 LTWPWE-PFFS-SC7001 FEATURES: - Female Connector - Front Mounting - IP 67 - Solder Contacts 8A: 5 to 7 Pins - UL Approved	 PANEL CUT-OUT	 LTWPWE-AMMM-SL7AX FEATURES: - Male Connector - In-line Molded Type (Cable to Cable or Cable to Field Installable) - With SR - IP 67 8A: 5 to 7 Pins	LTWPWE-BMMA-SL7001 FEATURES: - Male Connector - Solder Contacts - In-line Field Installable (Field Installable to Field Installable or Cable to Field Installable) - Without Cable - IP 67 8A: 5 to 7 Pins - UL Approved	

Panel (Chassis) Mount		Mating Parts		Accessories
CONNECTOR	P/N	CONNECTOR	P/N	
 PANEL CUT-OUT 	LTWPF-PMMS-SC7001 FEATURES: - Male Connector - Front Mounting - IP 67 - Solder Contacts 12A: 2 to 4 Pins - UL Approved		LTWPF-AFFM-SL7AX FEATURES: - Female Connector - In-line Molded Type (Cable to Cable or Cable to Field Installable) - With SR - IP 67 12A: 2 to 4 Pins	
			LTWPF-BFFA-SL7001 FEATURES: - Female Connector - Solder Contacts - In-line Field Installable (Field Installable to Field Installable or Cable to Field Installable) - Without SR - IP 67 12A: 2 to 4 Pins	
 PANEL CUT-OUT 	LTWPF-PFFS-SC7001 FEATURES: - Female Connector - Front Mounting - IP 67 - Solder Contacts 12A: 2 to 4 Pins - UL Approved		LTWPF-AMMM-SL7AX FEATURES: - Male Connector - In-line Molded Type (Cable to Cable or Cable to Field Installable) - With SR - IP 67 12A: 2 to 4 Pins	
			LTWPF-BMMA-SL7001 FEATURES: - Male Connector - Solder Contacts - In-line Field Installable (Field Installable to Field Installable or Cable to Field Installable) - Without Cable - IP 67 12A: 2 to 4 Pins	

Panel (Chassis) Mount		Mating Parts		Accessories
CONNECTOR	P/N	CONNECTOR	P/N	
 PANEL CUT-OUT 	LTWPG-04PFFB-SC FEATURES: - Male Connector, Screw Type Lock - Panel Type, Nylon + GF Material - IP 67 - Male Pins 16A (3+PE)		LTWPG-04BMMB-SL FEATURES: - Male Connector, Screw Type Lock - Straight Assembly Type, Nylon + GF Material - IP 67 - Male Pins 16A (3+PE)	
			LTWPG-04BMMB-SR FEATURES: - Male Connector, Screw Type Lock - Right Angle Assembly Type, Nylon + GF Material - IP 67 - Male Pins 16A (3+PE)	
 PANEL CUT-OUT 	LTWPG-04PMMB-SC FEATURES: - Female Connector, Screw Type Lock - Panel Type, Nylon + GF Material - IP 67 - Female Pins 16A (3+PE)		LTWPG-04BMMB-SL FEATURES: - Female Connector, Screw Type Lock - Straight Assembly Type, Nylon + GF Material - IP 67 - Female Pins 16A (3+PE)	
			LTWPG-04BMMB-SR FEATURES: - Female Connector, Screw Type Lock - Right Angle Assembly Type, Nylon + GF Material - IP 67 - Female Pins 16A (3+PE)	

Panel (Chassis) Mount		Mating Parts		Accessories
CONNECTOR	P/N	CONNECTOR	P/N	
 PANEL CUT-OUT 	LTWPMC-03RMMS-LC7001 LTWPMC-03RMMS-LC7002 FEATURES: • Panel Male Connector, Lock Type • Rear Mounting • IP 67 • 20A (2+PE) • Solder Type, Male Contacts • UL and TUV Approved: LTWPMC-03RMMS-LC7002	 LTWPMC-03AFFM-LL7AXX FEATURES: • Female Connector • In-line Molded Type • With SR • 20A (2+PE) Female Contacts • IP 67		
		 LTWPMC-03BFFA-LL7001 FEATURES: • Female Connector • Field Installable • 20A (2+PE) Female Contacts • IP 67		
 PANEL CUT-OUT 	LTWPMC-03RMFS-LC7001 LTWPMC-03RMFS-LC7002 FEATURES: • Panel Male Connector, Lock Type • Rear Mounting • IP 67 • 20A (2+PE) • Solder Type, Female Contacts • UL and TUV Approved: LTWPMC-03RMFS-LC7002	 LTWPMC-03AFMM-LL7AXX FEATURES: • Female Connector • In-line Molded Type • With SR • 20A (2+PE) Male Contacts • IP 67		
		 LTWPMC-03BFMA-LL7001 FEATURES: • Female Connector • Field Installable • 20A (2+PE) Male Contacts • IP 67		

Panel (Chassis) Mount		Mating Parts		Accessories
CONNECTOR	P/N	CONNECTOR	P/N	
 PANEL CUT-OUT 	LTWPWCU-04RMMS-LC7001 LTWPWCU-04RMMS-LC7002 FEATURES: • Panel Male Connector, Lock Type • Rear Mounting • IP 67 • 20A*3+2A Male Contacts • Solder Type • UL and TUV Approved: LTWPWU-03RMMS-LC7002	 LTWPWCU-04AFFM-LL7AXX FEATURES: • Female Connector • In-line Molded Type • With SR • 20A*3+2A Female Contacts • IP 67		
 PANEL CUT-OUT 	LTWPWCU-04RMFS-LC7001 LTWPWCU-04RMFS-LC7002 FEATURES: • Panel Male Connector, Lock Type • Rear Mounting • IP 67 • 20A*3+2A Female Contacts • Solder Type • UL and TUV Approved: LTWPWU-03RMFS-LC7002	 LTWPWCU-04AFMM-LL7AXX FEATURES: • Female Connector • Male Contact • In-line Molded Type • With SR • 20A*3+2A Male Contacts • IP 67		

Male Connector		Mating Parts		Accessories
CONNECTOR	P/N	CONNECTOR	P/N	
 PANEL CUT-OUT 	LTWPHW-03PMMB-SC7001 FEATURES: • Panel Male Connector • Screw Type • Front Mounting • 25A (2+PE) • IP 67 • Screw in Type Male Contacts		LTWPHW-03AFFM-SL7AXX FEATURES: • Female Connector • Screw Type with SR • Molded with Cable • 25A (2+PE) Female Pins • IP 67	
 PANEL CUT-OUT 	LTWPHW-03AMMM-SL7AXX FEATURES: • Screw Type with SR • Molded with Cable • 25A (2+PE) Male Pins • IP 67			

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9