

8.5 mm Diameter Fully Sealed Container Cermet Trimmer




Models P8PX and P8PY feature a TO-5 transistor type, rugged metal case housing.

The cermet track is printed to an alumina substrate allowing high dissipation and ensuring reliable performance under extreme environmental conditions.

FEATURES










- P8PX P8PY COMPL
- Product qualification according to CECC 41101-002 (A, B)
- · Fully sealed
- Multi-finger wiper contact in precious metal
- Tests according to CECC 41000 or IEC 60393-1
- Material categorization: for definitions of compliance please see <u>www.vishay.com/doc?99912</u>






Vishay Sfernice

Resistive element		Cermet		
Electrical travel		270° ± 15°		
Resistance range		10 Ω to 2.2 M Ω		
Standard series E3		1 - 2.2 - 4.7 and on request 1 - 2 - 5		
T.1	standard	± 10 %		
Tolerance	on request	± 5 %		
	P8PX - P8PY	0.5 W at +70 °C		
P8PT Power rating		1 W at 70 °C		
		P8PT P8PY 0.5 P8PY 0.		
Circuit diagram		$ \begin{array}{c} a \\ O \\ (1) \end{array} $ $ \begin{array}{c} b \\ O \\ \longrightarrow \end{array} $ $ \begin{array}{c} C \\ O \\ (3) \end{array} $ $ \begin{array}{c} C \\ O \\ O \\ \end{array} $		
Temperature coefficient		See standard resistive element table		
Limiting element voltage (linear law)		250 V		
Contact resistance variation		2 % Rn or 1 Ω		
End resistance (typical)		1 Ω		
Dielectric strength		1000 V		
Insulation resistance (500 V _{DC})		1 GΩ		

MECHANICAL SPECIFICATIONS				
Mechanical travel		300° ± 5°		
Operating torque (max. Ncm)		3		
End stop torque (max. Ncm)		6		
Unit weight (max. g) P8PX - P8PY P8PT		1.1 3.6		
Terminals		SnAg alloy (code e2)		

ENVIRONMENTAL SPECIFICATIONS			
Temperature range -55 °C to +125 °C			
Climatic category	55/125/56		
Sealing	Fully sealed - IP67		





		P8PX - P8PY			P8PT		
STANDARD RESISTANCE VALUES	MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. CURRENT THROUGH WIPER	MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. CURRENT THROUGH WIPER	TYPICAL TCR -55 °C +125 °C
Ω	W	V	mA	W	V	mA	ppm/°C
10	0.50	2.24	224	1.0	3.16	316	
22	0.50	3.32	150	1.0	4.69	213	
47	0.50	4.85	103	1.0	6.86	146	
100	0.50	7.07	70	1.0	10.0	100	
220	0.50	10.5	47	1.0	14.8	67	
470	0.50	15.3	32	1.0	21.7	46	
1K	0.50	22.4	22	1.0	31.6	32	
2.2K	0.50	33.2	15	1.0	46.9	21	
4.7K	0.50	48.5	10	1.0	68.6	15	± 100
10K	0.50	70.7	7.0	1.0	100.0	10.0	
22K	0.50	105	4.8	1.0	148	6.7	
47K	0.50	153	3.2	1.0	217	4.6	
100K	0.50	224	2.2	0.63	250	2.5	
220K	0.28	250	1.1	0.28	250	1.1	
470K	0.13	250	1.53	0.13	250	0.53	
1M	0.06	250	0.25	0.06	250	0.25	
2.2M	0.028	250	0.11	0.03	250	0.11	

PERFORMANCE							
CECC 41100					TYPICAL VALUES AND DRIFTS		
TESTS	CONDITIONS	ΔRT (%) REQUIREMENTS	$\frac{\Delta R_{1-2}}{R_{1-2}}$ (%)	∆RT RT (%)	$\frac{\Delta R_{1-2}}{R_{1-2}}$ (%)		
Climatic sequence	Phase A dry heat 125 °C Phase B damp heat Phase C cold -55 °C Phase D damp heat 5 cycles	± 2 %	± 3 %	± 0.5 %	± 1 %		
	50.1	± 2 %	± 3 %	± 0.5 %	± 1 %		
Long term damp heat	56 days 40 °C, 93 % RH	Dielectric strength: 700 V Insulation resistance: > 100 M Ω		Dielectric strength: 1000 V Insulation resistance: $> 104 \text{ M}\Omega$			
Rotational life	200 evelee	± 2 %		± 1 %			
Rotational life	200 cycles	Contact res. variat.: < 5 % Rn		Contact res. variat.: < 2 % Rn			
L and life	1000 h at rated power	± 2 %	± 3 %	± 1 %	± 2 %		
Load life 90'/30' - ambient temp. 70 °C		Contact res. variat.: < 5 % Rn		Contact res. variat.: < 1 % Rn			
Rapid temperature Change	5 cycles -55 °C to +125 °C	± 1.5 % ΔV ₁₋₂ V ₁₋₃	≤ ± 1 %	± 0.2 %	$\frac{\Delta V_{1-2}}{V_{1-3}} \leq \pm 0.5 \%$		
Shock	50 g at 11 m s 3 successive shocks in 3 directions	± 1 %	± 2 %	± 0.1 %	± 0.5 %		
Vibration	10 Hz to 55 Hz 0.75 mm or 10 <i>g</i> during 6 h	±1 % ΔV ₁₋₂ V ₁₋₃	≤ ± 2 %	± 0.2 %	$\begin{array}{cc} \Delta V_{1\text{-}2} & \leq \pm \ 0.5 \ \% & \end{array}$		

Note

• Nothing stated herein shall be construed as a guarantee of quality or durability.

www.vishay.com


Vishay Sfernice


MARKING

- · Vishay trademark
- Model
- Style
- Ohmic value (in Ω , $k\Omega$, $M\Omega$)
- Manufacturing date
- Tolerance (in %)
- Marking of terminal: 3

PACKAGING

• Box of 50 pieces code B25 (BL50)





RELATED DOCUMENTS				
APPLICATION NOTES				
Potentiometers and Trimmers	www.vishay.com/doc?51001			
Guidelines for Vishay Sfernice Resistive and Inductive Components	www.vishay.com/doc?52029			



Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Revision: 02-Oct-12 Document Number: 91000

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru 4 moschip.ru 9